

CAT Reporting Technical Specifications for Industry Members

8/11/2020

Version 4.0.0 r1

Table of Contents

| | |
|---|-----------|
| Preface | vi |
| Executive Summary | ix |
| 1. Introduction..... | 1 |
| 1.1. CAT Overview..... | 1 |
| 1.2. Registration | 2 |
| 2. CAT Reporting Fundamentals..... | 3 |
| 2.1. Industry Member Perspective..... | 3 |
| 2.2. Key Data Elements..... | 3 |
| 2.2.1. Firm Identifiers in File Submissions | 3 |
| 2.3. Order ID..... | 4 |
| 2.3.1. Timestamps | 4 |
| 2.3.2. Order Handling Instructions | 5 |
| 2.3.3. Firm ROE ID..... | 5 |
| 2.3.4. Error ROE ID..... | 5 |
| 2.4. Reference Data..... | 5 |
| 2.4.1. Industry Member Identifiers | 5 |
| 2.4.2. Firm Designated ID (FDID) | 8 |
| 2.4.3. Equity Symbols..... | 9 |
| 2.4.4. Option Symbols | 9 |
| 2.4.5. Corporate Actions | 10 |
| 2.5. Data Types..... | 10 |
| 2.5.1. Data Validation Based on Data Types | 10 |
| 2.5.2. Required, Conditional, and Optional Fields..... | 17 |
| 2.6. Linkage Overview | 17 |
| 2.6.1. CAT Linkage Keys | 17 |
| 2.6.2. Reporting Responsibilities of Sender/Receiver | 19 |
| 2.6.3. Summary of Route and TRF Linkage Keys | 21 |
| 3. Special Reporting Requirements..... | 27 |
| 3.1. Alternative Trading Systems (“ATS”) Reporting..... | 27 |
| 3.1.1. National Best Bid and Offer (NBBO)..... | 27 |
| 3.1.2. ATS Order Types | 27 |
| 3.1.3. Sequence Number | 28 |
| 3.1.4. Display and Non-Display ATSS | 28 |
| 3.1.5. CAT Reporter IMID..... | 28 |
| 3.2. Manual Orders..... | 28 |
| 3.2.1. Manually Received CAT Events Immediately Systematized | 28 |

| | | |
|---------|--|----|
| 3.2.2. | Manual CAT Events Followed by Separate Electronic Messages | 29 |
| 3.2.3. | Manual Trade events and Order Fulfillment events | 29 |
| 3.3. | Allocation Events | 30 |
| 3.3.1. | Definition and Requirements | 30 |
| 3.3.2. | Reporting Obligation | 30 |
| 3.4. | Responses to RFQs and Solicitation | 31 |
| 3.4.1. | Scope | 31 |
| 3.4.2. | Reporting | 32 |
| 3.5. | Multi-Leg Option Orders and Paired Orders | 32 |
| 4. | Equity Events | 33 |
| 4.1. | New Order Event | 35 |
| 4.2. | New Order Supplement Event | 39 |
| 4.3. | Order Route Event | 41 |
| 4.3.1. | Route Modified Event | 44 |
| 4.3.2. | Route Cancelled Event | 48 |
| 4.3.3. | Order Route Supplement Event | 50 |
| 4.4. | Order Accepted Event | 52 |
| 4.5. | Order Internal Route Accepted | 56 |
| 4.5.1. | Order Internal Route Accepted Event | 56 |
| 4.5.2. | Order Internal Route Modified Event | 58 |
| 4.5.3. | Order Internal Route Cancelled Event | 60 |
| 4.5.4. | Order Internal Route Modification Request | 62 |
| 4.5.5. | Order Internal Route Cancel Request | 63 |
| 4.6. | Child Order | 65 |
| 4.6.1. | Child Order Event | 65 |
| 4.6.2. | Child Order Modified Event | 67 |
| 4.6.3. | Child Order Cancelled Event | 70 |
| 4.7. | Order Modified and Cancel/Replace Event | 71 |
| 4.7.1. | Order Modification Request Event | 76 |
| 4.8. | Order Modified (Cancel/Replace) Supplement Event | 79 |
| 4.9. | Order Adjusted Event | 80 |
| 4.10. | Order Cancelled Event | 83 |
| 4.10.1. | Order Cancel Request Event | 84 |
| 4.11. | Quotes | 86 |
| 4.11.1. | New Quote Event | 86 |
| 4.11.2. | Quote Received Event | 89 |
| 4.11.3. | Quote Cancelled Event | 91 |

| | |
|---|-----|
| 4.12. Trade | 92 |
| 4.12.1. Trade Event..... | 94 |
| 4.12.2. Trade Supplement Event | 98 |
| 4.13. Order Fulfillment | 100 |
| 4.13.1. Order Fulfillment Event..... | 101 |
| 4.13.2. Order Fulfillment Supplement Event..... | 103 |
| 4.13.3. Order Fulfillment Amendment Event..... | 105 |
| 4.14. Allocations..... | 107 |
| 4.14.1. Post-Trade Allocation Event | 107 |
| 4.14.2. Amended Allocation Event..... | 108 |
| 4.15. Order Effective Event | 111 |
| 5. Option Events | 114 |
| 5.1. Simple Option Events..... | 116 |
| 5.1.1. New Option Order Event | 116 |
| 5.1.2. Option Order Supplement Event..... | 119 |
| 5.1.3. Option Order Route Event | 122 |
| 5.1.4. Option Order Accepted Event | 133 |
| 5.1.5. Option Order Internal Route Accepted..... | 136 |
| 5.1.6. Child Option Order Event..... | 145 |
| 5.1.7. Option Order Modified and Cancel/Replace Event | 151 |
| 5.1.8. Option Order Modified Supplement Event..... | 157 |
| 5.1.9. Option Order Adjusted Event | 159 |
| 5.1.10. Option Order Cancelled Event | 161 |
| 5.1.11. Option Trade | 164 |
| 5.1.12. Option Order Fulfillment Event..... | 166 |
| 5.1.13. Option Post-Trade Allocations Event..... | 171 |
| 5.1.14. Option Order Effective Event | 175 |
| 5.2. Multi-Leg Option Order Events..... | 177 |
| 5.2.1. Multi-Leg New Order Event..... | 178 |
| 5.2.2. Multi-Leg Order Route event | 182 |
| 5.2.3. Multi-Leg Order Accepted Event..... | 186 |
| 5.2.4. Multi-Leg Order Internal Route Accepted Event | 189 |
| 5.2.5. Multi-Leg Child Order Event | 192 |
| 5.2.6. Multi-Leg Order Modified Event | 195 |
| 5.2.7. Multi-Leg Order Cancelled Event | 199 |
| 5.2.8. Multi-Leg Supplement Event | 200 |
| 6. Submission Process | 205 |

| | |
|--|-----|
| 6.1. File Submissions and Data Formats | 205 |
| 6.1.1. File Submission Names | 205 |
| 6.1.2. Submission Formats | 207 |
| 6.1.3. Metadata File Submission..... | 208 |
| 6.1.4. Data File Submission | 211 |
| 6.1.5. Schema | 212 |
| 6.2. Connectivity | 215 |
| 6.3. CAT Interface Methods..... | 216 |
| 6.3.1. CAT File Transfer..... | 217 |
| 6.3.2. CAT Reporter Portal | 217 |
| 6.4. CAT Reporting Hours | 218 |
| 6.4.1. Submission of CAT Events..... | 218 |
| 6.4.2. Deadline of Repair for Errors Identified by CAT..... | 219 |
| 6.4.3. Deadline for Firm Initiated Corrections and Deletions | 219 |
| 6.5. Security..... | 220 |
| 6.5.1. Encryption (In-transit) | 220 |
| 6.5.2. Encryption (At-rest) | 220 |
| 6.5.3. Authentication..... | 220 |
| 7. Feedback and Corrections | 221 |
| 7.1. File and Error Feedback..... | 221 |
| 7.1.1. Feedback Generation | 222 |
| 7.1.2. Feedback File Names | 222 |
| 7.2. File Acknowledgement..... | 225 |
| 7.2.1. File Acknowledgement Feedback Definition | 225 |
| 7.2.2. JSON Examples of File Acknowledgement..... | 226 |
| 7.2.3. CSV Example for File Integrity Feedback..... | 227 |
| 7.2.4. CSV Examples of File Acknowledgement | 228 |
| 7.3. File Integrity..... | 229 |
| 7.3.1. JSON Examples for File Integrity Feedback | 229 |
| 7.3.2. File Integrity Feedback Definition | 231 |
| 7.4. Data Ingestion | 232 |
| 7.4.1. Ingestion Feedback Definitions | 233 |
| 7.4.2. JSON Examples for Data Ingestion Feedback..... | 234 |
| 7.4.3. CSV Examples for File Ingestion Feedback..... | 236 |
| 7.5. Linkage Discovery | 236 |
| 7.5.1. Linkage Discovery Feedback Definitions..... | 238 |
| 7.5.2. JSON Examples for Linkage Discovery Feedback..... | 244 |

| | |
|---|-----|
| 7.5.3. CSV Examples for Linkage Discovery Feedback | 245 |
| 7.6. Corrections | 246 |
| 7.6.1. Repair CAT Errors | 247 |
| 7.6.2. Firm Initiated Corrections | 248 |
| 7.6.3. Record Delete Instructions | 249 |
| 7.6.4. File Deletion | 250 |
| 7.6.5. Same Day Corrections | 252 |
| 8. Testing | 253 |
| 9. Additional Information | 254 |
| 9.1. Public Website | 254 |
| Appendices | 255 |
| Appendix A: Change Release Management Process | 256 |
| Appendix B: Clock Synchronization Requirement | 257 |
| Appendix C: Representative Order Linkages | 258 |
| C.1 Representative Order Reporting Requirements | 258 |
| C.1.1 Representative Order Reporting | 258 |
| C.1.2 Representative Order Linkages | 259 |
| C.2 Representative Order Marking and Linkage Requirements | 261 |
| C.2.1 Single Order Scenarios | 261 |
| C.2.2 Net Trading Scenarios | 262 |
| C.2.3 Aggregated Order Scenarios | 262 |
| C.2.4 Representative Eligible Scenarios | 263 |
| C.2.5 Options Scenarios | 263 |
| C.2.6 Multi-Leg Option Scenarios | 264 |
| Appendix D: CAT Date Definitions and Reporting Guidelines | 265 |
| Appendix E: Error Codes | 268 |
| E.1 File Integrity Errors | 268 |
| E.2 Data Ingestion Errors | 270 |
| E.3 Linkage Discovery Errors | 279 |
| E.4 Warning Error Codes | 286 |
| Appendix F: Glossary | 288 |
| Appendix G: Data Dictionary | 291 |
| Appendix H: Processing Stages Feedback and Examples | 315 |
| H.1: Processing Stages Feedback | 315 |
| H.2: File Feedback (JSON) | 316 |
| H.3: File Feedback (CSV) | 330 |

Preface

Rule 613 of the Securities Exchange Act of 1934 requires national securities exchanges and national securities associations (“SROs”) to submit a national market system plan to the Securities and Exchange Commission (“Commission” or “SEC”) to create, implement, and maintain a consolidated audit trail (the “CAT”) that would allow regulators to more efficiently and accurately track all activity in U.S. equity and listed options markets. Pursuant to Rule 613, the SROs filed with the Commission the National Market System Plan Governing the Consolidated Audit Trail (“CAT NMS Plan”), which was approved by the Commission on November 15, 2016.

Under Rule 613(g)(2), each member of a national securities exchange or national securities association is required to comply with all the provisions of the CAT NMS Plan. Relatedly, as mandated under Rule 613, the CAT NMS Plan requires each SRO to adopt rules requiring its members to comply with Rule 613 and the CAT NMS Plan, and to agree to enforce compliance by its members in that regard. Accordingly, each SRO has adopted rules requiring its members to comply with Rule 613 and the CAT NMS Plan. See, e.g., FINRA Rule 6800 Series.

The SROs jointly own Consolidated Audit Trail, LLC, which was formed by the SROs to arrange for and oversee the creation, implementation, and maintenance of the CAT as required under Rule 613. Thus, the CAT is a facility of each SRO.

This specification represents a phased approach to industry reporting. Key dates are as noted below. Version 4.0 of this specification reflects finalized Phase 2d reporting requirements based on versions 2.2.1 r6 and 3.1.0 r4. The Participants propose to seek a modification of the requirements of the CAT NMS Plan from the Commission to reflect the phased approach for Industry Member CAT reporting described in these Technical Specifications.

Table 1: Industry Specifications Phased Approach

| Phase 2a – Equities Part 1 Go Live 6/22/2020 | Phase 2c – Equities Part 2 Go Live 4/26/2021 |
|---|--|
| All events and scenarios covered by OATS | Linkages to the customer order(s) being represented for all representative order scenarios including agency average price, net trading, aggregated orders, OMS-EMS scenarios |
| All proprietary orders including market maker orders | Marking as a representative order any order originated to work a customer order in price guarantee scenarios, such as a guaranteed VWAP |
| Firm Designated ID | Rejected External Routes with flag indicating route was not accepted by receiving destination |
| All street side representative orders (both agency and proprietary) | Linkage of duplicate electronic messages related to a Manual Order Event between the electronic event and the original manual route |

| | |
|--|---|
| Linkage is required between the representative street side order and the order being represented when the representative order was originated specifically to represent a single order (received either from a customer or another broker-dealer) and there is: 1) an existing direct electronic link in the firm's system between the order being represented and the representative order, and 2) any resulting executions are immediately and automatically applied to the represented order in the firm's system | Special Handling instructions on Route Reports (limited to a defined set of values) |
| | Reporting changes to client instructions regarding modifications to algorithms |
| | Order Effective Time for orders that are received by an Industry Member and do not become effective until a later time. |
| Quotes in NMS stocks sent to a national securities exchange or facility of a national securities association *assumes exemptive relief request or Plan amendment for verbal quotes until July 2023 | Internal Route modifications and cancels (equities) |
| Unlisted quotes (OTC Equity Securities) received by a broker-dealer operating an inter-dealer quotation system (e.g., Global OTC, OTC Link) *see above comment on verbal quotes | Quote ID on Trade Events. |
| Unlisted equity quotes that meet the definition of bid or offer under the Plan sent by a broker-dealer to a quotation venue not operated by an SRO or broker-dealer *see above comment on verbal quotes | Responses to RFQs/solicitations through standard electronic messaging integrated with a firm's OMS/EMS (equities) |
| Electronic and manual capture time for manual orders | Allocations (equities) |
| OATS guidance regarding firm modifications to previously routed orders (OATS FAQ C35) applies to CAT | All FDIDs with LTIDs for accounts with equity CAT Reportable events in Phases 2a and 2c |

| Phase 2b – Options Part 1 Go Live 7/20/2020 | Phase 2d – Options Part 2 Go Live, Additional Equities Scope 12/13/2021 |
|---|--|
| Simple options electronic orders, excluding electronic paired orders | Simple options manual orders |
| | Electronic and manual paired orders |
| Responses to auctions of simple orders and paired simple orders | All complex orders with linkage to all CAT-reportable legs |
| Options combined orders must be reported and marked as a combined order. Linkage to the underlying orders is not required to be reported until Phase 2d | Revisit application of OATS guidance to CAT for firm modifications to previously routed orders (OATS FAQ C35) and require reporting in certain instances |
| | Internal Route modifications and cancels (options) |
| | Receipt time of cancellation and modification instructions through Order Cancel Request and Order Modification Request events (for options and equities). |
| | Unlisted quotes sent to an inter-dealer quotation system operated by a CAT Reporter that does not match or execute orders. |
| | All OTC Link messages reported as orders (Tentative for 2d but no later than July 2022) |
| | Responses to RFQs/solicitations through standard electronic messaging integrated with a firm's OMS/EMS (options) |
| | Linkage between an options combined order and the |

| | |
|--|---|
| | original customer orders |
| | Allocations (options) |
| | All FDIDs with LTIDs for accounts with options CAT Reportable events in Phases 2b and 2d |

| |
|---|
| Phase 2e – 7/11/2022 |
| Remainder of Customer and Account information, including CCID |

Executive Summary

This document describes the requirements for the reporting of data to CAT by Industry Members, including detailed information about data elements and file formats of each Reportable Event. It also describes how Industry Members submit files to CAT, including access instructions, network and transport options, and testing requirements.

A separate companion document containing detailed reporting scenarios entitled CAT Industry Member Reporting Scenarios should be used as a guide for determining how the event types and field values laid out in this document must be applied when reporting various order handling and execution scenarios for both equities and options.

An archived version of Table 2: Revision / Change Process detailing changes to previous versions of this document is available at www.catnmsplan.com.

Table 2: Revision / Change Process

| Version | Date | Author | Description |
|----------|---------|-------------------------------|---|
| 4.0.0 | 6/30/20 | Consolidated Audit Trail, LLC | <p>Initial publication for Phase 2d. Applicable Schema Version: 4.0.0</p> <p>Removed language regarding Phase 2a/2b/2c reporting requirements, ungreyed fields and values required to be reported in Phase 2d.</p> <p>Added and defined new events and fields applicable to Phase 2d reporting.</p> <p>Updated <i>orderID</i> uniqueness requirements for modification events.</p> <p>Clarified requirements for reporting Quote events.</p> <p>Removed <i>priorUnlinked</i> and <i>nextUnlinked</i> fields.</p> <p>Updated definition of <i>manualFlag</i> in MEOMR and MEOCR events.</p> <p>Removed <i>routedOrderID</i>, <i>aggregatedOrders</i>, <i>representativeInd</i>, and <i>initiator</i> fields from MEOMR event and updated applicable linkage keys</p> <p>Updated definition of <i>custType</i> values in the Data Dictionary</p> <p>Added <i>timeInForce</i> to MOOJ</p> <p>Added <i>side</i> value 'S' for options events.</p> |
| 4.0.0 r1 | 8/11/20 | Consolidated Audit Trail, LLC | <p>Applicable Schema Version: 4.0.0</p> <p>Made conforming changes with v3.1.0 r5</p> <p>Corrected a typo in Table 78</p> |

1. Introduction

1.1. CAT Overview

The Securities and Exchange Commission (SEC) approved Rule 613 under the Securities Exchange Act of 1934, which requires national securities exchanges and national securities associations (collectively, the Participants) to submit a national market system plan to create, implement, and maintain a consolidated audit trail ([CAT NMS Plan](#)) that would capture customer and order event information for orders in NMS Securities and OTC Equity Securities (Eligible Securities), across all markets, from the time of order inception through routing, cancellation, modification, execution, and allocation. The SEC approved the CAT NMS Plan on November 15, 2016.

In accordance with SEC Rule 613, the CAT NMS Plan requires a Central Repository that will comprehensively track orders throughout their lifecycle and identify the Participants and Industry Members handling them, as well as the account holders and authorized traders for any account that originates an order (Customers¹). Specific data elements will be submitted to the Central Repository by Participants, Industry Members, and CAT Reporting Agents. CAT Reporting Agents may be third-party firms reporting on behalf of other entities, or may be outside parties that are not required to submit data to the CAT, but from which the CAT may receive data per the CAT NMS Plan, such as the Securities Information Processors (SIPs).

The CAT NMS Plan also requires the selection of an entity as the Plan Processor to be responsible for performing the processing functions required by Rule 613 and the Plan. The Operating Committee of Consolidated Audit Trail, LLC, a governing body composed of representatives of the Participants, oversees the operation of the CAT. The duties of the Operating Committee are further described in Article IV of the CAT NMS Plan.

Refer to SEC Rule 613, available at: <https://www.sec.gov/rules/final/2012/34-67457.pdf> for more details.

Refer also to CAT NMS Plan, available at: <https://www.catnmsplan.com/wp-content/uploads/2018/02/34-79318-exhibit-a.pdf>.

¹ Customers are defined in SEC Rule 613(j)(3) as: (i) the account holder(s) of the account at a registered broker-dealer originating the order; and (ii) any person from whom the broker-dealer is authorized to accept trading instructions for such account, if different from the account holder(s).

1.2. Registration

Industry Members are required to register for the CAT NMS System by June 27, 2019 regardless of what phase they begin reporting. Third Party Transmitters are also required to register for the CAT NMS System prior to submission.

The [Registration Form](#) is available on the CAT Public Website, along with additional information on the registration process. Contact help@finracat.com for any questions regarding the registration process.

2. CAT Reporting Fundamentals

2.1. Industry Member Perspective

Industry Members must populate fields from their perspective. For example, for “*capacity*”, the Industry Member must report based on the capacity in which the Industry Member acted. For New Order and Order Accepted events, reports must indicate the instructions as received. For an Order Route, the fields must include the instructions as sent to the destination.

2.2. Key Data Elements

The sections below describe the key data elements of CAT that may be used in CAT events and/or Metadata files.

2.2.1. Firm Identifiers in File Submissions

The CAT submissions process relies on certain firm identifiers to determine whose data is being reported, to determine and verify the authorization of the submitter of the data, and to obtain and verify the authorization of the third party that may take action on the data.

CAT Reporter IMID

The CAT Reporter IMID is the SRO assigned identifier that an Industry Member uses to report to CAT. A CAT Reporter may use any SRO assigned identifier that is valid on the CAT Trading Day for which CAT events are submitted. CAT will use reference data submitted by Participant Reporters each day to identify the Industry Member to which the specific identifier is assigned. Each SRO assigned identifier is linked to the Industry Member's CRD number so that all reporting activity of a single Industry Member CAT reporter can be consolidated at the firm level in CAT. Refer to [Section 2.4.1.1](#) for additional information on populating the CAT Reporter IMID.

CAT Submitter ID

The CAT Submitter ID is a CAT assigned identifier for a firm that submits data to CAT. The Submitter ID uniquely identifies the Submitter and is not the same identifier as the CAT Reporter IMID. CAT Reporters may submit data for themselves or may authorize a Reporting Agent to report on the CAT Reporter's behalf. Additionally, CAT Reporters may authorize a Third Party Reporting Agent to view and take action on data submitted on behalf of the CAT Reporter by another Submitter.

Authorization between CAT Reporters, Submitter and Third Party Reporting Agents is granted through a reporting relationship that will be entered by the CAT Reporter using the CAT Reporter Portal. When a file

is received, CAT will verify that the CAT Reporter has authorized the Submitter to submit on their behalf. When the file is received with a Third Party Reporting Agent designated, CAT will verify the CAT Reporter has authorized the Third Party.

If the Submitter is an Industry Member, the CAT Submitter ID is the Submitter's CRD number. If the Submitter is not an Industry Member and does not have a CRD number (i.e. Service Bureaus), the CAT Submitter ID is the Submitter's Organization ID. Service bureaus may contact the FINRA CAT Helpdesk to obtain their Organization ID.

2.3. Order ID

The order ID used in CAT events represents the internal order ID assigned by the Industry Member. The order ID is used as a Linkage Key and must be unique when combined with the *orderKeyDate*, *CATReporterIMID* and *symbol* (or *optionID*). Other key linkage fields are fully described in [Section 2.6.1](#).

2.3.1. Timestamps

Each Industry Member must record and report Industry Member Data captured in an electronic system to CAT with timestamps in milliseconds. CAT will accept granularity up to nanoseconds. To the extent that any Industry Member's order handling or execution systems utilize timestamps in increments finer than milliseconds, the Industry Member must truncate its timestamps after the nanosecond level. Refer to [CAT FAQs B2](#) and [B8](#) for additional information.

Each Industry Member may record and report Manual CAT events in increments up to and including one second, provided that each Industry Member records and reports the time when a Manual CAT Event has been captured electronically in an order handling and execution system of such Industry Member ("Electronic Capture Time") in milliseconds. Allocation Reports must be reported in increments up to and including one second.

Each CAT event contains both an *eventTimestamp* and *electronicTimestamp*. The *eventTimestamp* is the time of order handling or execution pursuant to Section 6.8 of the CAT NMS Plan (e.g. origination, receipt) depending on the respective order event. For manual order handling, *eventTimestamp* is the manual handling or execution time, which is required to be reported in increments of at least one second. When the manual order is later captured electronically, the systematized time must be captured in the *electronicTimestamp* field.

2.3.2. Order Handling Instructions

Special handling instructions are reported in the *handlingInstructions* field using a standardized list of handling instructions and codes. Multiple codes and values can be used in combination to report special handling instructions.

Industry Members are required to report *handlingInstructions* on Order Route events. In the event an Industry Member routes an order with exactly the same handling instructions received from the customer, they may use *handlingInstructions* code "RAR" (Routed as Received) on the Order Route event rather than re-stating all *handlingInstructions* values from the New Order/Order Accepted event.

2.3.3. Firm ROE ID

The Firm ROE ID is the internal identifier assigned by the Industry Member to uniquely represent a record in CAT. The *firmROEID* is present on every CAT event and is used to support the corrections process.

The *firmROEID* must be unique for the Event Date and CAT Reporter IMID and is required to be formatted as follows: <Event Date>_<firm ROE Identifier>. This requirement applies to CAT Reporters that use multiple Submitters. An example of a *firmROEID* is: 20190429_323134567.

Event Date must represent the date portion of the *eventTimestamp* reported in the record. The inclusion of the event date provides processing efficiency for the corrections process by allowing the CAT Processor an efficient mechanism to locate the record being corrected.

Refer to [Section 7.6](#) for more information on the corrections process.

2.3.4. Error ROE ID

The Error ROE ID is the identifier assigned by CAT to uniquely identify an error record. The *errorROEID* is returned with error feedback to provide a mechanism for firms to repair errors generated during processing. When firms are submitting corrections to CAT that represent a repair of an error, the *errorROEID* provides an efficient mechanism to locate the error record being repaired.

Refer to [Section 7.6](#) for more information on the corrections process.

2.4. Reference Data

2.4.1. Industry Member Identifiers

An Industry Member Identifier is any identifier assigned by an SRO to one of its members. Examples of SRO assigned identifiers include FINRA MPIDs, Nasdaq MPIDs, NYSE Mnemonics, Cboe EFIDs, and

CHX Acronyms. Most Industry Members have multiple IMIDs. The following sections will provide guidance on which IMID to use for various fields and reporting circumstances.

2.4.1.1. IMID in the *CATReporterIMID* field

Populated in File names, within Metadata files, and optionally on CAT Events, the *CATReporterIMID* identifies the Industry Member whose data is represented in the CAT Event. The *CATReporterIMID* is populated with the SRO assigned identifier used to report to CAT. The *CATReporterIMID* is used to consolidate activity occurring both within the *CATReporterIMID* and at the firm (CRD) level. It also participates in the Linkage Keys used for Intrafirm Linkage and TRF Linkage. The *CATReporterIMID* does not participate in the Linkage Keys for Interfirm Linkage.

The *CATReporterIMID* is populated with the SRO assigned identifier used to report to CAT according to the following requirements:

1. FINRA members must populate the CAT Reporter IMID with the same MPID that it uses for related trade reporting facility (TRF) trade reporting, or, for quoting on an interdealer quotation system.
2. FINRA members that operate an alternative trading system (ATS) must use their FINRA ATS MPID.
3. If there is no ATS, TRF or quoting MPID requirement, any valid FINRA MPID may be populated.
4. Non-FINRA members may use any effective identifier of the firm as included in the Daily published Member Dictionary, as described in the [CAT Reporting Technical Specifications for Plan Participants](#).
5. When a CAT Reporter routes between different IMIDs of the same firm (same CRD), the CAT Reporter IMID may **not** be populated with the same value on the Order Route and Order Accepted events.
6. The *CATReporterIMID* populated in the data file name, within the related metadata file and in the CAT event (if populated) must be equal, otherwise the record will be rejected.

2.4.1.2. IMID on Routing Events in the *senderIMID*, *receiverIMID* and *destination* Fields

IMIDs are populated in Order Accepted and Order Route events with the Industry Member identifier used when routing between venues. This identifier is known to both parties and is required to be populated in the *senderIMID*, *receiverIMID* and *destination* fields where applicable.

The IMID participates in the Linkage Keys used for Inter-firm Linkage and Exchange Linkage. When the same Industry Member Identifier (IMID) is assigned by different SROs to represent different Industry Members, an IMID conflict is created. To avoid conflicts, to simplify the population of the Industry Member

Identifiers, and to streamline linkage processing, CAT reporters must populate the *senderIMID*, *receiverIMID* and *destination* (when routing to an IM) fields with both the CRD and IMID, formatted as <CRD of the CAT Reporter>:<IMID of the Industry Member performing the action in the CAT event>. The Industry Member ID must include the identifier that is known by the routing firm and destination venue. For example: CRD 123, IMID ABC is formatted as 123:ABC.

The IMID provided in the *senderIMID*, *receiverIMID* and *destination* fields can be different than the CAT Reporter IMID. For example, CAT Reporter ABCD (CRD 123) may use FRMA as its CAT Reporter IMID, but when routing to Exchange A, it uses the exchange assigned identifier ABC. In this scenario, on its Order Route event, Firm A would populate its identifier in the CAT Reporter IMID field as FRMA and its identifier in the *senderIMID* field as 123:ABC.

For orders received from or routed to an alternative trading system (ATS), the FINRA ATS MPID must be used. FINRA members must use the same MPID for CAT reporting that it uses for related trade reporting facility (TRF) trade reporting, or, for quoting on an interdealer quotation system. If there is no ATS, TRF or quoting MPID requirement, firms may agree to use any valid FINRA MPID when routing to or receiving from another FINRA member, as long as both CAT Reporters use the same MPID as the IMID. Routing identifiers representing FINRA members are populated as: <FINRA Member CRD>:<FINRA Member MPID>.

For orders received from or routed to a non-FINRA member firm, firms must agree to use the same IMID when reporting events to CAT. Non-FINRA members may use any effective identifier of the firm. Routing identifiers representing non-FINRA members are populated as: <non-FINRA Member CRD>:<non-FINRA Member MPID>.

For orders routed to or received from an exchange, CAT reporters must populate the IMID with both the CRD and exchange assigned identifier used in the order route message to the exchange, formatted as <CRD>:<exchange assigned identifier>.

Refer to [Section 2.6.3.1](#) for additional information on how IMIDs participate in linkage.

2.4.1.3. Default IMIDs

The Plan Processor will publish each day a list of all SRO-assigned identifiers that includes a designated default IMID. The default IMID is selected by each CAT Reporter when they register as a CAT Reporter. If two parties do not have a pre-determined agreement as to which IMID to use when routing between each other, the published default IMID must be used.

Routing identifiers populated using a default IMID are populated as: <default IMID CRD>:<default IMID>.

Example: A non-FINRA member firm (CRD 999) has a Cboe-assigned option identifier and a NYSE-assigned equity identifier, as follows:

- Cboe-assigned options ID - BDAO
- NYSE-assigned equity ID – BDA (default IMID)

In this example, when a second firm receives an order from the above firm, and the second firm does not have an agreement with the above firm as to which IMID to use, IMID BDA should be used to avoid a linkage error. The routing identifier is populated as 999:BDA.

2.4.2. Firm Designated ID (FDID)

Section 6.4 of the CAT NMS Plan requires that for the original receipt or origination of an order, Industry Members must report the Firm Designated ID (FDID). Therefore, FDID is required to be populated on all New Order events for both equities and options.

FDID is defined in Section 1.1 of the CAT NMS Plan as a unique identifier for each trading account. Industry Members must assign a single FDID to each trading account that is unique across all vendors the IM may use to report new orders to CAT and unique across time (with limited exceptions, such as closed accounts). For example, if an Industry Member uses multiple vendors for reporting, each vendor must report activity from the same account using the same FDID.

Examples of what an FDID would represent include:

- Individual Customer Account Number
- Institutional Customer Account Number
- Account Number of Average Price Account Designated for a Specific Customer (e.g., Master Account or agency Representative Order scenarios)
- Account Number of Firm Average Price Account Shared Across Customers (e.g., Master Account, Account Used For Agency Representative Order Flows)
- Entity ID of the firm when an employee of the firm is exercising discretion over multiple customer accounts
- Proprietary Trading Account Number
- Firm assigned identifier representing a trading relationship (Relationship ID) can be used when the trading account structure is unavailable at the time the order was placed

An actual account number may not be used as the FDID for a customer account for CAT reporting. See [CAT FAQ M2](#) for more information on the prohibition on use of actual account numbers. Refer to the [CAT Industry Presentation on FDID](#) for additional information.

Refer to [Section 4.2](#) and [Section 5.1.2](#) for details on reporting an FDID when an order is received for a new account and the new account number, on which the FDID is based, is not yet available.

Refer to the [CAT Reporting Customer & Account Technical Specifications for Industry Members](#) for information on reporting FDIDs to the CAT Customer & Account Information System (“CAIS”).

2.4.3. Equity Symbols

Industry Members must report CAT Events related to listed equity Eligible Securities to CAT using the symbology of the primary listing exchange and must report CAT Events related to OTC Equity Securities using FINRA OTC symbology.

2.4.3.1. CAT Symbol Master

CAT will provide a start-of-day equity symbol master list and an end-of-day equity symbol master list each day on the [CAT Public Website](#).

The symbol master file for Industry Members contains the following information:

- Listing exchange for listed securities with the symbol in the symbology of the listing exchange
- FINRA symbology for OTC Equity Securities
- Flag indicating whether the symbol is a test symbol.

2.4.4. Option Symbols

As stated above, the CAT NMS Plan requires symbols to be reported to CAT in the symbology of the listing exchange. Standard option symbols established across exchanges as the result of the Option Symbology Initiative (OSI) must be used for any single-leg listed options.

2.4.4.1. Flex Percent Option Symbols

FLEX Percent options can only be uniquely identified using the OSI once their deterministic prices are known. When reporting the *optionID* for a FLEX Percent option, Industry Members must append "%" to the beginning of the standard OSI symbol. This will enable the CAT system to differentiate between a strike value that is expressed in percent terms from one that is expressed in dollars and cents.

FLEX Percent option symbols expressed with percentage strike values will have 22 characters. For example, an option order with *optionID* %1AAPL 200131C00095000 indicates it is a Flex Percent option order on OSI symbol 1AAPL 200131C00095000.

2.4.5. Corporate Actions

The CAT System will maintain historical symbology in the Central Repository that includes corporate actions.

CAT will receive daily corporate action files and symbol updates from the various data sources (including equity and options listing exchanges, FINRA OTC Equity Symbols, Data Distribution Services from Options Clearing Corporation, etc.) and publish daily symbol master files to the Industry Members. The symbol changes impacted by corporate actions will be reflected in the daily symbol master files. Industry Members must use the updated symbol in Reportable Events from the effective date of the symbol change. Failure to report in the updated symbol would result in rejects of the record(s).

Industry Members are not required to report order adjustments due to corporate actions, e.g., price or size changes. However, if an Industry Member chooses to report an adjustment resulting from a corporate action, the adjustment must be reported using the Order Modified event (or Order Adjusted event).

2.4.5.1. Options Intraday Listing or Delisting

CAT accommodates intraday listing of options by exchanges. Industry Members must report the OSI symbol as the *optionID*, just like for previously listed options.

CAT will maintain a historical record of option symbols, including symbols that have been delisted. Exchanges and the OCC will provide reference data to CAT for option symbols that are listed or delisted intraday.

2.5. Data Types

CAT will accept two kinds of text-based files: JSON and CSV. Data types used throughout this document are described below.

To support JSON and CSV submissions, the [Industry Member Schema](#) (JSON) file is available on the CAT public website that describes each data type with required representation formats and a mapping that defines the position in a CSV representation.

2.5.1. Data Validation Based on Data Types

All data submitted to CAT will be validated based on the defined data type of each item, including proper formatting and range checking. All File Names, Field Names and Field Values are case sensitive in CAT with the exception of Data Type BOOLEAN. During validations, if the case does not match, an error will

occur. Examples of accepted values are detailed in the table below. Valid values for Choice fields are defined in the Data Dictionary for each data element. Valid data values, ranges, and formats will be specified in the record schema files, which will be used to validate submitted data element values. Records and values that fail validation will be rejected and will be reported as feedback to the Reporter and Data Submitter as detailed in [Section 7](#).

Table 3: Data Types

| Data Type | JSON Type | Description |
|-----------|-----------|---|
| Numeric | NUMBER | <p>Composed of digits with an optional decimal point. Values must represent the exact value as per the examples:</p> <ul style="list-style-type: none"> • 1235 • -1235 • 1235.67 • -1235.67 <p>Numeric data types described in this document will include two numbers, the first is the maximum number of digits before the decimal point, and the second is the maximum number of digits after the decimal point. For example, Numeric (6,4) indicates that the number can have a maximum of 6 digits before the decimal point and a maximum of 4 digits after the decimal point.</p> <p>Examples which comply with Numeric (6,4) include:</p> <ul style="list-style-type: none"> • -999999.9999 • -0.1 • 0 • 0.0001 • 100 • 100.100 • 999999.99 • 0.25 • 099999.9990 • 0999999.99990 <p>Numeric values must always include a digit in the portion before the decimal. The fractional portion is optional. (for example, 0.25 cannot be represented as .25).</p> <p>Examples which do not comply with Numeric (6,4) include:</p> <ul style="list-style-type: none"> • 1234567.0 • .123 • 1.12345 • 10. • 40a <p>Numeric data types that require 0 digits after the decimal place should not</p> |

| Data Type | JSON Type | Description |
|----------------|-----------|--|
| | | include a decimal. The following example does not comply with Numeric (6,0): <ul style="list-style-type: none"> • 1234.5 • 1234.0 |
| Price | NUMBER | Numeric (10,8), which supports prices in the inclusive range from -9999999999.99999999 to 9999999999.99999999. |
| Real Quantity | NUMBER | Numeric (12,6) with up to 12 digits before the decimal point and up to 6 digits after the decimal point. However, the type Real Quantity cannot have trailing zeros in the decimal quantities. Trailing zeros in the decimal quantity will result in a rejection. For example, a value of 100.00 would not be accepted for the type Real Quantity, only 100 would be accepted. Similarly, a value of 100.10 would not be accepted, only 100.1 is acceptable for the type Real Quantity. Real Quantity must not be a negative value. |
| Whole Quantity | NUMBER | Numeric (12,0). An integer value with no decimal fraction component. Whole Quantity must not be a negative value. |
| Integer | NUMBER | An integer value (positive, negative, or zero), with no decimal fraction component, in the inclusive range from -9,223,372,036,854,775,808 to 9,223,372,036,854,775,807 (the same range as a 64-bit signed integer). |
| Unsigned | NUMBER | An unsigned value, greater than or equal to zero, with no decimal fraction component, in the inclusive range from 0 to 18,446,744,073,709,551,615 (the same range as a 64-bit unsigned integer). |
| Boolean | BOOLEAN | A value with two choices: true or false. In CSV representation, the value must equal <code>true</code> or <code>false</code> (no quotation marks). In JSON representation, if the field is not present, the value is considered <code>false</code> . Boolean values are NOT case sensitive. |
| Alphanumeric | STRING | A string, composed only of letters and digits [a-zA-Z0-9]. When an Alphanumeric type is described, it will include a number, indicating the maximum length of the field. For example, Alphanumeric (7) means that the field can contain up to 7 characters. Alphanumeric values are case sensitive. |
| Text | STRING | A string, composed of any printable ASCII character from 32 to 126. The string may not include the following characters which serve as delimiters: <ul style="list-style-type: none"> • comma (ASCII decimal 44, hex 2C), • pipe (ASCII decimal 124, hex 7C), • double quote (ASCII decimal 34, hex 22), and • @ (ASCII decimal 64, hex 40). <p>When a Text data type is described, it will include a number, indicating the maximum length of the field. For example, Text (7) means that the field can contain up to 7 characters. Text values are case sensitive.</p> <p>When represented in JSON, the following rule applies: Backslash <code>\</code> is a reserved printable character in JSON and must be escaped in order to be used in strings by inserting a backslash prior to it within the string. For example: <code>routedOrderID = 1234\ABCD</code> must be reported to CAT as <code>"routedOrderID": "1234\ABCD"</code>. If the backslash is not escaped, it will be omitted from the string. For example if the following is reported to CAT, <code>"routedOrderID": "1234\ABCD"</code>, it will be stored as <code>routedOrderID = 1234ABCD</code>.</p> |

| Data Type | JSON Type | Description |
|------------------|---------------------------|--|
| | | Escape characters do not participate in the field value length. |
| Date | NUMBER | An 8-digit integer representing the date in YYYYMMDD. |
| Timestamp | STRING or Unsigned NUMBER | <p>A timestamp represents a moment in time. Two timestamp formats are supported including STRING and NUMBER.</p> <p>Timestamps formatted as a STRING have a maximum length of 25 and are formatted as 'YYYYMMDD HHMMSS.CCCNNNNNN' with the Date and Time portions, separated by a space (ASCII decimal 32, hex 20) or the letter T (ASCII decimal 84, hex 5A). All timestamps submitted in STRING format must be in Eastern Time (ET).</p> <ul style="list-style-type: none"> The Date portion must include four digit year, two digit month, and two digit day. Valid values: YYYY = 0000 - 9999, MM = 00 - 12, DD = 00 - 31. The Time portion must include a two digit hour, two digit minute, two digit seconds. Valid values: HH = 00 - 23, MM = 01 - 59, SS = 01 - 59, CCC = 000 - 999, NNNNNN = 000000 - 999999. <p>Examples which comply with Timestamp in STRING format:</p> <ul style="list-style-type: none"> 20190617T000120.000000000 20190617T000120 20190617T000120.000 20170107T213000.123456789 20170107 213000.123456789 20190617 000120.123000000 <p>Examples which do not comply with Timestamp in STRING format:</p> <ul style="list-style-type: none"> 20190617T0120 20190617T000120. <p>As an alternative format, timestamp can be submitted as a value of type Unsigned, representing the number of nanoseconds that have elapsed since 00:00:00 Coordinated Universal Time (UTC), Thursday, 1 January 1970, not counting leap seconds. This is also commonly known as POSIX time or UNIX time. The same point in time from the above example would be represented as the number 1483842600123456789. Timestamps submitted in UTC must not be adjusted for Eastern Time.</p> <p>Note that the data type is different between the two formats. In JSON, the first representation requires it to be surrounded by double quotes, while the second does not.</p> <p>Examples which comply with Timestamp in NUMBER format:</p> <ul style="list-style-type: none"> 1483842600123456789 <p>Examples which do not comply with Timestamp in NUMBER format:</p> <ul style="list-style-type: none"> 20190617T000120 20190617 000120 |
| Name/Value Pairs | OBJECT | An object composed of a list of zero or more attributes where each attribute is either a name with no value, or a name with an accompanying value. |

| Data Type | JSON Type | Description | | | | | | | | | | | | |
|-----------|--|--|----|------|-----|---|---------------------------------|--------------|---|--|----------------------------|---|-----------------------------|-----|
| | | <p>Multiple attributes are separated by a delimiter.</p> <p>When represented in JSON, the following rules apply:</p> <ul style="list-style-type: none"> • The OBJECT is contained within curly brackets { } • Name/Value Pairs are comma separated • A value accompanied by a name must be formatted as per the data type syntax required in JSON • A name with no value must include the Boolean value as indicated in the below examples. <p>For example <i>handlingInstructions</i> are represented as follows in JSON: "handlingInstructions":{ "AOK": true, "DISP": 10.00, "TMO": "20190419T092316.123456789", "AucResp": "AuctionID456" }</p> <p>When represented in CSV, the following rules apply:</p> <ul style="list-style-type: none"> • The OBJECT is represented in a single position delimited by comma • Name/Value Pairs are pipe delimited • A value accompanied by a name is prefixed by an equal sign • A name with no value must only include the name <p>In CSV, <i>handlingInstructions</i> is represented as: AOK DISP=10.00 TMO=20190419T092316.123456789 AucResp=AuctionID456</p> <p><i>timeInForce</i> is also defined as a Name/Value Pair, however only one Choice value is applicable. The following examples demonstrate how to represent in JSON and CSV:</p> <table border="1" data-bbox="609 1312 1421 1541"> <thead> <tr> <th>Ex</th> <th>JSON</th> <th>CSV</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>"timeInForce":{"DAY": 20190528}</td> <td>DAY=20190528</td> </tr> <tr> <td>2</td> <td>"timeInForce":{"GTT": "20190528T160000.000000"}"</td> <td>GTT=20190528T160000.000000</td> </tr> <tr> <td>3</td> <td>"timeInForce":{"IOC": true}</td> <td>IOC</td> </tr> </tbody> </table> | Ex | JSON | CSV | 1 | "timeInForce":{"DAY": 20190528} | DAY=20190528 | 2 | "timeInForce":{"GTT": "20190528T160000.000000"}" | GTT=20190528T160000.000000 | 3 | "timeInForce":{"IOC": true} | IOC |
| Ex | JSON | CSV | | | | | | | | | | | | |
| 1 | "timeInForce":{"DAY": 20190528} | DAY=20190528 | | | | | | | | | | | | |
| 2 | "timeInForce":{"GTT": "20190528T160000.000000"}" | GTT=20190528T160000.000000 | | | | | | | | | | | | |
| 3 | "timeInForce":{"IOC": true} | IOC | | | | | | | | | | | | |
| Array | ARRAY | <p>A list of 0, 1 or more values of the same data type.</p> <p>When represented in JSON, the following rules apply:</p> <ul style="list-style-type: none"> • ARRAY is within a set of brackets [] • Elements within the array are comma separated. <p>For example, <i>atsOrderType</i> is represented as the following in JSON: "atsOrderType":["PEG","midPEG"]</p> <p>When represented in CSV, the following rules apply:</p> <ul style="list-style-type: none"> • ARRAY is represented in a single position delimited by comma | | | | | | | | | | | | |

| Data Type | JSON Type | Description |
|---------------------------|-------------------------|--|
| | | <ul style="list-style-type: none"> Elements in the array are pipe delimited <p>When represented in CSV, it is: ,,,PEG midPEG,,,</p> |
| Choice | STRING | A Text field with an explicit list of acceptable values. The Data Dictionary section of this document lists the acceptable values for each Choice field. |
| Symbol | STRING | Text (22). Refer to Section 2.4.3 and Section 2.4.4 for more details on Equity and Options symbols. The string is case sensitive. |
| Message Type | STRING | Alphanumeric (5) indicating the type of message being reported. |
| CAT Reporter IMID | STRING | Alphanumeric (7) - a CAT Reporter IMID. |
| Exchange ID | STRING | Alphanumeric (7) – identifier that applies to exchanges. |
| CAT Submitter ID | Unsigned NUMBER | A unique ID assigned by CAT to the CAT Reporting Agent. |
| Industry Member ID (IMID) | STRING | Text (16) – CRD and SRO assigned Market Participant Identifier assigned by an SRO to one of its members. Formatted as <CRD of the Market Participant>:<SRO Assigned Identifier of the Market Participant>. Example: CRD 123, IMID ABCD is populated as 123:ABCD |
| Multi-Dimensional Array | Multi-Dimensional ARRAY | <p>A compound object that consists of an array of objects. The JSON and CSV syntax for this data type is consistent with other Multi-Dimensional Array JSON Types. Multi-Dimensional Array is specified as the data type within the Metadata File Definition for Submissions as well as Metadata File Definitions for Error Feedback.</p> <p>When represented in JSON, the following rules apply:</p> <ul style="list-style-type: none"> ARRAY is within a set of brackets [] Each OBJECT contained in the ARRAY is within curly brackets { } Elements within each object are comma separated Conditional elements that do not have a value are not required to be included. <p>When represented in CSV, the following rules apply:</p> <ul style="list-style-type: none"> ARRAY is represented in a single position delimited by comma Each object contained in the ARRAY is pipe delimited Elements within each object are delimited by @ All elements defined for the Object must be represented in their specified position, even when there is not applicable value. |
| Trade Side Details | Multi-Dimensional ARRAY | <p>A compound object that consists of a list of data elements which supports the reporting of buy side details and sell side details in a Trade Event. When Trade Side Details are reported, each side will represent one set of details. <i>buyDetails</i> and <i>sellDetails</i> are two different fields. Each field is defined to contain an ARRAY that is limited to one object.</p> <p>For example, Trade Side Details (<i>buyDetails</i> and <i>sellDetails</i>) are represented as follows in JSON:</p> <p>"buyDetails" : [</p> |

| Data Type | JSON Type | Description |
|--------------------------|-------------------------|---|
| | | <pre>{ "orderID" : "OrderABC", "orderKeyDate": "20190419T000000", "side" : "B"}], "sellDetails" : [{"side" : "SL", "firmDesignatedID" : "Prop123", "accountHolderType" : "P"}]</pre> <p>When represented in CSV, refer to the following example:</p> <pre>,,,20190419T000000000@OrderABC@B@@@@.@@S@@Prop123@P@ ,,, Refer to Section 4.12.1 Table 38: Trade Side Details for the list of fields.</pre> |
| Fulfillment Side Details | Multi-Dimensional ARRAY | A compound object that consists of a list of data elements that represents firm side or customer/client side details of an Order Fulfillment. Refer to Section 4.13.1 Table 42: Fulfillment Side Details and Section 5.1.12.1 Table 75: Options Fulfillment Side Details for the list of fields. |
| Leg Details | Multi-Dimensional ARRAY | A compound object that consists of a list of data elements that represents one or more individual legs of a multi-leg option order as required on all Multi-Leg Option events. |
| Aggregated Orders | Multi-Dimensional ARRAY | <p>A compound object that consists of a list of data elements that represents one or more orders being aggregated. The <i>aggregatedOrders</i> field may include 0, 1, or more orders, with each order having a set of required data elements.</p> <p>For example, an <i>aggregatedOrders</i> will be presented as following in JSON:</p> <pre>"aggregatedOrders":[{"OrderID" : "O1234", "OrderKeyDate": "20190419T000000"}, {"OrderID" : "O1235", "OrderKeyDate" : "20190419T092316.123456789"}, {"OrderID" : "O1236", "OrderKeyDate" : "1483842600123450000", "Quantity" : "800"}]</pre> <p>When represented in CSV, refer to the following example:</p> <pre>,,,O1234@20190419T000000@@ O1235@20190419T092316.123456789@@ O1236@1483842600123450000@800@,,, </pre> <p>If the multi-dimensional array is blank, CSV must only contain the first level delimiter, the comma. Only comma acts as the place holder, the lower level delimiter '@' must not be added.</p> |

2.5.2. Required, Conditional, and Optional Fields

Throughout this document, event types and their fields will be defined. Each field will be notated with the abbreviation R, C, O or A to represent whether it is required, conditional, optional or applicable for ATSS only. This codification will appear in the last column of each table describing an event.

Table 4: Include Key

| Value | Abbreviation | Description |
|-------------|--------------|--|
| Required | R | Required for the given event. This field must always be included. |
| Conditional | C | Conditionally required for the given event, depending upon other values submitted in the Reportable Event message. |
| Optional | O | Optional for the given event. May be included at the discretion of the reporter/submitter. |
| ATS | A | Applicable for ATSS only. Required when the CAT Reporter IMID is an ATS. |

2.6. Linkage Overview

This section describes the Linkage Keys that are used to create lifecycles in CAT and explains how the Linkage Keys are constructed via different data elements in respective Reportable Events. When combined, these data elements must create a Linkage Key that is unique. All Reportable Events will be linked in CAT via the daisy chain approach and do not rely on timestamps or sequence in order to link events within a lifecycle.

2.6.1. CAT Linkage Keys

Below is the list of Linkage Keys that connect CAT events within an Industry Member and across Industry Members. In instances of a merger or acquisition, the *originatingIMID* will be used in place of the *CATReporterIMID* to support linkage.

Table 5: Linkage Keys

| Linkage Key | Description | Fields |
|-------------|--|--------|
| Order Keys | Duplication of Order Keys results in the rejection of all events with the same key | |

| Linkage Key | Description | Fields |
|---|---|--|
| Order Key | Links together the events of the same order, within an Industry Member. For example, Order Key links an Order Accepted event to a subsequent Order Route event. | <ul style="list-style-type: none"> • <i>orderKeyDate</i> • <i>CATReporterIMID</i> • <i>symbol</i> (or <i>optionID</i>) • <i>orderID</i> |
| Prior Order Key | Links modifications to the original order. For example, Prior Order Key links an Order Modified event to the previous Order Accepted event. | <ul style="list-style-type: none"> • <i>priorOrderKeyDate</i> • <i>CATReporterIMID</i> • <i>symbol</i> (or <i>optionID</i>) • <i>priorOrderID</i> |
| Parent Order Key | Links Child (Option) Order events and (Option) Order Internal Route Accepted events to the related parent order event. For example, links an Order Internal Route Accepted event to a parent New Order event. | <ul style="list-style-type: none"> • <i>parentOrderKeyDate</i> • <i>CATReporterIMID</i> • <i>symbol</i> (or <i>optionID</i>) • <i>parentOrderID</i> |
| Manual Order Key | Links an order event representing a duplicative electronic message to the previously reported order event representing the original manual order. | <ul style="list-style-type: none"> • <i>manualOrderKeyDate</i> • <i>CATReporterIMID</i> • <i>symbol</i> (or <i>optionID</i>) • <i>manualOrderID</i> |
| Trade, Fulfillment and Allocation Keys – Duplication of Trade and Fulfillment Keys results in the rejection of all events with the same key. Duplication of TRF Linkage Keys results in in unlinked errors for all records with the same key. | | |
| Trade Key | Links Trade events to related Trade Supplement events. | <ul style="list-style-type: none"> • <i>tradeKeyDate</i> • <i>CATReporterIMID</i> • <i>symbol</i> • <i>tradeID</i> |
| Fulfillment Key | Links CAT Order Fulfillment events to related Order Fulfillment Supplement events. Links CAT Order Fulfillment events to a related Fulfillment Amendment or Order event if the <i>fulfillmentID</i> remains the same. | <ul style="list-style-type: none"> • <i>fillKeyDate</i> • <i>CATReporterIMID</i> • <i>symbol</i> (or <i>optionID</i>) • <i>fulfillmentID</i> |
| Prior Fulfillment Key | Links an Order Fulfillment event to a related Order Fulfillment Amendment event if a new <i>fulfillmentID</i> is assigned. | <ul style="list-style-type: none"> • <i>priorFillKeyDate</i> • <i>CATReporterIMID</i> • <i>symbol</i> (or <i>optionID</i>) • <i>priorFulfillmentID</i> |
| TRF Linkage Key | Links the Trade event reported by the Industry Member to the related tape report in the TRF/ADF/ORF. | <ul style="list-style-type: none"> • <i>Event Date</i> • <i>CATReporterIMID</i> • <i>symbol</i> • <i>tapeTradeID</i> • <i>marketCenterID</i> |
| Allocation Key | Links CAT Post Trade Allocation events to related Amended Allocation events if the <i>allocationID</i> remains the same. | <ul style="list-style-type: none"> • <i>allocationKeyDate</i> • <i>CATReporterIMID</i> • <i>symbol</i> (or <i>optionID</i>) • <i>allocationID</i> |

| Linkage Key | Description | Fields |
|---|--|--|
| Prior Allocation Key | Links CAT Post Trade Allocation events to related Amended Allocation events if a new <i>allocationID</i> is assigned. | <ul style="list-style-type: none"> • <i>priorAllocationKeyDate</i> • <i>CATReporterIMID</i> • <i>symbol (or optionID)</i> • <i>priorAllocationID</i> |
| Quote Keys – Duplication of Quote Keys results in the rejection of all events with the same key | | |
| Quote Key | Links New Quote events reported by the Industry Member to related order or quote events. For example, links a Quote Received event to a related Quote Cancelled event. | <ul style="list-style-type: none"> • <i>quoteKeyDate</i> • <i>CATReporterIMID</i> • <i>symbol</i> • <i>quoteID</i> |
| Prior Quote Key | Links a quote event being modified to the previous quote. | <ul style="list-style-type: none"> • <i>priorQuoteKeyDate</i> • <i>CATReporterIMID</i> • <i>symbol</i> • <i>priorQuoteID</i> |
| IDQS Linkage Key | For trades executed as the result of a quote sent to an IDQS, links the Trade event reported by an Industry Member to the related Quote Received event reported by the IDQS. | Refer to Section 2.6.3 below for more detailed descriptions. |
| Route Linkage Keys – Duplication of Route Linkage Keys will result in unlinked errors for all records having the same key | | |
| Route Linkage Key | Links the CAT events reported by the Industry Member routing an order away and the Industry Member accepting the order. | Refer to Section 2.6.3 below for more detailed descriptions. |
| Quote Route Key | Links quote events reported by an Industry Member routing a quote to an IDQS and the IDQS receiving the quote. | Refer to see Section 2.6.3 below for more detailed descriptions. |

2.6.2. Reporting Responsibilities of Sender/Receiver

Industry Members are responsible for reporting routes, modifications, and cancellations to CAT. When modifying or cancelling orders, Industry Members are required to report any request received from a customer denoting the time that the request was received. Industry Members are not required to report requests to modify or cancel an order that were sent to another Industry Member broker-dealer or exchange. Separately, Industry Members are required to report a modification or cancel once the cancellation or modification was confirmed.

Below is a list of sample scenarios and the reporting responsibilities of the sender (Broker A) and the receiver (Broker B). This guidance is also applicable to the sender (Broker A) when routing to an Exchange instead of another Industry Member Broker-Dealer.

Table 6: Reporting Responsibilities of Sender/Receiver

| Scenario | Sender (Broker A) | | Receiver (Broker B or Exchange) | |
|---|---|---|---|----------------------------|
| | Action | CAT Report | Action | CAT Report |
| Routing an Order | | | | |
| Broker A routes an order to Broker B | Routes the order to Broker B | Order Route | Accepts the order from Broker A | Order Accepted |
| An Order routed from Broker A to Broker B is rejected by Broker B | Routes the order to Broker B | Order Route with <i>routeRejectedFlag</i> populated as 'true' | Rejects the order from Broker A | N/A |
| Modifying an Order | | | | |
| Customer/client requests to modify an order previously routed to Broker B | Receives the customer modification request and routes to Broker B | Order Modification Request and Order Route | Receives the request from Broker A | Order Modification Request |
| | Confirms the modification in OMS/EMS | Order Modified | Modifies the order received from Broker A | Order Modified |
| Broker A requests to modify an order previously routed to Broker B | Sends modification request to Broker B | Order Route | Receives the request from Broker A | Order Modification Request |
| | Confirms the modification in OMS/EMS | Order Modified | Modifies the order received from Broker A | Order Modified |
| Broker B modifies an order that was received from Broker A | <None> | N/A | Modifies the order from Broker A | Order Modified |
| Modifying a Route | | | | |
| Broker A requests to modify a route that was sent to Broker B | Sends modification request to Broker B | N/A | Receives the request from Broker A | Order Modification Request |
| | Confirms the modification in OMS/EMS | Order Route Modified | Modifies the order received from Broker A | Order Modified |
| Cancelling an Order | | | | |
| Customer/client requests to cancel an order that was previously routed to Broker B. | Receives the customer cancellation requests and sends to Broker B | Order Cancel Request | Receives the request from Broker A | Order Cancel Request |
| | Confirms the cancellation in OMS/EMS | Order Cancelled | Cancels the order from Broker A | Order Cancelled |
| Broker A requests to cancel an order that was previously routed | Sends cancel request to Broker B | N/A | Receives the request from Broker A | Order Cancel Request |

| Scenario | Sender (Broker A) | | Receiver (Broker B or Exchange) | |
|--|--|-----------------------|--|----------------------|
| | Action | CAT Report | Action | CAT Report |
| to Broker B | Confirms the modification in OMS/EMS | Order Cancelled | Cancelled the order received from Broker A | Order Cancelled |
| Broker B initiates a cancel of an order received from Broker A | <None> | N/A | Cancels the order from Broker A | Order Cancelled |
| Cancelling a Route | | | | |
| Broker A requests to cancel a route that was sent to Broker B | Sends cancellation request to Broker B | N/A | Receives the request from Broker A | Order Cancel Request |
| | Confirms the cancellation in OMS/EMS | Order Route Cancelled | Cancels the order received from Broker A | Order Cancelled |

2.6.3. Summary of Route and TRF Linkage Keys

Table 7 below summarizes the required data elements to construct the Route Linkage Key, which is used for linking Route and Order Accepted events reported by different entities in CAT. The combination of the data elements that make up the Route Linkage Key must be unique for the sender and receiver. When the Route Linkage Key is not unique, unlinked errors will be returned for all records having the same Route Linkage Key.

The *routedOrderID* field, which participates in the Route Linkage Key, is defined as a Text field and may **not** include the following characters which serve as delimiters: comma, pipe, double quote, and the @ symbol. When reporting to CAT in JSON, backslash is a reserved printable character and must be escaped in order to participate in the *routedOrderID*. If a backslash is used in the *routedOrderID* field and is not escaped when reporting in JSON, route linkage errors may occur. Refer to [Section 6.1.2.1](#) for additional guidance.

Table 7 below also summarizes the required data elements to construct the TRF Linkage Key, which is used for linking Trade events to the related tape report in the TRF/ADF/ORF. Industry Members may link to either the Reporting Side or the Contra Side of the related Trade Report. The combination of the data elements that make up the TRF Linkage Key must be unique. When the TRF Linkage Key is not unique, all events with the same TRF Linkage Key will be rejected.

For Participant related event details, refer to the [CAT Reporting Technical Specifications for Plan Participants](#).

Table 7: Summary of Route and TRF Linkage Keys

| Item | Description | Sender | Receiver |
|------|---|---------------------------|---|
| 1 | Routing Between Industry Members (IMs) | IM | IM |
| | | senderIMID | senderIMID |
| | | destination (IMID) | receiverIMID |
| | | Event Date | Event Date |
| | | symbol (or optionID) | symbol (or optionID) |
| | | routedOrderID* | routedOrderID* |
| 2 | Routing from an Industry Member to an Exchange | IM | Participant |
| | | senderIMID | routingParty |
| | | destination (Exchange ID) | exchange (Exchange ID) |
| | | Event Date | Event Date |
| | | session | session |
| | | routedOrderID* | routedOrderID |
| 3 | Routing from an Exchange to the Exchange Affiliated/Routing Broker | Participant | IM |
| | | exchange (Exchange ID) | senderIMID (Exchange ID) |
| | | routingParty | receiverIMID |
| | | Event Date | Event Date |
| | | symbol (or optionID) | symbol (or optionID) |
| | | routedOrderID | routedOrderID* |
| 4 | Routing from an Industry Member to a non-reporting Foreign Entity | IM | Foreign Broker-Dealer |
| | | No Linkage | |
| 5 | Routing a quote event from an Industry Member broker-dealer to an IDQS. | IM | IDQS |
| | | senderIMID | senderIMID |
| | | destination (IMID) | receiverIMID |
| | | Event Date | Event Date |
| | | symbol | symbol |
| | | routedQuoteID* | receivedQuoteID* |
| 6 | Trade is executed and reported to both CAT and the TRF/ADF/ORF | IM | TRF/ADF/ORF |
| | | Event Date | Event Date portion of Execution Timestamp |
| | | CATReporterIMID | Reporting or Contra MPIDs |
| | | symbol | symbol |
| | | tapeTradeID | Reporting or Contra Branch Sequence Number or Compliance ID |

| Item | Description | Sender | Receiver |
|------|---|-----------------|------------------|
| | | marketCenterID | Market Center ID |
| 7 | Trade is executed as a result of a quote sent to an IDQS and links to a Quote Received event reported by the IDQS | IM | IDQS |
| | | quotingIDQS | receiverIMID |
| | | CATReporterIMID | senderIMID |
| | | Event Date | Event Date |
| | | symbol | symbol |
| | | quoteID | quoteID |

* Not required for manual order route/receipt.

2.6.3.1. Routing Between Industry Members

The Route Linkage Key used to link events between Industry Members must be unique for the Event Date, *senderIMID*, *destination/receiverIMID*, *symbol/optionID* and *routedOrderID*. Session does not participate in the Route Linkage Key for routes between Industry Members when validating for uniqueness and when performing linkages.² These requirements apply to both the sending and receiving Industry Member.

Order linkage between industry members requires that the Route Linkage Key is equal between the sender and receiver. The sending and receiving firms must mutually agree on the IMID to be used if they have multiple SRO assigned IMIDs.

Example Route Linkage Key when routing between Industry Members: CAT Reporter ABCD (CRD 123) routes an order to DEFG (CRD 456). CAT Reporter DEFG receives the order. In this example, CAT Reporter ABCD uses the SRO assigned identifier of ABC when routing.

Table 8: Route Linkage Key Fields When Routing Between Industry Members

| Sender – MEOR | | Receiver – MEOA | |
|--|----------|--|----------|
| CATReporterIMID ABCD | | CATReporterIMID DEFG | |
| senderIMID | 123:ABC | senderIMID | 123:ABC |
| destination | 456:DEFG | receiverIMID | 456:DEFG |
| Event Date (portion of eventTimestamp) | 05012018 | Event Date (portion of eventTimestamp) | 05012018 |

² Industry Members commonly establish multiple connections or “sessions” between counterparties. If Industry Members have multiple points of connection or sessions established with counterparties, Industry Members should be aware that many common protocols (*i.e.* FIX), require unique order IDs on each order message per session. Industry Members should take proactive steps to ensure Route Linkage Key uniqueness when establishing additional trading sessions between counterparties.

| Sender – MEOR | | Receiver – MEOA | |
|---------------|----------|-----------------|----------|
| symbol | XYZ | symbol | XYZ |
| routedOrderID | ROID1234 | routedOrderID | ROID1234 |

2.6.3.2. Routing to Exchanges

The Route Linkage Key used to link Routes to Exchanges must be unique for the Event Date, *senderIMID/routingParty*, *destination/exchange*, *symbol/optionID*, *routedOrderID* and *session*. Session participates in the Route Linkage Key for routes to an Exchange; it is used when validating for uniqueness and when performing linkages. The *session* represents the name of the connection used when routing an order to a national securities exchange.

When routing to exchanges, the destination must be the Exchange ID to which the order is routed. The *senderIMID* must be populated with the prefix equal to the CRD of the routing firm, and the suffix equal to exchange assigned identifier that was used in the order route message to the exchange. The identifier populated in the suffix must equal the *routingParty* field value reported by the exchange on the Participant Order Accepted event. See [CAT Reporting Technical Specifications for Plan Participants](#) for more details.

The *senderIMID* in this scenario may be different from the *CATReporterIMID*. Refer to [Section 2.4.1.1](#) for additional guidance on how to populate the *CATReporterIMID* and *senderIMID*. This requirement is consistent with current OATS guidance, which requires that the Exchange Participant ID field is populated with the exchange identifier used when entering the order.

The *routedOrderID* is assigned to the order by the Industry Member when routing the order to the exchange. The *routedOrderID* field must be reported to CAT in the exact format as sent to the exchange. Firms should take note of each exchange's interface specifications regarding special characters, spaces and leading zeros as some exchange transmission protocols may remove certain characters, spaces or leading zeros. This field value must match the value for *routedOrderID* reported by the exchange in their Order Accepted event.

Example Route Linkage Key when routing to an Exchange: CAT Reporter ABCD (CRD 123) routes an order to Exchange EXCH. ABCD's SRO identifier at EXCH is ABC.

Table 9: Route Linkage Key Fields When Routing to an Exchange

| Sender – MEOR | | Receiver – EOA | |
|----------------------|---------|----------------|-----|
| CATReporterIMID ABCD | | Exchange EXCH | |
| senderIMID | 123:ABC | routingParty | ABC |

| Sender – MEOR | | Receiver – EOA | |
|--|----------|--|----------|
| destination | EXCH | exchange | EXCH |
| Event Date (portion of eventTimestamp) | 05012018 | Event Date (portion of eventTimestamp) | 05012018 |
| Symbol | XYZ | symbol | XYZ |
| routedOrderID | ROID1234 | routedOrderID | ROID1234 |

For additional information on the values to be provided based on the exchange the order is routed to and specific guidance related to each field required for Exchange Route Matching, refer to the [Order Routing Field Mapping](#) document published on the IM Technical Specifications page of the CAT Public Website.

2.6.3.3. Routing from an Exchange to the Exchange's Routing Broker

The Route Linkage Key used to link events between a route from an Exchange to the Exchange's Routing Broker must be unique for the Event Date, *exchange/senderIMID*, *routingParty/receiverIMID*, *symbol/optionID* and *routedOrderID*. Session does not participate in the Route Linkage Key for routes between an Exchange and the Exchange's Routing Broker when validating for uniqueness and when performing linkages.

When an Industry Member that is an exchange routing broker receives an order routed from the exchange, the *senderIMID* field must be the Exchange ID from which the order is received. Firms receiving an order from an exchange must populate the *receiverIMID* with the prefix equal to the CRD of the receiving firm, and the suffix equal to the identifier known by the exchange sending the order. The identifier populated in the suffix must equal the *routingParty* field value reported by the exchange on the Participant Order Route event. See [CAT Reporting Technical Specifications for Plan Participants](#) for more details.

The *receiverIMID* in this scenario may be different from the CAT Reporter IMID. Refer to [Section 2.4.1.1](#) for additional guidance on how to populate the CAT Reporter IMID.

Example Route Linkage Key when receiving an order from an Exchange: Routing Broker ABCD (CRD 123) receives an order from Exchange EXCH. ABCD's SRO identifier at EXCH is ABC.

Table 10: Route Linkage Key Fields When Receiving an Order From an Exchange

| Sender - EOR | Receiver – MEOA |
|---------------|----------------------|
| Exchange EXCH | CATReporterIMID ABCD |

| Sender - EOR | | Receiver – MEOA | |
|--|----------|--|----------|
| routingParty | ABC | receiverIMID | 123:ABC |
| exchange | EXCH | senderIMID | EXCH |
| Event Date (portion of eventTimestamp) | 05012018 | Event Date (portion of eventTimestamp) | 05012018 |
| Symbol | XYZ | Symbol | XYZ |
| routedOrderID | ROID1234 | routedOrderID | ROID1234 |

2.6.3.4. Routing to Foreign Destinations

When an order is routed to a foreign non-CAT-reporting entity, the *destinationType* must be marked as N (Foreign). When routing to a foreign non-CAT-reporting entity, there is no requirement to report *senderIMID*, *destination*, or *routedOrderID*, but an Industry Member may choose to populate these fields.

3. Special Reporting Requirements

3.1. Alternative Trading Systems (“ATS”) Reporting

ATSs are required to submit additional information in applicable CAT events. ATS fields must be populated if the *CATReporterIMID* is an ATS and the *symbol* is an NMS security. Any ATS fields, such as *workingPrice*, that are not applicable to the event must be populated by the ATS using a value of “0”. Industry Members that are not ATSs must leave these fields blank.

3.1.1. National Best Bid and Offer (NBBO)

ATSs are required to report NBBO information.

The NBBO must be reported to CAT from the perspective of the ATS. Specifically, the NBBO (or relevant reference price) reported must be the NBBO in effect at the time of the order event, and the timestamp of when the ATS captured the effective NBBO (or relevant reference price). In addition, the ATS must identify the market data feed (NBBO Source) it used to obtain the NBBO (or relevant reference price).

If another reference price, such as the primary market's BBO, is used by the ATS, then the applicable reference price must be reported instead of the NBBO. If there is no price, the ATS must populate the *nbbPrice* and *nboPrice* fields with a value of “0”.

While the *nbbQty* and *nboQty* fields are optional for ATSs, if an ATS chooses not to populate a quantity in these fields, they must be populated with a value of “0”.

FINRA Rule 4554 requires ATSs using an alternative NBBO feed from what was reported on its ATS data submission to notify FINRA of the fact that an alternative source was used, identify the alternative source, and specify the date(s), time(s) and securities for which the alternative source was used. In order to comply with FINRA Rule 4554 for the purpose of CAT reporting, Industry Members must submit an [ATS NBBO Source Change Form](#) via email to FINRA CAT. Instructions for submitting this form is posted to www.catnmsplan.com.

3.1.2. ATS Order Types

For events reported by ATSs, *atsOrderType* field is used to capture ATS-specific order types. The *orderType* and *atsOrderType* fields are not mutually exclusive; ATSs must populate both fields on applicable events. Industry Members that are not ATSs must leave the *atsOrderType* field blank.

ATSs must register their order types with CAT at least 20 business days prior to the order type becoming effective using the CAT Reporter Portal. An order type must be registered before any relevant CAT

events can be submitted. Specific instructions for registering *atsOrderTypes* are available in [CAT Alert 2019-01](#) on www.catnmsplan.com.

3.1.3. Sequence Number

ATSs must also provide a sequence number assigned by the ATS's matching engine on all events reported to CAT by the ATS. Industry Members that are not ATSs are not required to populate the *seqNum* field.

3.1.4. Display and Non-Display ATSs

ATSs are required to populate the *atsDisplayInd* indicating if the order is displayed outside of the ATS to subscribers only, or via publicly disseminated quotation data. If the order is displayed (*atsDisplayInd* = 'S', 'Y', or 'A'), the ATS is required to populate both the *displayPrice* and *displayQty* fields indicating the price and quantity at which the order was displayed. If the order is not displayed (*atsDisplayInd* = 'N'), the ATS is required to populate the *displayPrice* and *displayQty* fields with a value of '0'. Industry Members that are not ATSs must leave the *atsDisplayInd*, *displayPrice*, and *displayQty* fields blank.

3.1.5. CAT Reporter IMID

When reporting to CAT, Industry Members operating an ATS must populate the *CATReporterIMID* using their FINRA assigned ATS MPID.

3.2. Manual Orders

The CAT NMS Plan defines a Manual Order Event as “non-electronic communication of order-related information for which CAT Reporters must record and report the time of the event.” Manual CAT events must be marked as a manual event using the *manualFlag* field and must include an electronic capture time if the manual event is captured in an order management or execution system.

Proprietary orders (both equities and options) that are simultaneously entered into an OMS/EMS upon origination are always considered electronic.

3.2.1. Manually Received CAT Events Immediately Systematized

Orders which are non-electronically communicated but immediately systematized (e.g., a broker received a call and directly enters the order into the order management system) must be marked as a manual event using the *manualFlag*. In this scenario, the Industry Member is required to report both the manual

time of order receipt and the electronic capture time, and the same timestamp must be reported in both fields in milliseconds³.

Orders which are received or routed via instant message (IM) or email are considered manual events. Refer to [CAT FAQ C7](#) for additional information.

Refer to [Section G](#) of the CAT FAQs for additional information on manual orders.

3.2.2. Manual CAT Events Followed by Separate Electronic Messages

If an Industry Member routes or receives an order manually and then subsequently sends or receives an electronic message to represent the manual instruction, the following reporting requirements apply:

- All material terms and conditions of a manually received or routed order, including time of route and receipt, must be reported to CAT on the required manual event, with all relevant timestamps representing when the manual CAT event occurred.
- Additional electronic messages related to a manual order or route that do not change any material term or condition of the original order are not required to be reported to CAT as they represent a duplicate of the original order.
- If the duplicate electronic message includes a routed order identifier that could be used to link the sender's route report to the receiver's new order, and the member has the ability to include this electronic information on the manual event (referred to as a "merged" event), the Industry Member must do so.
- If the Industry Member is not able to merge the manual and electronic information in a single manual event and elects to report the duplicate electronic message independently, such messages must be reported with the *electronicDupFlag* populated as *true*, and the *manualFlag* populated as *false*. Further, the *manualOrderID* may be populated with the *orderID* of the original manual order.

3.2.3. Manual Trade events and Order Fulfillment events

Trade events and Order Fulfillment events must be marked as either manual or electronic using the *manualFlag* field.

A Trade event is considered manual when the trade is executed outside of an OMS/EMS and must be manually entered before it can be trade reported. The time of execution populated in the *eventTimestamp*

³ Refer to [CAT FAQ G4](#) for additional information.

field is the time all terms and conditions were agreed to between the two parties, consistent with SRO and SEC rules.

An Order Fulfillment event is considered manual if the fill of the customer order occurred outside of an OMS/EMS and was manually entered into an electronic system. The fulfillment time populated in the *eventTimestamp* field would be the time the firm gave the fill to the order. If a trader manually “drags and drops” or “clicks” in an OMS to fill an order, the time of the trader’s action would be the fulfillment time, and the Order Fulfillment event could be considered either manual or electronic.

3.3. Allocation Events

3.3.1. Definition and Requirements

The CAT NMS Plan defines an Allocation Report as “a report made to the Central Repository by an Industry Member that identifies the Firm Designated ID for any account(s), including subaccount(s), to which executed shares are allocated”. This includes the placement of shares/contracts into the same account for which an order was originally placed, and the placement of shares/contracts into an account based on allocation instructions (e.g., subaccount allocations). In accordance with the CAT NMS Plan, allocation events are not be required to be linked to particular orders or executions.

Allocation events must be reported to CAT for all allocations to a client account, including DVP account allocations. Allocations to accounts other than a client account (e.g. proprietary accounts, step outs, correspondent flips) may optionally be reported to CAT, but must be appropriately marked in the *allocationType* field.

3.3.2. Reporting Obligation

The CAT reporting obligation for allocation events is separate and distinct from other CAT events defined in this document. While the CAT reporting obligation for other CAT events belongs to the firm receiving or originating the order, the CAT reporting obligation for allocation events belongs to the firm performing the allocation, which is generally the clearing or self-clearing firm processing the allocation.

The firm with the reporting obligation for New Order events must register the FDIDs it uses for new order reporting, and the firm with the reporting obligation for allocation events report must register the FDIDs it uses for allocation reporting.

3.4. Responses to RFQs and Solicitation

3.4.1. Scope

While Industry Members are not required to report Requests for Quotes (“RFQs”) to CAT, Industry Members are required to report responses to RFQs and other forms of solicitation as described in [CAT FAQ B45](#).

Responses communicated in standard electronic format (i.e. FIX) are reportable by both the CAT Reporter issuing the RFQ or solicitation (“the solicitor”) and the CAT Reporter responding to the RFQ solicitation (“the responder”), including responses that were not ultimately selected. These requirements apply to both equities and options activity.

Responses communicated through third party vendor RFQ platforms not operated by a broker-dealer that are not communicated in standard electronic format directly to the Solicitor who is a CAT Reporter are not considered electronic for CAT Reporting purposes and are not required to be reported to CAT in Phase 2d. However, this activity may be required in future phases of CAT.

Table 11: Reporting Responsibilities of Responder and Solicitor

| Scenario | Responder | | Solicitor | |
|--|--|--------------------------|---|---|
| Response is reportable | | | | |
| Response is communicated through third party vendor RFQ platform operated by a broker-dealer | New Order with <i>solicitationFlag</i> as ‘true’ | Order Route to Solicitor | Order Accepted for all responses received | Any subsequent actions taken on the winning order |
| Response is communicated directly to Solicitor in standard electronic format (i.e. FIX), and no additional action is required by the Responder | New Order with <i>solicitationFlag</i> as ‘true’ | Order Route to Solicitor | Order Accepted for all responses received | Any subsequent actions taken on the winning order |
| Response is not reportable | | | | |
| Response is communicated through third party vendor RFQ platform <u>not</u> operated by a broker-dealer | N/A | N/A | New Order with <i>solicitationFlag</i> as ‘true’ for winning response | Any subsequent actions taken on the winning order |
| Response is communicated manually (e.g. phone or IM) | N/A | N/A | New Order with <i>solicitationFlag</i> as ‘true’ for winning response | Any subsequent actions taken on the winning order |
| Response is communicated directly to Solicitor in standard electronic format (i.e. FIX), but additional action is required by the winning Responder before an order can be generated | N/A | N/A | New Order with <i>solicitationFlag</i> as ‘true’ for winning response | Any subsequent actions taken on the winning order |

3.4.2. Reporting

If an RFQ or solicitation response was provided as an order, the responder must report its response to CAT using a New Order event and Order Route event to the solicitor. The solicitor must report the receipt of each response using an Order Accepted event.

If an RFQ or solicitation response was provided as a quote, the response would be reported to CAT using quote events. However, FINRA CAT is unaware of any workflows meeting this criteria that fall within the scope for Phase 2d reporting outlined in [Section 3.4.1](#).

Industry Members are not required to report cancellation events for responses to an RFQ or solicitation that were ultimately not selected and the *solicitationFlag* is correctly populated as *true*.

3.5. Multi-Leg Option Orders and Paired Orders

Paired Orders are defined for CAT reporting purposes as orders that contain both the buy and sell side that are routed to another Industry Member or exchange for crossing and/or price improvement. Orders routed or received as a pair must be reported to CAT, and all Order Route, Option Order Route, and Multi-Leg Order Route events routed in the pair must be identified using a *pairedOrderID*.

Paired Orders Do Not Include:

- Orders that are not treated as a paired order by the recipient such as “post and wait”
- Preferenced or directed orders that do not contain both the buy side and the sell side

Multi-Leg orders must be reported using Multi-Leg Order events as defined in [Section 5.2](#).

4. Equity Events

This section describes Reportable Events for equities that are Eligible Securities. The following table lists each equity event type with its corresponding Message Type code.

Fields specified as Reserved for Future Use are also greyed out and must remain blank. Future enhancements to Message Types with positions that are Reserved for Future Use will occupy the available position before adding a new position.

Table 12: Equity Events

| Sec | Event | Message Type | Description |
|-------|--------------------------------|--------------|--|
| 4.1 | New Order Event | MENO | Reported when an Industry Member originates an order, receives a customer order, originates a bunched, representative or proprietary order, or receives an order from a non-reporting foreign entity. |
| 4.2 | New Order Supplement Event | MENOS | Supplement to the New Order event, used when the New Order event exceeds the maximum length allowed, or when the orders being represented are not captured in the New Order Event. Also used to provide an FDID once known if not available at time of reporting a MENO. |
| 4.3 | Order Route Event | MEOR | Reported when an Industry Member routes an order to another broker-dealer, exchange or ATS. |
| 4.3.1 | Order Route Modified | MEMR | Reported when an Industry Member modifies a route that was sent to another broker-dealer, exchange or ATS |
| 4.3.2 | Order Route Cancelled | MECR | Reported when an Industry Member cancels a route that was sent to another broker-dealer, exchange or ATS |
| 4.3.3 | Order Route Supplement Event | MEORS | Supplement to the Order Route event, optionally used when the status of the <i>routeRejectedFlag</i> is not reported on the MEOR event itself, because the firm chooses to report it using this separate event created at a later time. |
| 4.4 | Order Accepted | MEOA | Reported when an Industry Member, including an ATS, accepts a routed order that originated at another broker-dealer. |
| 4.5.1 | Order Internal Route Accepted | MEIR | Reported when an order moves within an Industry Member to another desk or other department. |
| 4.5.2 | Order Internal Route Modified | MEIM | Reported when an Order Internal Route Accepted was modified. |
| 4.5.3 | Order Internal Route Cancelled | MEIC | Reported when an Order Internal Route Accepted was cancelled. |

| Sec | Event | Message Type | Description |
|--------|---|--------------|--|
| 4.5.4 | Order Internal Route Modification Request | MEIMR | Reported when a modification to an internal route was requested. |
| 4.5.5 | Order Internal Route Cancel Request | MEICR | Reported when the cancellation of an internal route was requested. |
| 4.6.1 | Child Order | MECO | Reported when an order is sliced within the desk or department it is being worked, and is assigned a new order identifier. |
| 4.6.2 | Child Order Modified | MECOM | Reported when a Child Order is modified. |
| 4.6.3 | Child Order Cancelled | MECOC | Reported when a Child Order is cancelled. |
| 4.7 | Order Modified | MEOM | Reported when changes to the Material Terms of an order are made, or an order is cancel/replaced. |
| 4.7.1 | Order Modification Request | MEOMR | Reported when a customer has requested the modification of an order. |
| 4.8 | Order Modified Supplement Event | MEOMS | Supplement to the Order Modified event, used when the Order Modified event exceeds the maximum length allowed, or when the orders being represented are not captured in the Order Modified Event. |
| 4.9 | Order Adjusted | MEOJ | Used to report simple order modifications including changes to the price or quantity of the order. |
| 4.10 | Order Cancelled | MEOC | Reported when an Industry Member fully or partially cancels an order. |
| 4.10.1 | Order Cancel Request | MEOCR | Reported when a customer has requested the cancellation of an order. |
| 4.11 | New Quote | MENQ | Reported when quotations on equity Eligible Securities sent to a quote display facility or quote driven ATS, or a quote sent to a customer or broker-dealer that resulted in a trade. |
| 4.11.2 | Quote Received | MEQR | Reported when a quote is received by an Industry Member. |
| 4.11.3 | Quote Cancelled | MEQC | Reported when a quote is cancelled. |
| 4.12.1 | Trade Event | MEOT | Reported by the executing venue where the trade occurred, with details associated with each side of the trade. |
| 4.12.2 | Trade Supplement Event | MEOTS | Reported when there is more than one order associated with one side of a trade. |
| 4.13.1 | Order Fulfillment | MEOF | Reported when the execution of a customer/client order is not required to be reported for public dissemination. The event includes details associated with the client/customer side and firm side. |
| 4.13.2 | Order Fulfillment Supplement | MEOFS | Reported when there is more than one representative proprietary order associated with the fill of a customer order. |
| 4.13.3 | Order Fulfillment | MEFA | Reports the amendment of a previously |

| Sec | Event | Message Type | Description |
|--------|-----------------------|--------------|--|
| | Amendment | | reported fulfillment, including the full restatement of the event with applicable changes represented. |
| 4.14.1 | Post Trade Allocation | MEPA | Reported when executed shares are allocated to end customer accounts during post-trade processing. |
| 4.14.2 | Amended Allocation | MEAA | Reported when an amendment occurs to a previously reported post trade allocation. |
| 4.15 | Order Effective | MEOE | Reported when an order or an underlying condition of an order becomes effective. |

4.1. New Order Event

New Order events represent the beginning of the order lifecycle in CAT. An Industry Member must report a New Order event to CAT when an order is received or originated including:

- New customer orders
- Representative orders
- Proprietary orders
- Order(s) received from a foreign broker-dealer or affiliate that is not a CAT Reporter.

An order received from another CAT Reporter (US broker-dealer, ATS or an exchange) must be reported as an Order Accepted event.

Representative Orders

Industry Members are required to link representative street-side orders with the related customer order or client order being represented. The Industry Member must report a New Order event for the creation of the representative order, and populate the *representativeInd* field to indicate that it is a representative order. The Industry Member must also populate the *aggregatedOrders* field linking the representative order to the underlying orders.

Appendix C contains detailed descriptions of representative order scenarios and illustrates when marking of the representative order, linkage between the represented order and the representative order, and Order Fulfillment linkage is required.

Table 13: New Order Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MENO | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The internal order ID assigned to the order by the Industry Member. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | eventTimestamp | Timestamp | The date/time of receipt of the order. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 10 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is received or captured manually. | R |
| 11 | electronicDupFlag | Boolean | Indicates whether this is a duplicative electronic message of a manual event. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 13 | manualOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the related manual order. Required when <i>manualOrderID</i> is populated. | C |
| 14 | manualOrderID | Text (64) | When this is a duplicative electronic message of a previously (separately) reported manual New Order event, this field is to capture the internal <i>orderID</i> of the manual order. Required when <i>electronicDupFlag</i> is <i>true</i> . | C |
| 15 | deptType | Choice | This is the category of internal department, | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|---|----------------------|-------------------|---|-------------|
| | | | unit or desk originating or receiving the order. | |
| 16 | solicitationFlag | Boolean | Indicates if the order was originated in response to an RFQ or other solicitation process. This field is not used to indicate if a registered representative of the firm solicited a client order. | R |
| 17 | RFQID | Text (64) | For New Order events representing a response to an RFQ or solicitation, the ID assigned to the related RFQ or solicitation being responded to. Must be populated when available. | C |
| 18 | side | Choice | The side of the order. | R |
| 19 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 20 | quantity | Real Quantity | The order quantity. | R |
| 21 | minQty | Whole Quantity | The minimum quantity of an order to be executed, required when applicable. Must be > 0. | C |
| 22 | orderType | Choice | The type of order being submitted. | R |
| 23 | timeInForce | Name/Value Pairs | The time-in-force for the order. | R |
| 24 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 25 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 26 | custDsplIntrFlag | Boolean | Indicates if a customer has instructed that a limit order should not be displayed or that a block size order should be displayed. | R |
| 27 | firmDesignatedID | Text (40) | Refer to the Data Dictionary for definition and guidance for populating this field. | R |
| 28 | accountHolderType | Choice | Represents the type of beneficial owner of the account for which the order was received or originated. | R |
| 29 | affiliateFlag | Boolean | Indicates if the routing party is an affiliate of the Industry Member. | R |
| 30 | infoBarrierID | Text (20) | Specifies the identifier of the information barrier in place for a trading unit that will meet the criteria of the "no-knowledge" exception in FINRA Rule 5320.02. Any alphanumeric not containing a delimiter. | C |
| 31 | aggregatedOrders | Aggregated Orders | When applicable, the order ID of each customer order being represented. Refer to Appendix C for representative order linkage requirements. | C |
| <p>Aggregated Orders – Start</p> <p>For each order being represented <i>n</i>, the following values are required.</p> | | | | |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------------------------|---------------------|-------------------|--|-------------|
| 31.n.1 | orderID | Text (64) | <i>orderID</i> of the order being represented. | R |
| 31.n.2 | orderKeyDate | Timestamp | <i>orderKeyDate</i> of the order being represented. | R |
| 31.n.3 | quantity | Real Quantity | Required when a partial quantity of the order is being represented. | C |
| 31.n.4 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| Aggregated Orders – End | | | | |
| 32 | negotiatedTradeFlag | Boolean | Indicates whether the trade is a result of a negotiation. | R |
| 33 | representativeInd | Choice | Indicates if the order is a representative order and if linkage is required. | R |
| 34 | seqNum | Alphanumeric (40) | The sequence number assigned to the CAT event by the ATS's matching engine. Any alphanumeric not containing a delimiter. Only required for ATSs. | A |
| 35 | atsDisplayInd | Choice | Indicates if the order is displayed outside of the ATS to subscribers only, or via publicly disseminated quotation data. | A |
| 36 | displayPrice | Price | The displayed price for this order. If <i>atsDisplayInd</i> is populated as 'Y', 'S', or 'A', <i>displayPrice</i> must be the price at which the order was displayed. If the <i>atsDisplayInd</i> is 'N', <i>displayPrice</i> must be "0". | A |
| 37 | workingPrice | Price | The working price of the order at the time it was accepted. If no current <i>workingPrice</i> , value must be "0". | A |
| 38 | displayQty | Whole Quantity | The displayed quantity for this order. If the <i>atsDisplayInd</i> is populated as 'Y', 'S', or 'A', <i>displayQty</i> must be the quantity at which the order was displayed. If the <i>atsDisplayInd</i> is 'N', <i>displayQty</i> must be "0". | A |
| 39 | atsOrderType | Array | Shows the ATS-specific order type as selected from a list of order types defined by this reporter via the CAT Reporter Portal. | A |
| 40 | nbbPrice | Price | The NBBO at the moment the order was originated or received. Prices are required, quantities are optional. If no price or quantity, fields must be populated with a value of '0'. | A |
| 41 | nbbQty | Whole Quantity | | A |
| 42 | nboPrice | Price | | A |
| 43 | nboQty | Whole Quantity | | A |
| 44 | nbboSource | Choice | Source of the NBBO data used. If <i>nbboSource</i> is 'NA', NBBO price and quantity fields must be populated with a value of '0' and the <i>nbboTimestamp</i> must be blank. | A |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------|-----------|---|-------------|
| 45 | nbboTimestamp | Timestamp | The date/time at which the NBBO was referenced upon the receipt of the order. Must be blank if <i>nbboSource</i> is 'NA'. | A |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate, CATReporterIMID, symbol, orderID*
- Order Key: *aggregatedOrders.orderKeyDate, CATReporterIMID, symbol, aggregatedOrders.orderID*
- Manual Order Key: *manualOrderKeyDate, CATReporterIMID, symbol, manualOrderID*

4.2. New Order Supplement Event

The New Order Supplement event is a supplement to the New Order event. One New Order event can have multiple New Order Supplement events. Multiple New Order Supplement events are considered as additions, not replacements or modifications.

This event accommodates reporting in the following scenarios:

Aggregated Orders

This event accommodates reporting in scenarios when the number of Aggregated Orders included in the *aggregatedOrders* field causes the New Order event to exceed the maximum allowed message length, or when the orders being represented are not captured in the New Order Event. The *aggregatedOrders* field in the New Order Supplement event must contain the additional Aggregated Orders that were not captured in the original New Order event, or another Supplement event for the same order.

FDID

This event accommodates reporting in scenarios when an Industry Member receives an order for a new account and the new account number, on which the FDID is based, is not yet available for creation and reporting of the CAT new order event. If an FDID has not yet been created when an order has been received, the Industry Member must populate the *firmDesignatedID* field in its New Order event with a value of 'PENDING'.

Once the FDID becomes available, the Industry Member must report the actual FDID in the *firmDesignatedID* field in a New Order Supplement event. Any New Order Supplement event with an FDID populated will not be considered late for CAT reporting purposes if it is received by 8AM on T+3.

Table 14: New Order Supplement Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|--|------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MENOS | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the related New Order event which this event is Supplementing. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the related New Order event which this event is Supplementing. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time of the related New Order event which this event supplements (including scenarios in which the supplement is created at a later time). | R |
| 11 | aggregatedOrders | Aggregated Orders | When applicable, the order ID of each customer order being represented. Refer to Appendix C for representative order linkage requirements. | C |
| Aggregated Orders – Start | | | | |
| For each order being represented <i>n</i> , the following values are required. | | | | |
| 11.n.1 | orderID | Text (64) | <i>orderID</i> of the order being represented. | R |
| 11.n.2 | orderKeyDate | Timestamp | <i>orderKeyDate</i> of the order being represented. | R |
| 11.n.3 | quantity | Real Quantity | Required when a partial quantity of the order is being represented. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------------------------|------------------|-------------------|--|-------------|
| 11.n.4 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| Aggregated Orders – End | | | | |
| 12 | firmDesignatedID | Text (40) | Required when reporting a supplement to an MENO event that was reported prior to the FDID being available. Refer to the Data Dictionary for definition and guidance for populating this field. | C |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate, CATReporterIMID, symbol, orderID*
- Order Key: *aggregatedOrders.orderKeyDate, CATReporterIMID, symbol, aggregatedOrders.orderID*

4.3. Order Route Event

Industry Members are required to report an Order Route event to CAT in the following scenarios when an order is routed in full or in part:

- Routing to another Industry Member
- Routing to foreign broker-dealers
- Routing to exchanges
- Routing between two IMIDs (e.g. two different FINRA MPIDs) attributed to the same legal entity (i.e. the same CRD).

When routing between two IMIDs of the same legal entity, the *affiliateFlag* must be populated as *true* in accordance with [CAT FAQ E27](#). Internal routes to another desk or department within an Industry Member are reported using an Order Internal Route Accepted event. Refer to the [Order Internal Route Accepted](#) section for more details.

Handling Instructions on Order Route Events

Handling Instructions are required to be reported on the Order Route event. The handling instructions included in this event must represent the handling instructions sent by the routing firm to the receiving

destination. If the handling instructions do not change when the order is routed from the handling instructions received by the Industry Member and reported on the Order Accepted or New Order associated with the order, Industry Members may use the handling instruction code "RAR" (Routed as Received) instead of repeating each individual handling instruction.

Table 15: Order Route Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEOR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the event which is being routed. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the order event which is being routed. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time of the Order Route. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is routed manually. | R |
| 12 | electronicDupFlag | Boolean | Indicates whether this is a duplicative electronic message of a manual event. | R |
| 13 | electronicTimestamp | Timestamp | The time at which the event is systematized. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|----------------------------------|--|-------------|
| | | | Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | |
| 14 | senderIMID | Industry Member ID | <p>The IMID used to identify the Industry Member that is routing the order, known by the destination.</p> <p>When <i>destinationType</i> is 'F', this value must equal the <i>senderIMID</i> on the Order Accepted event reported by the destination.</p> <p>When <i>destinationType</i> is 'E', this value must equal the <i>routingParty</i> reported by the exchange on the Participant Order Accepted event.</p> <p>Not required when <i>destinationType</i> is 'N'.</p> | C |
| 15 | destination | Industry Member ID / Exchange ID | <p>When <i>destinationType</i> is 'F', this value is the IMID used to identify the Industry Member that is receiving this routed order, and it must equal the <i>receiverIMID</i> field on the Order Accepted event reported by the destination Industry Member.</p> <p>When <i>destinationType</i> is 'E', this value is the Exchange ID of the destination exchange, and it must equal the <i>exchange</i> field on the Order Accepted event reported by the destination exchange.</p> <p>Not required if <i>destinationType</i> is 'N'.</p> | C |
| 16 | destinationType | Choice | Indicates whether the destination of the route is an Industry Member, an exchange or a foreign broker-dealer. | R |
| 17 | routedOrderID | Text (64) | <p>The ID assigned to the order by the Industry Member when routing the order to the destination. This value must match the value for <i>routedOrderID</i> reported by the destination in their Order Accepted report.</p> <p>Must be unique per combination of Event Date, symbol, <i>destination</i>, <i>senderIMID</i>, and <i>session</i> (applicable only on routes to exchanges).</p> <p>Required when <i>destinationType</i> is 'F' or 'E' and <i>manualFlag</i> is <i>false</i>.</p> | C |
| 18 | session | Text (40) | <p>The session ID used when routing the order.</p> <p>Must only be populated when <i>destinationType</i> is 'E'. This must match the session ID reported in the Participant Order Accepted event by the receiving exchange.</p> | C |
| 19 | side | Choice | The side of the order. | R |
| 20 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 21 | quantity | Real Quantity | The order quantity. | R |
| 22 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required when applicable. Must be | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|-------------------|--|-------------|
| | | | > 0. | |
| 23 | orderType | Choice | The type of order being routed. | R |
| 24 | timeInForce | Name/Value Pairs | The Time-in-Force for the order. | R |
| 25 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 26 | affiliateFlag | Boolean | Indicates if the order is being routed to an affiliate of the Industry Member. | R |
| 27 | isInd | Choice | Indicates the order was routed as an Intermarket Sweep Order. | R |
| 28 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 29 | routeRejectedFlag | Boolean | Indicates the routed order was not accepted by the destination (rejected or no response) when marked <i>true</i> . | R |
| 30 | dupROIDCond | Boolean | Indicates when a modification to an order previously routed to a national securities exchange requires the use of the original <i>routedOrderID</i> . This field can only be populated as <i>true</i> on Order Route events when <i>destinationType</i> is 'E'. | R |
| 31 | seqNum | Alphanumeric (40) | The sequence number assigned to the CAT event by the ATS's matching engine. Any alphanumeric not containing a delimiter. | A |
| 32 | multiLegInd | Boolean | Indicates when the order being routed is related to a multi-leg order event. Refer to Section 5.2 for additional guidance. | R |
| 33 | pairedOrderID | Text (64) | If the order was routed as a pair, the internal identifier assigned to all orders included in the paired route. | C |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*
- Route Linkage Key: Event Date, *senderIMID*, *destination*, *symbol*, *session*, *routedOrderID*

4.3.1. Route Modified Event

Industry Members must report a Route Modified event to CAT when the Material Terms of a route have been changed (e.g., price, quantity), or when a route is cancel/replaced, and the Material Terms of the order have not changed. Route Modified events maintain the same *orderID* as the original Order Route event.

All attributes and Material Terms of the route listed on this event must be restated with the modification(s) reflected. The *side* field is required to be reported, but side adjustments are only allowed for same-side changes, including changes between Short Sale and Sell Long. Route Modified events must not be used to reflect a change in *senderIMID*, *destination*, or *destinationType*. These changes must be reflected as a Route Cancelled event followed by a new Order Route event.

The *routedOrderID* of the Order Route event being modified must be reflected in the Route Modification event. If the *routedOrderID* changed when the route was modified, the *routedOrderID* of the Order Route event being modified must be populated in the *priorRoutedOrderID* field. If the *routedOrderID* did not change when the route was modified, the *routedOrderID* of the Order Route event must be populated in the *routedOrderID* field, and the *dupROIDCond* must be populated as true.

If a route modification request is rejected by the destination venue, the Route Modification event must be reported with a *routeRejectedFlag* of true.

Table 16: Route Modification Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEMR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the route which is being modified. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the route which is being modified. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|----------------------------------|---|-------------|
| | | | surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | |
| 10 | eventTimestamp | Timestamp | The date/time the route was modified (e.g., the time that the order was confirmed to be modified in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the route is modified manually. | R |
| 12 | senderIMID | Industry Member ID | The IMID used to identify the Industry Member that is routing the modification, known by the destination. Must equal the <i>senderIMID</i> on the Order Route event being modified. When <i>destinationType</i> is 'F', this value must equal the <i>senderIMID</i> on the Order Accepted event reported by the destination. When <i>destinationType</i> is 'E', this value must equal the <i>routingParty</i> reported by the exchange on the Participant Order Accepted event. Not required when <i>destinationType</i> is 'N'. | C |
| 13 | destination | Industry Member ID / Exchange ID | The <i>destination</i> of the route modification. Must equal the <i>destination</i> on the Order Route event being modified. When <i>destinationType</i> is 'F', this value is the IMID used to identify the Industry Member that is receiving this routed order. Must equal the <i>receiverIMID</i> field on the Order Accepted event reported by the destination Industry Member. When <i>destinationType</i> is 'E', this value is the Exchange ID of the destination exchange, and it must equal the <i>exchange</i> field on the Order Accepted event reported by the destination exchange. Not required if <i>destinationType</i> is 'N'. | C |
| 14 | destinationType | Choice | Indicates whether the destination of the route modification is an Industry Member, an exchange or a foreign broker-dealer. Must equal the <i>destinationType</i> on the Order Route event being modified. | R |
| 15 | routedOrderID | Text (64) | The ID assigned to the order by the Industry Member when routing the modification to the destination. Must be unique per combination of Event Date, symbol, <i>destination</i> , <i>senderIMID</i> , and <i>session</i> (applicable only on routes to exchanges). Required when <i>destinationType</i> is 'F' or 'E' | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|-------------------|---|-------------|
| | | | and <i>manualFlag</i> is false. | |
| 16 | priorRoutedOrderID | Text (65) | The <i>routedOrderID</i> of the Order Route event being modified if the <i>routedOrderID</i> changed when the modification was routed to the destination. | C |
| 17 | session | Text (40) | The session ID used when routing the modification. Must be equal to the <i>session</i> on the Order Route event being modified Must only be populated when <i>destinationType</i> is 'E'. This must match the session ID reported in the Participant Order Accepted event by the receiving exchange. | C |
| 18 | side | Choice | The side of the order. For this Reportable Event, only same-side adjustments are allowed (e.g., sell long to short sell). | R |
| 19 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 20 | quantity | Real Quantity | The order quantity. | R |
| 21 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required when applicable. Must be > 0. | C |
| 22 | leavesQty | Real Quantity | The quantity left open after the modification event. Must be less than or equal to <i>quantity</i> . The full cancel will result in zero in this field. | R |
| 23 | orderType | Choice | The type of order being routed. | R |
| 24 | timeInForce | Name/Value Pairs | The Time-in-Force for the order. | R |
| 25 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 26 | affiliateFlag | Boolean | Indicates if the order is being routed to an affiliate of the Industry Member. | R |
| 27 | isoInd | Choice | Indicates the order was routed as an Intermarket Sweep Order. | R |
| 28 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 29 | routeRejectedFlag | Boolean | Indicates the route modification was not accepted by the destination (rejected or no response) when marked <i>true</i> . | R |
| 30 | dupROIDCond | Boolean | Indicates when a modification to a route previously routed to a national securities exchange requires the use of the original <i>routedOrderID</i> . This field can only be populated as <i>true</i> on Order Route events when <i>destinationType</i> is 'E'. | R |
| 31 | seqNum | Alphanumeric (40) | The sequence number assigned to the CAT event by the ATS's matching engine. Any alphanumeric not containing a delimiter. | A |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*
- Route Linkage Key: Event Date, *senderIMID*, *destination*, *symbol*, *session*, *routedOrderID*

4.3.2. Route Cancelled Event

Industry Members must report a Route Cancelled event to CAT when a route has been fully or partially cancelled, but the order remains open on the firm's books and records. Partial cancellations of a route may be reported to CAT using a Route Cancelled event or a Route Modified event.

The *routedOrderID* of the Order Route event being cancelled must be reflected in the Route Cancelled event. If a route cancellation request is rejected by the destination venue, the Route Cancelled event must be reported with a *routeRejectedFlag* of true.

Table 17: Order Route Cancelled Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MECR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the route which is being cancelled. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the route which is being cancelled. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|----------------------------------|--|-------------|
| | | | linkage to an event that was reported with a different <i>CATReporterIMID</i> . | |
| 10 | eventTimestamp | Timestamp | The date/time the route was cancelled (e.g., the time that the route was confirmed to be cancelled in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the route being cancelled was a manual route. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 13 | cancelQty | Real Quantity | The quantity being cancelled. | R |
| 14 | leavesQty | Real Quantity | The quantity left open after the cancel event. Must be less than or equal to <i>quantity</i> . The full cancel will result in zero in this field. | R |
| 15 | senderIMID | Industry Member ID | The IMID used to identify the Industry Member that is routing the cancellation, known by the destination. Must equal the <i>senderIMID</i> in the Order Route event being cancelled. When <i>destinationType</i> is 'F', this value must equal the <i>senderIMID</i> on the Order Accepted event reported by the destination. When <i>destinationType</i> is 'E', this value must equal the <i>routingParty</i> reported by the exchange on the Participant Order Accepted event. Not required when <i>destinationType</i> is 'N'. | C |
| 16 | destination | Industry Member ID / Exchange ID | When <i>destinationType</i> is 'F', this value is the IMID used to identify the Industry Member that is routed order. Must equal the <i>destination</i> in the Order Route event being cancelled. Must equal the <i>receiverIMID</i> field on the Order Accepted event reported by the destination Industry Member. When <i>destinationType</i> is 'E', this value is the Exchange ID of the destination exchange, and it must equal the <i>exchange</i> field on the Order Accepted event reported by the destination exchange. Not required if <i>destinationType</i> is 'N'. | C |
| 17 | destinationType | Choice | Indicates whether the destination of the original Order Route event was an Industry Member, an exchange or a foreign broker-dealer. | R |
| 18 | routedOrderID | Text (64) | The ID assigned to the Order Route event being cancelled. This value must match the | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|-------------------|---|-------------|
| | | | value for <i>routedOrderID</i> reported by the destination in their Order Accepted report. Must be unique per combination of Event Date, symbol, <i>destination</i> , <i>senderIMID</i> , and <i>session</i> (applicable only on routes to exchanges). Required when <i>destinationType</i> is 'F' or 'E' and <i>manualFlag</i> is <i>false</i> . | |
| 19 | session | Text (40) | The session ID used when routing the order. Must equal the <i>session</i> in the Order Route event being cancelled. Must only be populated when <i>destinationType</i> is 'E'. This must match the session ID reported in the Participant Order Accepted event by the receiving exchange. | C |
| 20 | seqNum | Alphanumeric (40) | The sequence number assigned to the CAT event by the ATS's matching engine. Any alphanumeric not containing a delimiter. | A |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*

4.3.3. Order Route Supplement Event

The Order Route Supplement event is a supplement to the Order Route event. Order Route Supplement events are considered as additions to an Order Route event, not replacements or modifications. This event accommodates reporting in scenarios where a route is rejected by the venue to which an order was routed, and the Industry Member chooses to report the *routeRejectedFlag* in this separate Order Route Supplement event created at a later time on the same day.

Table 18: Order Route Supplement Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|-----------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|----------------------------------|---|-------------|
| | | | Reporter IMID. | |
| 4 | type | Message Type | MEORS | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the related Order Route event this event is supplementing. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the related Order Route event which this event is supplementing. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time of the related Order Route event this event supplements (including scenarios in which the supplement is created at a later time). | R |
| 11 | manualFlag | Boolean | The <i>manualFlag</i> of the related Order Route event this event supplements. Must be marked as <i>true</i> if the order is routed manually. | R |
| 12 | senderIMID | Industry Member ID | The <i>senderIMID</i> of the Order Route event that this event supplements. When <i>destinationType</i> is 'F', this value must equal the <i>senderIMID</i> on the Order Accepted event reported by the destination. When <i>destinationType</i> is 'E', this value must equal the <i>routingParty</i> reported by the exchange on the Participant Order Accepted event. Not required when <i>destinationType</i> is 'N'. | C |
| 13 | destination | Industry Member ID / Exchange ID | The <i>destination</i> of the Order Route event that this event supplements. When <i>destinationType</i> is 'F', this value is the IMID used to identify the Industry Member that is receiving this routed order, and it must equal the <i>receiverIMID</i> field on the Order Accepted event reported by the destination Industry Member. When <i>destinationType</i> is 'E', this value is the Exchange ID of the destination exchange, and it must equal the <i>exchange</i> field on the Order Accepted event reported by the destination exchange. Not required if <i>destinationType</i> is 'N'. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|-----------|--|-------------|
| 14 | destinationType | Choice | The <i>destinationType</i> of the Order Route event that this event supplements. Indicates whether the destination of the route is an Industry Member, an exchange or a foreign broker-dealer. | R |
| 15 | routedOrderID | Text (64) | The ID assigned to the order by the Industry Member when routing the order to the destination. Must match the <i>routedOrderID</i> of the Order Route event that this event supplements. Required when <i>destinationType</i> is 'F' or 'E' and <i>manualFlag</i> is <i>false</i> . | C |
| 16 | session | Text (40) | The <i>session</i> of the Order Route event that this event supplements. Must only be populated when <i>destinationType</i> is 'E'. This must match the session ID reported in the Participant Order Accepted event by the receiving exchange. | C |
| 17 | routeRejectedFlag | Boolean | Indicates the routed order was not accepted by the destination (rejected or no response) when marked <i>true</i> . | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*
- Route Linkage Key: Event Date, *senderIMID*, *destination*, *symbol*, *session*, *routedOrderID*

4.4. Order Accepted Event

An Order Accepted event must be reported to CAT when an Industry Member receives an order from another CAT Reporter (i.e., Industry Member, ATS or exchange), or from another IMID belonging to the same Industry Member (i.e., the same CRD).

New customer orders, orders received from a non-broker-dealer affiliate, and orders received from a non-reporting foreign broker-dealer must be reported using a New Order event.

Table 19: Order Accepted Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|-----------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|----------------------------------|---|-------------|
| | | | blank when <i>actionType</i> is 'NEW'. | |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEOA | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | Order ID assigned to the order by the Industry Member upon acceptance. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | eventTimestamp | Timestamp | The date/time of receipt of the order. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 10 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is received or captured manually. | R |
| 11 | electronicDupFlag | Boolean | Indicates whether this is a duplicative electronic message of a manual event. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 13 | receiverIMID | Industry Member ID | The IMID of the Industry Member receiving the order. When <i>senderType</i> is 'F', this value must equal the <i>destination</i> field on the Order Route event reported by the routing Industry Member. When <i>senderType</i> is 'E', this value must equal the <i>routingParty</i> on the Order Route event reported by the exchange. | R |
| 14 | senderIMID | Industry Member ID / Exchange ID | When <i>senderType</i> is 'F', this value is the IMID of the sending Industry Member from which the order is routed, and must equal <i>senderIMID</i> in the Order Route event reported by the routing Industry Member. When <i>senderType</i> is 'E', this value is the Exchange ID of the sending entity from which the order is routed, and must equal the <i>exchange</i> field in the Order Route event | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|-------------------|--|-------------|
| | | | reported by the exchange. | |
| 15 | senderType | Choice | Indicates the type of origin from which the order is routed. | R |
| 16 | routedOrderID | Text (64) | The ID for the order as sent by the routing entity. Must be unique per combination of Event Date, symbol, <i>senderIMID</i> , and <i>receiverIMID</i> . Required when <i>manualFlag</i> is <i>false</i> . | C |
| 17 | manualOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the related manual order. Required when <i>manualOrderID</i> is populated. | C |
| 18 | manualOrderID | Text (64) | When this is a duplicative electronic message of a previously (separately) reported manual Order Accepted event, this field is to capture the internal order ID of the manual order. Required when <i>electronicDupFlag</i> is <i>true</i> . | C |
| 19 | affiliateFlag | Boolean | Indicates if the routing party is an affiliate of the Industry Member. | R |
| 20 | deptType | Choice | This is the category of internal department, unit or desk receiving the order. | R |
| 21 | side | Choice | The side of the order. | R |
| 22 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 23 | quantity | Real Quantity | The order quantity. | R |
| 24 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required when applicable. Must be > 0. | C |
| 25 | orderType | Choice | The type of order as routed to the destination reporting the accepted event. | R |
| 26 | timeInForce | Name/Value Pairs | The Time-in-Force for the order. | R |
| 27 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 28 | isolInd | Choice | Indicates the order was accepted as an Intermarket Sweep Order. | R |
| 29 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 30 | custDspIntrFlag | Boolean | Indicates if a customer has instructed that a limit order should not be displayed or that a block size order should be displayed. | R |
| 31 | infoBarrierID | Text (20) | Specifies the identifier of the information barrier in place for a trading unit that will meet the criteria of the "no-knowledge" exception in FINRA Rule 5320.02. Any alphanumeric not containing a delimiter. | C |
| 32 | seqNum | Alphanumeric (40) | The sequence number assigned to the CAT event by the ATS's matching engine. Any alphanumeric not containing a delimiter. | A |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------------|----------------|--|-------------|
| 33 | atsDisplayInd | Choice | Indicates if the order is displayed outside of the ATS to subscribers only, or via publicly disseminated quotation data. | A |
| 34 | displayPrice | Price | The displayed price for the order. If <i>atsDisplayInd</i> is populated as 'Y', 'S', or 'A', <i>displayPrice</i> must be the price at which the order was displayed. If the <i>atsDisplayInd</i> is 'N', <i>displayPrice</i> must be "0". | A |
| 35 | workingPrice | Price | The working price of the order at the time it was accepted. If no current <i>workingPrice</i> , value must be "0". | A |
| 36 | displayQty | Whole Quantity | The displayed quantity of the order. If the <i>atsDisplayInd</i> is populated as 'Y', 'S', or 'A', <i>displayQty</i> must be the quantity at which the order was displayed. If the <i>atsDisplayInd</i> is 'N', <i>displayQty</i> must be "0". | A |
| 37 | atsOrderType | Array | Shows the ATS-specific order type as selected from a list of order types defined by this Industry Member via the CAT Reporter Portal. | A |
| 38 | nbbPrice | Price | The NBBO at the moment the order was received. Prices are required, quantities are optional. If no price or quantity, fields must be populated with a value of '0'. | A |
| 39 | nbbQty | Whole Quantity | | A |
| 40 | nboPrice | Price | | A |
| 41 | nboQty | Whole Quantity | | A |
| 42 | nbboSource | Choice | Source of the NBBO data used. If <i>nbboSource</i> is 'NA', NBBO price and quantity fields must be populated with a value of '0' and the <i>nbboTimestamp</i> must be blank. | A |
| 43 | nbboTimestamp | Timestamp | The date/time at which the NBBO was referenced upon the receipt of the order. Must be blank if <i>nbboSource</i> is 'NA'. | A |
| 44 | solicitationFlag | Boolean | Indicates if the order was received in response to an RFQ or other solicitation process. This field is not used to indicate if a registered representative of the firm solicited a client order. | R |
| 45 | pairedOrderID | Text (64) | If the order was received as a pair, the internal identifier assigned to all orders included in the paired route. | C |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*
- Route Linkage Key: Event Date, *senderIMID*, *receiverIMID*, *symbol*, *routedOrderID*

- Manual Order Key: *manualOrderKeyDate*, *CATReporterIMID*, *symbol*, *manualOrderID*

4.5. Order Internal Route Accepted

An Order Internal Route Accepted event must be reported when an order is passed to a different department or desk within the *CATReporterIMID*. Routes between different IMIDs attributed to the same Industry Member must be reported as Order Route and Order Accepted events.

An Order Internal Route Accepted event is required to be reported from the perspective of the recipient desk, and indicates that an order was received by an internal destination. Industry Members are required to assign a new Order Key to all Order Internal Route Accepted events. A unique *orderID* must be assigned, the *parentOrderID* must be populated with the *orderID* of the event that was internally routed, and the *parentOrderKeyDate* must be populated.

An Industry Member may generate child orders using the Child Order event prior to routing internally to another desk. This approach is acceptable for CAT reporting and will not result in unlinked events.

4.5.1. Order Internal Route Accepted Event

Table 20: Order Internal Route Accepted Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEIR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The internal order ID assigned to the order by the Industry Member. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| | | | the primary listing exchange or FINRA for OTC Equity Securities. | |
| 9 | parentOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the event from which the Order Internal Route Accepted event originated. | R |
| 10 | parentOrderID | Text (64) | The <i>orderID</i> of the event from which the Order Internal Route Accepted event originated. The <i>parentOrderID</i> must not be equal to the <i>orderID</i> within the record. | R |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 12 | eventTimestamp | Timestamp | The date/time of receipt by the receiving desk. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 13 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is routed to another desk manually. | R |
| 14 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 15 | deptType | Choice | The category of department, unit, or desk that received this Order Internal Route Accepted event. | R |
| 16 | receivingDeskType | Choice | Indicates the type of desk or department receiving the order. More granular than the field <i>deptType</i> . | R |
| 17 | infoBarrierID | Text (20) | Specifies the identifier of the information barrier in place for the desk to which the order was routed that will meet the criteria of the "no-knowledge" exception in FINRA Rule 5320.02. Any alphanumeric not containing a delimiter. | C |
| 18 | side | Choice | The side of the order. | R |
| 19 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 20 | quantity | Real Quantity | The order quantity. | R |
| 21 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required when applicable. Must be > 0. | C |
| 22 | orderType | Choice | The type of order received from the routing desk or department. | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|--|-------------|
| 23 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 24 | timeInForce | Name/Value Pairs | The Time-in-Force for the order. | R |
| 25 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 26 | multiLegInd | Boolean | Indicates when the order that was routed internally is related to a multi-leg order event. Refer to Section 5.2 for additional guidance. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*
- Parent Order Key: *parentOrderKeyDate*, *CATReporterIMID*, *symbol*, and *parentOrderID*

4.5.2. Order Internal Route Modified Event

Industry Members must report an Order Internal Route Modified event to CAT when the Material Terms of the internal route have been changed (e.g., price, quantity). All attributes and Material Terms of the modified internal route listed on this event must be restated with the modification(s) reflected.

Industry Members are required to assign a new Order Key to all Order Internal Route Modified events. A unique *orderID* must be assigned, the *priorOrderID* must be populated with the *orderID* of the Order Internal Route Accepted event that is being modified, and the *priorOrderKeyDate* must be populated.

Table 21: Order Internal Route Modified Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEIM | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the | O |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| | | | filename. | |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The internal order ID assigned to the order by the Industry Member. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | priorOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the Order Internal Route Accepted event being modified. | R |
| 10 | priorOrderID | Text (64) | The <i>orderID</i> of the Order Internal Route Accepted event being modified. The <i>priorOrderID</i> must not be equal to the <i>orderID</i> within the record. | R |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 12 | eventTimestamp | Timestamp | The date/time the internal route was modified (e.g., the time that the order was confirmed to be modified in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 13 | manualFlag | Boolean | Must be marked as <i>true</i> if the internal route is modified manually. | R |
| 14 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 15 | deptType | Choice | The category of department, unit, or desk that received the internal route. | R |
| 16 | receivingDeskType | Choice | Indicates the type of desk that received the internal route. More granular than the field <i>deptType</i> . | R |
| 17 | infoBarrierID | Text (20) | Specifies the identifier of the information barrier in place for the desk to which the order was routed that will meet the criteria of the "no-knowledge" exception in FINRA Rule 5320.02. Any alphanumeric not containing a delimiter. | C |
| 18 | initiator | Choice | Indicates who initiated the internal route modification. | R |
| 19 | side | Choice | The side of the order. | R |
| 20 | price | Price | The limit price of the order, required when | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|--|-------------|
| | | | <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | |
| 21 | quantity | Real Quantity | The order quantity. | R |
| 22 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required when applicable. Must be > 0. | C |
| 23 | leavesQty | Real Quantity | The number of shares of the order left open at the receiving desk after the modification has occurred. Must be less than or equal to <i>quantity</i> . | R |
| 24 | orderType | Choice | The type of order received from the routing desk or department. | R |
| 25 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 26 | timeInForce | Name/Value Pairs | The Time-in-Force for the order. | R |
| 27 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*
- Prior Order Key: *priorOrderKeyDate*, *CATReporterIMID*, *symbol*, and *priorOrderID*

4.5.3. Order Internal Route Cancelled Event

If an internal route is cancelled, an Order Internal Route Cancelled event must be reported. Partial cancellations may be reported using an Order Internal Route Modified event or Order Internal Route Cancelled event with *leavesQty*.

Table 22: Order Internal Route Cancelled Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|-----------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| 4 | type | Message Type | MEIC | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the internal route which is being cancelled. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the internal route which is being cancelled. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time the internal route was cancelled (e.g., the time that the order was confirmed to be cancelled in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is cancelled manually. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 13 | cancelQty | Real Quantity | The quantity being cancelled. | R |
| 14 | leavesQty | Real Quantity | The number of shares of the order left open at the receiving desk after the modification has occurred. Must be less than or equal to <i>quantity</i> . | R |
| 15 | initiator | Choice | Indicates who initiated the internal route cancellation. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*

4.5.4. Order Internal Route Modification Request

Industry Members must report an Order Internal Route Modification Request event to CAT when a desk within the firm receives a request to modify the Material Terms of an internal route. All attributes and Material Terms of the modified internal route listed on this event must be restated with the modification(s) reflected.

Table 23: Order Internal Route Modification Request Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEIMR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the order event for which the internal route modification was requested. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the order event for which the internal route modification was requested. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time the internal route modification request was received. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the internal route | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|--|-------------|
| | | | modification was requested manually. | |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 13 | deptType | Choice | The category of department, unit, or desk that received the internal route modification request. | R |
| 14 | receivingDeskType | Choice | Indicates the type of desk that received the internal route modification request. More granular than the field <i>deptType</i> . | R |
| 15 | infoBarrierID | Text (20) | Specifies the identifier of the information barrier in place for the desk to which the order was routed that will meet the criteria of the “no-knowledge” exception in FINRA Rule 5320.02. Any alphanumeric not containing a delimiter. | C |
| 16 | side | Choice | The side of the order. | R |
| 17 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 18 | quantity | Real Quantity | The order quantity. | R |
| 19 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required when applicable. Must be > 0. | C |
| 20 | leavesQty | Real Quantity | The number of shares of the order left open at the receiving desk after the modification has occurred. Must be less than or equal to <i>quantity</i> . | R |
| 21 | orderType | Choice | The type of order received from the routing desk or department. | R |
| 22 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 23 | timeInForce | Name/Value Pairs | The Time-in-Force for the order. | R |
| 24 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*

4.5.5. Order Internal Route Cancel Request

Industry Members must report an Order Internal Route Cancel Request event to CAT when a desk within the firm receives a request to cancel an internal route.

Table 24: Order Internal Route Cancel Request Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEICR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the order event for which the cancellation was requested. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the order event for which the cancellation was requested. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time the internal route cancellation request was received. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the cancel request was received manually. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 13 | leavesQty | Real Quantity | The number of shares of the order left open at the receiving desk after the modification has occurred. Must be less than or equal to <i>quantity</i> . | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate, CATReporterIMID, symbol, orderID*

4.6. Child Order

The Child Order is used to represent instances when an order is sliced within the desk or department it is being worked, and is assigned a new order identifier. Child Order events are not required to be reported to CAT, but are provided for the convenience of Industry Members to help model these types of order handling scenarios.

Child Order events are defined to include only the key data elements that may be changed when the event is created including fields to link to the parent order. The following rules apply with respect to Child Orders:

1. Child Order events can only be reported when new order IDs are assigned within the same desk. An Order Internal Route Accepted event must be reported when routed to another desk.
2. A child order may be generated off of another child order without limitation.
3. Child Order events must belong to the same FDID as the parent order. Child Orders must not be used to create representative orders. If the FDID changes, a representative New Order event must be reported and not a Child Order.
4. Child Order events must **not** be used to represent a multi-leg option order being “legged out”. However, the Child Order event may be used in scenarios where an order is “legged out” and subsequently entered into another OMS/EMS or Algo within the same desk or department where a new orderID is assigned to each leg upon entry.

4.6.1. Child Order Event

Table 25: Child Order Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|-----------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|-------------------|--|-------------|
| 4 | type | Message Type | MECO | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The internal order ID assigned to the child order by the Industry Member. Must be unique with the <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | parentOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the event from which the Child Order originated. | R |
| 10 | parentOrderID | Text (64) | The <i>orderID</i> of the event from which the Child Order originated. The <i>parentOrderID</i> must not be equal to the <i>orderID</i> within the record. | R |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 12 | eventTimestamp | Timestamp | The date/time at which the child order was originated. | R |
| 13 | side | Choice | The side of the order. | R |
| 14 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 15 | quantity | Real Quantity | The Child order quantity. | R |
| 16 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required when applicable. Must be > 0. | C |
| 17 | orderType | Choice | The type of order. | R |
| 18 | timeInForce | Name/Value Pairs | The Time-in-Force for the order. | R |
| 19 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 20 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 21 | seqNum | Alphanumeric (40) | The sequence number assigned to the CAT event by the ATS's matching engine. Any alphanumeric not containing a delimiter. | A |
| 22 | atsDisplayInd | Choice | Indicates if the order is displayed outside of the ATS to subscribers only, or via publicly disseminated quotation data. | A |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------|----------------|--|-------------|
| 23 | displayPrice | Price | The displayed price for this order. If <i>atsDisplayInd</i> is populated as 'Y', 'S', or 'A', <i>displayPrice</i> must be the price at which the order was displayed. If the <i>atsDisplayInd</i> is 'N', <i>displayPrice</i> must be "0". | A |
| 24 | workingPrice | Price | The working price of the order at the time it was originated or received. If no current <i>workingPrice</i> , value must be "0". | A |
| 25 | displayQty | Whole Quantity | The displayed quantity for this order. If the <i>atsDisplayInd</i> is populated as 'Y', 'S', or 'A', <i>displayQty</i> must be the quantity at which the order was displayed. If the <i>atsDisplayInd</i> is 'N', <i>displayQty</i> must be "0". | A |
| 26 | nbbPrice | Price | The NBBO at the moment the order was originated or received. Prices are required, quantities are optional. If no price or quantity, fields must be populated with a value of '0'. | A |
| 27 | nbbQty | Whole Quantity | | A |
| 28 | nboPrice | Price | | A |
| 29 | nboQty | Whole Quantity | | A |
| 30 | nbboSource | Choice | Source of the NBBO data used. If <i>nbboSource</i> is 'NA', NBBO price and quantity fields must be populated with a value of '0' and the <i>nbboTimestamp</i> must be blank. | A |
| 31 | nbboTimestamp | Timestamp | The date/time at which the NBBO was referenced upon the receipt of the order. Must be blank if <i>nbboSource</i> is 'NA'. | A |
| 32 | multiLegInd | Boolean | Indicates when the Child Order was originated from a multi-leg order event. Refer to Section 5.2 for additional guidance. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*
- Parent Order Key: *parentOrderKeyDate*, *CATReporterIMID*, *symbol*, *parentOrderID*

4.6.2. Child Order Modified Event

Industry Members must report a Child Order Modified event to CAT when the Material Terms of the child order have been changed (e.g., price, quantity). All attributes and Material Terms of the modified child order listed on this event must be restated with the modification(s) reflected. A Child Order Modified event may not be used when modifying an Order Internal Route Accepted event.

Industry Members are required to assign a new Order Key to all Child Order Modified events. A unique *orderID* must be assigned, the *priorOrderID* must be populated with the *orderID* of the Child Order event that is being modified, and the *priorOrderKeyDate* must be populated.

Table 26: Child Order Modified Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MECOM | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The internal order ID assigned to the order by the Industry Member. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | priorOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the Child Order event being modified. | R |
| 10 | priorOrderID | Text (64) | The <i>orderID</i> of the Child Order event being modified. The <i>priorOrderID</i> must not be equal to the <i>orderID</i> within the record. | R |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 12 | eventTimestamp | Timestamp | The date/time at which the child order was modified (e.g., the time that the child order was confirmed to be cancelled in the firm's OMS/EMS). | R |
| 13 | side | Choice | The side of the order. | R |
| 14 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 15 | quantity | Real Quantity | The Child order quantity. | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|-------------------|--|-------------|
| 16 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Must be > 0. | C |
| 17 | leavesQty | Real Quantity | The number of shares of the Child Order left open after the modification has occurred. Must be less than or equal to <i>quantity</i> . | R |
| 18 | orderType | Choice | The type of order. | R |
| 19 | timeInForce | Name/Value Pairs | The Time-in-Force for the order. | R |
| 20 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 21 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 22 | seqNum | Alphanumeric (40) | The sequence number assigned to the CAT event by the ATS's matching engine. Any alphanumeric not containing a delimiter. | A |
| 23 | atsDisplayInd | Choice | Indicates if the order is displayed outside of the ATS to subscribers only, or via publicly disseminated quotation data. | A |
| 24 | displayPrice | Price | The displayed price of this order. If <i>atsDisplayInd</i> is populated as 'Y', 'S', or 'A', <i>displayPrice</i> must be the price at which the order was displayed. If the <i>atsDisplayInd</i> is 'N', <i>displayPrice</i> must be "0". | A |
| 25 | workingPrice | Price | The working price of the order at the time it was originated. If no current <i>workingPrice</i> , value must be "0". | A |
| 26 | displayQty | Whole Quantity | The displayed quantity of the order. If the <i>atsDisplayInd</i> is populated as 'Y', 'S', or 'A', <i>displayQty</i> must be the quantity at which the order was displayed. If the <i>atsDisplayInd</i> is 'N', <i>displayQty</i> must be "0". | A |
| 27 | nbbPrice | Price | The NBBO at the moment the order was routed. Prices are required, quantities are optional. If no price or quantity, fields must be populated with a value of '0'. | A |
| 28 | nbbQty | Whole Quantity | | A |
| 29 | nboPrice | Price | | A |
| 30 | nboQty | Whole Quantity | | A |
| 31 | nbboSource | Choice | Source of the NBBO data used. If <i>nbboSource</i> is 'NA', NBBO price and quantity fields must be populated with a value of '0' and the <i>nbboTimestamp</i> must be blank. | A |
| 32 | nbboTimestamp | Timestamp | The date/time at which the NBBO was referenced upon the receipt of the order. Must be blank if <i>nbboSource</i> is 'NA'. | A |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*
- Prior Order Key: *priorOrderKeyDate*, *CATReporterIMID*, *symbol*, and *priorOrderID*

4.6.3. Child Order Cancelled Event

If a child order is cancelled, a Child Order Cancelled event must be reported. Partial cancellations may be reported using a Child Order Modified event or Child Order Cancelled event with *leavesQty*.

Table 27: Child Order Cancelled Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MECOC | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the Child Order event which is being cancelled. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the Child Order event which is being cancelled. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time at which the child order was cancelled (e.g., the time that the child order was confirmed to be cancelled in the firm's OMS/EMS). | R |
| 11 | side | Choice | The side of the order. | R |
| 12 | cancelQty | Real Quantity | The quantity of the Child order being cancelled. | R |
| 13 | leavesQty | Real Quantity | The number of shares of the Child Order left open after the cancellation. Must be less than or equal to <i>quantity</i> . | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|-------------------|--|-------------|
| | | | Full cancellation will result in a zero in this field. | |
| 14 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 15 | seqNum | Alphanumeric (40) | The sequence number assigned to the CAT event by the ATS's matching engine. Any alphanumeric not containing a delimiter. | A |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*

4.7. Order Modified and Cancel/Replace Event

Industry Members must report an Order Modified event to CAT when the Material Terms of an order have been changed (e.g., price, quantity) or when an order is cancel/replaced. All attributes and Material Terms of the modified order listed on this event must be restated with the modification(s) reflected. If the order is a representative order, the *aggregatedOrders* field must be restated every time the order is modified or cancel/replaced. Changes to the orders being represented in the *aggregatedOrders* field are considered a modification to the order. The *side* field is required to be reported, but side adjustments are only allowed for same-side changes, including changes between Short Sale and Sell Long.

Industry Members are required to assign a new Order Key to all Order Modified events. A unique *orderID* must be assigned, the *priorOrderID* must be populated with the *orderID* of the order that is being modified, and the *priorOrderKeyDate* must be populated. If the order has been modified more than once, the *priorOrderID* must refer to *orderID* of the immediately preceding modification which will not be the original Order ID.

Table 28: Order Modified and Cancel/Replace Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|-----------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|---|-------------|
| | | | Must be unique for the Event Date and CAT Reporter IMID. | |
| 4 | type | Message Type | MEOM | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The internal order ID assigned to the order by the Industry Member. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | priorOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the event being modified. | R |
| 10 | priorOrderID | Text (64) | The <i>orderID</i> of the event being modified. The <i>priorOrderID</i> must not be equal to the <i>orderID</i> within the record. | R |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 12 | eventTimestamp | Timestamp | The date/time the order was modified (e.g., the time that the order was confirmed to be modified in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 13 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is modified or replaced manually. | R |
| 14 | manualOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the related manual order. Required when <i>manualOrderID</i> is populated. | C |
| 15 | manualOrderID | Text (64) | When this is a duplicative electronic message of a previously (separately) reported manual Order Modified and Cancel/Replaced event, this field is to capture the internal order ID of the manual order. Required when <i>electronicDupFlag</i> is <i>true</i> . | C |
| 16 | electronicDupFlag | Boolean | Indicates whether this is a duplicative electronic message of a manual event. | R |
| 17 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|----------------------------------|--|-------------|
| 18 | receiverIMID | Industry Member ID | Required when the modification is received from an Industry Member or an exchange. The IMID of the Industry Member receiving the routed order modification. When <i>senderType</i> is 'F', this value must equal the <i>destination</i> field on the Order Route event reported by the routing Industry Member. When <i>senderType</i> is 'E', this value must equal the <i>routingParty</i> on the Participant Order Modification event reported by the exchange. | C |
| 19 | senderIMID | Industry Member ID / Exchange ID | Required when the modification is received from an Industry Member or an exchange. When <i>senderType</i> is 'F', this value is the IMID of the sending Industry Member from which the order is routed, and must equal the <i>senderIMID</i> in the Order Route event reported by the routing Industry Member. When <i>senderType</i> is 'E', this value is the Exchange ID of the sending entity from which the order is routed, and must equal the <i>exchange</i> field in the Participant Order Modification event reported by the exchange. | C |
| 20 | senderType | Choice | Required when the modification is received from an Industry Member or an exchange. Indicates the type of origin from which the order is routed. | C |
| 21 | routedOrderID | Text (64) | The ID for the order as sent by the routing entity. Must be unique per combination of Event Date, symbol, <i>senderIMID</i> , and <i>receiverIMID</i> . Required when <i>senderType</i> is 'F' or 'E' and <i>manualFlag</i> is <i>false</i> . | C |
| 22 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 23 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 24 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 25 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 26 | initiator | Choice | Indicates who initiated the order modification. | R |
| 27 | side | Choice | The side of the order. For this Reportable Event, only same-side adjustments are allowed (e.g., sell long to short sell). | R |
| 28 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 29 | quantity | Real Quantity | The order quantity. | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|--|----------------------|-------------------|--|-------------|
| 30 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required when applicable. Must be > 0. | C |
| 31 | leavesQty | Real Quantity | The number of shares left open after the modification has occurred. Must be less than or equal to <i>quantity</i> . | R |
| 32 | orderType | Choice | The type of order being submitted (e.g., market, limit). | R |
| 33 | timeInForce | Name/Value Pairs | The time-in-force for the order (e.g. DAY, IOC, GTC). | R |
| 34 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 35 | isoInd | Choice | Indicates the order was an Intermarket Sweep Order. | R |
| 36 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 37 | custDspIntrFlag | Boolean | Indicates if a customer has instructed that a limit order should not be displayed or that a block size order should be displayed. | R |
| 38 | infoBarrierID | Text (20) | Specifying the identifier of the information barrier in place for a trading unit that will meet the criteria of the “no-knowledge” exception in FINRA Rule 5320.02. Any alphanumeric not containing a delimiter. | C |
| 39 | aggregatedOrders | Aggregated Orders | When applicable, the order ID of each customer order being represented. Refer to Appendix C for representative order linkage requirements. | C |
| Aggregated Orders – Start | | | | |
| For each order being represented <i>n</i> , the following values are required. | | | | |
| 39.n.1 | orderID | Text (64) | <i>orderID</i> of the order being represented. | R |
| 39.n.2 | orderKeyDate | Timestamp | <i>orderKeyDate</i> of the order being represented. | R |
| 39.n.3 | quantity | Real Quantity | Required when a partial quantity of the order is being represented. | C |
| 39.n.4 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| Aggregated Orders – End | | | | |
| 40 | representativeInd | Choice | Indicates if the order is a representative order and if linkage is required. | R |
| 41 | seqNum | Alphanumeric (40) | The sequence number assigned to the CAT event by the ATS's matching engine. Any alphanumeric not containing a delimiter. | A |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------|----------------|---|-------------|
| 42 | atsDisplayInd | Choice | Indicates if the order is displayed outside of the ATS to subscribers only, or via publicly disseminated quotation data. | A |
| 43 | displayPrice | Price | The displayed price of this order. If <i>atsDisplayInd</i> is populated as 'Y', 'S', or 'A', <i>displayPrice</i> must be the price at which the order was displayed. If the <i>atsDisplayInd</i> is 'N', <i>displayPrice</i> must be "0". | A |
| 44 | workingPrice | Price | The working price of the order at the time of the modification. If no current <i>workingPrice</i> , value must be "0". | A |
| 45 | displayQty | Whole Quantity | The displayed quantity for this order at the time the order was modified. If the <i>atsDisplayInd</i> is populated as 'Y', 'S', or 'A', <i>displayQty</i> must be the quantity at which the order was displayed. If the <i>atsDisplayInd</i> is 'N', <i>displayQty</i> must be "0". | A |
| 46 | atsOrderType | Array | Shows the ATS-specific order types as selected from a list of order types defined by this ATS. | A |
| 47 | nbbPrice | Price | The NBBO at the moment the order was modified. Prices are required, quantities are optional. If no price or quantity, fields must be populated with a value of '0'. | A |
| 48 | nbbQty | Whole Quantity | | A |
| 49 | nboPrice | Price | | A |
| 50 | nboQty | Whole Quantity | | A |
| 51 | nbboSource | Choice | Source of the NBBO data used. If <i>nbboSource</i> is 'NA', NBBO price and quantity fields must be populated with a value of '0' and the <i>nbboTimestamp</i> must be blank. | A |
| 52 | nbboTimestamp | Timestamp | The date/time at which the NBBO was referenced upon the receipt of the order. Must be blank if <i>nbboSource</i> is 'NA'. | A |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*
- Order Key: *aggregatedOrders.orderKeyDate*, *CATReporterIMID*, *symbol*, *aggregatedOrders.orderID*
- Prior Order Key: *priorOrderKeyDate*, *CATReporterIMID*, *symbol*, and *priorOrderID*
- Route Linkage Key: Event Date, *symbol*, *receiverIMID*, *senderIMID*, *routedOrderID*
- Manual Order Key: *manualOrderKeyDate*, *CATReporterIMID*, *symbol*, *manualOrderID*

4.7.1. Order Modification Request Event

The Order Modification Request event is required when a customer has requested the modification to the Material Terms of an order.

Table 29: Order Modification Request Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEOMR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the order event for which the modification was requested. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the order event for which the modification was requested. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time of receipt of the modification request. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the modification is requested manually. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|----------------------------------|---|-------------|
| 13 | receiverIMID | Industry Member ID | Required when the modification request is received from an Industry Member or an exchange (<i>senderType</i> is 'F' or 'E'). The IMID of the Industry Member receiving the modification request. | C |
| 14 | senderIMID | Industry Member ID / Exchange ID | Required when the modification request is received from an Industry Member or an exchange. When <i>senderType</i> is 'F', this value is the IMID of the sending Industry Member from which the order is routed. When <i>senderType</i> is 'E', this value is the Exchange ID of the sending entity from which the modification was requested. | C |
| 15 | senderType | Choice | Required when the modification request is received from an Industry Member or an exchange. Indicates the type of origin from which the modification was requested. | C |
| 16 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 17 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 18 | side | Choice | The side of the order. For this Reportable Event, only same-side adjustments are allowed (e.g., sell long to short sell). | R |
| 19 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 20 | quantity | Real Quantity | The order quantity. | R |
| 21 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required when applicable. Must be > 0. | C |
| 22 | orderType | Choice | The type of order being submitted (e.g., market, limit). | R |
| 23 | timeInForce | Name/Value Pairs | The time-in-force for the order (e.g. DAY, IOC, GTC). | R |
| 24 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 25 | isInId | Choice | Indicates the order was an Intermarket Sweep Order. | R |
| 26 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 27 | custDspIntrFlag | Boolean | Indicates if a customer has instructed that a limit order should not be displayed or that a block size order should be displayed. | R |
| 28 | infoBarrierID | Text (20) | Specifying the identifier of the information barrier in place for a trading unit that will meet the criteria of the "no-knowledge" exception in FINRA Rule 5320.02. Any alphanumeric not | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|-------------------|--|-------------|
| | | | containing a delimiter. | |
| 29 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 30 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 31 | seqNum | Alphanumeric (40) | The sequence number assigned to the CAT event by the ATS's matching engine. Any alphanumeric not containing a delimiter. | A |
| 32 | atsDisplayInd | Choice | Indicates if the order is displayed outside of the ATS to subscribers only, or via publicly disseminated quotation data. | A |
| 33 | displayPrice | Price | The displayed price of this order. If <i>atsDisplayInd</i> is populated as 'Y', 'S', or 'A', <i>displayPrice</i> must be the price at which the order was displayed. If the <i>atsDisplayInd</i> is 'N', <i>displayPrice</i> must be "0". | A |
| 34 | workingPrice | Price | The working price of the order at the time of the modification request. If no current <i>workingPrice</i> , value must be "0". | A |
| 35 | displayQty | Whole Quantity | The displayed quantity for this order at the time of the modification request. If the <i>atsDisplayInd</i> is populated as 'Y', 'S', or 'A', <i>displayQty</i> must be the quantity at which the order was displayed. If the <i>atsDisplayInd</i> is 'N', <i>displayQty</i> must be "0". | A |
| 36 | atsOrderType | Array | Shows the ATS-specific order types as selected from a list of order types defined by this ATS. | A |
| 37 | nbbPrice | Price | The NBBO at the time of the modification request. Prices are required, quantities are optional. If no price or quantity, fields must be populated with a value of '0'. | A |
| 38 | nbbQty | Whole Quantity | | A |
| 39 | nboPrice | Price | | A |
| 40 | nboQty | Whole Quantity | | A |
| 41 | nbboSource | Choice | Source of the NBBO data used. If <i>nbboSource</i> is 'NA', NBBO price and quantity fields must be populated with a value of '0' and the <i>nbboTimestamp</i> must be blank. | A |
| 42 | nbboTimestamp | Timestamp | The date/time at which the NBBO was referenced upon the receipt of the order. Must be blank if <i>nbboSource</i> is 'NA'. | A |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*

4.8. Order Modified (Cancel/Replace) Supplement Event

The Order Modified Supplement event serves as a supplement to the Order Modified event, just as the New Order Supplement event serves as a supplement to the New Order event.

Table 30: Order Modified Supplement Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|---|------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEOMS | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the related Order Modified and Cancel/Replace event which this event is supplementing. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the related Order Modified and Cancel/Replace event which this event is supplementing. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time of the Order Modified this event supplements. | R |
| 11 | aggregatedOrders | Aggregated Orders | The order ID of each customer order being represented. Refer to Appendix C for representative order linkage requirements. | R |
| Aggregated Orders – Start For each order being represented <i>n</i> , the following values are required. | | | | |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------------------------|-----------------|-------------------|--|-------------|
| 11.n.1 | orderID | Text (64) | <i>orderID</i> of the order being represented. | R |
| 11.n.2 | orderKeyDate | Timestamp | <i>orderKeyDate</i> of the order being represented. | R |
| 11.n.3 | quantity | Real Quantity | Required when a partial quantity of the order is being represented. | C |
| 11.n.4 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| Aggregated Orders – End | | | | |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*
- Order Key: *aggregatedOrders.orderKeyDate*, *CATReporterIMID*, *symbol*, *aggregatedOrders.orderID*

4.9. Order Adjusted Event

An Order Adjusted event must be used when the display price or quantity changes as the result of a Display ATS matching engine action and not from a customer instruction. The Order Adjusted event may be used by non-ATS firms instead of an Order Modified event to report changes to the price or quantity of an order.

The following rules apply:

1. If any of the price fields change, then all price fields (i.e. *price*, *displayPrice*, and *workingPrice*) must be reported to represent current state of the order relative to price. The quantity fields are not required.
2. If any of the quantity fields change, then all quantity fields (i.e. *quantity*, *minQty*, *leavesQty*, *displayQty*) must be reported to represent the current state of the order relative to quantity. The price fields are not required.

Any modification that cannot be fully represented in this Reportable Event must be reported via the Order Modified event.

Industry Members are required to assign a new Order Key to all Order Adjusted events. A unique *orderID* must be assigned, the *priorOrderID* must be populated with the *orderID* of the order that is being

modified, and the *priorOrderKeyDate* must be populated. If the order has been modified more than once, the *priorOrderID* must refer to *orderID* of the immediately preceding modification which will not be the original Order ID.

Table 31: Order Adjusted Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEOJ | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The internal order ID assigned to the order by the Industry Member. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | priorOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the event being adjusted. | R |
| 10 | priorOrderID | Text (64) | The <i>orderID</i> of the event being adjusted. The <i>priorOrderID</i> must not be equal to the <i>orderID</i> within the record. | R |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 12 | eventTimestamp | Timestamp | The date/time at which the order was modified (e.g., the time that the order was confirmed to be modified in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|---|-------------|
| | | | timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | |
| 13 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is adjusted manually. | R |
| 14 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 15 | initiator | Choice | Indicates who initiated the order adjustment. | R |
| 16 | price | Price | The limit price of the order. Required when <i>price</i> , <i>displayPrice</i> , or <i>workingPrice</i> changed. | C |
| 17 | quantity | Real Quantity | The order quantity. Required when <i>quantity</i> , <i>minQty</i> , <i>leavesQty</i> , or <i>displayQty</i> changed. | C |
| 18 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required when applicable and when <i>quantity</i> , <i>minQty</i> , <i>leavesQty</i> , or <i>displayQty</i> changed. Must be > 0. | C |
| 19 | leavesQty | Real Quantity | The number of shares left open after the adjustment/modification has occurred. Required when <i>quantity</i> , <i>minQty</i> , <i>leavesQty</i> , or <i>displayQty</i> changed. Must be less than or equal to <i>quantity</i> . | C |
| 20 | seqNum | Alphanumeric (40) | The sequence number assigned to the CAT event by the ATS's matching engine. Any alphanumeric not containing a delimiter. | A |
| 21 | atsDisplayInd | Choice | Indicates if the order is displayed outside of the ATS to subscribers only, or via publicly disseminated quotation data. | A |
| 22 | displayPrice | Price | The displayed price of the order. Required when applicable and when <i>price</i> , <i>workingPrice</i> , or <i>displayPrice</i> changed. | C |
| 23 | workingPrice | Price | The working price of the order. Required when applicable and when <i>price</i> , <i>workingPrice</i> , or <i>displayPrice</i> changed. | C |
| 24 | displayQty | Whole Quantity | The displayed quantity for this order. Required when applicable and when <i>quantity</i> , <i>minQty</i> , <i>leavesQty</i> , or <i>displayQty</i> changed. | C |
| 25 | nbbPrice | Price | The NBBO at the moment the order was modified. Prices are required, quantities are optional. If no price or quantity, fields must be populated with a value of '0'. | A |
| 26 | nbbQty | Whole Quantity | | A |
| 27 | nboPrice | Price | | A |
| 28 | nboQty | Whole Quantity | | A |
| 29 | nbboSource | Choice | Source of the NBBO data used. If <i>nbboSource</i> is 'NA', NBBO price and quantity fields must be populated with a value of '0' and the <i>nbboTimestamp</i> must be blank. | A |
| 30 | nbboTimestamp | Timestamp | The date/time at which the NBBO was referenced upon the receipt of the order. Must be blank if <i>nbboSource</i> is 'NA'. | A |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------|------------------|----------------------------------|-------------|
| 31 | timeInForce | Name/Value Pairs | The time-in-force for the order. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*
- Prior Order Key: *priorOrderKeyDate*, *CATReporterIMID*, *symbol*, and *priorOrderID*

4.10. Order Cancelled Event

The Order Cancelled event is reported when an order is fully or partially cancelled. Partial cancellations of an order may be reported to CAT using an Order Cancelled event or an Order Modified event. Implicit order cancellations, such as cancellations due to expiration of Time in Force, are not required to be reported to CAT.

Order Cancelled events are required to be reported by the entity that initiated the cancellation. When an Order is routed from Firm A to Firm B, the following rules apply:

1. If Firm A or its customer initiates the cancel, Firm A and Firm B must report the Order Cancelled.
2. If Firm B initiates the cancel, Firm B must report the Order Cancelled.

Table 32: Order Cancelled Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEOC | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the order event which is | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|---|-------------|
| | | | being cancelled. | |
| 7 | orderID | Text (64) | The <i>orderID</i> of the order event which is being cancelled. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time the order was cancelled (e.g., the time that the order was confirmed to be cancelled in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is cancelled manually. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 13 | cancelQty | Real Quantity | The quantity being cancelled. | R |
| 14 | leavesQty | Real Quantity | The quantity left open after the cancel event. Must be less than or equal to <i>quantity</i> . The full cancel will result in zero in this field. | R |
| 15 | initiator | Choice | Indicates who initiated the order cancellation. | R |
| 16 | seqNum | Alphanumeric (40) | The sequence number assigned to the CAT event by the ATS's matching engine. Any alphanumeric not containing a delimiter. | A |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*

4.10.1. Order Cancel Request Event

The Order Cancel Request event is required when a customer has requested the cancellation of an order.

Table 33: Order Cancel Request Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEOCR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the order event for which the cancellation was requested. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the order event for which the cancellation was requested. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time of receipt of the cancel request. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the cancellation is requested manually. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 13 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 14 | seqNum | Alphanumeric (40) | The sequence number assigned to the CAT event by the ATS's matching engine. Any alphanumeric not containing a delimiter. | A |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*

4.11. Quotes

Quote events are used to report electronic quotes which are provided by or received in a CAT Reporter's order/quote handling or execution systems in CAT reportable securities and are provided by an Industry Member to other market participants off a national securities exchanges, as described in [CAT FAQ B45](#).

The following guidance applies to quotes in OTC Equity Securities sent to an inter-dealer quotation system:

1. Quotes in OTC Equity Securities sent to an inter-dealer quotation system operated by an Industry Member must be reported using the New Quote event.
2. Quotes in OTC Equity Securities received by an Industry Member CAT Reporter operating an inter-dealer quotation system using the Quote Received event.
3. Quotes in OTC Equity Securities that meet the definition of bid or offer under the CAT NMS Plan sent by a broker-dealer to a quotation venue not operated by a CAT Reporter must be reported using the New Quote event.

Quotes in NMS Securities sent to an exchange or the ADF must be reported using the New Order and Route events.

4.11.1. New Quote Event

The New Quote Event is used to report the following:

- Quotes in OTC equity securities sent to an inter-dealer quotation system operated by an Industry Member
- Quotes in OTC Equity securities sent to a quotation venue not operated by a CAT Reporter.
- Any other electronic quotes which are provided by or received in a CAT Reporter's order/quote handling or execution systems in CAT reportable securities and are provided by an Industry Member to other market participants off a national securities exchanges, as described in [CAT FAQ B45](#).

For two-sided quote events, the *bidPrice*, *bidQty*, *askPrice*, and *askQty* fields must be populated. For one-sided quote events, the price and quantity of the applicable side must be populated.

Modifications to a previously reported quote event are considered to be a replacement, and must include the *priorQuoteID* of the quote being replaced. If a modification does not result in a change to the quote ID, the *priorQuoteID* and the *quoteID* fields must be populated and must be equal. Otherwise, if the field *onlyOneQuoteFlag* = true, any New Quote event offered by the same CATReporterIMID to the same destination in the same symbol will be considered cancelled by CAT.

Table 34: New Quote Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MENQ | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | quoteKeyDate | Timestamp | The date and time the <i>quoteID</i> was assigned. | R |
| 7 | quoteID | Text (64) | The internal quote ID assigned to the quote by the Industry Member. Must be unique within <i>quoteKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | priorQuoteKeyDate | Timestamp | If a new Quote ID has been assigned, this is the <i>quoteKeyDate</i> of the event being modified. | C |
| 10 | priorQuoteID | Text (64) | This field is only relevant for an update/replacement of an existing quote, and must not be populated for new Quotes. After this Reportable Event, the quote specified in this field will be considered to have been replaced. This field does not have to be included if <i>onlyOneQuoteFlag</i> is true, since it is known implicitly that the previous quote is being replaced. This field is the <i>quoteID</i> of the quote that is being replaced. | C |
| 11 | eventTimestamp | Timestamp | The date/time the quote was sent by the Industry Member to the recipient. If | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|--------------------|--|-------------|
| | | | <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | |
| 12 | seqNum | Alphanumeric (40) | The sequence number assigned to the quote by the reporter. Any alphanumeric not containing a delimiter. Required for inter-dealer quotation systems only. | C |
| 13 | senderIMID | Industry Member ID | The IMID of the Industry Member that is sending the quote, as known by the destination. This value must match the <i>senderIMID</i> on the Quote Received event reported by the destination. Not required if the recipient of the quote is not a reporter to CAT. | C |
| 14 | destination | Industry Member ID | This field contains the SRO assigned identifier of the destination Industry Member. This value must match the <i>receiverIMID</i> field on the Quote Received event reported by the destination. Required if the destination of the quote is another broker-dealer or ATS. | C |
| 15 | routedQuoteID | Text (64) | The quote ID sent to the recipient of the quote. Not required if the recipient of the quote is a customer/client (e.g. not an Industry Member). | C |
| 16 | onlyOneQuoteFlag | Boolean | Value is <i>true</i> if the recipient only allows one quote per <i>symbol</i> for this Industry Member. Otherwise, <i>false</i> . | R |
| 17 | bidPrice | Price | Price being bid. If <i>askPrice</i> is blank, <i>bidPrice</i> must be populated. | C |
| 18 | bidQty | Whole Quantity | Quantity being bid. If <i>askQty</i> is blank, <i>bidQty</i> must be populated. | C |
| 19 | askPrice | Price | Price being asked. If <i>bidPrice</i> is blank, <i>askPrice</i> must be populated. | C |
| 20 | askQty | Whole Quantity | Quantity being asked. If <i>bidQty</i> is blank, <i>askQty</i> must be populated. | C |
| 21 | firmDesignatedID | Text (40) | Refer to the Data Dictionary for definition and guidance for populating this field. | R |
| 22 | accountHolderType | Choice | Represents the type of account that originated this quote. Must be provided when <i>firmDesignatedID</i> is present. | R |
| 23 | unsolicitedInd | Choice | Indicates whether this is an unsolicited quote. | R |
| 24 | mpStatusCode | Choice | Market Participant Status Code, indicates if the market maker's quote is open or closed. Only required when the quote is sent to an inter-dealer quotation system. | C |
| 25 | quoteRejectedFlag | Boolean | If the result of the quote is rejected or no response was received, value should be <i>true</i> . | R |

Linkage Keys for this Reportable Event:

- Quote Key: *quoteKeyDate*, *CATReporterIMID*, *symbol*, *quoteID*
- Prior Quote Key: *priorQuoteKeyDate*, *CATReporterIMID*, *symbol*, and *priorQuoteID*
- Quote Route Key: Event Date, *CATReporterIMID*, *symbol*, *routedQuoteID*

4.11.2. Quote Received Event

The Quote Received event is used to report Quotes in OTC Equity securities received by an Industry Member inter-dealer quotation system.

For two-sided quote events, the *bidPrice*, *bidQty*, *askPrice*, and *askQty* fields must be populated. For one-sided quote events, the price and quantity of the applicable side must be populated. For quotes representing a name only quote for which a price and quantity is not applicable, the price and quantity of the applicable side must be populated with zero, and the *unpricedInd* must be populated as 'true'.

Modifications to a previously reported quote event are considered to be a replacement, and must include the *priorQuoteID* of the quote being replaced. If a modification does not result in a change to the quote ID, the *priorQuoteID* and the *quoteID* fields must be populated and must be equal. Otherwise, if the field *onlyOneQuoteFlag* = true, any New Quote event offered by the same *CATReporterIMID* to the same destination in the same symbol will be considered cancelled by CAT.

Table 35: Quote Received Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------------------|-------------------|---|-------------|
| 1 | <i>actionType</i> | Choice | Indicates whether the event is a new event, firm initiated correction or a repair of a CAT error. | R |
| 2 | <i>errorROEID</i> | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | <i>firmROEID</i> | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | <i>type</i> | Message Type | MEQR | R |
| 5 | <i>CATReporterIMID</i> | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | <i>quoteKeyDate</i> | Timestamp | The date and time the <i>quoteID</i> was assigned. | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|--------------------|---|-------------|
| 7 | quoteID | Text (64) | The internal quote ID assigned to the quote by Industry Member. Must be unique within <i>quoteKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | receivedQuoteID | Text (64) | The quote ID as received by the ATS or Industry Member, should match the <i>routedQuoteID</i> in the New Quote event created by the issuer of the quote. | R |
| 10 | eventTimestamp | Timestamp | The date/time the quote was received by the ATS or Industry Member. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | seqNum | Alphanumeric (40) | The sequence number assigned to the quote received message by the reporter. Any alphanumeric not containing a delimiter. Required for inter-dealer quotation systems only. | C |
| 12 | receiverIMID | Industry Member ID | The IMID of the Industry Member receiving the quote (the Industry Member reporting this Reportable Event). It must match the <i>destination</i> field on the New Quote event reported by the routing entity. | R |
| 13 | senderIMID | Industry Member ID | The IMID of the Industry Member providing the quote. This value must match the <i>senderIMID</i> in the New Quote event reported by the routing Industry Member. | R |
| 14 | onlyOneQuoteFlag | Boolean | <i>true</i> if the Industry Member only allows one quote per <i>symbol</i> for the issue of the quote; <i>false</i> otherwise. | R |
| 15 | priorQuoteKeyDate | Timestamp | If a new Quote ID has been assigned, this is the <i>quoteKeyDate</i> of the event being modified. | C |
| 16 | priorQuoteID | Text (64) | <i>quoteID</i> of the quote previously accepted by the Industry Member that is being replaced. Required to report the update/replacement of an existing quote. After this Reportable Event, the quote specified in this field will be considered to have been replaced. Not required if <i>onlyOneQuoteFlag</i> is <i>true</i> . | C |
| 17 | bidPrice | Price | Price being bid. | C |
| 18 | bidQty | Whole Quantity | Quantity being bid. | C |
| 19 | askPrice | Price | Price being asked. | C |
| 20 | askQty | Whole Quantity | Quantity being asked. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------|-----------|---|-------------|
| 21 | mpStatusCode | Choice | Market Participant Status Code, indicates if the market maker's quote is open or closed. Only required for quotes sent to an inter-dealer quotation system. | C |
| 22 | unsolicitedInd | Choice | Indicates whether this is an unsolicited quote. | R |
| 23 | quoteWantedInd | Choice | Indicates if the quote message received by an IDQS is a request for a bid or an ask. This field is only applicable to IDQSSs. When <i>quoteWantedInd</i> is populated, bid and ask fields are not required. | C |
| 24 | unpricedInd | Boolean | If this is an unpriced quote, must be populated as <i>true</i> . When <i>unpricedInd</i> is <i>true</i> , bid and ask fields are not required. | R |

Linkage Keys for this Reportable Event:

- Quote Key: *quoteKeyDate*, *CATReporterIMID*, *symbol*, *quoteID*
- Quote Route Key: Event Date, *CATReporterIMID*, *symbol*, *receivedQuoteID*
- Prior Quote Key: *priorQuoteKeyDate*, *CATReporterIMID*, *symbol*, and *priorQuoteID*
- IDQS Linkage Key: Event Date, *senderIMID*, *receiverIMID*, *symbol*, *quoteID*

4.11.3. Quote Cancelled Event

Reported when a quote is cancelled. If a quote is cancelled that was sent to an ATS or an Industry Member, then both the sender of the quote and the entity that accepted the quote must report Quote Cancelled events.

Table 36: Quote Cancelled Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|--------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEQC | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|-------------------|--|-------------|
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | quoteKeyDate | Timestamp | The <i>quoteKeyDate</i> of the Quote event which is being cancelled. | R |
| 7 | quoteID | Text (64) | The <i>quoteID</i> of the Quote event which is being cancelled. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time the quote was cancelled by the Industry Member to the recipient. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | seqNum | Alphanumeric (40) | The sequence number of the quote cancel message. Any alphanumeric not containing a delimiter. Required for inter-dealer quotation systems only. | C |
| 12 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 13 | initiator | Choice | Indicates who initiated the order cancellation. | R |
| 14 | mpStatusCode | Choice | Market Participant Status Code, indicates if the market maker's quote is open or closed. Only required for quotes sent to an inter-dealer quotation system. | C |

Linkage Keys for this Reportable Event:

- Quote Key: *quoteKeyDate*, *CATReporterIMID*, *symbol*, *quoteID*

4.12. Trade

A Trade Event is used when the Industry Member acts as the executing broker and is required to report the trade for public dissemination purposes. When an Industry Member is not required to report the

execution of a customer order for public dissemination purposes, with the exceptions noted below, an Order Fulfillment event must be used. See [Section 4.13 Order Fulfillment](#) for more details.

Reporting Exception Codes

In general, Trade events are required to match to a TRF/ORF/ADF report. However, there are four circumstances when an MEOT would not be able to be linked to a TRF report and a Reporting Exception Code (REC) is required on a Trade event to allow the Processor to identify that there will be no link to a TRF/ORF/ADF report:

1. An Industry Member executes a trade between two desks or departments of the same firm, but because there is no change in beneficial ownership, no trade is reported for public dissemination. In this instance a REC of "P" should be used on the Trade event.
2. An Industry Member executes a trade and must report the trade via Form T. In this instance, a REC of "F" should be used on the Trade event.
3. A trade was executed by a non-FINRA member firm and was reported to the TRF by the FINRA member counterparty. In this instance, the non-FINRA member must populate a REC of "N" on the Trade event.
4. Industry Member was the contra side of the trade report for a negotiated trade not executed as the result of an OTC Link ATS trade message and which was reported to a TRF via a QSR or AGU. In this instances, a REC of 'C' should be used on the Trade event. The following rules apply when REC 'C' is used:
 - The *marketCenterID* field must be populated.
 - The *clearingFirm* and *counterparty* fields must be populated.
 - The *cancelFlag* and *cancelTimestamp* must be populated for all negotiated trades that are reported to a TRF via a QSR or AGU and later cancelled, as the CAT would not be able to link to a related TRF cancellation.

FINRA CAT will closely monitor all uses of REC 'C' to ensure compliance with the above noted guidelines.

Trade Side Details

Trade events are two-sided, containing information on both sides of the trade. Exceptions requiring only one side of the Trade event to be populated are noted below. The details of each side are reported using Trade Side Details. The data type Trade Side Details is described as a list of fields in in Table 38 below. Trade Side Details must contain only one *orderID* per side. The *buyDetails* must contain the *orderID* of the buy side of the trade and the *sellDetails* must contain the *orderID* of the sell side of the trade. If there

is more than one *orderID* associated with one side of the trade, the Trade Side Details related to each *orderID* must be populated in a separate Trade Supplement event.

Internalized Trade

When an Industry Member internalizes an order by filling it from a proprietary account, the Industry Member must report the *orderID* on the customer side and the FDID and the *accountHolderType* of the proprietary account on the firm side. In this scenario, no *orderID* is required on the firm side of the Trade event.

However, if the Industry Member generates a proprietary order to facilitate the execution of the customer order, the Industry Member must report the *orderID* of both the customer side and the firm side of the Trade event. Refer to [CAT FAQ B41](#) for additional information.

One-Sided Trade events

There are several exceptions which only require one side of a Trade event to be populated. These exceptions include:

1. Trade is executed as the result of a negotiation between two Industry Members.
2. Order is routed by a FINRA Member to a non-FINRA member, and the FINRA Member has the obligation to submit a media trade report to a TRF/ADF/ORF.
3. Order is routed by an Industry Member to a foreign broker-dealer, and the foreign broker-dealer executes the order at a net price, creating a media trade reporting obligation in the United States.

In these scenarios, each party that is required to report a Trade event to CAT must populate the *sideDetailsInd* indicating which side of the trade the Industry Member was associated with, and which Trade Side Details will be populated in the Trade event.

4.12.1. Trade Event

The tables below describe the data elements to report a trade executed by an Industry Member.

Table 37: Trade Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|-----------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| | | | blank when <i>actionType</i> is 'NEW'. | |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEOT | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | tradeKeyDate | Timestamp | The date and time the <i>tradeID</i> was assigned. | R |
| 7 | tradeID | Text (64) | Unique ID assigned to this execution by the Industry Member. This ID will be used in subsequent events when a specific trade needs to be identified. The combination of date, <i>CATReporterIMID</i> , <i>symbol</i> , and <i>tradeID</i> must be unique. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | eventTimestamp | Timestamp | The date/time at which the trade was executed. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 10 | manualFlag | Boolean | Must be marked as <i>true</i> if this is a manual execution. | R |
| 11 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 12 | cancelFlag | Boolean | Must be marked as <i>true</i> if the execution is cancelled and was not reported to the TRF/ADF/ORF. | R |
| 13 | cancelTimestamp | Timestamp | When <i>cancelFlag</i> is <i>true</i> , the time at which the execution was cancelled. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | C |
| 14 | quoteKeyDate | Timestamp | The date and time the <i>quoteID</i> was assigned. Required when <i>quoteID</i> is populated. | C |
| 15 | quoteID | Text (64) | If this trade was the result of a quote that was sent to an IDQS, this is the <i>quoteID</i> of the related Quote Received event reported by the IDQS. Required if this order was executed as the result of a quote. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------|--------------------|--|-------------|
| 16 | quantity | Real Quantity | Quantity of the trade. | R |
| 17 | price | Price | The execution price of the trade. | R |
| 18 | capacity | Choice | The capacity in which the Industry Member acted. | R |
| 19 | tapeTradeID | Text (40) | <p>The unique identifier reported by the Industry Member to the TRF/ADF/ORF based on the reporting specifications of the specific facility, required when the ID was supplied to a transaction reporting system:</p> <ul style="list-style-type: none"> • Compliance ID in ORF and ADF • Branch Sequence Number in FINRA/NQ TRF • FINRA Compliance Number in FINRA/NYSE TRF <p>Must be unique per combination of Event Date, <i>CATReporterIMID</i>, <i>marketCenterID</i> and <i>symbol</i>.</p> <p>The <i>tapeTradeID</i> may link to either the reporting side or the contra-side of the tape report.</p> <p>When the <i>reportingExceptionCode</i> field is blank, the <i>tapeTradeID</i> field must be populated. When the <i>reportingExceptionCode</i> field is populated, the <i>tapeTradeID</i> field must be blank.</p> | C |
| 20 | marketCenterID | Choice | <p>The national securities exchange or transaction reporting system operated by FINRA where the trade was reported.</p> <p>When the <i>marketCenterID</i> field is blank, the <i>reportingExceptionCode</i> must be populated with a value other than 'C'. When the <i>marketCenterID</i> field is populated, the <i>reportingExceptionCode</i> field must be blank, or must be populated with a value of 'C'.</p> | C |
| 21 | sideDetailsInd | Choice | <p>Identifies if a Trade event is one sided, and which side of the trade the Industry Member is populating in the Trade Side Details.</p> <p>When <i>sideDetailsInd</i> is 'BUY', only the <i>buyDetails</i> are populated. When <i>sideDetailsInd</i> is 'SELL', only the <i>sellDetails</i> are populated.</p> | R |
| 22 | buyDetails | Trade Side Details | <p>See Table 38: Trade Side Details below.</p> <p>Applicable if there is only one <i>orderID</i> associated with this side of the trade. If there is more than one <i>orderID</i>, must be populated in separate MEOTS events.</p> | C |
| 23 | sellDetails | Trade Side Details | <p>See Table 38: Trade Side Details below.</p> <p>Applicable if there is only one <i>orderID</i> associated with this side of the trade. If there is more than one <i>orderID</i>, must be populated in separate MEOTS events.</p> | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------------------|--------------------|---|-------------|
| 24 | reportingExceptionCode | Choice | <p>Indicates the reason that a unique identifier (e.g., Branch Sequence Number, Compliance ID) was not supplied to a transaction reporting system. Must be provided if the execution is not reported to a FINRA transaction reporting system.</p> <p>When the <i>tapeTradeID</i> field is blank, the <i>reportingExceptionCode</i> field must be populated. When the <i>tapeTradeID</i> field is populated, the <i>reportingExceptionCode</i> field must be blank.</p> <p>When the <i>marketCenterID</i> field is blank, the <i>reportingExceptionCode</i> field must be populated. When the <i>marketCenterID</i> field is populated, the <i>reportingExceptionCode</i> must be blank.</p> | C |
| 25 | seqNum | Alphanumeric (40) | The sequence number assigned to the Reportable Event by the ATS's matching engine. Any alphanumeric not containing a delimiter. | A |
| 26 | nbbPrice | Price | The NBBO at the moment the trade occurred. Prices are required, quantities are optional. If no price or quantity, fields must be populated with a value of '0'. | A |
| 27 | nbbQty | Whole Quantity | | A |
| 28 | nboPrice | Price | | A |
| 29 | nboQty | Whole Quantity | | A |
| 30 | nbboSource | Choice | Source of the NBBO Data Used. If <i>nbboSource</i> is 'NA', NBBO price and quantity fields must be populated with a value of '0' and the <i>nbboTimestamp</i> must be blank. | A |
| 31 | nbboTimestamp | Timestamp | The date/time at which the NBBO was referenced upon the receipt of the order. Must be blank if <i>nbboSource</i> is 'NA'. | A |
| 32 | quotingIDQS | Industry Member ID | If this trade was the result of a quote that was sent to an IDQS, this is the IMID of the IDQS that submitted the related Quote Received event. Required when <i>quoteID</i> is populated. Must be blank when <i>quoteID</i> is blank. | C |
| 33 | clearingFirm | Unsigned | The clearing number of the Industry Member's clearing firm. Required when the <i>reportingExceptionCode</i> is 'C'. | C |
| 34 | counterparty | Industry Member ID | The counterparty to the trade. Required when the <i>reportingExceptionCode</i> is 'C'. | C |

Table 38: Trade Side Details

The Trade Side Details associated with fields: *buyDetails* and *sellDetails*:
Limited to 1 set of details for each side.

| Seq # | Field Name | Data Type | Description | Include Key |
|-----------|-------------------|-------------------|--|-------------|
| <seq>.1.1 | orderKeyDate | Timestamp | Required if <i>orderID</i> is populated. The <i>orderKeyDate</i> of the order on this side. | C |
| <seq>.1.2 | orderID | Text (64) | The order ID of the order on this side. When <i>firmDesignatedID</i> is populated, <i>orderID</i> must be blank. When <i>orderID</i> is populated, <i>firmDesignatedID</i> must be blank. | C |
| <seq>.1.3 | side | Choice | The side of the trade. | R |
| <seq>.1.4 | quantity | Real Quantity | The execution quantity associated with this <i>orderID</i> . | O |
| <seq>.1.5 | firmDesignatedID | Text (40) | Applicable to internalized trades as described in Section 4.12 . Refer to the Data Dictionary for definition and guidance for populating this field. When <i>firmDesignatedID</i> is populated, <i>orderID</i> must be blank. When <i>orderID</i> is populated, <i>firmDesignatedID</i> must be blank. | C |
| <seq>.1.6 | accountHolderType | Choice | Required if <i>firmDesignatedID</i> is populated. Represents the type of account against which a customer/client order is being filled. | C |
| <seq>.1.7 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |

Linkage Keys for this Reportable Event:

- Order Key: *buyDetails.orderKeyDate*, *CATReporterIMID*, *symbol*, *buyDetails.orderID*
- Order Key: *sellDetails.orderKeyDate*, *CATReporterIMID*, *symbol*, *sellDetails.orderID*
- Trade Key: *tradeKeyDate*, *CATReporterIMID*, *symbol*, *tradeID*
- TRF Linkage Key: Event Date, *CATReporterIMID*, *symbol*, *tapeTradeID*, *marketCenterID*
- IDQS Linkage Key: Event Date, *CATReporterIMID*, *quotingIDQS*, *symbol*, *quoteID*

4.12.2. Trade Supplement Event

The tables below describe the data elements used to report when there is more than one order associated with one side of the trade.

Table 39: Trade Supplement Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|--------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEO TS | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | tradeKeyDate | Timestamp | The <i>tradeKeyDate</i> of the Trade event which this event is supplementing. | R |
| 7 | tradeID | Text (64) | The <i>tradeID</i> of the Trade event which this event is supplementing. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | eventTimestamp | Timestamp | The date/time at which the trade was executed. This must match the <i>eventTimestamp</i> value reported on the Trade this event supplements (including scenarios in which the supplement is created at a later time). | R |
| 10 | buyDetails | Trade Side Details | Required if the subject order was a buy order. See Table 40: Trade Side Details below. | C |
| 11 | sellDetails | Trade Side Details | Required if the subject order was a sell order. See Table 40: Trade Side Details below. | C |

Table 40: Trade Side Details

| The Trade Side Details associated with fields: <i>buyDetails</i> and <i>sellDetails</i> : Limited to 1 set of details for each side. | | | | |
|---|--------------|-----------|--|-------------|
| Seq # | Field Name | Data Type | Description | Include Key |
| <seq>.1.1 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the order on this side. | R |
| <seq>.1.2 | orderID | Text (64) | The order ID assigned by the Industry | R |

| The Trade Side Details associated with fields: <i>buyDetails</i> and <i>sellDetails</i> : Limited to 1 set of details for each side. | | | | |
|---|-----------------|-------------------|--|-------------|
| Seq # | Field Name | Data Type | Description | Include Key |
| | | | Member to the order on this side. | |
| <seq>.1.3 | side | Choice | The side of the trade. | R |
| <seq>.1.4 | quantity | Real Quantity | The execution quantity associated with this <i>orderID</i> . | R |
| <seq>.1.5 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |

Linkage Keys for this Reportable Event:

- Order Key: *buyDetails.orderKeyDate*, *CATReporterIMID*, *symbol*, *buyDetails.orderID*
- Order Key: *sellDetails.orderKeyDate*, *CATReporterIMID*, *symbol*, *sellDetails.orderID*
- Trade Key: *tradeKeyDate*, *CATReporterIMID*, *symbol*, *tradeID*

4.13. Order Fulfillment

The Order Fulfillment event is used to report the execution of a customer/client order that is not required to be reported for public dissemination purposes.

Order Fulfillment events are required in scenarios where:

1. A representative order was used to facilitate the execution of the customer/client order.
2. An order is routed to a foreign market and the resulting foreign execution is not captured by CAT.

The Order Fulfillment event is designed to capture the customer/client details and the firm side details. Firm side details provide linkage to the representative order used to facilitate the execution of the customer/client order.

The *fulfillmentLinkType* field is used to indicate if the firm side details are required. Appendix C contains detailed descriptions of representative order scenarios and illustrates when marking of the representative order, linkage between the represented order and the representative order, and Order Fulfillment linkage is required.

4.13.1. Order Fulfillment Event

Table 41: Order Fulfillment Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEOF | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | fillKeyDate | Timestamp | The date and time the <i>fulfillmentID</i> was assigned. | R |
| 7 | fulfillmentID | Text (64) | The unique identifier for the fulfillment. The combination of reporter, <i>fillKeyDate</i> , <i>symbol</i> and <i>fulfillmentID</i> must be unique. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | eventTimestamp | Timestamp | The date/time when the fulfillment was processed by the Industry Member. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 10 | manualFlag | Boolean | Must be marked as <i>true</i> if this is a manual process. | R |
| 11 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 12 | fulfillmentLinkType | Choice | Refer to Appendix C for representative order linkage requirements. | R |
| 13 | cancelFlag | Boolean | Must be marked as <i>true</i> if the fulfillment was cancelled. | R |
| 14 | cancelTimestamp | Timestamp | When <i>cancelFlag</i> is <i>true</i> , the time at which the fulfillment was cancelled. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------|--------------------------|--|-------------|
| | | | or a finer increment up to nanoseconds. | |
| 15 | quantity | Real Quantity | Quantity being executed and assigned. It may or may not be the full quantity of the order. | R |
| 16 | price | Price | Price of the executed shares. | R |
| 17 | capacity | Choice | The capacity in which the Industry Member acted. | R |
| 18 | clientDetails | Fulfillment Side Details | See Table 42: Fulfillment Side Details below. | R |
| 19 | firmDetails | Fulfillment Side Details | Used to capture the Industry Member side order details. Applicable if there is only one <i>orderID</i> associated with this side of the fulfillment. If more than one representative order was used to fill the customer order, this field must be blank and the <i>firmDetails</i> for each related representative order must be populated in separate MEOFS events. If <i>firmDetails</i> are captured in an MEOFS event, the <i>fulfillmentLinkType</i> field must be populated with a value of 'YS'. See Table 42: Fulfillment Side Details below. Refer to Appendix C for more details. | C |

Table 42: Fulfillment Side Details

| The Fulfillment Side Details associated with fields: <i>clientDetails</i> and <i>firmDetails</i> : Limited to 1 set of details for each side. | | | | |
|--|------------------|---------------|--|-------------|
| Seq # | Field Name | Data Type | Description | Include Key |
| <seq>.1.1 | orderKeyDate | Timestamp | Required if <i>orderID</i> is populated. The <i>orderKeyDate</i> of the order on this side. | C |
| <seq>.1.2 | orderID | Text (64) | The order ID assigned by the Industry Member to the order on this side. When <i>firmDesignatedID</i> is populated, <i>orderID</i> must be blank. When <i>orderID</i> is populated, <i>firmDesignatedID</i> must be blank. | C |
| <seq>.1.3 | side | Choice | The side of the fulfillment. | R |
| <seq>.1.4 | quantity | Real Quantity | The execution quantity associated with this <i>orderID</i> . | O |
| <seq>.1.5 | firmDesignatedID | Text (40) | Applicable to <i>firmDetails</i> when <i>fulfillmentLinkType</i> "YE" is populated, as described in Appendix C. Refer to the Data Dictionary for definition and guidance for populating this field. When <i>firmDesignatedID</i> is populated, <i>orderID</i> must be blank. When <i>orderID</i> is populated, <i>firmDesignatedID</i> must be blank. | C |

| The Fulfillment Side Details associated with fields: <i>clientDetails</i> and <i>firmDetails</i> : Limited to 1 set of details for each side. | | | | |
|--|-------------------|-------------------|--|-------------|
| Seq # | Field Name | Data Type | Description | Include Key |
| <seq>.1.6 | accountHolderType | Choice | Required if <i>firmDesignatedID</i> is populated. Represents the type of account against which a customer/client order is being filled. | C |
| <seq>.1.7 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |

Linkage Keys for this Reportable Event:

- Order Key: *firmDetails.orderKeyDate*, *CATReporterIMID*, *symbol*, *firmDetails.orderID*
- Order Key: *clientDetails.orderKeyDate*, *CATReporterIMID*, *symbol*, *clientDetails.orderID*
- Fulfillment Key: *fillKeyDate*, *CATReporterIMID*, *symbol*, *fulfillmentID*

4.13.2. Order Fulfillment Supplement Event

The tables below describe the data elements used to report a customer order is filled from multiple representative orders. Only one *orderID* may be represented in each Order Fulfillment Supplement event. If multiple representative orders were used to fill a customer order, the *orderID* for each representative order must be populated in its own Order Fulfillment Supplement event.

Table 43: Order Fulfillment Supplement Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|--------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEOFS | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|--------------------------|---|-------------|
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | fillKeyDate | Timestamp | The <i>fillKeyDate</i> of the Order Fulfillment event which this event is supplementing. | R |
| 7 | fulfillmentID | Text (64) | The <i>fulfillmentID</i> of the Order Fulfillment event which this event is supplementing. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | eventTimestamp | Timestamp | The date/time at which the fulfillment was processed by the Industry Member. This must match the <i>eventTimestamp</i> value reported on the Order Fulfillment this event supplements (including scenarios in which the supplement is created at a later time). | R |
| 10 | firmDetails | Fulfillment Side Details | Used to capture the Industry Member side order details. See Table 44: Fulfillment Side Details below. Refer to Appendix C for more details. | R |

Table 44: Fulfillment Side Details

| The Fulfillment Side Details associated with fields: <i>firmDetails</i> Limited to 1 set of details. | | | | |
|---|-----------------|-------------------|--|-------------|
| Seq # | Field Name | Data Type | Description | Include Key |
| <seq>.1.1 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the order on this side. | R |
| <seq>.1.2 | orderId | Text (64) | The order ID assigned by the Industry Member to the order on this side. | R |
| <seq>.1.3 | side | Choice | The side of the trade. | R |
| <seq>.1.4 | quantity | Real Quantity | The execution quantity associated with this <i>orderId</i> . | R |
| <seq>.1.5 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |

Linkage Keys for this Reportable Event:

- Order Key: *firmDetails.orderKeyDate*, *CATReporterIMID*, *symbol*, *firmDetails.orderID*
- Fulfillment Key: *fillKeyDate*, *CATReporterIMID*, *symbol*, *fulfillmentID*

4.13.3. Order Fulfillment Amendment Event

This CAT event is used to report the amendment of a previously reported fulfillment that occurs on the same day or on a subsequent day. This Reportable Event must capture the entire state of the fulfillment after it has been amended, even though some of the data elements may remain unchanged. Order Fulfillment Amendments are not required in scenarios where:

- A trade correction comes before any initial fulfillment has been made, and the Industry Member directly gives the corrected shares to the customer
- An Industry Member makes a correction via a debit/credit to the customer's account instead of modifying the executed shares given back to the customer.

Table 45: Order Fulfillment Amendment Event

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. | R |
| 4 | type | Message Type | MEFA | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | fillKeyDate | Timestamp | When a new Fulfillment Key is assigned, the date and time the <i>fulfillmentID</i> was assigned. When a new Fulfillment Key is not assigned, the <i>fillKeyDate</i> of the fulfillment event being modified. | R |
| 7 | fulfillmentID | Text (64) | When a new Fulfillment Key is assigned, the internal fulfillment ID assigned to the fulfillment event by the Industry Member. When a new Fulfillment Key is not assigned, the <i>fulfillmentID</i> of the fulfillment event being modified. Must be unique within <i>fillKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | R |
| 8 | priorFillKeyDate | Timestamp | In cases when a new <i>fulfillmentID</i> is assigned, the <i>priorFillKeyDate</i> is the <i>fillKeyDate</i> of the | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|--------------------------|--|-------------|
| | | | fulfillment that is being modified. Required if <i>priorFulfillmentID</i> is populated. | |
| 9 | priorFulfillmentID | Text (64) | If a new fulfillment ID is assigned, this is the <i>fulfillmentID</i> of the event being modified. | C |
| 10 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 12 | eventTimestamp | Timestamp | The date/time when the fulfillment was processed by the Industry Member. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 13 | manualFlag | Boolean | Must be marked as <i>true</i> if this is a manual process. | R |
| 14 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 15 | quantity | Real Quantity | Quantity being executed and assigned. It may or may not be the full quantity of the order. | R |
| 16 | capacity | Choice | The capacity in which the Industry Member acted. | R |
| 17 | price | Price | Price of the executed shares. | R |
| 18 | fulfillmentLinkType | Choice | Refer to Appendix C for representative order linkage requirements. | R |
| 19 | clientDetails | Fulfillment Side Details | Refer to Fulfillment Side Details in Table 42: Fulfillment Side Details . | R |
| 20 | firmDetails | Fulfillment Side Details | Refer to Fulfillment Side Details in Table 42: Fulfillment Side Details . | C |

Linkage Keys for this Reportable Event:

- Order Key: *firmDetails.orderKeyDate*, *CATReporterIMID*, *symbol*, *firmDetails.orderID*
- Order Key: *clientDetails.orderKeyDate*, *CATReporterIMID*, *symbol*, *clientDetails.orderID*
- Fulfillment Key: *fillKeyDate*, *CATReporterIMID*, *symbol*, *fulfillmentID*
- Prior Fulfillment Key: *priorFillKeyDate*, *CATReporterIMID*, *symbol*, *priorFulfillmentID*

4.14. Allocations

Industry Members that perform allocations are required to submit a Post-Trade Allocation event to CAT any time shares are allocated to a client account regardless of whether the Industry Member was involved in executing the underlying order(s). Refer to [Section 3.3](#) for additional information on the requirements for reporting allocation events to CAT.

4.14.1. Post-Trade Allocation Event

Table 46: Post-Trade Allocation Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when actionType is 'RPR' | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEPA | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. | O |
| 6 | allocationKeyDate | Timestamp | The date and time the <i>allocationID</i> was assigned. | R |
| 7 | allocationID | Text (64) | The internal allocation ID assigned to the allocation event by the Industry Member. The combination of <i>CATReporterIMID</i> , <i>allocationKeyDate</i> , <i>symbol</i> and <i>allocationID</i> must be unique. | R |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | eventTimestamp | Timestamp | The date/time the allocation was processed. | R |
| 10 | cancelFlag | Boolean | Must be marked as <i>true</i> if the allocation was cancelled. | R |
| 11 | cancelTimestamp | Timestamp | When <i>cancelFlag</i> is <i>true</i> , the time at which the allocation was cancelled. | C |
| 12 | quantity | Real Quantity | Quantity being allocated. | R |
| 13 | price | Price | Price of the allocated shares. | R |
| 14 | side | Choice | The side of customer receiving the allocation. | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------------|-----------|---|-------------|
| 15 | firmDesignatedID | Text (40) | The FDID of the account receiving the allocation, including subaccounts. Refer to the Data Dictionary for definition and guidance for populating this field. | R |
| 16 | custType | Choice | Indicates if the account holder is a natural person or legal entity. | R |
| 17 | institutionFlag | Boolean | Indicates if the account meets the definition of institution under FINRA Rule 4512(c) | R |
| 18 | tradeDate | Date | The trade date of the securities being allocated | R |
| 19 | settlementDate | Date | The settlement date of the securities being allocated | R |
| 20 | allocationType | Choice | Indicates the type of allocation being made (e.g. custody, DVP, step out, correspondent flip). | R |
| 21 | DVPCustodianID | Text (40) | Applicable to DVP transactions. If the custodian is a US broker-dealer, this field must represent the clearing number of the custodian. If the custodian is a US bank and is not a registered broker-dealer, this field must represent the DTC number of the bank. If the custodian is a foreign entity, must be populated with a value of 'FOREIGN'. | C |
| 22 | correspondentCRD | Unsigned | The CRD number of the related Introducing Broker or Correspondent firm, if applicable. | C |
| 23 | newOrderFDID | Text (40) | The FDID of the related New Order event, if available in the booking system. Requirements for populating this field may be expanded in future phases of CAT. | C |
| 24 | allocationInstructionTime | Timestamp | The date/time the time the allocation instruction was received. | O |

Linkage Keys for this Reportable Event:

- Allocation Key: *allocationKeyDate*, *CATReporterIMID*, *symbol*, *allocationID*

4.14.2. Amended Allocation Event

This CAT event is used to report the amendment of a previously reported allocation that occurs on the same day or on a subsequent day. This Reportable Event must capture the entire state of the allocation after it has been amended, even though some of the data elements may remain unchanged. Amended Allocation events are not required in scenarios where:

- An amendment comes before any initial allocation has been made, and the Industry Member directly gives the corrected shares to the customer
- An Industry Member makes a correction via a debit/credit to the customer's account instead of modifying the allocation given to the customer.

Any changes to the FDID after a Post-Trade Allocation event has been reported to CAT must be reported using an Amended Allocation event.

Table 47: Amended Allocation Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when actionType is 'RPR' | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEAA | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. | O |
| 6 | allocationKeyDate | Timestamp | When a new Allocation Key is assigned, the date and time the <i>allocationID</i> was assigned. When a new Allocation Key is not assigned, the <i>allocationKeyDate</i> of the allocation event being modified. | R |
| 7 | allocationID | Text (64) | When a new Allocation Key is assigned, the internal allocation ID assigned to the allocation event by the Industry Member. When a new Allocation Key is not assigned, the <i>allocationID</i> of the allocation event being modified. Must be unique within <i>allocationKeyDate</i> , <i>CATReporterIMID</i> , and symbol combination. | R |
| 8 | priorAllocationKeyDate | Timestamp | In cases when a new <i>allocationID</i> is assigned, the <i>priorAllocationKeyDate</i> is the <i>allocationKeyDate</i> of the allocation event that is being modified. Required if <i>priorAllocationID</i> is populated. | C |
| 9 | priorAllocationID | Text (64) | If a new allocation ID is assigned, this is the <i>allocationID</i> of the event being modified. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------------|---------------|---|-------------|
| 10 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 11 | eventTimestamp | Timestamp | The date/time the time the allocation amendment was processed. | R |
| 12 | quantity | Real Quantity | Quantity being allocated. | R |
| 13 | price | Price | Price of the allocated shares. | R |
| 14 | side | Choice | The side of customer receiving the allocation. | R |
| 15 | firmDesignatedID | Text (40) | The FDID of the account receiving the allocation, including subaccounts. Refer to the Data Dictionary for definition and guidance for populating this field. | R |
| 16 | custType | Choice | Indicates if the account holder is a natural person or legal entity. | R |
| 17 | institutionFlag | Boolean | Indicates if the account meets the definition of institution under FINRA Rule 4512(c) | R |
| 18 | tradeDate | Date | The trade date of the securities being allocated | R |
| 19 | settlementDate | Date | The settlement date of the securities being allocated | R |
| 20 | allocationType | Choice | Indicates the type of allocation being made (e.g. custody, DVP, step out, correspondent flip). | R |
| 21 | DVPCustodianID | Text (40) | Applicable to DVP transactions. If the custodian is a US broker-dealer, this field must represent the clearing number of the custodian. If the custodian is a US bank and is not a registered broker-dealer, this field must represent the DTC number of the bank. If the custodian is a foreign entity, must be populated with a value of 'FOREIGN'. | C |
| 22 | correspondentCRD | Unsigned | The CRD number of the related Introducing Broker or Correspondent firm, if applicable. | C |
| 23 | newOrderFDID | Text (40) | The FDID of the related New Order event, if available in the booking system. Requirements for populating this field may be expanded in future phases of CAT. | C |
| 24 | allocationInstructionTime | Timestamp | The date/time the time the allocation amendment instruction was received. | O |

Linkage Keys for this Reportable Event:

- Allocation Key: *allocationKeyDate*, *CATReporterIMID*, *symbol*, *allocationID*

- Prior Allocation Key: *priorAllocationKeyDate*, *CATReporterIMID*, *symbol*, *priorAllocationID*

4.15. Order Effective Event

The Order Effective event is used indicate that an order, or an underlying condition of an order, has become effective. This event is applicable to orders such as conditional (Refer to [FAQ D26](#)), Stop, Stop Limit, Trailing Stop, Stop on Quote, and Stop Limit on Quote orders. This event is NOT applicable to Stop Stock transactions. The Order Effective event must be reported by the party that was holding the order at the time the order or condition became effective.

If a new order ID is generated when the order becomes effective, which replaces the prior order ID, the *orderID* field must capture the new order ID, and the *priorOrderID* field must reflect the order ID that is being replaced. If the *orderID* remains the same when the order becomes effective, the *priorOrderID* and *priorOrderKeyDate* must remain blank.

Table 48: Order Effective Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEOE | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | When a new Order Key is assigned, the date and time the <i>orderID</i> was assigned. When a new Order Key is not assigned, the <i>orderKeyDate</i> of the CAT event which is being modified. | R |
| 7 | orderID | Text (64) | When a new Order Key is assigned, the internal order ID assigned to the order by the Industry Member. When a new Order Key is not assigned, the <i>orderID</i> of the Order Modified and Cancel/Replace event which is being | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|-------------------|--|-------------|
| | | | modified. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | |
| 8 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | R |
| 9 | priorOrderKeyDate | Timestamp | If a new Order Key has been assigned, this is the <i>orderKeyDate</i> of the event being modified. | C |
| 10 | priorOrderID | Text (64) | If a new Order Key has been assigned, this is the <i>orderID</i> of the event being modified. When populated, the <i>priorOrderID</i> must not be equal to the <i>orderID</i> within the record. | C |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 12 | eventTimestamp | Timestamp | The date/time the order or underlying condition became effective. | R |
| 13 | timeInForce | Name/Value Pairs | The time-in-force for the order (e.g. DAY, IOC, GTC). | R |
| 14 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 15 | deptType | Choice | The category of department, unit, or desk that is the destination of this internal route event. | R |
| 16 | side | Choice | The side of the order. For this Reportable Event, only same-side adjustments are allowed (e.g., sell long to short sell). Required if the field changed when the order or underlying condition became effective. | C |
| 17 | price | Price | The limit price of the order. Required if the field changed when the order became effective. | C |
| 18 | quantity | Real Quantity | The order quantity. Required if the field changed when the order or underlying condition became effective. | C |
| 19 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required if the field changed when the order or underlying condition became effective. Must be > 0. | C |
| 20 | orderType | Choice | The type of order being submitted (e.g., market, limit). Required if the field changed when the order became effective. | C |
| 21 | seqNum | Alphanumeric (40) | The sequence number assigned to the CAT event by the ATS's matching engine. Any alphanumeric not containing a delimiter. | A |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------|----------------|---|-------------|
| 22 | atsDisplayInd | Choice | Indicates if the order is displayed outside of the ATS to subscribers only, or via publicly disseminated quotation data. | A |
| 23 | displayPrice | Price | The displayed price of the order. Required when applicable and the field changed when the order or underlying condition became effective. | C |
| 24 | workingPrice | Price | The working price of the order. Required when applicable and the field changed when the order or underlying condition became effective. | C |
| 25 | displayQty | Whole Quantity | The displayed quantity for this order. Required when applicable and the field changed when the order or underlying condition became effective. | C |
| 26 | nbbPrice | Price | The NBBO at the moment the order was originated or received. Prices are required, quantities are optional. If no price or quantity, fields must be populated with a value of '0'. | A |
| 27 | nbbQty | Whole Quantity | | A |
| 28 | nboPrice | Price | | A |
| 29 | nboQty | Whole Quantity | | A |
| 30 | nbboSource | Choice | Source of the NBBO data used. If <i>nbboSource</i> is 'NA', NBBO price and quantity fields must be populated with a value of '0' and the <i>nbboTimestamp</i> must be blank. | A |
| 31 | nbboTimestamp | Timestamp | The date/time at which the NBBO was referenced upon the receipt of the order. Must be blank if <i>nbboSource</i> is 'NA'. | A |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*

5. Option Events

This section describes Reportable Events for option transactions, including single leg option events and multi-leg option events. The following table lists each option Reportable Event type with its corresponding Message Type code.

Fields specified as Reserved for Future Use are greyed out and must remain blank. Future enhancements to Message Types with positions that are Reserved for Future Use will occupy the available position before adding a new position.

Table 49: Summary of Simple Option Events

| Section | Event | Message Type | Description |
|---------|---|--------------|---|
| 5.1.1 | New Option Order | MONO | Event used to report new option orders to CAT. |
| 5.1.2 | Option Order Supplement | MONOS | Supplement to the New Option Order event, used when the New Option Order event exceeds the maximum length allowed, or when the orders being combined are not captured in the New Order Event. Also used to provide an FDID once known if not available at time of reporting a MONO. |
| 5.1.3 | Option Order Route | MOOR | Reported to CAT by an Industry Member that has routed an option order to another Industry Member or an exchange. |
| 5.1.3.1 | Option Route Modified | MOMR | Reported when an Industry Member modifies a simple option route that was sent to another broker-dealer or exchange. |
| 5.1.3.2 | Option Route Cancelled | MOCR | Reported when an Industry Member modifies a simple option route that was sent to another broker-dealer or exchange. |
| 5.1.3.3 | Option Order Route Supplement | MOORS | Supplement to the Order Route event, optionally used when the status of the <i>routeRejectedFlag</i> is not reported on the MEOR event itself, because the firm chooses to report it using this separate event created at a later time. |
| 5.1.4 | Option Order Accepted | MOOA | Reported when an Industry Member accepts a single-leg option order routed from another Industry Member or an exchange. |
| 5.1.5.1 | Option Order Internal Route Accepted | MOIR | Reported when an order is internally routed from where it was accepted or originated to another desk or other internal destination. |
| 5.1.5.2 | Option Order Internal Route Modified | MOIM | Reported when an Industry Member modifies an option internal route. |
| 5.1.5.3 | Option Order Internal Route Cancelled | MOIC | Reported when an Industry Member cancels an option internal route. |
| 5.1.5.4 | Order Internal Route Modification Request | MEIMR | Reported when a modification to an internal route was requested. |

| Section | Event | Message Type | Description |
|----------|--------------------------------------|--------------|---|
| 5.1.5.5 | Order Internal Route Cancel Request | MEICR | Reported when the cancellation of an internal route was requested. |
| 5.1.6.1 | Child Option Order | MOCO | Reported to represent instances when an order is sliced within the desk or department it is being worked, and is assigned a new order identifier. |
| 5.1.6.2 | Child Option Order Modified | MOCOM | Reported when a Child Option Order is modified. |
| 5.1.6.3 | Child Option Order Cancelled | MOCOC | Reported when a Child Option Order is cancelled. |
| 5.1.7 | Option Order Modified | MOOM | Reported when changes to the Material Terms of an order are made, or an order is cancel/replaced. |
| 5.1.7.1 | Option Order Modified Request | MOOMR | Reported when a customer has requested the modification of a simple options order. |
| 5.1.8 | Option Order Modified Supplement | MOOMS | Used for certain aggregated orders in addition to the Option Order Modified event. |
| 5.1.9 | Option Order Adjusted | MOOJ | Used to report simple order modifications including changes to the price or quantity of the order. |
| 5.1.10 | Option Order Cancelled | MOOC | Reported when an order is fully or partially cancelled. |
| 5.1.10.1 | Option Order Cancel Request | MOOCR | Reported when a customer has requested the cancellation of a simple options order. |
| 5.1.12.1 | Option Order Fulfillment | MOOF | Reports the fill of a customer order in a combined option order scenario. |
| 5.1.12.2 | Option Order Fulfillment Amendment | MOFA | Reports how an order fulfillment was amended. |
| 5.1.13.1 | Option Post-Trade Allocation | MOPA | Reports how option positions (executed contracts) are allocated to end customer accounts and sub-accounts by clearing firms during post-trade processing. |
| 5.1.13.2 | Option Post-Trade Amended Allocation | MOAA | Reports an amendment to a previously reported allocation. |
| 5.1.14 | Option Order Effective | MOOE | Reported when an order or an underlying condition of an order becomes effective |

Table 50: Summary of Multi-Leg Option Events

| Section | Event | Message Type | Description |
|---------|----------------------------|--------------|---|
| 5.2.1 | Multi-Leg New Option Order | MLNO | Event used to report new Multi-Leg option orders to CAT. |
| 5.2.2 | Multi-Leg Order Route | MLOR | Reported to CAT by an Industry Member that has routed a Multi-Leg option order to another Industry Member or an exchange. |

| Section | Event | Message Type | Description |
|---------|---|--------------|---|
| 5.2.3 | Multi-Leg Order Accepted | MLOA | Reported when an Industry Member accepts a Multi-Leg option order routed from another Industry Member. |
| 5.2.4 | Multi-Leg Order Internal Route Accepted | MLIR | Reported when changes to the Material Terms of an order are made, or an order is cancel/replaced. |
| 5.2.5 | Multi-Leg Child Order | MLCO | Reported to represent instances when a Multi-Leg order is sliced within the desk or department it is being worked, and is assigned a new order identifier. |
| 5.2.6 | Multi-Leg Order Modified | MLOM | Reported when changes to the Material Terms of a Multi-Leg order are made, when a Multi-Leg order is cancel/replaced, or when a Multi-Leg order is partially cancelled. |
| 5.2.7 | Multi-Leg Order Modified | MLOC | Reported when an order is fully cancelled. |
| 5.2.8 | Multi-Leg Supplement | MLOS | Reported when a Multi-Leg order is being supplemented with additional information. |

5.1. Simple Option Events

5.1.1. New Option Order Event

An Industry Member must report a New Option Order event to CAT when an order is received or originated. This includes:

1. New customer orders
2. Combined orders
3. Proprietary orders
4. Order(s) received from a non-reporting foreign broker-dealer or affiliate.

An order received from another CAT Reporter (US broker-dealer or an exchange) must be reported as an Option Order Accepted event.

Combined Orders

Industry Members are required to populate a *representativeInd* value of “O” in scenarios where the Industry Member, subject to applicable SRO rules, combines individual, simple option orders from customers before routing to an exchange as a single, simple order for execution. Explicit linkage is required between the combined order and the original customer orders through the *aggregatedOrders* field.

Industry Members are required to populate a *representativeInd* value of “OS” when the number of combined orders included in the *aggregatedOrders* field causes the New Order event to exceed the

maximum allowed message length, or when the orders being represented are not captured in the New Order Event.

Table 51: New Option Order Event

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|--------------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MONO | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderId</i> was assigned. | R |
| 7 | orderId | Text (64) | The internal order ID assigned to the order by the Industry Member. Must be unique within same date, <i>CATReporterIMID</i> , and <i>optionID</i> combination. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | eventTimestamp | Timestamp | The date/time of receipt of the order. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 10 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is handled manually. | R |
| 11 | manualOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the related manual order. Required when <i>manualOrderID</i> is populated. | C |
| 12 | manualOrderID | Text (64) | When this is a duplicative electronic message of a previously (separately) reported manual New Option Order event (<i>electronicDupFlag</i> is <i>true</i>), this field is to capture the internal order ID of the manual order. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|---|----------------------|-------------------|--|-------------|
| 13 | electronicDupFlag | Boolean | Indicates whether this is a duplicative electronic message of a manual event. | R |
| 14 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 15 | deptType | Choice | This is the category of internal department, unit or desk originating the order. | R |
| 16 | side | Choice | The side of the order. | R |
| 17 | price | Price | The limit price of the order per contract. Required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. For FLEX Percent options, this field may reflect a percentage of the underlying closing price, e.g., for a price equal to 95.5% of the underlying close price, this field would contain 95.5. | C |
| 18 | quantity | Real Quantity | The quantity of contracts. | R |
| 19 | minQty | Whole Quantity | The minimum quantity of contracts to be executed. Must be > 0. | C |
| 20 | orderType | Choice | The type of order being submitted. | R |
| 21 | timeInForce | Name/Value Pairs | The time-in-force for the order. | R |
| 22 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 23 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 24 | firmDesignatedID | Text (40) | Refer to the Data Dictionary for definition and guidance for populating this field. | R |
| 25 | accountHolderType | Choice | Represents the type of beneficial owner of the account for which the order was received or originated. | R |
| 26 | affiliateFlag | Boolean | Indicates if the routing party is an affiliate of the Industry Member. | R |
| 27 | aggregatedOrders | Aggregated Orders | When applicable, the order ID of each customer order being combined. Refer to Appendix C for representative order linkage requirements. | C |
| Aggregated Orders – Start | | | | |
| For each order being combined <i>n</i> , the following values are required. | | | | |
| 27.n.1 | orderID | Text (64) | <i>orderID</i> of the order being combined. | R |
| 27.n.2 | orderKeyDate | Timestamp | <i>orderKeyDate</i> of the order being combined. | R |
| 27.n.3 | quantity | Real Quantity | Required when a partial quantity of the order is being combined. | C |
| 27.n.4 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------------------------|--------------------|-----------|---|-------------|
| | | | linkage to an event that was reported with a different <i>CATReporterIMID</i> . | |
| Aggregated Orders – End | | | | |
| 28 | solicitationFlag | Boolean | Indicates if the order was originated in response to an RFQ or other solicitation process. This field is not used to indicate if a registered representative of the firm solicited a client order. | R |
| 29 | openCloseIndicator | Choice | Indicates whether the action taken (buy or sell) will open a new position or will close an existing position in the order originator's account. Required when the exchange's rules require an order to be marked as open or close upon entry into the exchange. | C |
| 30 | representativeInd | Choice | Indicates if the order is a combined order. | R |
| 31 | RFQID | Text (64) | For New Option Order events representing a response to an RFQ or solicitation, the ID assigned to the related RFQ or solicitation being responded to. Must be populated when available. | C |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate, CATReporterIMID, optionID, orderID*
- Order Key: *aggregatedOrders.orderKeyDate, CATReporterIMID, optionID, aggregatedOrders.orderID*
- Manual Order Key: *manualOrderKeyDate, CATReporterIMID, optionID, manualOrderID*

5.1.2. Option Order Supplement Event

The Option Order Supplement Event is a supplement to the New Option Order event. One New Option Order event can have multiple Option Order Supplement events. Multiple Option Order Supplement events are considered additions, not replacements or modifications.

This event accommodates reporting in the following scenarios:

Aggregated Orders

The Option Order Supplement can be used in scenarios when the New Option Order event exceeds the maximum length allowed, or when the orders being combined are not captured in the New Option Order Event.

The *aggregatedOrders* field in the Option Order Supplement event must contain the additional Aggregated Orders that were not captured in the original New Option Order event, or another Supplement event for the same order.

FDID

This event accommodates reporting in scenarios when an Industry Member receives an order for a new account and the new account number, on which the FDID is based, is not yet available for creation and reporting of the CAT new order event. If an FDID has not yet been created when an order has been received, the Industry Member must populate the *firmDesignatedID* field in its New Option Order event with a value of 'PENDING'.

Once the FDID becomes available, the Industry Member must report the actual FDID in the *firmDesignatedID* field in an Option Order Supplement event. Any Option Order Supplement event with an FDID populated will not be considered late for CAT reporting purposes if it is received by 8AM on T+3.

Table 52: Option Order Supplement Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MONOS | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the related New Option Order event which this event is Supplementing. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the related New Option Order event which this event is Supplementing. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>optionID</i> combination. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|---|----------------------|-------------------|--|-------------|
| | | | symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time of the related New Option Order event this event supplements (including scenarios in which the supplement is created at a later time). | R |
| 11 | aggregatedOrders | Aggregated Orders | When applicable, the order ID of each customer order being combined. Refer to Appendix C for combined order linkage requirements. | C |
| Aggregated Orders – Start | | | | |
| For each order being combined <i>n</i> , the following values are required. | | | | |
| 11.n.1 | orderID | Text (64) | <i>orderID</i> of the order being combined. | R |
| 11.n.2 | orderKeyDate | Timestamp | <i>orderKeyDate</i> of the order being combined. | R |
| 11.n.3 | quantity | Real Quantity | Required when a partial quantity of the order is being combined. | C |
| 11.n.4 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| Aggregated Orders – End | | | | |
| 12 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 13 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 14 | firmDesignatedID | Text (40) | Required when reporting a supplement to an MONO event that was reported prior to the FDID being available. Refer to the Data Dictionary for definition and guidance for populating this field. | C |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*

- Order Key: *aggregatedOrders.orderKeyDate*, *CATReporterIMID*, *optionID*, *aggregatedOrders.orderID*

5.1.3. Option Order Route Event

An Industry Member must report to CAT an Option Order Route Event when:

- Routing to another Industry Member
- Routing to exchanges
- Routing between two IMIDs (e.g. two different FINRA MPIDs) attributed to the same legal entity (i.e. the same CRD)

In order for CAT to maintain order lifecycle linkage, the *orderID* populated in the Option Order Route event must reference the most recent internal ID of the order. For example, if an order was modified before routing out, the Route Event must use the ID assigned on the order modification.

Internal routes to another desk or department within an Industry Member are not reported using the Option Order Route event; instead an Option Order Internal Route Accepted event is used. See the [Option Order Internal Route Accepted](#) section for more details.

Handling Instructions on the Option Order Route

The handling instructions included in this event must represent the handling instructions sent by the routing firm to the receiving destination. If the handling instructions do not change when the order is routed from the handling instructions received by the Industry Member and reported on the Option Order Accepted or New Option Order associated with the order, Industry Members may use the handling instruction code "RAR" (Routed as Received) instead of repeating each individual handling instruction.

Table 53: Option Order Route Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|-----------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|----------------------------------|--|-------------|
| | | | CAT Reporter IMID. | |
| 4 | type | Message Type | MOOR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the event which is being routed. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the event which is being routed. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time of the route. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is handled manually. | R |
| 12 | electronicDupFlag | Boolean | Indicates whether this is a duplicative electronic message of a manual event. | R |
| 13 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> . | C |
| 14 | senderIMID | Industry Member ID | The IMID used to identify the Industry Member that is routing the order, known by the destination. When <i>destinationType</i> is 'F', this value must equal the <i>senderIMID</i> on the Option Order Accepted event reported by the destination. When <i>destinationType</i> is 'E', this value must equal the <i>routingParty</i> reported by the exchange on the Participant Order Accepted event. | C |
| 15 | destination | Industry Member ID / Exchange ID | When <i>destinationType</i> is 'F', this value is the IMID used to identify the Industry Member that is receiving this | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|------------------|--|-------------|
| | | | routed order, and must equal the <i>receiverIMID</i> field on the Option Order Accepted event reported by the destination Industry Member. When <i>destinationType</i> is 'E', this value is the Exchange ID of the destination exchange, and must equal the <i>exchange</i> field on the Order Accepted event reported by the destination exchange. | |
| 16 | destinationType | Choice | Indicates whether the destination of the route is an Industry Member, or an exchange. | R |
| 17 | routedOrderID | Text (64) | The ID assigned to the order by the Industry Member when routing the order to another Industry Member or exchange. This value must match the value for <i>routedOrderID</i> reported by the destination in their Option Order Accepted event. Must be unique per combination of Event Date, optionID, <i>destination</i> , <i>senderIMID</i> , and <i>session</i> (applicable only on routes to exchanges). Required when <i>destinationType</i> is 'F' or 'E' and <i>manualFlag</i> is <i>false</i> . | C |
| 18 | session | Text (40) | The session ID used when routing the order. Must only be populated when <i>destinationType</i> is 'E'. This must match the session ID reported in the Participant Option Order Accepted event by the receiving exchange. | C |
| 19 | side | Choice | The side of the order. | R |
| 20 | price | Price | The limit price per contract included on the order when routed. Required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. For FLEX Percent options, this field may reflect a percentage of the underlying close price (e.g. a contract price of 101% of the underlying close price would be represented in this field as 101.00). | C |
| 21 | quantity | Real Quantity | The quantity of contracts included on the order when routed. | R |
| 22 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required if included on the order when routed. Must be > 0. | C |
| 23 | orderType | Choice | The type of order being routed. | R |
| 24 | timeInForce | Name/Value Pairs | The Time-in-Force for the order. | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|--|-------------|
| 25 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade | R |
| 26 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 27 | routeRejectedFlag | Boolean | Indicates the routed order was not accepted by the destination (rejected or no response) when marked <i>true</i> . | R |
| 28 | exchOriginCode | Text (4) | The code signifying the origin of the account as sent to the exchange. Required when <i>destinationType</i> is 'E'. | C |
| 29 | affiliateFlag | Boolean | Indicates if the order is being routed to an affiliate of the Industry Member. | R |
| 30 | multiLegInd | Boolean | Indicates when the order being routed is related to a multi-leg order event. Refer to Section 5.2 for additional guidance. | R |
| 31 | openCloseIndicator | Choice | Indicates when exchange rules require an order to be marked as open or close upon entry into the exchange. | C |
| 32 | pairedOrderID | Text (64) | If the order was routed as a pair, the internal identifier assigned to all orders included in the paired route. | C |
| 33 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*
- Route Linkage Key: Event Date, *senderIMID*, *destination*, *optionID*, *session*, *routedOrderID*

5.1.3.1. Option Route Modified Event

Industry Members must report an Option Route Modified event to CAT when the Material Terms of a route have been changed (e.g., price, quantity), or when an option route is cancel/replaced, and the Material Terms of the order have not changed. Option Modify Route events maintain the same *orderID* as the original Option Order Route event.

All attributes and Material Terms of the route listed on this event must be restated with the modification(s) reflected. The *side* field is required to be reported, but side adjustments are only allowed for same-side changes, including changes between Short Sale and Sell Long. Option Route Modified events must not be used to reflect a change in *senderIMID*, *destination*, or *destinationType*. These changes must be reflected as an Option Route Cancelled event followed by a new Option Order Route event.

The *routedOrderID* of the Option Order Route event being modified must be reflected in the Option Route Modified event. If the *routedOrderID* changed when the route was modified, the *routedOrderID* of the Option Order Route event being modified must be populated in the *priorRoutedOrderID* field. If the *routedOrderID* did not change when the route was modified, the *routedOrderID* of the Order Route event must be populated in the *routedOrderID* field, and the *electronicDupFlag* must be populated as true.

If a route modification is rejected by the destination venue, the Option Route Modification event must be reported with a *routeRejectedFlag* of true.

Table 54: Option Route Modification Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOMR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the route which is being modified. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the route which is being modified. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time of the route modification. If <i>manualFlag</i> is true, timestamp must be reported to seconds. If <i>manualFlag</i> is false, timestamp must be reported to milliseconds | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|--------------------|----------------------------------|--|-------------|
| | | | or a finer increment up to nanoseconds. | |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the route is modified manually. | R |
| 12 | senderIMID | Industry Member ID | The IMID used to identify the Industry Member that is routing the modification, known by the destination. Must equal the <i>senderIMID</i> on the Order Route event being modified. When <i>destinationType</i> is 'F', this value must equal the <i>senderIMID</i> on the Order Accepted event reported by the destination. When <i>destinationType</i> is 'E', this value must equal the <i>routingParty</i> reported by the exchange on the Participant Order Accepted event. | C |
| 13 | destination | Industry Member ID / Exchange ID | The <i>destination</i> of the route modification. Must equal the <i>destination</i> on the Order Route event being modified. When <i>destinationType</i> is 'F', this value is the IMID used to identify the Industry Member that is receiving this routed order. Must equal the <i>receiverIMID</i> field on the Order Accepted event reported by the destination Industry Member. When <i>destinationType</i> is 'E', this value is the Exchange ID of the destination exchange, and it must equal the <i>exchange</i> field on the Order Accepted event reported by the destination exchange. | C |
| 14 | destinationType | Choice | Indicates whether the destination of the route modification is an Industry Member, an exchange or a foreign broker-dealer. Must equal the <i>destinationType</i> on the Order Route event being modified. | R |
| 15 | routedOrderID | Text (64) | The ID assigned to the order by the Industry Member when routing the modification to the destination. Must be unique per combination of Event Date, optionID, <i>destination</i> , <i>senderIMID</i> , and <i>session</i> (applicable only on routes to exchanges). Required when <i>destinationType</i> is 'F' or 'E' and <i>manualFlag</i> is <i>false</i> . | C |
| 16 | priorRoutedOrderID | Text (65) | The <i>routedOrderID</i> of the Order Route event being modified if the <i>routedOrderID</i> changed when the modification was routed to the destination. | C |
| 17 | session | Text (40) | The session ID used when routing the modification. Must be equal to the <i>session</i> on the Order Route event being modified Must only be populated when <i>destinationType</i> is 'E'. This must match the | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|---|-------------|
| | | | session ID reported in the Participant Order Accepted event by the receiving exchange. | |
| 18 | side | Choice | The side of the order. For this Reportable Event, only same-side adjustments are allowed (e.g., sell long to short sell). | R |
| 19 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 20 | quantity | Real Quantity | The order quantity. | R |
| 21 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required when applicable. Must be > 0. | C |
| 22 | leavesQty | Real Quantity | The quantity left open after the modification event. Must be less than or equal to <i>quantity</i> . The full cancel will result in zero in this field. | R |
| 23 | orderType | Choice | The type of order being routed. | R |
| 24 | timeInForce | Name/Value Pairs | The Time-in-Force for the order. | R |
| 25 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 26 | affiliateFlag | Boolean | Indicates if the order is being routed to an affiliate of the Industry Member. | R |
| 28 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 29 | routeRejectedFlag | Boolean | Indicates the route modification was not accepted by the destination (rejected or no response) when marked <i>true</i> . | R |
| 30 | dupROIDCond | Boolean | Indicates when a modification to a route previously routed to a national securities exchange requires the use of the original <i>routedOrderID</i> . This field can only be populated as <i>true</i> on Order Route events when <i>destinationType</i> is 'E'. | R |
| 28 | exchOriginCode | Text (4) | The code signifying the origin of the account as sent to the exchange. Required when <i>destinationType</i> is 'E'. | C |
| 30 | openCloseIndicator | Choice | Indicates when exchange rules require an order to be marked as open or close upon entry into the exchange. | C |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*
- Route Linkage Key: Event Date, *senderIMID*, *destination*, *optionID*, *session*, *routedOrderID*

5.1.3.2. Option Route Cancelled Event

Industry Members must report an Option Route Cancelled event to CAT when a route has been fully or partially cancelled, but the order remains open on the firm's books and records. Partial cancellations of a route may be reported to CAT using an Option Route Cancelled event or an Option Route Modification event.

The *routeOrderID* of the Option Order Route event being cancelled must be reflected in the Option Route Cancelled event. If a route cancellation is rejected by the destination venue, the Option Route Cancelled event must be reported with a *routeRejectedFlag* of true.

Table 55: Option Route Cancelled Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MECR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the route which is being cancelled. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the route which is being cancelled. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|----------------------------------|--|-------------|
| 10 | eventTimestamp | Timestamp | The date/time the route was cancelled (e.g., the time that the route was confirmed to be cancelled in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the route being cancelled was a manual route. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 13 | cancelQty | Real Quantity | The quantity being cancelled. | R |
| 14 | leavesQty | Real Quantity | The quantity left open after the cancel event. Must be less than or equal to <i>quantity</i> . The full cancel will result in zero in this field. | R |
| 15 | senderIMID | Industry Member ID | The IMID used to identify the Industry Member that is routing the cancellation, known by the destination. Must equal the <i>senderIMID</i> in the Order Route event being cancelled. When <i>destinationType</i> is 'F', this value must equal the <i>senderIMID</i> on the Order Accepted event reported by the destination. When <i>destinationType</i> is 'E', this value must equal the <i>routingParty</i> reported by the exchange on the Participant Order Accepted event. | C |
| 16 | destination | Industry Member ID / Exchange ID | When <i>destinationType</i> is 'F', this value is the IMID used to identify the Industry Member that is routed order. Must equal the <i>destination</i> in the Order Route event being cancelled. Must equal the <i>receiverIMID</i> field on the Order Accepted event reported by the destination Industry Member. When <i>destinationType</i> is 'E', this value is the Exchange ID of the destination exchange, and it must equal the <i>exchange</i> field on the Order Accepted event reported by the destination exchange. | C |
| 17 | destinationType | Choice | Indicates whether the destination of the original Order Route event was an Industry Member, an exchange or a foreign broker-dealer. | R |
| 18 | routedOrderID | Text (64) | The ID assigned to the Order Route event being cancelled. This value must match the value for <i>routedOrderID</i> reported by the destination in their Order Accepted report. Must be unique per combination of Event Date, optionID, <i>destination</i> , <i>senderIMID</i> , and <i>session</i> (applicable only on routes to | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|-----------|--|-------------|
| | | | exchanges). Required when <i>destinationType</i> is 'F' or 'E' and <i>manualFlag</i> is <i>false</i> . | |
| 19 | session | Text (40) | The session ID used when routing the order. Must equal the <i>session</i> in the Order Route event being cancelled. Must only be populated when <i>destinationType</i> is 'E'. This must match the session ID reported in the Participant Order Accepted event by the receiving exchange. | C |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*

5.1.3.3. Option Order Route Supplement Event

The Option Order Route Supplement event is a supplement to the Option Order Route event. Option Order Route Supplement events are considered as additions, not replacements or modifications. This event accommodates reporting in scenarios where a route is rejected by the venue to which an order was routed, and the Industry Member chooses to report the *routeRejectedFlag* in this separate event created at a later time on the same day.

Table 56: Option Order Route Supplement Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOORS | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the Option Order Route | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|----------------------------------|--|-------------|
| | | | event that is being supplemented. | |
| 7 | orderID | Text (64) | The <i>orderID</i> of the Option Order Route event that is being supplemented. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option being routed. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time of the related Option Order Route event this event supplements (including scenarios in which the supplement is created at a later time). | R |
| 11 | senderIMID | Industry Member ID | <i>The senderIMID</i> of the Option Order Route event that this event supplements. When <i>destinationType</i> is 'F', this value must equal the <i>senderIMID</i> on the Option Order Accepted event reported by the destination. When <i>destinationType</i> is 'E', this value must equal the <i>routingParty</i> reported by the exchange on the Participant Order Accepted event. | C |
| 12 | destination | Industry Member ID / Exchange ID | <i>The destination</i> of the Option Order Route event that this event supplements. When <i>destinationType</i> is 'F', this value is the IMID used to identify the Industry Member that is receiving this routed order, and must equal the <i>receiverIMID</i> field on the Option Order Accepted event reported by the destination Industry Member. When <i>destinationType</i> is 'E', this value is the Exchange ID of the destination exchange, and must equal the <i>exchange</i> field on the Option Order Accepted event reported by the destination exchange. | C |
| 13 | destinationType | Choice | <i>The destinationType</i> of the Option Order Route event that this event supplements. Indicates whether the destination of the route is an Industry Member, or an exchange. | R |
| 14 | routedOrderID | Text (64) | The ID assigned to the order by the Industry Member when routing the order to the destination. Must match the <i>routedOrderID</i> of the Option Order Route event that this event supplements. | R |
| 15 | session | Text (40) | <i>The session</i> of the Option Order Route event that this event supplements. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|-----------|---|-------------|
| | | | Must only be populated when <i>destinationType</i> is 'E'. This must match the session ID reported in the Participant Order Accepted event by the receiving exchange. | |
| 16 | routeRejectedFlag | Boolean | Indicates the routed order was not accepted by the destination (rejected or no response) when marked <i>true</i> . | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*
- Route Linkage Key: Event Date, *senderIMID*, *destination*, *optionID*, *session*, *routedOrderID*

5.1.4. Option Order Accepted Event

An Option Order Accepted event must be reported to CAT when an Industry Member receives an order from another CAT Reporter (i.e., Industry Member or exchange), or from another IMID belonging to the same Industry Member (i.e., the same CRD).

New customer orders, orders received from a non-broker-dealer affiliate, and orders received from a non-reporting foreign broker-dealer must be reported using a New Option Order event.

Table 57: Option Order Accepted Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOOA | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|----------------------------------|---|-------------|
| | | | assigned. | |
| 7 | orderID | Text (64) | The order ID assigned to the order by the Industry Member upon acceptance. Must be unique within same date, <i>CATReporterIMID</i> , and <i>optionID</i> combination. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | eventTimestamp | Timestamp | The date/time of receipt of the order. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 10 | manualOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the related manual order. Required when <i>manualOrderID</i> is populated. | C |
| 11 | manualOrderID | Text (64) | When this is a duplicative electronic message of a previously (separately) reported manual Option Order Accepted event (<i>electronicDupFlag</i> is <i>true</i>), this field is to capture the internal order ID of the manual order. | C |
| 12 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is handled manually. | R |
| 13 | electronicDupFlag | Boolean | Indicates whether this is a duplicative electronic message of a manual event. | R |
| 14 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 15 | receiverIMID | Industry Member ID | The IMID of the Industry Member receiving the order. When <i>senderType</i> is 'F', this value must equal the <i>destination</i> field on the Option Order Route event reported by the routing Industry Member. When <i>senderType</i> is 'E', this value must equal the <i>routingParty</i> on the Option Order Route event reported by the exchange. | R |
| 16 | senderIMID | Industry Member ID / Exchange ID | When <i>senderType</i> is 'F', this value is the IMID of the sending Industry Member from which the order is routed, and must equal the <i>senderIMID</i> in the Option Order Route event reported by the routing Industry Member. When <i>senderType</i> is 'E', this value is the Exchange ID of the sending Industry Member from which the order is routed, and must equal the <i>exchange</i> field in the Order Route event reported by the exchange. | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|---|-------------|
| 17 | senderType | Choice | Indicates the type of origin from which the order is routed. | R |
| 18 | routedOrderID | Text (64) | The ID for the order as sent by the routing entity. Must be unique per combination of Event Date, optionID, <i>senderIMID</i> , and <i>receiverIMID</i> . Required when <i>manualFlag</i> is <i>false</i> . | C |
| 19 | deptType | Choice | This is the category of internal department, unit or desk receiving the order. | R |
| 20 | side | Choice | The side of the order. | R |
| 21 | price | Price | The price per contract received on this order. Required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 22 | quantity | Real Quantity | The quantity of contracts on the accepted order. | R |
| 23 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required if included on the order when received. Must be > 0. | C |
| 24 | orderType | Choice | The type of order received | R |
| 25 | timeInForce | Name/Value Pairs | The Time-in-Force for the order. | R |
| 26 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 27 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 28 | affiliateFlag | Boolean | Indicates if the routing party is an affiliate of the Industry Member. | R |
| 29 | solicitationFlag | Boolean | Indicates if the order was received in response to an RFQ or other solicitation process. This field is not used to indicate if a registered representative of the firm solicited a client order. | R |
| 30 | pairedOrderID | Text (64) | If the order was received as a pair, the internal identifier assigned to all orders included in the paired route. | C |
| 31 | openCloseIndicator | Choice | Indicates whether the action taken (buy or sell) will open a new position or will close an existing position in the order originator's account. Required when the exchange's rules require an order to be marked as open or close upon entry into the exchange. | C |
| 32 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 33 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*
- Route Linkage Key: Event Date, *senderIMID*, *receiverIMID*, *optionID*, *routedOrderID*
- Manual Order Key: *manualOrderKeyDate*, *CATReporterIMID*, *optionID*, *manualOrderID*

5.1.5. Option Order Internal Route Accepted

An Option Order Internal Route Accepted event must be reported when an order is passed internally to a different department or desk within a *CATReporterIMID*. Routes between different IMIDs attributed to the same Industry Member must be reported as Option Order Route and Option Order Accepted events.

An Option Order Internal Route Accepted event is required to be reported from the perspective of the recipient desk, and indicates that an order was received by an internal destination. Industry Members are required to assign a new Order Key to all Option Order Internal Route Accepted events. A unique *orderID* must be assigned, the *parentOrderID* must be populated with the *orderID* of the event that was internally routed, and the *parentOrderKeyDate* must be populated.

Industry Members may generate child orders using the Child Option Order event prior to routing internally to another desk. This approach is acceptable for CAT reporting and will not result in unlinked events.

5.1.5.1. Option Order Internal Route Accepted Event

Option Order Internal Route Accepted event is used to report an order sent internally to another desk.

Table 58: Option Order Internal Route Accepted Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOIR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| | | | assigned. | |
| 7 | orderID | Text (64) | The internal order ID assigned to the order by the Industry Member. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>optionID</i> combination. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | parentOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the event from which the Option Order Internal Route Accepted event originated. | R |
| 10 | parentOrderID | Text (64) | The <i>orderID</i> of the event from which the Option Order Internal Route Accepted event originated. The <i>parentOrderID</i> must not be equal to the <i>orderID</i> within the record. | R |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 12 | eventTimestamp | Timestamp | The date/time of receipt by the receiving desk. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 13 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is handled manually. | R |
| 14 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 15 | deptType | Choice | The category of department, unit, or desk that is the destination of this internal route event. | R |
| 16 | receivingDeskType | Choice | Field indicates the type of desk receiving the internally routed order. More granular than the field <i>deptType</i> . | R |
| 17 | side | Choice | The side of the order. | R |
| 18 | price | Price | The limit price of the order. Required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 19 | quantity | Real Quantity | The quantity of contracts on the order when internally routed. | R |
| 20 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required if included on the order | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|---|-------------|
| | | | when internally routed. Must be > 0. | |
| 21 | orderType | Choice | The type of order received from the routing desk or department. | R |
| 22 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 23 | openCloseIndicator | Choice | Indicates whether the action taken (buy or sell) will open a new position or will close an existing position in the order originator's account. Required when the exchange's rules require an order to be marked as open or close upon entry into the exchange. | C |
| 24 | multiLegInd | Boolean | Indicates when the order that was routed internally is related to a multi-leg order event. Refer to Section 5.2 for additional guidance. | R |
| 25 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 26 | timeInForce | Name/Value Pairs | The Time-in-Force for the order. | R |
| 27 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*
- Parent Order Key: *parentOrderKeyDate*, *CATReporterIMID*, *optionID*, and *parentOrderID*

5.1.5.2. Option Order Internal Route Modified Event

Industry Members must report an Option Order Internal Route Modified event to CAT when the Material Terms of the option internal route have been changed (e.g., price, quantity). All attributes and Material Terms of the modified option internal route listed on this event must be restated with the modification(s) reflected.

Industry Members are required to assign a new Order Key to all Option Order Internal Route Modified events. A unique *orderID* must be assigned, the *priorOrderID* must be populated with the *orderID* of the Option Order Internal Route Accepted event that is being modified, and the *priorOrderKeyDate* must be populated.

Table 59: Option Order Internal Route Modified Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOIM | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The internal order ID assigned to the order by the Industry Member. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | priorOrderKeyDate | Timestamp | This is the <i>orderKeyDate</i> of the Option Order Internal Route Accepted event being modified. The <i>priorOrderID</i> must not be equal to the <i>orderID</i> within the record. | R |
| 10 | priorOrderID | Text (64) | The <i>orderID</i> of the Option Order Internal Route Accepted event being modified. | R |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 12 | eventTimestamp | Timestamp | The date/time the internal route was modified (e.g., the time that the order was confirmed to be modified in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 13 | manualFlag | Boolean | Must be marked as <i>true</i> if the internal route is | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|---|-------------|
| | | | modified manually. | |
| 14 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 15 | deptType | Choice | The category of department, unit, or desk that received the internal route. | R |
| 16 | receivingDeskType | Choice | Indicates the type of desk that received the internal route. More granular than the field <i>deptType</i> . | R |
| 17 | initiator | Choice | Indicates who initiated the internal route modification. | R |
| 18 | side | Choice | The side of the order. | R |
| 19 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 20 | quantity | Real Quantity | The order quantity. | R |
| 21 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required when applicable. Must be > 0. | C |
| 22 | leavesQty | Real Quantity | The number of shares of the order left open at the receiving desk after the modification has occurred. Must be less than or equal to <i>quantity</i> . | R |
| 23 | orderType | Choice | The type of order received from the routing desk or department. | R |
| 24 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 25 | openCloseIndicator | Choice | Indicates whether the action taken (buy or sell) will open a new position or will close an existing position in the order originator's account. Required when the exchange's rules require an order to be marked as open or close upon entry into the exchange. | C |
| 26 | timeInForce | Name/Value Pairs | The Time-in-Force for the order. | R |
| 27 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*
- Prior Order Key: *priorOrderKeyDate*, *CATReporterIMID*, *optionID*, and *priorOrderID*

5.1.5.3. Option Order Internal Route Cancelled Event

If an option internal route is cancelled, an Option Order Internal Route Cancelled event must be reported. Partial cancellations may be reported using an Option Order Internal Route Modified event or Option Order Internal Route Cancelled event with *leavesQty*.

Table 60: Option Order Internal Route Cancelled Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOIC | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the internal route which is being cancelled. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the internal route which is being cancelled. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time the internal route was cancelled (e.g., the time that the order was confirmed to be cancelled in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|---------------|--|-------------|
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is cancelled manually. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 13 | cancelQty | Real Quantity | The quantity being cancelled. | R |
| 14 | leavesQty | Real Quantity | The number of shares of the order left open at the receiving desk after the modification has occurred. Must be less than or equal to <i>quantity</i> . | R |
| 15 | initiator | Choice | Indicates who initiated the internal route cancellation. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *symbol*, *orderID*

5.1.5.4. Option Order Internal Route Modification Request

Industry Members must report an Option Order Internal Route Modification Request event to CAT when a desk within the firm receives a request to modify the Material Terms of an internal route. All attributes and Material Terms of the modified internal route listed on this event must be restated with the modification(s) reflected.

Table 61: Option Order Internal Route Modification Request Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOIMR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the | O |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| | | | filename. | |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the order event for which the internal route modification was requested. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the order event for which the internal route modification was requested. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time the internal route modification request was received. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the internal route modification was requested manually. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 13 | deptType | Choice | The category of department, unit, or desk that received the internal route modification request. | R |
| 14 | receivingDeskType | Choice | Indicates the type of desk that received the internal route modification request. More granular than the field <i>deptType</i> . | R |
| 15 | side | Choice | The side of the order. | R |
| 16 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 17 | quantity | Real Quantity | The order quantity. | R |
| 18 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required when applicable. Must be > 0. | C |
| 19 | leavesQty | Real Quantity | The number of shares of the order left open at the receiving desk after the modification has occurred. Must be less than or equal to <i>quantity</i> . | R |
| 20 | orderType | Choice | The type of order received from the routing desk or department. | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|--|-------------|
| 21 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 22 | timeInForce | Name/Value Pairs | The Time-in-Force for the order. | R |
| 23 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*

5.1.5.5. Option Order Internal Route Cancel Request

Industry Members must report an Order Internal Route Cancel Request event to CAT when a desk within the firm receives a request to cancel an internal route.

Table 62: Option Order Internal Route Cancel Request Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEICR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the order event for which the cancellation was requested. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the order event for which the cancellation was requested. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|---------------|--|-------------|
| | | | open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | |
| 10 | eventTimestamp | Timestamp | The date/time the internal route cancellation request was received. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the cancel request was received manually. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 13 | leavesQty | Real Quantity | The number of shares of the order left open at the receiving desk after the modification has occurred. Must be less than or equal to <i>quantity</i> . | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*

5.1.6. Child Option Order Event

The Child Option Order is used to represent instances when an order is sliced within the desk or department it is being worked, and is assigned a new order identifier. Child Option Order events are not required to be reported to CAT, but are provided for the convenience of Industry Members to help model these types of order handling scenarios.

Child Option Order events are defined to include only the key data elements that may be changed when the event is created including fields to link to the parent order. The following rules apply with respect to Child Option Orders:

1. Child Option Order events can only be used when an order is sliced and assigned new order IDs within the same desk. An Option Order Internal Route Accepted event must be reported when routed to another desk.
2. A child order may be generated off of another child order without limitation.
3. Child Option Orders must belong to the same FDID as the parent order.
4. Child Option Orders must **not** be used to represent a multi-leg option order being “legged out”. However, the Child Order event may be used in scenarios where an order is “legged out” and

subsequently entered into another OMS/EMS or Algo within the same desk or department where a new orderID is assigned to each leg upon entry.

5.1.6.1. Child Option Order Event

Table 63: Child Option Order Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|--------------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOCO | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The internal order ID assigned to the child order by the Industry Member. Must be unique with the <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>optionID</i> combination. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | parentOrderKeyDate | Timestamp | <i>orderKeyDate</i> of the event from which the Child Order originated. | R |
| 10 | parentOrderID | Text (64) | The <i>orderID</i> of the event from which the Child Order originated. The <i>parentOrderID</i> must not be equal to the <i>orderID</i> within the record. | R |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|--|-------------|
| | | | different <i>CATReporterIMID</i> . | |
| 12 | eventTimestamp | Timestamp | The date/time at which the child order was originated. | R |
| 13 | side | Choice | The side of the order. | R |
| 14 | price | Price | The limit price of the order per contract. Required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. For FLEX Percent options, this field may reflect a percentage of the underlying closing price, e.g., for a price equal to 95.5% of the underlying close price, this field would contain 95.5. | C |
| 15 | quantity | Real Quantity | The quantity of contracts of the Child order. | R |
| 16 | minQty | Whole Quantity | The minimum quantity of contracts to be executed. Must be > 0. | C |
| 17 | orderType | Choice | The type of order being submitted (i.e. market, limit, or cabinet). | R |
| 18 | timeInForce | Name/Value Pairs | The time-in-force for the order (e.g. DAY, IOC, GTC). | R |
| 19 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 20 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 21 | openCloseIndicator | Choice | Indicates when exchange rules require an order to be marked as open or close upon entry into the exchange. | R |
| 22 | multiLegInd | Boolean | Indicates when the Child Order was originated from a Multi-leg order. Refer to Section 5.2 for additional guidance. | R |
| 23 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*
- Parent Order Key: *parentOrderKeyDate*, *CATReporterIMID*, *optionID*, *parentOrderID*

5.1.6.2. Child Option Order Modified Event

Industry Members must report a Child Option Order Modified event to CAT when the Material Terms of the child order have been changed (e.g. price, quantity). All attributes and Material Terms of the modified child order listed on this event must be restated with the modification(s) reflected.

A Child Option Order Modification event is reported only in cases when a Child Option Order is modified. A Child Option Order Modified event must not be used when modifying an Option Order Internal Route Accepted event.

Industry Members are required to assign a new Order Key to all Child Option Order Modified events. A unique *orderID* must be assigned, the *priorOrderID* must be populated with the *orderID* of the Child Option Order event that is being modified, and the *priorOrderKeyDate* must be populated.

Table 64: Child Option Order Modified Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOCOM | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The internal order ID assigned to the order by the Industry Member. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>optionID</i> combination. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | priorOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the Child Option Order event being modified. | R |
| 10 | priorOrderID | Text (64) | The <i>orderID</i> of the Child Option Order event being modified. The <i>priorOrderID</i> must not be equal to the <i>orderID</i> within the record. | R |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|--|-------------|
| | | | executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | |
| 12 | eventTimestamp | Timestamp | The date/time at which the child order was modified (e.g., the time that the child order was confirmed to be modified in the firm's OMS/EMS). | R |
| 13 | side | Choice | The side of the order. | R |
| 14 | price | Price | The limit price of the order per contract. Required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. For FLEX Percent options, this field may reflect a percentage of the underlying closing price, e.g., for a price equal to 95.5% of the underlying close price, this field would contain 95.5. | C |
| 15 | quantity | Real Quantity | The quantity of contracts of the Child Order. | R |
| 16 | minQty | Whole Quantity | The minimum quantity of contracts to be executed. Must be > 0. | C |
| 17 | leavesQty | Real Quantity | The number of shares of the Child Order left open after the modification has occurred. Must be less than or equal to <i>quantity</i> . | R |
| 18 | orderType | Choice | The type of order being submitted. | R |
| 19 | timeInForce | Name/Value Pairs | The time-in-force for the order. | R |
| 20 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 21 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 22 | openCloseIndicator | Choice | Indicates whether the action taken (buy or sell) will open a new position or will close an existing position in the order originator's account. Required when the exchange's rules require an order to be marked as open or close upon entry into the exchange. | C |
| 23 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 24 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*
- Prior Order Key: *priorOrderKeyDate*, *CATReporterIMID*, *optionID*, and *priorOrderID*

5.1.6.3. Child Option Order Cancelled Event

If a child option order is cancelled, a Child Option Order Cancelled event must be reported to CAT by the Industry Member.

A partial cancellation can be reported either with a Child Option Order Modified event or Child Option Order Cancelled event with *leavesQty*, depending on how it is handled by the Industry Member. If a cancel message was used, the Industry Member must report a Child Option Order Cancelled event to CAT. If a modify or cancel/replace message was used, a Child Option Order Modified event must be reported to CAT. This keeps the reported event in line with the action taken by the Industry Member.

Table 65: Child Option Order Cancelled Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOCOC | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the Child Option Order event which is being cancelled. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the Child Option Order event which is being cancelled. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbol section for more information. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|---------------|--|-------------|
| 10 | eventTimestamp | Timestamp | The date/time at which the child order was cancelled (e.g., the time that the child order was confirmed to be cancelled in the firm's OMS/EMS). | R |
| 11 | side | Choice | The side of the order. | R |
| 12 | cancelQty | Real Quantity | The quantity of the Child order being cancelled. | R |
| 13 | leavesQty | Real Quantity | The number of shares of the Child Order left open after the cancellation. Must be less than or equal to <i>quantity</i> . Full cancellation will result in a zero in the field. | R |
| 14 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 15 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*

5.1.7. Option Order Modified and Cancel/Replace Event

Industry Members must report an Option Order Modified event to CAT when the Material Terms of an order have been changed (e.g. price, quantity), or when an order is cancel/replaced. All attributes and Material Terms of the modified order must be restated with the modification(s) reflected. If the order is a combined order, the *aggregatedOrders* field must be restated every time the order is modified or cancel/replaced. Changes to the orders being combined in the *aggregatedOrders* field are considered a modification to the order. The *side* field is required to be reported, but side adjustments are only allowed for same-side changes, including changes between Short Sale and Sell Long.

Industry Members are required to assign a new Order Key to all Option Order Modified events. A unique *orderID* must be assigned, the *priorOrderID* must be populated with the *orderID* of the event that is being modified, and the *priorOrderKeyDate* must be populated. If the order has been modified several times, the *priorOrderID* must refer to order ID of the order that is being replaced. If the order ID remains the same during the modification, the *priorOrderID* must remain blank.

All attributes and Material Terms of the modified order listed on this event must be reported when applicable, including the fields that remain unchanged.

Table 66: Option Order Modified and Cancel/Replace Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOOM | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderId</i> was assigned. | R |
| 7 | orderId | Text (64) | The internal order ID assigned to the order by the Industry Member. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>optionID</i> combination. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | priorOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the event being modified. | R |
| 10 | priorOrderID | Text (64) | The <i>OrderID</i> of the event being modified. The <i>priorOrderID</i> must not be equal to the <i>orderId</i> within the record. | R |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 12 | eventTimestamp | Timestamp | The date/time at which the order was modified (e.g., the time that the order was confirmed to be modified in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|----------------------------------|---|-------------|
| 13 | manualOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the related manual order. Required when <i>manualOrderID</i> is populated. | C |
| 14 | manualOrderID | Text (64) | When this is a duplicative electronic message of a previously (separately) reported manual Option Order Modified and Cancel/Replace event (<i>electronicDupFlag</i> is <i>true</i>), this field is to capture the internal order ID of the manual order. | C |
| 15 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is handled manually. | R |
| 16 | electronicDupFlag | Boolean | Indicates whether this is a duplicative electronic message of a manual event. | R |
| 17 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 18 | receiverIMID | Industry Member ID | Required when the modification is received from an Industry Member or an exchange. The IMID of the Industry Member receiving the routed order modification. When <i>senderType</i> is 'F', this value must equal the <i>destination</i> field on the Order Route event reported by the routing Industry Member. When <i>senderType</i> is 'E', this value must equal the <i>routingParty</i> on the Participant Option Order Modified event reported by the exchange. | C |
| 19 | senderIMID | Industry Member ID / Exchange ID | Required when the modification is received from an Industry Member or an exchange. When <i>senderType</i> is 'F', this value is the IMID of the sending Industry Member from which the order is routed, and must equal the <i>senderIMID</i> in the Order Route event reported by the routing Industry Member. When <i>senderType</i> is 'E', this value is the Exchange ID of the sending entity from which the order is routed, and must equal the <i>exchange</i> field in the Participant Option Order Modified event reported by the exchange. | C |
| 20 | senderType | Choice | Required when the modification is received from an Industry Member or an exchange. Indicates the type of origin from which the order is routed. | C |
| 21 | routedOrderID | Text (64) | The ID for the order as sent by the routing entity. Must be unique per combination of Event Date, optionID, <i>senderIMID</i> , and <i>receiverIMID</i> . Required when <i>senderType</i> is 'F' or 'E' and <i>manualFlag</i> is <i>false</i> . | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|---|----------------------|-------------------|--|-------------|
| 22 | initiator | Choice | Indicates who initiated the order modification. | R |
| 23 | side | Choice | The side of the order. | R |
| 24 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 25 | quantity | Real Quantity | The order quantity. | R |
| 26 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required if included on the order when originated. Must be > 0. | C |
| 27 | leavesQty | Real Quantity | The number of contracts left open after the modification has occurred. Must be less than or equal to <i>quantity</i> . | R |
| 28 | orderType | Choice | The type of order being submitted. | R |
| 29 | timeInForce | Name/Value Pairs | The time-in-force for the order. | R |
| 30 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 31 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 32 | openCloseIndicator | Choice | Indicates whether the action taken (buy or sell) will open a new position or will close an existing position in the order originator's account. Required when the exchange's rules require an order to be marked as open or close upon entry into the exchange. | C |
| 33 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 34 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 35 | aggregatedOrders | Aggregated Orders | When applicable, the order ID of each customer order being combined. Refer to Appendix C for combined order linkage requirements. | C |
| Aggregated Orders – Start | | | | |
| For each order being combined <i>n</i> , the following values are required. | | | | |
| 35.n.1 | orderID | Text (64) | <i>orderID</i> of the order being combined. | R |
| 35.n.2 | orderKeyDate | Timestamp | <i>orderKeyDate</i> of the order being combined. | R |
| 35.n.3 | quantity | Real Quantity | Required when a partial quantity of the order is being combined. | C |
| 35.n.4 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| Aggregated Orders – End | | | | |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|-----------|--|-------------|
| 36 | representativeInd | Choice | Indicates if the order is a combined order and if linkage is required. | R |
| 37 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 38 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate, CATReporterIMID, optionID, orderID*
- Order Key: *aggregatedOrders.orderKeyDate, CATReporterIMID, optionID, aggregatedOrders.orderID*
- Prior Order Key: *priorOrderKeyDate, CATReporterIMID, optionID, and priorOrderID*
- Route Linkage Key: *Event Date, optionID, receiverIMID, senderIMID, routedOrderID*
- Manual Order Key: *manualOrderKeyDate, CATReporterIMID, optionID, manualOrderID*

5.1.7.1. Option Order Modification Request Event

The Option Order Modification Request event is required when a customer has requested the modification to the Material Terms of an order.

Table 67: Option Order Modification Request Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOOMR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|----------------------------------|--|-------------|
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the option order event for which the modification was requested. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the option order event for which the modification was requested. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time of receipt of the modification request. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the modification was requested manually. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 13 | receiverIMID | Industry Member ID | Required when the modification request is received from an Industry Member or an exchange. The IMID of the Industry Member receiving the routed order modification. | C |
| 14 | senderIMID | Industry Member ID / Exchange ID | Required when the modification request is received from an Industry Member or an exchange. When <i>senderType</i> is 'F', this value is the IMID of the sending Industry Member from which the order is routed. When <i>senderType</i> is 'E', this value is the Exchange ID of the sending entity from which the order is routed. | C |
| 15 | senderType | Choice | Required when the modification request is received from an Industry Member or an exchange. Indicates the type of origin from which the order is routed. | C |
| 16 | side | Choice | The side of the order. | R |
| 17 | price | Price | The limit price of the order, required when <i>orderType</i> is 'LMT'. Must be blank when <i>orderType</i> is 'MKT'. | C |
| 18 | quantity | Real Quantity | The order quantity. | R |
| 19 | minQty | Whole Quantity | The minimum quantity of an order to be | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|---|-------------|
| | | | executed. Required if included on the order when originated. Must be > 0. | |
| 20 | leavesQty | Real Quantity | The number of contracts left open after the modification has occurred. Must be less than or equal to <i>quantity</i> . | R |
| 21 | orderType | Choice | The type of order being submitted. | R |
| 22 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 23 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 24 | openCloseIndicator | Choice | Indicates whether the action taken (buy or sell) will open a new position or will close an existing position in the order originator's account. Required when the exchange's rules require an order to be marked as open or close upon entry into the exchange. | C |

5.1.8. Option Order Modified Supplement Event

The Option Order Modified Supplement event serves as a supplement to the Option Order Modified event, just as the New Option Order Supplement event serves as a supplement to the New Option Order event.

Table 68: Option Order Modified Supplement Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOOMS | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the related Order Modified and Cancel/Replace event which this event is supplementing. | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|--|------------------|-------------------|--|-------------|
| 7 | orderID | Text (64) | The <i>orderID</i> of the related Order Modified and Cancel/Replace event which this event is supplementing. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time of the Option Order Modified this event supplements. | R |
| 11 | aggregatedOrders | Aggregated Orders | The order ID of each customer order being combined. Refer to Appendix C for representative order linkage requirements. | R |
| Aggregated Orders – Start | | | | |
| For each order being represented <i>n</i> , the following values are required. | | | | |
| 11.n.1 | orderID | Text (64) | <i>orderID</i> of the order being combined. | R |
| 11.n.2 | orderKeyDate | Timestamp | <i>orderKeyDate</i> of the order being combined. | R |
| 11.n.3 | Quantity | Real Quantity | Required when a partial quantity of the order is being combined. | C |
| 11.n.4 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| Aggregated Orders – End | | | | |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*
- Order Key: *aggregatedOrders.orderKeyDate*, *CATReporterIMID*, *optionID*, *aggregatedOrders.orderID*

5.1.9. Option Order Adjusted Event

The Option Order Adjusted event may be used instead of an Order Modified event to report changes to the price or quantity of an order. However, the Option Order Adjust events must not be used when changes to the price or quantity is initiated by a routing Industry Member.

The following rules apply:

1. If the price changes, then *price* must be reported to represent current state of the order relative to price. The quantity fields are not required.
2. If any of the quantity fields change, then all quantity fields (i.e. *quantity*, *minQty*, *leavesQty*) must be reported to represent the current state of the order relative to quantity. The price field is not required.

Any modification that cannot be fully represented in this Reportable Event must be reported via the Option Order Modified event.

Industry Members are required to assign a new Order Key to all Option Order Adjusted events. A unique *orderID* must be assigned, the *priorOrderID* must be populated with the *orderID* of the event that is being modified, and the *priorOrderKeyDate* must be populated. If the order has been modified several times, the *priorOrderID* must refer to order ID of the order that is being replaced. If the order ID remains the same during the modification, the *priorOrderID* must remain blank.

Table 69: Option Order Adjusted Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOOJ | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The internal order ID assigned to the order by the Industry Member. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>optionID</i> combination. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | priorOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the event being adjusted. | R |
| 10 | priorOrderID | Text (64) | The <i>orderID</i> of the event being modified. When populated, the <i>priorOrderID</i> must not be equal to the <i>orderID</i> within the record. | R |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 12 | eventTimestamp | Timestamp | The date/time at which the order was modified (e.g., the time that the order was confirmed to be modified in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 13 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is handled manually. | R |
| 14 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 15 | initiator | Choice | Indicates who initiated the order adjustment. | R |
| 16 | price | Price | The limit price of the order. Required if <i>price</i> changed. | C |
| 17 | quantity | Real Quantity | The order quantity. Required if <i>quantity</i> , <i>minQty</i> or <i>leavesQty</i> changed. | C |
| 18 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required when applicable and when <i>quantity</i> , <i>minQty</i> , or | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|---|-------------|
| | | | <i>leavesQty</i> changed. Must be > 0. | |
| 19 | leavesQty | Real Quantity | The number of contracts left open after the adjustment/has occurred. Required when <i>quantity</i> , <i>minQty</i> or <i>leavesQty</i> changed. Must be less than or equal to <i>quantity</i> . | C |
| 20 | timeInForce | Name/Value Pairs | The time-in-force for the order. | R |
| 21 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*
- Prior Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *priorOrderID*

5.1.10. Option Order Cancelled Event

The Option Order Cancelled event is reported when an order is fully or partially cancelled. Partial cancellations of an order may be reported to CAT using an Order Cancelled event or an Order Modified event. Implicit order cancellations, such as cancellations due to expiration of Time in Force, are not required to be reported to CAT.

Option Order Cancelled events are required to be reported by the entity that initiated the cancellation.

When an Order is routed from Firm A to Firm B, the following rules apply:

1. If Firm A or its customer initiates the cancel, then Firm A and Firm B must report the Order Cancelled.
2. If Firm B initiates the cancel, then Firm B must report the Order Cancelled.

Table 70: Option Order Cancelled Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|-----------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|-------------------|--|-------------|
| | | | Reporter IMID. | |
| 4 | type | Message Type | MOOC | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the Options order event which is being cancelled. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the Options order event which is being cancelled. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time at which the order was cancelled (e.g., the time that the order was confirmed to be cancelled in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is handled manually. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> . | C |
| 13 | cancelQty | Real Quantity | The quantity being cancelled. | R |
| 14 | leavesQty | Real Quantity | The quantity of contracts left open after the cancel event. Must be less than or equal to <i>quantity</i> . For full order cancellations, zero must be populated in this field. | R |
| 15 | initiator | Choice | Indicates who initiated the order cancellation. | R |
| 16 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*

5.1.10.1. Option Order Cancel Request Event

Table 71: Option Order Cancel Request Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOOCR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the Options order event for which the cancellation was requested. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the Options order event for which the cancellation was requested. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 10 | eventTimestamp | Timestamp | The date/time of receipt of the cancel request. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or finer increment up to nanoseconds. | R |
| 11 | manualFlag | Boolean | Must be marked as <i>true</i> if the cancellation was requested manually. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> . | C |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *optionID*, *orderID*

5.1.11. Option Trade

An Option Trade event is used when a simple option order is manually executed on an options trading floor. The Option Trade event is one-sided. Both parties to the trade are required to report an Option Trade event with the *sideDetailsInd* populated indicating which side of the trade the Industry Member was associated with, and which Trade Side Details will be populated in the Trade event.

Table 72: Option Trade Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOOT | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | tradeKeyDate | Timestamp | The date and time the <i>tradeID</i> was assigned. | R |
| 7 | tradeID | Text (64) | Unique ID assigned to this execution by the Industry Member. This ID will be used in subsequent events when a specific trade needs to be identified. The combination of date, <i>CATReporterIMID</i> , <i>optionID</i> , and <i>tradeID</i> must be unique. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | eventTimestamp | Timestamp | The date/time at which the trade was executed. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|--------------------|---|-------------|
| 10 | manualFlag | Boolean | Must be marked as <i>true</i> if this is a manual execution. | R |
| 11 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 12 | cancelFlag | Boolean | Must be marked as <i>true</i> if the execution is cancelled and was not reported to an options trade reporting facility. | R |
| 13 | cancelTimestamp | Timestamp | When <i>cancelFlag</i> is <i>true</i> , the time at which the execution was cancelled. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | C |
| 14 | quantity | Real Quantity | Quantity of the trade. | R |
| 15 | price | Price | The execution price of the trade. | R |
| 16 | capacity | Choice | The capacity in which the Industry Member acted. | R |
| 17 | tapeTradeID | Text (40) | The unique identifier assigned by the executing firm which links together both sides of the trade. | C |
| 18 | sideDetailsInd | Choice | Identifies if a Trade event is one sided, and which side of the trade the Industry Member is populating in the Trade Side Details. When <i>sideDetailsInd</i> is 'BUY', only the <i>buyDetails</i> are populated. When <i>sideDetailsInd</i> is 'SELL', only the <i>sellDetails</i> are populated. | R |
| 19 | buyDetails | Trade Side Details | See Table 73: Trade Side Details below. Must be populated if <i>sideDetailsInd</i> is 'BUY'. Must be blank if <i>sideDetailsInd</i> is 'SELL'. | C |
| 20 | sellDetails | Trade Side Details | See Table 73: Trade Side Details below. Must be populated if <i>sideDetailsInd</i> is 'SELL'. Must be blank if <i>sideDetailsInd</i> is 'BUY'. | C |

Table 73: Trade Side Details

| The Trade Side Details associated with fields: <i>buyDetails</i> and <i>sellDetails</i> : Limited to 1 set of details for each side. | | | | |
|---|--------------|-----------|---|-------------|
| Seq # | Field Name | Data Type | Description | Include Key |
| <seq>.1.1 | orderKeyDate | Timestamp | Required if <i>orderID</i> is populated. The <i>orderKeyDate</i> of the order on this side. | C |
| <seq>.1.2 | orderID | Text (64) | The order ID of the order on this side. When <i>firmDesignatedID</i> is populated, <i>orderID</i> must be blank. When <i>orderID</i> is | C |

| The Trade Side Details associated with fields: <i>buyDetails</i> and <i>sellDetails</i> : Limited to 1 set of details for each side. | | | | |
|---|-----------------|-------------------|--|-------------|
| Seq # | Field Name | Data Type | Description | Include Key |
| | | | populated, <i>firmDesignatedID</i> must be blank. | |
| <seq>.1.3 | side | Choice | The side of the trade. | R |
| <seq>.1.4 | quantity | Real Quantity | The execution quantity associated with this <i>orderID</i> . | R |
| <seq>.1.5 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |

Linkage Keys for this Reportable Event:

- Order Key: *buyDetails.orderKeyDate*, *CATReporterIMID*, *optionID*, *buyDetails.orderID*
- Order Key: *sellDetails.orderKeyDate*, *CATReporterIMID*, *optionID*, *sellDetails.orderID*
- Trade Key: *tradeKeyDate*, *CATReporterIMID*, *optionID*, *tradeID*
- TRF Linkage Key: *eventTimestamp*, *CATReporterIMID*, *optionID*, *tapeTradeID*

5.1.12. Option Order Fulfillment Event

An Option Order Fulfillment event must be reported when an Industry Member (subject to applicable SRO rules) combines individual simple option orders from customers before routing to an exchange as a single simple order for execution and reflects the fill given to each individual order. Explicit linkage is required between the combined order and the original customer orders through the *fulfillmentLinkType* field.

5.1.12.1. Option Order Fulfillment Event

Table 74: Option Order Fulfillment Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|-----------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|--------------------------|---|-------------|
| | | | reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | |
| 4 | Type | Message Type | MOOF | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | fillKeyDate | Timestamp | The date and time the <i>fulfillmentID</i> was assigned. | R |
| 7 | fulfillmentID | Text (64) | A unique identifier for the fulfillment. For each Industry Member, the combination of <i>fillKeyDate</i> , <i>optionID</i> , and <i>fulfillmentID</i> must be unique. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | eventTimestamp | Timestamp | The date/time when the fulfillment was processed by the Industry Member. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or finer increment up to nanoseconds. | R |
| 10 | manualFlag | Boolean | Must be marked as <i>true</i> if this is a manual process. | R |
| 11 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 12 | quantity | Real Quantity | Quantity being reported as fulfilled with this event. It may or may not be the full quantity of the order. | R |
| 13 | price | Price | Price at which the order contracts are being fulfilled. | R |
| 14 | fulfillmentLinkType | Choice | Refer to Appendix C for combined order linkage requirements. | R |
| 15 | clientDetails | Fulfillment Side Details | Refer to Table 75: Options Fulfillment Side Details . | R |
| 16 | firmDetails | Fulfillment Side Details | Refer to Table 75: Options Fulfillment Side Details . | R |
| 17 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |
| 18 | cancelFlag | Boolean | Must be marked as <i>true</i> if the fulfillment was cancelled. | R |
| 19 | cancelTimestamp | Timestamp | When <i>cancelFlag</i> is <i>true</i> , the time at which | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|-----------|--|-------------|
| | | | the fulfillment was cancelled. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | |

Table 75: Options Fulfillment Side Details

| The Fulfillment Side Details associated with fields: <i>clientDetails</i> and <i>firmDetails</i> : Limited to 1 set of details for each side. | | | | |
|--|-----------------|-------------------|--|-------------|
| Seq # | Field Name | Data Type | Description | Include Key |
| <seq>.1.1 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the order on this side. | R |
| <seq>.1.2 | orderID | Text (64) | The order ID assigned by the Industry Member to the order on this side. | R |
| <seq>.1.3 | side | Choice | The side of the fulfillment. | R |
| <seq>.1.4 | quantity | Real Quantity | The execution quantity associated with this <i>orderID</i> . | O |
| <seq>.1.5 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |

Linkage Keys for this Reportable Event:

- Order Key: *firmDetails.orderKeyDate*, *CATReporterIMID*, *optionID*, *firmDetails.orderID*
- Order Key: *clientDetails.orderKeyDate*, *CATReporterIMID*, *optionID*, *clientDetails.orderID*
- Fulfillment Key: *fillKeyDate*, *CATReporterIMID*, *optionID*, *fulfillmentID*

5.1.12.2. Option Order Fulfillment Amendment Event

This CAT event is used to report the amendment of a previously reported fulfillment that occurs on the same day or on a subsequent day. This Reportable Event must capture the entire state of the fulfillment after it has been amended, even though some of the data elements may remain unchanged.

Option Order Fulfillment Amendments are not required in scenarios where:

- A trade correction comes before any initial fulfillment has been made, and the Industry Member directly gives the corrected shares to the customer.

- An Industry Member makes a correction via a debit/credit to the customer's account instead of modifying the executed shares given back to the customer.
- When an Industry Member fulfils an order and receives a trade break from the exchange, it is possible that the Industry Member may choose to take the delta (e.g. using an error account) without amending the manner by which the order was fulfilled.

Table 76: Option Order Fulfillment Amendment Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOFA | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | fillKeyDate | Timestamp | When a new Fulfillment Key is assigned, the date and time the <i>fulfillmentID</i> was assigned. When a new Fulfillment Key is not assigned, the <i>fillKeyDate</i> of the fulfillment event being modified. | R |
| 7 | fulfillmentID | Text (64) | When a new Fulfillment Key is assigned, the internal fulfillment ID assigned to the order by the Industry Member. When a new Fulfillment Key is not assigned, the <i>fulfillmentID</i> of the fulfillment event being modified. Must be unique within <i>fillKeyDate</i> , <i>CATReporterIMID</i> , and <i>optionID</i> combination. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | priorFillKeyDate | Timestamp | In cases when a new <i>fulfillmentID</i> is assigned, the <i>priorFillKeyDate</i> is the <i>fillKeyDate</i> of the fulfillment that is being modified. Required if <i>priorFulfillmentID</i> is | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|--------------------------|--|-------------|
| | | | populated. | |
| 10 | priorFulfillmentID | Text (64) | If a new fulfillment ID is assigned, this is the <i>fulfillmentID</i> of the event being modified. | C |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 12 | eventTimestamp | Timestamp | The date/time that the fulfillment was amended. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or finer increment up to nanoseconds. | R |
| 13 | manualFlag | Boolean | Must be marked as <i>true</i> if this is a manual process. | R |
| 14 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 15 | fulfillmentLinkType | Choice | Refer to Appendix C for combined order linkage requirements. | R |
| 16 | quantity | Real Quantity | Amended quantity being reported as fulfilled with this event. It may or may not be the full quantity of the order. | R |
| 17 | price | Price | Amended price at which the order contracts are being fulfilled. | R |
| 18 | clientDetails | Fulfillment Side Details | Refer to Table 75: Options Fulfillment Side Details . | R |
| 19 | firmDetails | Fulfillment Side Details | Refer to Table 75: Options Fulfillment Side Details . | R |
| 20 | reservedForFutureUse | | Field is Reserved for Future Use and must remain blank. | |

Linkage Keys for this Reportable Event:

- Order Key: *firmDetails.orderKeyDate*, *CATReporterIMID*, *optionID*, *firmDetails.orderID*
- Order Key: *clientDetails.orderKeyDate*, *CATReporterIMID*, *optionID*, *clientDetails.orderID*
- Fulfillment Key: *fillKeyDate*, *CATReporterIMID*, *optionID*, *fulfillmentID*
- Prior Fulfillment Key: *priorFillKeyDate*, *CATReporterIMID*, *optionID*, *priorFulfillmentID*

5.1.13. Option Post-Trade Allocations Event

Industry Members that perform allocations are required to submit a Post-Trade Allocation event to CAT any time shares are allocated to a client account regardless of whether the Industry Member was involved in executing the underlying order(s). Refer to [Section 3.3](#) for additional information on the requirements for reporting allocation events to CAT.

5.1.13.1. Option Post-Trade Allocation Event

Table 77: Option Post-Trade Allocation Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when actionType is 'RPR' | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOPA | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. | O |
| 6 | allocationKeyDate | Timestamp | The date and time the <i>allocationID</i> was assigned. | R |
| 7 | allocationID | Text (64) | The internal allocation ID assigned to the allocation event by the Industry Member. The combination of <i>CATReporterIMID</i> , <i>allocationKeyDate</i> , <i>symbol</i> and <i>allocationID</i> must be unique. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | eventTimestamp | Timestamp | The date/time the allocation was processed. | R |
| 10 | cancelFlag | Boolean | Must be marked as <i>true</i> if the allocation was cancelled. | R |
| 11 | cancelTimestamp | Timestamp | When <i>cancelFlag</i> is <i>true</i> , the time at which the allocation was cancelled. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------------|---------------|---|-------------|
| 12 | quantity | Real Quantity | Quantity being allocated. | R |
| 13 | price | Price | Price of the allocated shares. | R |
| 14 | side | Choice | The side of customer receiving the allocation. | R |
| 15 | firmDesignatedID | Text (40) | The FDID of the account receiving the allocation, including subaccounts. Refer to the Data Dictionary for definition and guidance for populating this field. | R |
| 16 | custType | Choice | Indicates if the account holder is a natural person or legal entity. | R |
| 17 | institutionFlag | Boolean | Indicates if the account meets the definition of institution under FINRA Rule 4512(c) | R |
| 18 | tradeDate | Date | The trade date of the securities being allocated | R |
| 19 | settlementDate | Date | The settlement date of the securities being allocated | R |
| 20 | allocationType | Choice | Indicates the type of allocation being made (e.g. custody, DVP, step out, correspondent flip). | R |
| 21 | DVPCustodianID | Text (40) | Applicable to DVP transactions. If the custodian is a US broker-dealer, this field must represent the clearing number of the custodian. If the custodian is a US bank and is not a registered broker-dealer, this field must represent the DTC number of the bank. If the custodian is a foreign entity, must be populated with a value of 'FOREIGN'. | C |
| 22 | correspondentCRD | Unsigned | The CRD number of the related Introducing Broker or Correspondent firm, if applicable. | C |
| 23 | newOrderFDID | Text (40) | The FDID of the related New Order event, if available in the booking system. Requirements for populating this field may be expanded in future phases of CAT. | C |
| 24 | allocationInstructionTime | Timestamp | The date/time the time the allocation instruction was received. | O |

Linkage Keys for this Reportable Event:

- Allocation Key: *allocationKeyDate*, *CATReporterIMID*, *optionID*, *allocationID*

5.1.13.2. Option Amended Allocation Event

This CAT event is used to report the amendment of a previously reported option allocation that occurs on the same day or on a subsequent day. This Reportable Event must capture the entire state of the allocation after it has been amended, even though some of the data elements may remain unchanged.

Option Amended Allocation events are not required in scenarios where:

- An amendment comes before any initial allocation has been made, and the Industry Member directly gives the corrected shares to the customer
- An Industry Member makes a correction via a debit/credit to the customer's account instead of modifying the allocation given to the customer.

Any changes to the FDID after a Post-Trade Allocation event has been reported to CAT must be reported using an Amended Allocation event.

Table 78: Option Amended Allocation Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when actionType is 'RPR' | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MOAA | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. | O |
| 6 | allocationKeyDate | Timestamp | When a new Allocation Key is assigned, the date and time the <i>allocationID</i> was assigned. When a new Allocation Key is not assigned, the <i>allocationKeyDate</i> of the allocation event being modified. | R |
| 7 | allocationID | Text (64) | When a new Allocation Key is assigned, the internal allocation ID assigned to the allocation event by the Industry Member. When a new Allocation Key is not assigned, the <i>allocationID</i> of the allocation event being modified. Must be unique within <i>allocationKeyDate</i> , <i>CATReporterIMID</i> , and symbol | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------------------|---------------|---|-------------|
| | | | combination. | |
| 8 | priorAllocationKeyDate | Timestamp | In cases when a new <i>allocationID</i> is assigned, the <i>priorAllocationKeyDate</i> is the <i>allocationKeyDate</i> of the allocation event that is being modified. Required if <i>priorAllocationID</i> is populated. | C |
| 9 | priorAllocationID | Text (64) | If a new allocation ID is assigned, this is the <i>allocationID</i> of the event being modified. | C |
| 10 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 11 | eventTimestamp | Timestamp | The date/time the time the allocation amendment was processed. | R |
| 12 | quantity | Real Quantity | Quantity being allocated. | R |
| 13 | price | Price | Price of the allocated shares. | R |
| 14 | side | Choice | The side of customer receiving the allocation. | R |
| 15 | firmDesignatedID | Text (40) | The FDID of the account receiving the allocation, including subaccounts. Refer to the Data Dictionary for definition and guidance for populating this field. | R |
| 16 | custType | Choice | Indicates if the account holder is a natural person or legal entity. | R |
| 17 | institutionFlag | Boolean | Indicates if the account meets the definition of institution under FINRA Rule 4512(c) | R |
| 18 | tradeDate | Date | The trade date of the securities being allocated | R |
| 19 | settlementDate | Date | The settlement date of the securities being allocated | R |
| 20 | allocationType | Choice | Indicates the type of allocation being made (e.g. custody, DVP, step out, correspondent flip). | R |
| 21 | DVPCustodianID | Text (40) | Applicable to DVP transactions. If the custodian is a US broker-dealer, this field must represent the clearing number of the custodian. If the custodian is a US bank and is not a registered broker-dealer, this field must represent the DTC number of the bank. If the custodian is a foreign entity, must be populated with a value of 'FOREIGN'. | C |
| 22 | correspondentCRD | Unsigned | The CRD number of the related Introducing Broker or Correspondent firm, if applicable. | C |
| 23 | newOrderFDID | Text (40) | The FDID of the related New Order event, if available in the booking system. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------------|-----------|---|-------------|
| | | | Requirements for populating this field may be expanded in future phases of CAT. | |
| 24 | allocationInstructionTime | Timestamp | The date/time the time the allocation amendment instruction was received. | O |

Linkage Keys for this Reportable Event:

- Allocation Key: *allocationKeyDate*, *CATReporterIMID*, *optionID*, *allocationID*
- Prior Allocation Key: *priorAllocationKeyDate*, *CATReporterIMID*, *optionID*, *priorAllocationID*

5.1.14. Option Order Effective Event

The Option Order Effective event is used indicate that an order, or an underlying condition of an order, has become effective. This event is applicable to orders such as conditional (Refer to [FAQ D26](#)), Stop, Stop Limit, Trailing Stop, Stop on Quote, and Stop Limit on Quote orders. This event is NOT applicable to Stop Stock transactions. The Option Order Effective event must be reported by the party that was holding the order at the time the order or condition became effective.

If a new order ID is generated when the order becomes effective, which replaces the prior order ID, the *orderID* field must capture the new order ID, and the *priorOrderID* field must reflect the order ID that is being replaced. If the *orderID* remains the same when the order becomes effective, the *priorOrderID* and *priorOrderKeyDate* must remain blank.

Table 79: Order Effective Event Field Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|--------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MEOE | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|-------------------|--|-------------|
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | When a new Order Key is assigned, the date and time the <i>orderID</i> was assigned. When a new Order Key is not assigned, the <i>orderKeyDate</i> of the CAT event which is being modified. | R |
| 7 | orderID | Text (64) | When a new Order Key is assigned, the internal order ID assigned to the order by the Industry Member. When a new Order Key is not assigned, the <i>orderID</i> of the Order Modified and Cancel/Replace event which is being modified. Must be unique within <i>orderKeyDate</i> , <i>CATReporterIMID</i> , and <i>symbol</i> combination. | R |
| 8 | optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | R |
| 9 | priorOrderKeyDate | Timestamp | If a new Order Key has been assigned, this is the <i>orderKeyDate</i> of the event being modified. | C |
| 10 | priorOrderID | Text (64) | If a new Order Key has been assigned, this is the <i>orderID</i> of the event being modified. When populated, the <i>priorOrderID</i> must not be equal to the <i>orderID</i> within the record. | C |
| 11 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| 12 | eventTimestamp | Timestamp | The date/time the order or underlying condition became effective. | R |
| 13 | timeInForce | Name/Value Pairs | The time-in-force for the order (e.g. DAY, IOC, GTC). | R |
| 14 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 15 | deptType | Choice | The category of department, unit, or desk that is the destination of this internal route event. | R |
| 16 | side | Choice | The side of the order. For this Reportable Event, only same-side adjustments are allowed (e.g., sell long to short sell). Required if the field changed when the order or underlying condition became effective. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|--------------------|----------------|--|-------------|
| 17 | price | Price | The limit price of the order. Required if the field changed when the order became effective. | C |
| 18 | quantity | Real Quantity | The order quantity. Required if the field changed when the order or underlying condition became effective. | C |
| 19 | minQty | Whole Quantity | The minimum quantity of an order to be executed. Required if the field changed when the order or underlying condition became effective. Must be > 0. | C |
| 20 | orderType | Choice | The type of order being submitted (e.g., market, limit). Required if the field changed when the order became effective. | C |
| 21 | openCloseIndicator | Choice | Indicates whether the action taken (buy or sell) will open a new position or will close an existing position in the order originator's account. Required if the field changed when the order became effective. | C |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate, CATReporterIMID, symbol, orderID*

5.2. Multi-Leg Option Order Events

Multi-leg Option Order events must be reported to CAT in scenarios where:

- A multi-leg order that meets the definition of an exchange-defined complex order and is routed to an options exchange as a complex order. The definition of complex order in this context is not dependent on any NMS or options linkage plan trade through exemption provision embedded within an exchange's definition of a complex order.
- A multi-leg order involving at least one option leg received by a broker-dealer as a single instruction where all legs of the order are linked and such linkage affects the price of any individual leg of the order. A typical example of this type of order would be a Buy/Write.

The following are examples of orders that would not be reported to CAT as a multi-leg order:

- Baskets
- Complex/multi-leg orders that do not involve an option

Multi-Leg Order events include both strategy level details, and leg level details that are represented as a multi-dimensional array. The number of legs must be identified in the *numberOfLegs* field. There is no limit to the number of *legDetails* that may be included in a multi-leg order event, however, the number of legs able to be represented in each record is constrained by record size limits. If a Multi-Leg Order event has more legs than can be represented in an order event, additional legs must be represented in a Multi-Leg Order Supplement event.

Route of a Multi-Leg Option Order as Individual Legs

In scenarios where the Multi-Leg order is “legged-out” and routed as individual legs, the route of each leg must be reported as a simple Order Route or Option Order Route event with the *multiLegInd* populated.

This guidance applies in scenarios where:

- A Multi-Leg order is received/originated and routed directly to the destination venue as a simple Order Route or Option Order Route event. In this scenario, the *multiLegInd* must be populated as ‘true’ on each Order Route or Option Order Route event.
- A Multi-Leg order is received/originated and routed internally as individual legs before being routed to the destination venue by the receiving desk or department. In this scenario, the *multiLegInd* must be populated as ‘true’ on each Order Internal Route Accepted or Option Order Internal Route Accepted event. The *multiLegInd* must be ‘false’ on subsequent Order Route or Option Order Route events.
- A Multi-Leg order is received/originated and is entered into a separate OMS/EMS or Algo as individual legs where a new *orderID* is generated, and the Industry Member chooses to report simple Child Order or Child Option Order events. While Child Order events must not be used to represent the order being “legged out”, in this case a new *orderID* is assigned to each individual leg when entered into the OMS/EMS or Algo. In this scenario, the *multiLegInd* must be populated as ‘true’ on each Child Order or Child Option Order event. The *multiLegInd* must be ‘false’ on subsequent Order Route or Option Order Route events.

5.2.1. Multi-Leg New Order Event

Multi-Leg New Order events are used to report the receipt or origination of a Multi-Leg order event.

Combined Orders

Industry Members are required to populate a *representativeInd* value of “OML” in scenarios where the Industry Member, subject to applicable SRO rules, combines individual Multi-Leg Option orders from customers with the same strategy before routing to an exchange as a single Multi-Leg order for

execution. Explicit linkage is required between the combined Multi-Leg order and the original customer orders through the *aggregatedOrders* field.

Industry Members are required to populate a *representativeInd* value of “OMS” when the number of combined orders included in the *aggregatedOrders* field causes the Multi-Leg New Order event to exceed the maximum allowed message length, or when the orders being represented are not captured in the Multi-Leg New Order Event.

Fills of a Multi-Leg order occur at the leg level and must be reported to CAT as simple Order Fulfillment or Options Order Fulfillment events with a *fulfillmentLinkType* value of “OML” to indicate that the *orderID* referenced in the *firmDetails* is a Multi-Leg New Order event.

Individual Legs Represented as FIX Messages

In scenarios where a multi-leg order is received as individual FIX messages for each leg with instructions to treat as a complex order, or in scenarios where a multi-leg order is received manually and is followed by individual FIX messages for each leg, the receipt of the individual FIX messages are not required to be reported to CAT. The industry Member is only required to report the receipt of the Multi-Leg order.

If the Industry Member is unable to suppress the reporting of these FIX messages, they must be reported as simple New Order or Order Accepted events with a *handlingInstructions* value of ‘CMPX’. Events with a *handlingInstructions* value of ‘CMPX’ will not be linked to the Multi-Leg New Order event.

Table 80: Multi-Leg New Order Event Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is ‘RPR’. Must be blank when <i>actionType</i> is ‘NEW’. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MLNO | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|---|-------------|
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The internal order ID assigned to the order by the Industry Member. Must be unique within same date, <i>CATReporterIMID</i> , and <i>optionID</i> combination. | R |
| 8 | underlying | Symbol | The symbol of the underlying stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | O |
| 9 | eventTimestamp | Timestamp | The date/time of receipt of the order. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 10 | manualFlag | Boolean | Must be marked as <i>true</i> if the order was received manually. | R |
| 11 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 12 | deptType | Choice | This is the category of internal department, unit or desk originating the order. | R |
| 13 | price | Price | The net price of the multi-leg order at a net debit/credit. This field represents a net price for all legs in the order inclusive of ratio and side, and must specify whether the price is a debit or credit. Debits must be represented as a positive number, and credits must be represented as a negative number. | R |
| 14 | quantity | Real Quantity | The number of units of the multi-leg order. | R |
| 15 | minQty | Whole Quantity | The minimum quantity of units to be executed. Must be > 0. | C |
| 16 | orderType | Choice | The type of order being submitted. | R |
| 17 | timeInForce | Name/Value Pairs | The time-in-force for the order. | R |
| 18 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 19 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 22 | firmDesignatedID | Text (40) | Refer to the Data Dictionary for definition and guidance for populating this field. | R |
| 21 | accountHolderType | Choice | Represents the type of beneficial owner of the account for which the order was | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|---|-------------------|-------------------|--|-------------|
| | | | received or originated. | |
| 22 | affiliateFlag | Boolean | Indicates if the routing party is an affiliate of the Industry Member. | R |
| 23 | aggregatedOrders | Aggregated Orders | When applicable, the order ID of each customer order being combined. Refer to Appendix C for representative order linkage requirements. | C |
| Aggregated Orders – Start | | | | |
| For each order being combined <i>n</i> , the following values are required. | | | | |
| 23.n.1 | orderID | Text (64) | <i>orderID</i> of the order being combined. | R |
| 23.n.2 | orderKeyDate | Timestamp | <i>orderKeyDate</i> of the order being combined. | R |
| 23.n.3 | quantity | Real Quantity | Required when a partial quantity of the order is being combined. | C |
| 23.n.4 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| Aggregated Orders – End | | | | |
| 24 | representativeInd | Choice | Indicates if the order is a combined order. | R |
| 25 | solicitationFlag | Boolean | Indicates if the order was originated in response to an RFQ or other solicitation process. This field is not used to indicate if a registered representative of the firm solicited a client order. | R |
| 26 | RFQID | Text (64) | For New Order events representing a response to an RFQ or solicitation, the ID assigned to the related RFQ or solicitation being responded to. Must be populated when available. | C |
| 27 | numberOfLegs | Whole Quantity | Indicates the number of legs in the multi-leg order. | R |
| 28 | legDetails | Leg Details | See Table 81: Leg Details below. | R |

Table 81: Leg Details

| The Leg Details associated with field: <i>legDetails</i> | | | | |
|---|--------------------|---------------|--|-------------|
| The number legs that may be represented in each record is limited by file size. Legs that cannot be represented due to file size constraints must be represented in a Multi-Leg Supplement event. | | | | |
| Seq # | Field Name | Data Type | Description | Include Key |
| 28.n.1 | legRefID | Text (64) | Unique identifier of the leg. | O |
| 28.n.2 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. Required if the leg being represented is an equity leg. Must be blank if <i>optionID</i> is populated. | C |
| 28.n.3 | optionID | Option ID | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the <u>Option Symbols</u> section for more information. Required if the leg being represented is an option leg. Must be blank if <i>symbol</i> is populated. | C |
| 28.n.4 | openCloseIndicator | Choice | Indicates whether the action taken (buy or sell) will open a new position or will close an existing position in the order originator's account. Required when the exchange's rules require a leg to be marked as open or close upon entry into the exchange. | C |
| 28.n.5 | side | Choice | The side of the leg. | R |
| 28.n.6 | legRatioQuantity | Real Quantity | The ratio of quantity for this individual leg relative to the entire multi-leg security. May be represented as the entire quantity for the leg, or as the lowest common factor. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *orderID*
- Order Key: *aggregatedOrders.orderKeyDate*, *CATReporterIMID*, *aggregatedOrders.orderID*

5.2.2. Multi-Leg Order Route event

Multi-Leg Order Route events are used to report the route of a Multi-Leg order at the strategy level. Leg level details are required to be restated on the Multi-Leg Order Route event.

Handling Instructions on Multi-Leg Order Route Events

Handling Instructions are required to be reported on the Multi-Leg Order Route event. The handling instructions included in this event must represent the handling instructions sent by the routing firm to the receiving destination. If the handling instructions do not change when the order is routed from the handling instructions received by the Industry Member and reported on the Multi-Leg Order Accepted or Multi-Leg New Order associated with the order, Industry Members may use the *handlingInstructions* value "RAR" (Routed as Received) instead of repeating each individual handling instruction.

Table 82: Multi-Leg Order Route Event Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MLOR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the event which is being routed. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the order event which is being routed. | R |
| 8 | underlying | Symbol | The symbol of the underlying stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | O |
| 9 | eventTimestamp | Timestamp | The date/time of the Multi-Leg Order Route. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 10 | manualFlag | Boolean | Must be marked as <i>true</i> if the order was routed manually. | R |
| 11 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|----------------------------------|---|-------------|
| | | | systematized. | |
| 12 | senderIMID | Industry Member ID | <p>The IMID used to identify the Industry Member that is routing the order, known by the destination.</p> <p>When <i>destinationType</i> is 'F', this value must equal the <i>senderIMID</i> on the Multi-Leg Order Accepted event reported by the destination.</p> <p>When <i>destinationType</i> is 'E', this value must equal the <i>routingParty</i> reported by the exchange on the Participant Complex Option Order Accepted event.</p> | C |
| 13 | destination | Industry Member ID / Exchange ID | <p>When <i>destinationType</i> is 'F', this value is the IMID used to identify the Industry Member that is receiving this routed order, and it must equal the <i>receiverIMID</i> field on the Order Accepted event reported by the destination Industry Member.</p> <p>When <i>destinationType</i> is 'E', this value is the Exchange ID of the destination exchange, and it must equal the <i>exchange</i> field on the Complex Option Order Accepted event reported by the destination exchange.</p> | C |
| 14 | destinationType | Choice | Indicates whether the destination of the route is an Industry Member or an exchange. | R |
| 15 | routedOrderID | Text (64) | <p>The ID assigned to the order by the Industry Member when routing the order to the destination. This value must match the value for <i>routedOrderID</i> reported by the destination in their Order Accepted report.</p> <p>Must be unique per combination of Event Date, <i>destination</i>, <i>senderIMID</i>, and <i>session</i> (applicable only on routes to exchanges).</p> <p>Required when <i>destinationType</i> is 'F' or 'E' and <i>manualFlag</i> is false.</p> | C |
| 16 | session | Text (40) | <p>The session ID used when routing the order.</p> <p>Must only be populated when <i>destinationType</i> is 'E'. This must match the session ID reported in the Participant Complex Option Order Accepted event by the receiving exchange.</p> | C |
| 17 | price | Price | <p>The net price of the multi-leg order at a net debit/credit.</p> <p>This field represents a net price for all legs in the order inclusive of ratio and side, and must specify whether the price is a debit or credit. Debits must be</p> | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|---|-------------|
| | | | represented as a positive number, and credits must be represented as a negative number. | |
| 18 | quantity | Real Quantity | The number of units of the multi-leg order. | R |
| 19 | minQty | Whole Quantity | The minimum quantity of units to be executed. Must be > 0. | C |
| 20 | orderType | Choice | The type of order being routed. | R |
| 21 | timeInForce | Name/Value Pairs | The time-in-force for the order. | R |
| 22 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 23 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 24 | affiliateFlag | Boolean | Indicates if the order is being routed to an affiliate | R |
| 25 | routeRejectedFlag | Boolean | Indicates the routed order was not accepted by the destination (rejected or no response) when marked <i>true</i> . | R |
| 26 | exchOriginCode | Text (4) | The code signifying the origin of the account as sent to the exchange. Required when <i>destinationType</i> is 'E'. | C |
| 27 | pairedOrderID | Text (64) | If the order was routed as a pair, the internal identifier assigned to all orders included in the paired route. | C |
| 29 | numberOfLegs | Whole Quantity | Indicates the number of legs in the multi-leg order. | R |
| 30 | legDetails | Leg Details | See Table 83: Leg Details below. | R |

Table 83: Leg Details

| Seq # | Field Name | Data Type | Description | Include Key |
|---|------------|-----------|---|-------------|
| The Leg Details associated with field: <i>legDetails</i> | | | | |
| The number legs that may be represented in each record is limited by file size. Legs that cannot be represented due to file size constraints must be represented in a Multi-Leg Supplement event. | | | | |
| 30.n.1 | legRefID | Text (64) | Unique identifier of the leg. | O |
| 30.n.2 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. Required if the leg being represented is an equity leg. Must be blank if <i>optionID</i> is populated. | C |
| 30.n.3 | optionID | Option ID | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more | C |

| The Leg Details associated with field: <i>legDetails</i> | | | | |
|---|--------------------|---------------|--|-------------|
| The number legs that may be represented in each record is limited by file size. Legs that cannot be represented due to file size constraints must be represented in a Multi-Leg Supplement event. | | | | |
| Seq # | Field Name | Data Type | Description | Include Key |
| | | | information. Required if the leg being represented is an option leg. Must be blank if <i>symbol</i> is populated. | |
| 30.n.4 | openCloseIndicator | Choice | Indicates whether the action taken (buy or sell) will open a new position or will close an existing position in the order originator's account. Required when the exchange's rules require a leg to be marked as open or close upon entry into the exchange. | C |
| 30.n.5 | side | Choice | The side of the leg. | R |
| 30.n.6 | legRatioQuantity | Real Quantity | The ratio of quantity for this individual leg relative to the entire multi-leg security. May be represented as the entire quantity for the leg, or as the lowest common factor. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *orderID*
- Route Linkage Key: Event Date, *senderIMID*, *destination*, *session*, *routedOrderID*

5.2.3. Multi-Leg Order Accepted Event

A Multi-Leg Order Accepted event must be reported to CAT when an Industry Member receives an order from another CAT Reporter (i.e., Industry Member or exchange), or from another IMID belonging to the same Industry Member (i.e., the same CRD).

New customer orders, orders received from a non-broker-dealer affiliate, and orders received from a non-reporting foreign broker-dealer must be reported using a Multi-Leg New Order event.

Table 84: Multi-Leg Order Accepted Event Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|-----------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|----------------------------------|---|-------------|
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MLOA | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The order ID assigned to the order by the Industry Member upon acceptance. Must be unique within same date, <i>CATReporterIMID</i> , and <i>optionID</i> combination. | R |
| 8 | underlying | Symbol | The symbol of the underlying stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | O |
| 9 | eventTimestamp | Timestamp | The date/time of receipt of the Multi-Leg order. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 10 | manualFlag | Boolean | Must be marked as <i>true</i> if the order was received manually. | R |
| 11 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 12 | receiverIMID | Industry Member ID | The IMID of the Industry Member receiving the order. When <i>senderType</i> is 'F', this value must equal the <i>destination</i> field on the Multi-Leg Order Route event reported by the routing Industry Member. | R |
| 13 | senderIMID | Industry Member ID / Exchange ID | When <i>senderType</i> is 'F', this value is the IMID of the sending Industry Member from which the order is routed, and must equal the <i>senderIMID</i> in the Multi-Leg Order Route event reported by the routing Industry Member. | R |
| 14 | senderType | Choice | Indicates the type of origin from which the order is routed. | R |
| 15 | routedOrderID | Text (64) | The ID for the order as sent by the routing entity. Must be unique per combination of Event Date, <i>optionID</i> , <i>senderIMID</i> , and <i>receiverIMID</i> . | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|---|-------------|
| | | | Required when <i>manualFlag</i> is <i>false</i> . | |
| 16 | price | Price | The net price of the multi-leg order at a net debit/credit. This field represents a net price for all legs in the order inclusive of ratio and side, and must specify whether the price is a debit or credit. Debits must be represented as a positive number, and credits must be represented as a negative number. | R |
| 17 | quantity | Real Quantity | The number of units of the multi-leg order. | R |
| 18 | minQty | Whole Quantity | The minimum quantity of units to be executed. Must be > 0. | C |
| 19 | orderType | Choice | The type of order received. | R |
| 20 | timeInForce | Name/Value Pairs | The time-in-force for the order. | R |
| 21 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 22 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 23 | affiliateFlag | Boolean | Indicates if the routing party is an affiliate of the Industry Member. | R |
| 24 | solicitationFlag | Boolean | Indicates if the order was originated in response to an RFQ or other solicitation process. This field is not used to indicate if a registered representative of the firm solicited a client order. | R |
| 25 | pairedOrderID | Text (64) | If the order was received as a pair, the internal identifier assigned to all orders included in the paired route. | C |
| 26 | numberOfLegs | Whole Quantity | Indicates the number of legs in the multi-leg order. | R |
| 27 | legDetails | Leg Details | See Table 85: Leg Details below. | R |

Table 85: Leg Details

| The Leg Details associated with field: <i>legDetails</i> | | | | |
|---|------------|-----------|--|-------------|
| The number legs that may be represented in each record is limited by file size. Legs that cannot be represented due to file size constraints must be represented in a Multi-Leg Supplement event. | | | | |
| Seq # | Field Name | Data Type | Description | Include Key |
| 27.n.1 | legRefID | Text (64) | Unique identifier of the leg. | O |
| 27.n.2 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity | C |

The Leg Details associated with field: *legDetails*
The number legs that may be represented in each record is limited by file size. Legs that cannot be represented due to file size constraints must be represented in a Multi-Leg Supplement event.

| Seq # | Field Name | Data Type | Description | Include Key |
|--------|--------------------|---------------|---|-------------|
| | | | Securities. Required if the leg being represented is an equity leg. Must be blank if <i>optionID</i> is populated. | |
| 27.n.3 | optionID | Option ID | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. Required if the leg being represented is an option leg. Must be blank if <i>symbol</i> is populated. | C |
| 27.n.4 | openCloseIndicator | Choice | Indicates whether the action taken (buy or sell) will open a new position or will close an existing position in the order originator's account. Required when the exchange's rules require a leg to be marked as open or close upon entry into the exchange. | C |
| 27.n.5 | side | Choice | The side of the leg. | R |
| 27.n.6 | legRatioQuantity | Real Quantity | The ratio of quantity for this individual leg relative to the entire multi-leg security. May be represented as the entire quantity for the leg, or as the lowest common factor. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *orderID*
- Route Linkage Key: Event Date, *senderIMID*, *destination*, *session*, *routedOrderID*

5.2.4. Multi-Leg Order Internal Route Accepted Event

A Multi-Leg Order Internal Route Accepted event must be reported to CAT when a Multi-Leg order is passed to a different department or desk within the *CATReporterIMID*. A Multi-Leg Order Internal Route Accepted event is required to be reported from the perspective of the recipient desk, and indicates that an order was received by an internal destination.

Industry Members are required to assign a new Order Key to all Multi-Leg Order Internal Route Accepted events. A unique *orderID* must be assigned, the *parentOrderID* must be populated with the *orderID* of the event that was internally routed, and the *parentOrderKeyDate* must be populated.

Table 86: Multi-Leg Order Internal Route Accepted Event Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MLIR | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The order ID assigned to the order by the Industry Member upon acceptance. Must be unique within same date, <i>CATReporterIMID</i> , and <i>optionID</i> combination. | R |
| 8 | parentOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the event from which the Multi-Leg Order Internal Route Accepted event originated. | R |
| 9 | parentOrderID | Text (64) | The <i>orderID</i> of the event from which the Multi-Leg Order Internal Route Accepted event originated. The <i>parentOrderID</i> must not be equal to the <i>orderID</i> within the record. | R |
| 10 | underlying | Symbol | The symbol of the underlying stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | O |
| 11 | eventTimestamp | Timestamp | The date/time of receipt of the Multi-Leg internal route. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 12 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is handled manually. | R |
| 13 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 14 | deptType | Choice | The category of department, unit, or desk that is the destination of this internal route | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|---|-------------|
| | | | event. | |
| 15 | receivingDeskType | Choice | Field indicates the type of desk receiving the internally routed order. More granular than the field <i>deptType</i> . | R |
| 16 | price | Price | The net price of the multi-leg order at a net debit/credit. This field represents a net price for all legs in the order inclusive of ratio and side, and must specify whether the price is a debit or credit. Debits must be represented as a positive number, and credits must be represented as a negative number. | R |
| 17 | quantity | Real Quantity | The number of units of the multi-leg order. | R |
| 18 | minQty | Whole Quantity | The minimum quantity of units to be executed. Must be > 0. | C |
| 19 | orderType | Choice | The type of order received. | R |
| 20 | timeInForce | Name/Value Pairs | The time-in-force for the order. | R |
| 21 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 22 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 23 | numberOfLegs | Whole Quantity | Indicates the number of legs in the multi-leg order. | R |
| 24 | legDetails | Leg Details | See Table 87: Leg Details below. | R |

Table 87: Leg Details

| The Leg Details associated with field: <i>legDetails</i> | | | | |
|---|------------|-----------|---|-------------|
| The number legs that may be represented in each record is limited by file size. Legs that cannot be represented due to file size constraints must be represented in a Multi-Leg Supplement event. | | | | |
| Seq # | Field Name | Data Type | Description | Include Key |
| 24.n.1 | legRefID | Text (64) | Unique identifier of the leg. | O |
| 24.n.2 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. Required if the leg being represented is an equity leg. Must be blank if <i>optionID</i> is populated. | C |
| 24.n.3 | optionID | Option ID | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. | C |

The Leg Details associated with field: *legDetails*
The number legs that may be represented in each record is limited by file size. Legs that cannot be represented due to file size constraints must be represented in a Multi-Leg Supplement event.

| Seq # | Field Name | Data Type | Description | Include Key |
|--------|--------------------|---------------|--|-------------|
| | | | Required if the leg being represented is an option leg. Must be blank if <i>symbol</i> is populated. | |
| 24.n.4 | openCloseIndicator | Choice | Indicates whether the action taken (buy or sell) will open a new position or will close an existing position in the order originator's account. Required when the exchange's rules require a leg to be marked as open or close upon entry into the exchange. | C |
| 24.n.5 | side | Choice | The side of the leg. | R |
| 24.n.6 | legRatioQuantity | Real Quantity | The ratio of quantity for this individual leg relative to the entire multi-leg security. May be represented as the entire quantity for the leg, or as the lowest common factor. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate, CATReporterIMID, orderID*
- Parent Order Key: *parentOrderKeyDate, CATReporterIMID, parentOrderID*

5.2.5. Multi-Leg Child Order Event

A Multi-Leg Child Order event must be reported to CAT when a Multi-Leg order is sliced within the desk or department it is being worked, and is assigned a new order identifier. Multi-Leg Child Order events are not required to be reported to CAT, but are provided for the convenience of Industry Members to help model these types of order handling scenarios.

The following rules apply with respect to Child Option Orders:

1. Multi-Leg Child Order events can only be used when an order is sliced and assigned new order IDs within the same desk. A Multi-Leg Order Internal Route Accepted event must be reported when routed to another desk.
2. A child order may be generated off of another child order without limitation.
3. Multi-Leg Child Orders must belong to the same FDID as the parent order.

Table 88: Multi-Leg Child Order Event Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MLCO | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The order ID assigned to the order by the Industry Member upon acceptance. Must be unique within same date, <i>CATReporterIMID</i> , and <i>optionID</i> combination. | R |
| 8 | parentOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the event from which the Multi-Leg Child Order event originated. | R |
| 9 | parentOrderID | Text (64) | The <i>orderID</i> of the event from which the Multi-Leg Child Order event originated. The <i>parentOrderID</i> must not be equal to the <i>orderID</i> within the record. | R |
| 10 | underlying | Symbol | The symbol of the underlying stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | O |
| 11 | eventTimestamp | Timestamp | The date/time the Multi-Leg child order was originated. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 12 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 12 | price | Price | The net price of the multi-leg order at a net debit/credit. This field represents a net price for all legs in the order inclusive of ratio and side, and must specify whether the price | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|------------------|--|-------------|
| | | | is a debit or credit. Debits must be represented as a positive number, and credits must be represented as a negative number. | |
| 13 | quantity | Real Quantity | The number of units of the multi-leg order. | R |
| 14 | minQty | Whole Quantity | The minimum quantity of units to be executed. Must be > 0. | C |
| 15 | orderType | Choice | The type of order received. | R |
| 16 | timeInForce | Name/Value Pairs | The time-in-force for the order. | R |
| 17 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 18 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 19 | numberOfLegs | Whole Quantity | Indicates the number of legs in the multi-leg order. | R |
| 20 | legDetails | Leg Details | See Table 89: Leg Details below. | R |

Table 89: Leg Details

| The Leg Details associated with field: <i>legDetails</i> | | | | |
|---|--------------------|-----------|---|-------------|
| The number legs that may be represented in each record is limited by file size. Legs that cannot be represented due to file size constraints must be represented in a Multi-Leg Supplement event. | | | | |
| Seq # | Field Name | Data Type | Description | Include Key |
| 20.n.1 | legRefID | Text (64) | Unique identifier of the leg. | O |
| 20.n.2 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. Required if the leg being represented is an equity leg. Must be blank if <i>optionID</i> is populated. | C |
| 20.n.3 | optionID | Option ID | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. Required if the leg being represented is an option leg. Must be blank if <i>symbol</i> is populated. | C |
| 20.n.4 | openCloseIndicator | Choice | Indicates whether the action taken (buy or sell) will open a new position or will close an existing position in the order originator's account. Required when the exchange's rules require a leg to be marked as open or close upon entry into the exchange. | C |

| The Leg Details associated with field: <i>legDetails</i> | | | | |
|---|------------------|---------------|---|-------------|
| The number legs that may be represented in each record is limited by file size. Legs that cannot be represented due to file size constraints must be represented in a Multi-Leg Supplement event. | | | | |
| Seq # | Field Name | Data Type | Description | Include Key |
| 20.n.5 | side | Choice | The side of the leg. | R |
| 20.n.6 | legRatioQuantity | Real Quantity | The ratio of quantity for this individual leg relative to the entire multi-leg security. May be represented as the entire quantity for the leg, or as the lowest common factor. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *orderID*
- Parent Order Key: *parentOrderKeyDate*, *CATReporterIMID*, *parentOrderID*

5.2.6. Multi-Leg Order Modified Event

Industry Members must report a Multi-Leg Order Modified event to CAT when the Material Terms of a Multi-Leg order have been changed (e.g., price, quantity) or when a Multi-Leg order is cancel/replaced. All attributes and Material Terms of the modified order listed on this event must be restated with the modification(s) reflected. If the order is a combined order, the *aggregatedOrders* field must be restated every time the order is modified or cancel/replaced. Changes to the orders being combined in the *aggregatedOrders* field are considered a modification to the order.

Industry Members are required to assign a new Order Key to all Multi-Leg Order Modified events. A unique *orderID* must be assigned, the *priorOrderID* must be populated with the *orderID* of the order that is being modified, and the *priorOrderKeyDate* must be populated. If the order has been modified more than once, the *priorOrderID* must refer to *orderID* of the immediately preceding modification which will not be the original Order ID.

Table 90: Multi-Leg Order Modified Event Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|-----------|---|-------------|
| 1 | <i>actionType</i> | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | <i>errorROEID</i> | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | <i>firmROEID</i> | Text (64) | An identifier assigned to the record by | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|----------------------------------|--|-------------|
| | | | the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | |
| 4 | type | Message Type | MLOM | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The date and time the <i>orderID</i> was assigned. | R |
| 7 | orderID | Text (64) | The internal order ID assigned to the order by the Industry Member. Must be unique within same date, <i>CATReporterIMID</i> , and <i>optionID</i> combination. | R |
| 8 | priorOrderKeyDate | Timestamp | The <i>orderKeyDate</i> of the event being modified. | R |
| 9 | priorOrderID | Text (64) | The <i>OrderID</i> of the event being modified. The <i>priorOrderID</i> must not be equal to the <i>orderID</i> within the record. | R |
| 10 | underlying | Symbol | The symbol of the underlying stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | O |
| 11 | eventTimestamp | Timestamp | The date/time at which the order was modified (e.g., the time that the order was confirmed to be modified in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 12 | manualFlag | Boolean | Must be marked as <i>true</i> if the order is handled manually. | R |
| 13 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 14 | receiverIMID | Industry Member ID | Required when the modification is received from an Industry Member. The IMID of the Industry Member receiving the routed order modification. When <i>senderType</i> is 'F', this value must equal the <i>destination</i> field on the Multi-Leg Order Route event reported by the routing Industry Member. | C |
| 15 | senderIMID | Industry Member ID / Exchange ID | Required when the modification is received from an Industry Member. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|----------------------|-------------------|---|-------------|
| | | | When <i>senderType</i> is 'F', this value is the IMID of the sending Industry Member from which the order is routed, and must equal the <i>senderIMID</i> in the Order Route event reported by the routing Industry Member. | |
| 16 | senderType | Choice | Required when the modification is received from an Industry Member. Indicates the type of origin from which the order is routed. | C |
| 17 | routedOrderID | Text (64) | The ID for the order as sent by the routing entity. Must be unique per combination of Event Date, optionID, <i>senderIMID</i> , and <i>receiverIMID</i> . Required when <i>senderType</i> is 'F' and <i>manualFlag</i> is false. | C |
| 18 | initiator | Choice | Indicates who initiated the order modification. | R |
| 19 | deptType | Choice | This is the category of internal department, unit or desk originating the order. | R |
| 20 | price | Price | The net price of the multi-leg order at a net debit/credit. This field represents a net price for all legs in the order inclusive of ratio and side, and must specify whether the price is a debit or credit. Debits must be represented as a positive number, and credits must be represented as a negative number. | R |
| 21 | quantity | Real Quantity | The number of units of the multi-leg order. | R |
| 22 | minQty | Whole Quantity | The minimum quantity of units to be executed. Must be > 0. | C |
| 23 | leavesQty | Real Quantity | The number of units left open after the modification has occurred. Must be less than or equal to <i>quantity</i> . | R |
| 23 | orderType | Choice | The type of order being submitted. | R |
| 24 | timeInForce | Name/Value Pairs | The time-in-force for the order. | R |
| 25 | tradingSession | Choice | The trading session(s) during which an order is eligible to trade. | R |
| 27 | handlingInstructions | Name/Value Pairs | The order handling instructions for the order. | C |
| 27 | affiliateFlag | Boolean | Indicates if the routing party is an affiliate of the Industry Member. | R |
| 28 | aggregatedOrders | Aggregated Orders | When applicable, the order ID of each customer order being combined. Refer to Appendix C for representative order linkage requirements. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|---|-------------------|-------------------|--|-------------|
| Aggregated Orders – Start | | | | |
| For each order being combined <i>n</i> , the following values are required. | | | | |
| 28.n.1 | orderID | Text (64) | <i>orderID</i> of the order being combined. | R |
| 28.n.2 | orderKeyDate | Timestamp | <i>orderKeyDate</i> of the order being combined. | R |
| 28.n.3 | quantity | Real Quantity | Required when a partial quantity of the order is being combined. | C |
| 28.n.4 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| Aggregated Orders – End | | | | |
| 29 | representativeInd | Choice | Indicates if the order is a combined order. | R |
| 30 | numberOfLegs | Whole Quantity | Indicates the number of legs in the multi-leg order. | R |
| 31 | legDetails | Leg Details | See Table 91: Leg Details below. | R |

Table 91: Leg Details

| The Leg Details associated with field: <i>legDetails</i> | | | | |
|---|--------------------|-----------|---|-------------|
| The number legs that may be represented in each record is limited by file size. Legs that cannot be represented due to file size constraints must be represented in a Multi-Leg Supplement event. | | | | |
| Seq # | Field Name | Data Type | Description | Include Key |
| 31.n.1 | legRefID | Text (64) | Unique identifier of the leg. | O |
| 31.n.2 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. Required if the leg being represented is an equity leg. Must be blank if <i>optionID</i> is populated. | C |
| 31.n.3 | optionID | Option ID | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. Required if the leg being represented is an option leg. Must be blank if <i>symbol</i> is populated. | C |
| 31.n.4 | openCloseIndicator | Choice | Indicates whether the action taken (buy | C |

The Leg Details associated with field: *legDetails*
The number legs that may be represented in each record is limited by file size. Legs that cannot be represented due to file size constraints must be represented in a Multi-Leg Supplement event.

| Seq # | Field Name | Data Type | Description | Include Key |
|--------|------------------|---------------|--|-------------|
| | | | or sell) will open a new position or will close an existing position in the order originator's account. Required when the exchange's rules require a leg to be marked as open or close upon entry into the exchange. | |
| 31.n.5 | side | Choice | The side of the leg. | R |
| 31.n.6 | legRatioQuantity | Real Quantity | The ratio of quantity for this individual leg relative to the entire multi-leg security. May be represented as the entire quantity for the leg, or as the lowest common factor. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *orderID*
- Order Key: *aggregatedOrders.orderKeyDate*, *CATReporterIMID*, *aggregatedOrders.orderID*
- Prior Order Key: *priorOrderKeyDate*, *CATReporterIMID*, and *priorOrderID*
- Route Linkage Key: Event Date, *receiverIMID*, *senderIMID*, *routedOrderID*

5.2.7. Multi-Leg Order Cancelled Event

The Multi-Leg Order Cancelled event is reported when a Multi-Leg order is fully cancelled. Restatement of the leg details is not required in a Multi-Leg Order Cancelled event. Partial cancellations of a Multi-Leg order must therefore be reported to CAT using a Multi-Leg Order Modified event.

Table 92: Multi-Leg Order Cancelled Event Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|------------|-----------|--|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|---------------------|-------------------|--|-------------|
| | | | CAT Reporter IMID. | |
| 4 | type | Message Type | MLOC | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the Multi-Leg order event which is being cancelled. | R |
| 7 | orderID | Text (64) | The <i>orderID</i> of the Multi-Leg order event which is being cancelled. | R |
| 8 | underlying | Symbol | The symbol of the underlying stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | O |
| 9 | eventTimestamp | Timestamp | The date/time at which the order was cancelled (e.g., the time that the order was confirmed to be cancelled in the firm's OMS/EMS). If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 10 | manualFlag | Boolean | Must be marked as <i>true</i> if the order was cancelled manually. | R |
| 11 | electronicTimestamp | Timestamp | The time at which the event is systematized. Required when <i>manualFlag</i> is <i>true</i> and the event is systematized. | C |
| 12 | initiator | Choice | Indicates who initiated the order cancellation. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *orderID*

5.2.8. Multi-Leg Supplement Event

The Multi-Leg Supplement event may be used to supplement any Multi-Leg Order event. Multi-Leg Supplement events are considered as additions to a Multi-Leg Order event, not replacements or modifications. There is no limit to the number of Multi-Leg Supplement events that may supplement a single Multi-Leg Order event. When supplementing a Multi-Leg Order Route event, the Industry Member must identify the specific Multi-Leg Order Route event being supplemented by populating the Route Linkage Key fields.

The Multi-Leg Supplement event is used in the following scenarios.

- A Multi-Leg Order event has more legs than can be represented in an order event, additional legs must be represented in a Multi-Leg Order Supplement event.
- Aggregated Orders included in the *aggregatedOrders* field causes the Multi-Leg New Order event or Multi-Leg Order Modified event to exceed the maximum allowed message length, or when the orders being represented are not captured in the Multi-Leg New Order event or Multi-Leg Order Modified event. The *aggregatedOrders* field in the Multi-Leg Supplement event must contain the additional Aggregated Orders that were not captured in the original New Order event, or another Supplement event for the same order.
- An Industry Member receives an order for a new account and the new account number, on which the FDID is based, is not yet available for creation and reporting of the CAT new order event. If an FDID has not yet been created when an order has been received, the Industry Member must populate the *firmDesignatedID* field in its Multi-Leg New Order event with a value of 'PENDING'.
- A Multi-Leg route is rejected by the venue to which it was routed, and the Industry Member chooses to report the *routeRejectedFlag* in this separate Multi-Leg supplement event.

Table 93: Multi-Leg Supplement Event Specifications

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-----------------|-------------------|---|-------------|
| 1 | actionType | Choice | Indicates whether the event is a new event, a firm initiated correction or a repair of a CAT error. | R |
| 2 | errorROEID | Unsigned | Required when <i>actionType</i> is 'RPR'. Must be blank when <i>actionType</i> is 'NEW'. | C |
| 3 | firmROEID | Text (64) | An identifier assigned to the record by the reporting firm. Formatted as <eventDate>_<firm ROE Identifier> Must be unique for the Event Date and CAT Reporter IMID. | R |
| 4 | type | Message Type | MLOS | R |
| 5 | CATReporterIMID | CAT Reporter IMID | The SRO assigned identifier that an Industry Member uses to report to CAT. If populated, must equal the <i>CATReporterIMID</i> in the filename. | O |
| 6 | orderKeyDate | Timestamp | The <i>orderKeyDate</i> of the Multi-Leg order event this event supplements. | R |
| 7 | orderId | Text (64) | The <i>orderId</i> of the Multi-Leg order event | R |

| Seq # | Field Name | Data Type | Description | Include Key |
|---|------------------|--------------------|--|-------------|
| | | | this event supplements. | |
| 8 | underlying | Symbol | The symbol of the underlying stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. | O |
| 9 | eventTimestamp | Timestamp | The date/time of Multi-Leg order event this event supplements. If <i>manualFlag</i> is <i>true</i> , timestamp must be reported to seconds. If <i>manualFlag</i> is <i>false</i> , timestamp must be reported to milliseconds or a finer increment up to nanoseconds. | R |
| 10 | manualFlag | Boolean | Must be marked as <i>true</i> if the Multi-Leg order event this event supplements was handled manually. | R |
| 11 | aggregatedOrders | Aggregated Orders | The order ID of each customer order being combined when supplementing the <i>aggregatedOrders</i> on a Multi-Leg New Order or Multi-Leg Order Modified event. Refer to Appendix C for representative order linkage requirements. | C |
| Aggregated Orders – Start | | | | |
| For each order being combined <i>n</i> , the following values are required. | | | | |
| 11.n.1 | orderID | Text (64) | <i>orderID</i> of the order being combined. | R |
| 11.n.2 | orderKeyDate | Timestamp | <i>orderKeyDate</i> of the order being combined. | R |
| 11.n.3 | quantity | Real Quantity | Required when a partial quantity of the order is being combined. | C |
| 11.n.4 | originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . | C |
| Aggregated Orders – End | | | | |
| 12 | firmDesignatedID | Text (40) | Required when reporting a supplement to an MENO event that was reported prior to the FDID being available. Refer to the Data Dictionary for definition and guidance for populating this field. | C |
| 13 | senderIMID | Industry Member ID | When supplementing a Multi-Leg Order Route event, the <i>senderIMID</i> of the Multi-Leg Order Route event that this event supplements. When <i>destinationType</i> is 'F', this value must equal the <i>senderIMID</i> on the Order Accepted event reported by the destination. | C |

| Seq # | Field Name | Data Type | Description | Include Key |
|-------|-------------------|----------------------------------|---|-------------|
| | | | When <i>destinationType</i> is 'E', this value must equal the <i>routingParty</i> reported by the exchange on the Participant Complex Option Order Accepted event. | |
| 14 | destination | Industry Member ID / Exchange ID | <p>When supplementing a Multi-Leg Order Route event, the <i>destination</i> of the Multi-Leg Order Route event that this event supplements.</p> <p>When <i>destinationType</i> is 'F', this value is the IMID used to identify the Industry Member that is receiving this routed order, and it must equal the <i>receiverIMID</i> field on the Order Accepted event reported by the destination Industry Member.</p> <p>When <i>destinationType</i> is 'E', this value is the Exchange ID of the destination exchange, and it must equal the <i>exchange</i> field on the Complex Option Order Accepted event reported by the destination exchange.</p> | C |
| 15 | destinationType | Choice | When supplementing a Multi-Leg Order Route event, the <i>destinationType</i> of the Multi-Leg Order Route event that this event supplements. Indicates whether the destination of the route is an Industry Member, an exchange or a foreign broker-dealer. | C |
| 16 | routedOrderID | Text (64) | <p>When supplementing a Multi-Leg Order Route event, the ID assigned to the order by the Industry Member when routing the order to the destination. Must match the <i>routedOrderID</i> of the Order Route event that this event supplements.</p> <p>Required when <i>destinationType</i> is 'F' or 'E' and <i>manualFlag</i> is <i>false</i>.</p> | C |
| 17 | session | Text (40) | <p>When supplementing a Multi-Leg Order Route event, the <i>session</i> of the Multi-Leg Order Route event that this event supplements.</p> <p>Must only be populated when <i>destinationType</i> is 'E'. This must match the session ID reported in the Participant Complex Option Order Accepted event by the receiving exchange.</p> | C |
| 18 | routeRejectedFlag | Boolean | Indicates the routed order was not accepted by the destination (rejected or no response) when marked <i>true</i> . | C |
| 19 | legDetails | Leg Details | Required when representing additional legs on a Multi-Leg record. See Table 94: Leg Details below. | R |

Table 94: Leg Details

| The Leg Details associated with field: <i>legDetails</i> | | | | |
|---|--------------------|---------------|---|-------------|
| The number legs that may be represented in each record is limited by file size. Legs that cannot be represented due to file size constraints must be represented in a Multi-Leg Supplement event. | | | | |
| Seq # | Field Name | Data Type | Description | Include Key |
| 19.n.1 | legRefID | Text (64) | Unique identifier of the leg. | O |
| 19.n.2 | symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. Required if the leg being represented is an equity leg. Must be blank if <i>optionID</i> is populated. | C |
| 19.n.3 | optionID | Option ID | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is appended before the OSI symbol elements. See the Option Symbols section for more information. Required if the leg being represented is an option leg. Must be blank if <i>symbol</i> is populated. | C |
| 19.n.4 | openCloseIndicator | Choice | Indicates whether the action taken (buy or sell) will open a new position or will close an existing position in the order originator's account. Required when the exchange's rules require a leg to be marked as open or close upon entry into the exchange. | C |
| 19.n.5 | side | Choice | The side of the leg. | R |
| 19.n.6 | legRatioQuantity | Real Quantity | The ratio of quantity for this individual leg relative to the entire multi-leg security. May be represented as the entire quantity for the leg, or as the lowest common factor. | R |

Linkage Keys for this Reportable Event:

- Order Key: *orderKeyDate*, *CATReporterIMID*, *orderID*
- Order Key: *aggregatedOrders.orderKeyDate*, *CATReporterIMID*, *aggregatedOrders.orderID*
- Route Linkage Key: Event Date, *senderIMID*, *destination*, *routedOrderID*

6. Submission Process

This section contains information pertaining to CAT data and file formats, CAT submissions (including a general data flow overview), network and transport options, CAT access and reporting hours.

6.1. File Submissions and Data Formats

CAT submissions must include data files with at least one metadata file that enumerates the data files. Data and metadata files have a prescribed naming convention and are supported in JSON and CSV formats. The format of the data file and metadata file must be the same.

6.1.1. File Submission Names

1. Data Files must be named using the following format:

```
<CAT Submitter ID>_<CAT Reporter IMID>_<File Generation
Date>_[<Group>_]<File Kind>_<File Number>[.File Instruction].<Format
Extension>.<Compression Extension>
```

For example: SUBID_MYID_20170101_FileGroup1_OrderEvents_000123.csv.bz2

2. Metadata Files must be named using the following format:

```
<CAT Submitter ID>_<CAT Reporter IMID>_<File Generation
Date>_[<Group>_]<File Kind>_<File Number>.meta[.File
Instruction].<Format Extension>
```

For example: SUBID_MYID_20170101_FileGroup1_OrderEvents_000122.meta.csv

3. The values assigned within the format of a file name include:

Table 95: Elements of a File Submission Name

| Field Name | Data Type | Description | Include Key |
|----------------------|-------------------|--|-------------|
| CAT Submitter ID | Unsigned | CAT Reporting Agent that submitted the file to CAT. | R |
| CAT Reporter IMID | Alphanumeric (7) | The SRO assigned identifier of the firm to which the data within the file belongs. Case sensitive. | R |
| File Generation Date | Date | The date the file was generated or reported. Used to guarantee uniqueness of a file across dates. Date must be less than or equal to System Date. Future dates are not acceptable. | R |
| Group | Alphanumeric (20) | Reporter defined string to guarantee uniqueness of a file across dates. Filenames associated with web submission directly | O |

| Field Name | Data Type | Description | Include Key |
|-----------------------|-------------------|--|-------------|
| | | entered into the CAT Reporter Portal will be assigned the value 'catweb'. | |
| File Kind | Alphanumeric (20) | Set to 'OrderEvents'. Case sensitive. | R |
| File Number | Unsigned | Sequence number of the file, 6-digits long, left-padded with zeros. The File Number of the data file and its associated metadata file are not required to be the same number. The File Number is not required to be populated in submission order. | R |
| Type | Alphanumeric (4) | Applicable to Metadata Files. Set to '.meta'. Case sensitive. | R |
| File Instruction | Alphanumeric (4) | Applicable to Delete Files. Set equal to '.DEL' for a Delete File Instruction. Case sensitive. | C |
| Format Extension | Alphanumeric (4) | Represents the format of the data submission. JSON formatted submissions must be 'json', and CSV submissions must be populated with 'csv'. Case sensitive. | R |
| Compression Extension | Alphanumeric (3) | Applicable to Data Files. Set to 'bz2'. Case sensitive. | R |

4. Data file names must be globally unique among all other data files using the base name (the portion of the file name without the format and compression extensions) of the data file. The following data files are duplicates:

Table 96: Filename / Base Name Examples

| Data Filename | Base Name |
|--|---|
| SUBID_MYID_20170101_Group1_OrderEvents_000123.csv.bz2 | SUBID_MYID_20170101_Group1_OrderEvents_000123 |
| SUBID_MYID_20170101_Group1_OrderEvents_000123.json.bz2 | SUBID_MYID_20170101_Group1_OrderEvents_000123 |

5. Metadata file names must be globally unique among all other metadata files using the base name (the portion of the file name without the META and format extension) of the metadata file. The following metadata files are duplicates:

Table 97: Filename / Base Name Examples

| Meta Filename | Base Name |
|--|--|
| SUBID_MYID_20170101_OrderEvents_000123.meta.csv | SUBID_MYID_20170101_OrderEvents_000123 |
| SUBID_MYID_20170101_OrderEvents_000123.meta.json | SUBID_MYID_20170101_OrderEvents_000123 |

6.1.2. Submission Formats

CAT supports the submission of data in JSON and CSV formats. The following rules apply to both formats:

1. CAT submissions must include data files with at least one metadata file that enumerates the data files.
2. The format (JSON or CSV) of the data file and metadata file must be the same.
3. Each line in a file must contain exactly one complete record.
4. The total maximum length of a line is 8190 bytes.
5. Non-printable characters and whitespace are bytes that will be included when validating a record has NOT exceeded the maximum length.

6.1.2.1. JSON Format

1. The CAT Processor will support standard JSON syntax for each record or as specified in this document.
2. Backslash '\ ' is a reserved printable character in JSON and must be escaped in order to be used in strings by inserting a backslash prior to it within the string. For example: *routedOrderID* = 1234\ABCD must be reported to CAT as "routedOrderID":"1234\ABCD". If a backslash is not escaped, it will be omitted from the string. For example if the following is reported to CAT, "routedOrderID":"1234\ABCD", it will be stored as *routedOrderID* = 1234ABCD.
3. Data files serve as top-level containers for each object. Each object is a normal JSON object, separated with a new-line (ASCII decimal 10, hex 0A).
 - a. Data within the object must not include new-lines.
 - b. Conditional and optional fields without a value must be omitted.
 - c. Each line within a Data file must contain exactly one complete record. The following example is a CAT event in the required submission format. The record is delivered in a single line with a new-line character at the end:

```
{"actionType":"RPR","errorROEID":12345678,"firmROEID":"20170801_firmROEO12345","type":  
"MENO","orderKeyDate":"20170801T143031.000000","orderID":"O12345","symbol":"XYZ","even  
tTimestamp":"20170801T143031.123456","manualFlag":false,"deptType":"O","side":"B","pri  
ce":10.01,"quantity":500,"orderType":"LMT","timeInForce":{"DAY":20170801},"tradingSess  
ion":"REG","custDspIntrFlag":false,"firmDesignatedID":"PROP456","accountHolderType":"O  
","negotiatedTradeFlag":false}
```

JSON Data file examples presented in this document with fields represented in multiple lines are provided for readability.

4. Metadata file contains one complete JSON object with fields as per the Metadata File Specifications in Table 50. Refer to [Section 6.1.3.1](#).

5. JSON objects within a metadata file may include a new-line (ASCII decimal 10, hex 0A) termination and will be ignored during processing.

6.1.2.2. CSV Format

1. The sequence of fields is fixed; the position of each field is relative to the beginning of its associated record. The format of every file and record must be in the sequence described within the Industry Member Technical Specifications.
2. Each specified field, except for the last field in a record, must be terminated by a delimiter including instances when the field is null, blank and when the field is the maximum length and when the field is greyed out or Reserved for Future Use.
3. None of the fields in the record can contain the character used for the delimiter.
4. The last field in a record is not required to be terminated by a delimiter, but the field will still be considered to be acceptable if the delimiter is included.
5. The field delimiter is a comma (ASCII decimal 44, hex 2C).
6. Other delimiters defined for usage include the '|' (pipe), '@' (at sign) and '“ ’ (double quotes). Use of '|' and '@' have been specified for reporting complex data types where a field contains multiple values. Refer to [Section 2.5 Data Types](#).
7. Each record must end with an end of record marker (ASCII LF or CR/LF).
8. Optional (O) and Conditional fields (C) are omitted by only including the delimiter.
9. Required (R) fields must contain an appropriate value and be terminated by the delimiter.
10. Values do not need to fill the entire data type length of the field; Values may not exceed the data type length.
11. Leading zeros will be removed during processing.
12. Leading and trailing blanks will be removed during processing.

6.1.3. Metadata File Submission

CAT submissions require a metadata file associated with every data file. The following rules apply:

1. A Metadata file may be paired with one or more data files for the same File Generation Date, CAT Reporter IMID and Submitter.
2. The Metadata file must be in the same format as all associated data files.
3. Submitters may package multiple metadata "blocks" for multiple data files into one metadata file. Files must be for the same CAT Reporter IMID, on the same file version and Submitter IMID. Each metadata "block" contains a checksum of the respective file that is used during verification.
4. A maximum of 100 associated data files for a single metadata file is required. Metadata files exceeding the 100 associated data file limit will be rejected.

5. If a metadata file includes a metadata block that references a file that is not found, an error associated with the block will be returned and the remaining blocks will be processed.
6. Data files are recommended to be submitted prior to the Metadata file submission.
7. A Data file without an associated Metadata file within 30 minutes of the data file submission will result in a warning.
8. A Data file without an associated Metadata file within 2 hours of the data file submission will result in an error.
9. The processing date of all submissions will be assigned based on the received timestamp of the associated metadata file. If a data file is received prior to T+1 8:00 AM EST with the associated metadata file submitted after T+1 8:00 AM EST, the submissions will be considered late.
10. Each block within the metadata must contain the hash of the compressed data file. The compressed hash will be used to verify the integrity of the data file submitted by computing the hash of the data file and comparing it to the value sent in the metadata file. If the compressed hash is not sent, the data file submission will be rejected.
11. The CAT Submitter ID, CAT Reporter IMID, File Generation Date must be the same for the metadata file and all associated data file(s).
12. The submission of a metadata file with *doneForDay* = true indicates to the CAT Processor that the files submitted by the Submitter for the Industry Member have been completed and are ready for linkage discovery. Note - should an Industry Member need to make additional data submissions after a metadata file with *doneForDay* = true has been processed, the Industry Member may continue to submit files and provide a secondary metadata file *doneForDay* = true.
13. If a metadata file with *doneForDay* = true has not been submitted by 8:00 AM EST, all files submitted up to that point will be considered ready and processed for linkage discovery at that time.

Table 98: Metadata File Specifications

| Seq | Field Name | Data Type | Description | Include Key |
|-----|---------------------------|------------------|--|-------------|
| 1 | <i>type</i> | Message Type | Set to "META" | R |
| 2 | <i>doneForDay</i> | Boolean | Used to indicate the last metadata file for the Submitter/Industry Member Reporter on the date. Any file submitted with <i>doneForDay</i> =true must be the last set of files submitted for the day. It defaults to false. | R |
| 3 | <i>fileGenerationDate</i> | Date | The date the file was generated or reported. This date is part of the key used to define a unique file. | R |
| 4 | <i>reporter</i> | Alphanumeric (7) | The SRO assigned identifier that an Industry Member uses to report CAT events. All events within the file must be for the same CAT Reporter IMID. | R |
| 5 | <i>submitter</i> | Unsigned | The CAT-assigned ID for the entity submitting data on behalf of the reporter. The CAT | R |

| Seq | Field Name | Data Type | Description | Include Key |
|---|-------------------------------|-------------------------|--|-------------|
| | | | Reporting Agent must be authorized to submit data on behalf of the CAT Reporter IMID. | |
| 6 | <i>fileVersion</i> | Text (10) | A version number for the schema file used to encode and format this file. | R |
| 7 | <i>files</i> | Multi-Dimensional Array | File information and related meta data for each file associated with the Metadata file. Refer to File Details – Metadata Block for required information associated with each file. | R |
| File Details – Metadata Block Start | | | | |
| For each file <i>n</i> , the following values are required: | | | | |
| 7.n.1 | → <i>fileName</i> | As described above | The file name of the corresponding data file of the metadata block, including all extensions. | R |
| 7.n.2 | → <i>recordCount</i> | Unsigned | The number of new-line delimited records in the data file | R |
| 7.n.3 | → <i>reservedForFutureUse</i> | | | |
| 7.n.4 | → <i>compressedHash</i> | Alphanumeric (64) | SHA256 of the compressed data file. Must be submitted as 64-character hexadecimal string encodings of the hash value | R |
| File Details – Metadata Block End | | | | |
| 8 | <i>thirdParty</i> | Unsigned | The CAT-assigned ID for the Third Party Reporting Agent that is authorized to view feedback and error data for data submitted on behalf of the CAT Reporter. Although the Third Party Reporting Agent is specified in the Metadata File by the Submitter, the Third Party Reporting Agent must be authorized to view the data by the CAT Reporter. Additionally, in order for the <i>thirdParty</i> to be able to make corrections for the CAT Reporter, the Reporting Agent must be authorized to submit data for the CAT Reporter. | O |

6.1.3.1. Metadata File JSON Example

```
{
  "type": "META",
  "doneForDay": false,
  "fileGenerationDate": 20180919,
  "reporter": "MPID",
  "submitter": "ORGID",
  "fileVersion": "2.2.1",
  "files": [
    {
      "fileName": "SUBID_MPID_20180919_OrderEvents_000001.json.bz2",
      "recordCount": 5217,

```

```

        "compressedHash": "99A7712E2CC1CB3A5789B91E3C1D1E76D7F83D82C8D35FF1F56B
156A49C228E2"
    },
    {
        "fileName": "SUBID_MPID_20180919_OrderEvents_000002.json.bz2",
        "recordCount": 9999,

        "compressedHash": "00660828E45FFCCA37EF9CCF2A4967308DDA033CD498B0A1810F
3BFC4BF6BFCC"
    }
]
}

```

6.1.3.2. Metadata File CSV Example

```

LINE 1  META,false,20180919,MPID,ORGID,2.1.1,SUBID_MPID_20180919_OrderEvent
s_000001.csv.bz2@5217@99A7712E2CC1CB3A5789B91E3C1D1E76D7F83D82C8D3
5FF1F56B156A49C228E2|SUBID_MPID_20180919_OrderEvents_000002.csv.bz2
@9999@00660828E45FFCCA37EF9CCF2A4967308DDA033CD498B0A1810F3BFC4BF6
BFCC,

```

6.1.4. Data File Submission

The following rules apply to Data Files:

1. All data files sent from the CAT Reporter (or the third-party CAT Reporting Agent for the CAT Reporter) must be compressed using BZip2. The associated compression extension is "bz2".
2. Data files must be individually compressed and submitted. Compressed files may not be bundled into a single container file.
3. Data files must be associated with a Metadata file; otherwise, the file will not be processed.
4. Data files for which an associated Metadata file is not received within 30 minutes of the receipt of the file will result in a warning.
5. A Data file without an associated Metadata file within 2 hours of the data file submission will result in an error.
6. Data files are recommended to be submitted prior to the Metadata file submission.
7. The data contained within the data file must represent data for the CAT Reporter IMID identified within the associated Metadata file.
8. All events within the file must be for the same CAT Reporter IMID. However, Industry Member Identifiers populated in the *senderIMID*, *receiverIMID* and *destination* fields may be different.
9. Files submitted through SFTP are limited to a maximum uncompressed size of 100GB.
10. Larger file submissions are recommended to reduce number of files for Reporters to transfer and manage and to allow feedback to be returned consistently and faster.

11. Files submitted through the CAT Reporter Portal are limited to a maximum uncompressed size of 1GB, with a record limit of 100,000 records per file. Files with more than 100,000 records will be rejected.
12. Schema files will be maintained by the Plan Processor and will be versioned as the Technical Specifications change.
13. Data files may contain events for any Event Date that is less than or equal to the date on which the file is processed.
14. Events within a data file may be in any sequence.
15. Data files may contain original submissions, firm initiated corrections, CAT error corrections and record delete instructions.
16. Data files are recommended to contain data for the same CAT Trading Day to ensure the usage of the File Delete Instruction. Refer to [Section 7.6.4](#). This is not a requirement.
17. Empty data files will be accepted.

6.1.4.1. Data File JSON Example

```
{
  "actionType": "NEW",
  "firmROEID": "20170901_ROE1234567",
  "type": "MEOJ",
  "orderKeyDate": "20170901T120102.123456",
  "eventTimestamp": "20170901T120102.123456",
  "manualFlag": false,
  "symbol": "XYZ",
  "orderID": "T12346",
  "priorOrderID": "T12345",
  "priorOrderKeyDate": "20170901T120102.000000",
  "initiator": "C",
  "quantity": 1100,
  "minQty": 100,
  "leavesQty": 100
}
```

6.1.4.2. Data File CSV Example

```
LINE 1  NEW,, 20170901_ROE1234567,MEOJ,, 20170901T120201.123456,T12346,XYZ,T1
2345,20170901T120102.000000,, 20170901T120102.123456,false,,C,,1100,
100,100,,,,,,,,,,,,,
```

6.1.5. Schema

An [Industry Member Schema](#) file that details the structure and expected contents of every message type is available on the CAT public website. The schema file will be maintained by the Plan Processor and will be versioned as the message specifications change.

6.1.5.1. Schema Version

Schema changes will be updated when changes to the CAT Reporting Technical Specifications for Industry Members occur that impact the schema. The following rules apply:

1. The Schema Version is assigned to a File Kind. The events within this Technical Specifications are assigned to File Kind 'OrderEvents'.
2. The Schema Version is formatted as <Major>.<Minor>.<Patch>. All digits must be represented.
 - **Major** – updated when a change occurs that impacts all or a significant portion of Industry Member CAT Reporters. In such cases, the schema is not backward compatible and will be specified accordingly.
 - **Minor** – updated when a change occurs that does not require coding changes for all Industry Member CAT Reporters. In such cases, the schema is backward compatible with support for previous version(s) as specified.
 - **Patch** – updated when a change occurs that does not require coding changes for any Industry Member CAT Reporters.
 - **Revision** – not part of the Schema Version. Used to represent updates to the Industry Member Technical Specifications which do not impact the Schema definition. Revision added to the end of the Schema Version as <Schema Version> r<#>.
3. Metadata File Submissions must set the *fileVersion* equal to the applicable Schema Version for the File Kind.
4. Records contained in a Data File must be formatted as per the Schema Version populated in the paired Metadata File *fileVersion*.
5. Meta Feedback provided by CAT will set the *feedbackVersion* equal to the applicable Schema Version for the File Kind.

6.1.5.2. Schema Definition

The schema file is a JSON format file that represents the following:

1. **Data Types** – CAT defined data types containing the following elements:
 - **dataType**: Data Type (e.g. Price) as defined in [Table 3: Data Types](#)
 - **JSONDataType**: JSON standard data type to be used to submit data of this type. The JSON standard data types used in this schema are BOOLEAN, STRING, NUMBER, ARRAY and OBJECT. Timestamp data type has two possible representations, so the JSONDataType is an array of choices.

- **maxLength:** Maximum length of the string submission. Applicable to text and alphanumeric types only.
 - **scale:** Number of digits after the decimal point. Applicable to numeric types only.
 - **precision:** Number of digits in a number. Applicable to numeric types only.
2. **Event Definitions** – Field specifications for events defined in Table 12: Equity Events and Table 49: Summary of Simple Option Events. Each field specification object contains the following elements:
 - **name:** Field Name set equal to Message Type for each event being specified.
 - **dataType:** Data Type. Fields noted Reserved for Future Use are specified with datatype Text (0).
 - **JSONDataType:** JSON standard data type to be used to submit data of this type.
 - **required:** Indicates whether the field is "Required," "Conditional," or "Optional." Fields applicable to ATs are marked "Conditional".
 - **position** – The applicable CSV position of the field.
 3. **Choices** – For choice data types, the list of possible values.
 4. **Name/Value Pairs** – Field specifications for Name/Value Pair fields.
 - **name:** Field Name. Case sensitive.
 - **dataType:** Data Type or an array of Data Types.
 - **JSONDataType:** The JSON standard data type or an array of JSON standard data types.
 - **required:** Indicates whether the field is "Required," "Conditional," or "Optional."

6.1.5.3. Example

The following is an abbreviated example of a schema containing part of the equity Child Order event.

```
"eventDefinitions": [{
  "eventName": "MECO",
  "fields": [{
    "name": "actionType",
    "dataType": "Choice",
    "JSONDataType": "STRING",
    "required": "Required",
    "position": "1"
  }, {
    "name": "errorROEID",
    "dataType": "Unsigned",
    "JSONDataType": "NUMBER",
    "required": "Conditional",
    "position": "2"
  }, {
    "name": "firmROEID",
    "dataType": "Text (64)",
    "JSONDataType": "STRING",
```

```

        "required": "Required",
        "position": "3"
    },
    .....
    {
        "name": "nbboSource",
        "dataType": "Choice",
        "JSONDataType": "STRING",
        "required": "Conditional",
        "position": "30"
    }, {
        "name": "nbboTimestamp",
        "dataType": "Timestamp",
        "JSONDataType": ["STRING", "NUMBER"],
        "required": "Conditional",
        "position": "31"
    }
    ]
},

```

6.2. Connectivity

Connectivity to CAT will be through at least one of the following methods:

- Private Line provided by a Managed Network Service Provider (MNSP)
- AWS PrivateLink⁴
- CAT Secure Reporting Gateway (SRG) Reporter Portal

Both the Private Line and AWS PrivateLink connectivity methods will support the CAT File Transfer service, which provides access for automated, machine-to-machine file submissions, acknowledgements, rejections, and corrections using the Secure File Transfer Protocol (SFTP) service as well as to the CAT Reporter Portal for interactive reporting through web-based forms or manual file uploads.

The CAT Secure Reporting Gateway (SRG) connectivity method will only support the CAT Report Portal. The SRG requires multi-factor authentication (MFA) to establish a secure, encrypted session before accessing the CAT Reporter Portal. The SRG requires the use of modern browsers supporting HTML5 and TLS (Transport Layer Security). No client software installation is required.

The combinations of Connectivity and Interface Methods are summarized below.

⁴ The AWS PrivateLink service is currently under development. Availability will be announced along with updated instructions on how to leverage PrivateLink for cloud-to-cloud connectivity. Industry Members and CAT Reporting Agents -interested in AWS PrivateLink should contact the FINRA Help Desk at 888-696-3348 or at help@finracat.com.

Table 99: Connectivity Methods and Supported CAT Interfaces Methods

| Connectivity Methods | Interface Methods | |
|------------------------------------|-------------------|---------------------|
| | CAT File Transfer | CAT Reporter Portal |
| Private Line provided by MNSP | Y | Y |
| AWS PrivateLink | Y | Y |
| CAT Secure Reporting Gateway (SRG) | N | Y |

For a detailed description of the CAT Connectivity Methods, including instructions for establishing access and connectivity to the CAT system, refer to the [FINRA CAT Connectivity Supplement for Industry Members](#).

6.3. CAT Interface Methods

The interface methods available to Industry Members and CAT Reporting Agents to submit data and retrieve reporting feedback include CAT File Transfer and the CAT Reporter Portal. For a detailed description of the CAT Interface Methods, including instructions for establishing access and connectivity to the CAT system, refer to the [FINRA CAT Connectivity Supplement for Industry Members](#).

The following identifies the types of CAT information with the respective interface methods available for each:

Table 100: CAT Data and Feedback Interface Methods

| CAT Data Submission and Feedback | Category | SFTP | CAT Reporter Portal |
|---|----------------|------|---------------------|
| Submission of CAT Events | Submission | ✓ | ✓ |
| Resubmission of Rejected Files/Records, Corrections and Deletions | Submission | ✓ | ✓ |
| Interactive CAT Reportable Event Entry | Submission | | ✓ |
| File Status Retrieval | Feedback | ✓ | ✓ |
| Reporting Statistics | Feedback | | ✓ |
| Error Feedback | Feedback | ✓ | ✓ |
| Corrections Feedback | Feedback | | ✓ |
| System Status and Announcements | Feedback | | ✓ |
| Account Maintenance | Administration | | ✓ |
| Establishment of Reporting Relationships and ATS Order Types | Administration | | ✓ |

6.3.1. CAT File Transfer

The CAT File Transfer method is an automated, machine-to-machine interface utilizing the Secure File Transfer Protocol (“SFTP”) for file submissions, acknowledgements, rejections and corrections. SFTP enables Industry Members and CAT Reporting Agents to create machine-to-machine connections to securely transmit data and retrieve data from FINRA CAT.

The following is the SFTP directory structure that will be made available in the submitter’s home directory. Files associated with data submissions and associated feedback will be uploaded in SFTP directories as per the following table.

Table 101: SFTP Directories

| SFTP Directory | Usage |
|---------------------------|--|
| /submitterID/cat/upload | SFTP submissions uploaded by Submitters including Metadata and Data files. CAT will move files from this directory for further processing. |
| /submitterID/cat/feedback | Metadata feedback files associated with each processing state. |
| /submitterID/cat/errors | Feedback data files containing errors generated during Ingestion and Linkage Discovery. |

The following rules apply:

1. Processing is initiated when a file appears in the /submitterID/cat/upload directory.
2. CAT will remove files from the upload directory as soon as each file upload is complete.
3. The Submitter must not delete files from the /submitterID/cat/upload directory.

6.3.2. CAT Reporter Portal

The CAT Reporter Portal is a web interface utilizing secure encryption protocols (HTTPS/TLS) and multifactor authentication (MFA). The CAT Reporter Portal will facilitate data submissions using the following methods:

- Manual data file uploads for files up to 1GB in size and limited to 100,000 records meeting all requirements of data files as specified in 6.1.3 and 6.1.4.
- Data entry for original submissions, repairs for CAT identified errors, and firm initiated corrections and deletion instructions. These entries will be converted to Data files with an associated Metadata file generated by the portal; Data files will be available for view and download for a time period specified.

6.4. CAT Reporting Hours

6.4.1. Submission of CAT Events

Pursuant to SEC Rule 613, the CAT NMS Plan requires Industry Members to record order, quote, fulfillment and trade events. Real-time reporting to CAT is not required. Data may be bulk uploaded at the end of the Trading Day, or may be submitted in batches with associated uploads throughout the day. All Reportable Events for a Trading Day are required to be reported to CAT by 8:00 AM Eastern Time on the next Trading Day.

Trading Day for Industry Members is defined as:

- **Start:** immediately after 4:15:00 PM and no fractions of a second Eastern Time on one trade date
- **End:** exactly 4:15:00 PM and no fraction of a second Eastern Time on the next trade date (T=Trading Day, a defined term)^{5,6}

The Trading Day is used to determine the reporting deadline of CAT events, including when all error repairs and firm initiated corrections are due. Weekends or any day that all equities or options national securities exchanges are closed are not considered a Trading Day.

CAT accepts submissions (via SFTP and the CAT Reporter Portal) 24 hours per day, 6 days per week beginning at 12:01AM ET on Monday and ending at 11:59PM ET on Saturday. Events that occurred during a particular CAT Trading Day may be reported anytime between the time the event occurred and the reporting deadline, which is 8:00 AM Eastern Time on the next Trading Day. Reports received after the deadline will be considered late.

The table below provides examples of the reporting deadline.

Table 102: Reporting Deadline Examples

| Event Occurs | Holiday | Report Due to CAT (T+1) |
|--------------------|---------|-------------------------|
| Monday 14:20 PM ET | N/A | Tuesday 8:00 AM ET |
| Monday 23:40 PM ET | N/A | Wednesday 8:00 AM ET |
| Friday 11:00 AM ET | N/A | Monday 8:00 AM ET |
| Friday 16:02 PM ET | N/A | Monday 8:00 AM ET |

⁵ Note that the Trading Day definition for Participants is different. It starts on 1 millisecond from 12:00AM of T, and ends at 12:00AM of T+1.

⁶ A Trading Day which is also an early close will end 15 minutes after market close.

| Event Occurs | Holiday | Report Due to CAT (T+1) |
|------------------------------|---|-------------------------|
| Friday 16:02 PM ET | The Following Monday | Tuesday 8:00 AM ET |
| Friday 14:00 PM ET | Market Close on the Event Date 13:00 PM ET | Tuesday 8:00 AM ET |
| Wednesday 15:00 PM ET | Thursday, Friday is half day | Friday 8:00 AM ET |
| Saturday 11:15 AM ET | N/A | Tuesday 8:00 AM ET |
| Saturday 11:15 AM ET | The Following Monday | Wednesday 8:00 AM ET |
| Monday 10:00 AM ET (holiday) | On the Event Date | Wednesday 8:00 AM ET |

6.4.2. Deadline of Repair for Errors Identified by CAT

Errors identified by CAT will be provided to Industry Members. Once available, repairs can be made immediately. All errors that require repair must be repaired prior to **8AM Eastern Time on T+3** (CAT Trading Day of event + three Trading Days). Repairs received after the repair deadline will be considered late.

Table 103: Repair Window Examples

| Event Occurs | Holiday | Initial Report Due (T+1) | Repair Due (T+3) |
|------------------------------|------------------------------------|--------------------------|----------------------|
| Monday 14:20 PM ET | N/A | Tuesday 8:00 AM ET | Thursday 8:00 AM ET |
| Monday 23:40 PM ET | N/A | Wednesday 8:00 AM ET | Friday 8:00 AM ET |
| Friday 11:00 AM ET | N/A | Monday 8:00 AM ET | Wednesday 8:00 AM ET |
| Friday 16:02 PM ET | N/A | Monday 8:00 AM ET | Wednesday 8:00 AM ET |
| Friday 16:02 PM ET | Next Monday | Tuesday 8:00 AM ET | Thursday 8:00 AM ET |
| Wednesday 15:00 PM ET | Thursday, Friday is half day | Friday 8:00 AM ET | Tuesday 8:00 AM ET |
| Saturday 11:15 AM ET | N/A | Tuesday 8:00 AM ET | Thursday 8:00 AM ET |
| Saturday 11:15 AM ET | The Following Monday | Wednesday 8:00 AM ET | Friday 8:00 AM ET |
| Monday 10:00 AM ET (holiday) | On the Event Date | Wednesday 8:00 AM ET | Friday 8:00 AM ET |

6.4.3. Deadline for Firm Initiated Corrections and Deletions

CAT specifications allow for Industry Members to correct and delete events that did not produce an error during processing. All such corrections must be submitted within the same correction deadline as described in 6.4.2.

6.5. Security

6.5.1. Encryption (In-transit)

TLS-based encryption, version 1.2 minimum, is required for connection to the Reporter Portal (whether accessed via private line or the SRG) and to the Security Reporter Gateway itself.

For SFTP, in addition to the fact that the SFTP service is only accessible via private line, traffic will be encrypted by virtue of the intrinsic encryption capabilities of SFTP. AES256 will be supported for SFTP; support for other encryption protocols is under evaluation.

6.5.2. Encryption (At-rest)

The CAT system will use native AWS encryption features to encrypt data upon receipt. No action is required by the Industry Member.

6.5.3. Authentication

Two-factor authentication will be required for access to the Reporter Portal. The first factor will be username and password which will require periodic rotation.

The second factor will be via push notification to an off-the-shelf application installed on a mobile device provided by the user. The user will be required to install the application to their mobile device through their mobile operating system's application store and then complete a registration process on the Reporter Portal or SRG. There is no cost to the Reporter or the user for this mobile application.

The SFTP service similarly requires that two conditions be met to access the interface. The first factor is authentication via username and password. The second is the use of a defined IP source address that is established during initial onboarding. The SFTP system implements an IP whitelist that prevents access from any system not on the whitelist.

More detailed information related to Security is described in the [FINRA CAT Connectivity Supplement for Industry Members](#) available at <https://www.catnmsplan.com/registration/>.

7. Feedback and Corrections

CAT provides feedback associated with CAT submissions for CAT Reporters and Submitters including:

- **File Status:** available via SFTP and the CAT Reporter Portal, indicates the acceptance or associated errors with a Meta and/or Data Submission files.
- **Reporting Statistics:** available via the CAT Reporter Portal, daily summary statistics representing reporting activity and errors for prior submissions and CAT Trading days. Error Rate is also included.
- **Error Feedback:** available via SFTP and the CAT Reporter Portal, errors found during processing will be made available including Rejections, Out of Sequence, and Unlinked events.
- **Corrections Feedback:** available via the CAT Reporter Portal, information is provided for the repair status of all Corrections. When an error has been corrected, the updated status will be reflected.
- **System Status and Announcements:** available via the CAT Reporter Portal, the status of CAT processing will be made available with a distinction for instances when a processing delay or issue is occurring. Additionally, announcements related to system maintenance and upcoming changes will be presented.

This section describes the procedures for obtaining feedback and making corrections/deletions associated with feedback of errors. Additionally this section describes the requirement for making correction/deletions for accepted data for which there was no feedback.

7.1. File and Error Feedback

Feedback files with associated errors are generated at different stages of processing and returned to the CAT Reporter and Submitter. Errors identified during each processing stage will be provided in the following order with the associated Feedback and Error Correction availability:

Table 104: Feedback and Error Correction Availability

| Seq | Processing Stage | Feedback | Anticipated Delivery | Delivery No Later Than |
|-----|----------------------|--|---|-------------------------------------|
| 1 | File Acknowledgement | File Submission Error | Within 10 minutes of File Submission | 1 hour of File Submission |
| 2 | File Integrity | File Integrity Error | Within 30 minutes of Metadata File Submission | 2 hours of Metadata File Submission |
| 3 | Data Ingestion | Data Errors including syntax and semantic errors | Within an 1 hour of File Integrity Feedback | 4 hours of File Integrity Feedback |
| | | Corrections Feedback for | Within 1 hour of File | 4 hours of File Integrity |

| Seq | Processing Stage | Feedback | Anticipated Delivery | Delivery No Later Than |
|-----|-------------------|---|--|--|
| | | Ingestion Errors | Integrity Feedback | Feedback |
| 4 | Linkage Discovery | Linkage errors including duplicates, out of sequence and linkage errors | T+1 at Noon | T+1 at Noon |
| | | Corrections Feedback for Linkage Errors | Processing Date of Correction Submission + 1 at Noon | Processing Date of Correction Submission + 1 at Noon |

7.1.1. Feedback Generation

Feedback associated with all processing stages will be made available via SFTP and/or the CAT Reporter Portal as described in Table 100: CAT Data and Feedback Interface Methods.

For Feedback files made available via SFTP, the following rules apply:

1. The format of feedback files will match the format of the original file submission.
2. Meta Feedback files will be accessible under the `cat/feedback` directory in the Submitter's home directory on the Feedback SFTP server.
3. Error Data Feedback files will be accessible under the `cat/errors` directory in the Submitter's home directory on the Feedback SFTP server.
4. Feedback for data submitted by a CAT Reporting Agent on behalf of a CAT Reporter will be accessible under the CAT Reporter's home directory on the Feedback SFTP server if the CAT Reporter has an SFTP account.
5. If a file is rejected, it will not proceed to the next processing stage.
6. Error Data Feedback files generated during Data Ingestion and Linkage Discovery will be compressed. Each line in the Data File will contain exactly one record ending with a new-line character.
7. The minimum retention time for feedback files on the SFTP server is 10 calendar days. After that time, they may be removed from the server. Feedback will be available via the CAT Reporter Portal for at least 90 days.

7.1.2. Feedback File Names

1. File Submissions, including Meta and Data files, which have a malformed file name will receive a feedback file name, using the following format:

`<original File Name>.ack.error`

Example: `SUBID_MYID_20170101_000001.ack.error`

2. Meta Feedback Files created by CAT during Acknowledgement, File Integrity and Data Ingestion will be named using the following format:

```
<original File Base Name>[.<Type>][.<File Instruction>].<Stage>[_<Feedback File Number>].<Format Extension>
```

Example: SUBID_MYID_20170101_Group1_OrderEvents_000123.DEL.integrity.json

Table 105: Elements of a Meta Feedback File Name generated during Acknowledgement, File Integrity and Data Ingestion

| Field Name | Data Type | Description | Include Key |
|-------------------------|------------------|---|-------------|
| Original File Base Name | | Base Name of the Original File Submission. <CAT Submitter ID>_<CAT Reporter IMID>_<File Generation Date>_ [<Group>_] <File Kind>_<File Number> | R |
| Type | Alphanumeric (4) | If the Original File Submission for which feedback is generated was a Metadata File, Type will be set to .meta If the Original File Submission for which feedback is generated was a Data File, Type will not be included. | C |
| File Instruction | Alphanumeric (4) | Applicable to Delete Files. Set equal to '.DEL' for feedback associated with a Delete File Instruction. | C |
| Stage | Alphanumeric (9) | Processing stage associated with the Feedback including: <ul style="list-style-type: none"> ack - Acknowledgement integrity – File Integrity ingestion – Data Ingestion | R |
| Feedback File Number | Unsigned | Sequence number of the file, 6-digits long, left-padded with zeros. Will be populated as needed to prevent duplicate Feedback file names for instances when multiple feedback files are generated for the same File Submission. The File Number is not required to be populated in submission order. | C |
| Format Extension | Alphanumeric (4) | Represents the feedback format; Set equal to the feedback format of the original submission. JSON formatted feedback will be set to 'json', and CSV formatted feedback will be populated with 'csv'. | R |

3. Meta Feedback Files created by CAT during Linkage Discovery will be named using the following format:

```
<CAT Submitter ID>_<CAT Reporter IMID>_<CAT File Generation Date>_<File Kind>.linkage[_<Feedback File Number>].<Format Extension>
```

For example: SUBID_MYID_20170101_OrderEvents.linkage_000001.json

Table 106: Elements of a Meta Feedback File Name generated during Linkage Discovery

| Field Name | Data Type | Description | Include Key |
|--------------------------|-------------------|---|-------------|
| CAT Submitter ID | Unsigned | CAT Reporting Agent that submitted the data to CAT. | R |
| CAT Reporter IMID | Alphanumeric (7) | The SRO assigned identifier of the firm to which the data within the file belongs. | R |
| CAT File Generation Date | Date | The date the file was generated by CAT. | R |
| File Kind | Alphanumeric (20) | Set to 'OrderEvents' | R |
| Type | | Not applicable for Linkage Discovery Feedback files | |
| Stage | Alphanumeric (9) | Set to 'LINKAGE' | R |
| Feedback File Number | Unsigned | Sequence number of the file, 6-digits long, left-padded with zeros. Will be populated as needed to prevent duplicate Feedback file names for instances when multiple feedback files are generated for Linkage errors. The File Number is not required to be populated in submission order. | C |
| Format Extension | Alphanumeric (4) | Represents the feedback format; Set equal to the feedback format of the original submission. JSON formatted feedback will be set to 'json', and CSV formatted feedback will be populated with 'csv'. | R |

4. When there are no Linkage Errors found in Linkage Discovery, the feedback file name will have the following format:

```
<CAT Submitter ID>_<CAT Reporter IMID>_<CAT File Generation Date>_OrderEvents.linkage[_<Feedback File Number>].success
```

5. Error Data Feedback Files of Ingestion Errors created by CAT during File Ingestion will be named using the following format: (refer to [Table 106](#) for applicable field definitions)

```
<original File Base Name>.ingestion.error[_<Feedback File Number>].<Format Extension>.bz2
```

Example: SUBID_MYID_20170101_Group1_OrderEvents_000123.ingestion.error.json.bz2

6. Error Data Feedback Files of Linkage Errors created by CAT during Linkage Discovery will be named using the following format: (refer to [Table 106](#) for applicable field definitions)

<CAT Submitter ID>_<CAT Reporter IMID>_<CAT File Generation Date>_<File Kind>.linkage.error[_<Feedback File Number>].<Format Extension>.bz2

Example: SUBID_MYID_20170101_OrderEvents.linkage.error_000001.json.bz2

7.2. File Acknowledgement

The File Acknowledgement processing stage is where files are received and processing is initiated. Every file submission is acknowledged, and file names are validated.

The following rules apply to File Acknowledgment:

1. Acknowledgement feedback will be generated for all files submissions, including Meta and Data files.
2. The Plan Processor will remove files from the upload directory as soon as each file upload is complete.
3. The Submitter must not delete files from the /submitterID/cat/upload directory.
4. File acknowledgement feedback files will include the file extension .ack
5. File acknowledgement errors, including when a File Name is malformed, will return the original filename with the .ack.error extension. The file will be empty.

7.2.1. File Acknowledgement Feedback Definition

Table 107: File Acknowledgement Feedback

| Seq | Name | Data Type (Length) | Description |
|-----|------------------------|--------------------|--|
| 1 | feedbackVersion | Text (10) | The schema version of the feedback file. |
| 2 | submitter | Unsigned | The CAT Submitter ID from the file name. |
| 3 | reporter | CAT Reporter IMID | The CAT Reporter IMID from the file name. |
| 4 | fileGenerationDate | Date | The file generation date from the file name. |
| 5 | fileName | Alphanumeric (90) | File name as submitted for which feedback is being provided. |
| 6 | receiptTimestamp | Timestamp | Date and time the file was received. Timestamp will be in STRING format. |
| 7 | stage | Alphanumeric (20) | Set to 'FILE_ACKNOWLEDGEMENT' |
| 8 | stageCompleteTimestamp | Timestamp | Date and time when the file completed the acknowledgement stage. Timestamp will be in STRING format. |
| 9 | status | Alphanumeric (7) | Set to 'Success'. |
| 10 | severity | Alphanumeric (7) | Not applicable for the acknowledgement stage. |
| 11 | code | Unsigned | Not applicable for the acknowledgement stage. |
| 12 | errorFileName | Alphanumeric (90) | Not applicable for the acknowledgement stage. |

| Seq | Name | Data Type (Length) | Description |
|---|----------------|-------------------------|---|
| 13 | errorCount | Unsigned | Not applicable for the acknowledgement stage |
| 14 | errorDetails | Multi-Dimensional Array | Not applicable for the acknowledgement stage. |
| Error Details – Metadata File Block Start | | | |
| For each Error Type <i>n</i> , the following values will be included: | | | |
| 14.n.1 | errorType | Alphanumeric (20) | Not applicable for the acknowledgement stage. |
| 14.n.2 | errorTypeCount | Unsigned | |
| Error Details – Metadata Block End | | | |
| 15 | doneForDay | Boolean | Not applicable for the acknowledgement stage. |
| 16 | metaFileName | Alphanumeric (90) | Not applicable for the acknowledgement stage. |

7.2.2. JSON Examples of File Acknowledgement

Metadata File Submission Acknowledgement Success:

| | |
|------------------------------------|---|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.meta.json |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.meta.ack.json |
| Acknowledgement of Meta File | <pre>{ "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.json", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_ACKNOWLEDGEMENT", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success" }</pre> |

Data File Submission Acknowledgement Success:

| | |
|------------------------------------|---|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.json.bz2 |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.ack.json |
| Acknowledgement of Data File | <pre>{ "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID MYID 20170307 OrderEvents 000123.json.bz2",</pre> |

| | |
|--|---|
| | <pre>"receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_ACKNOWLEDGEMENT", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success" }</pre> |
|--|---|

Data File Submission Acknowledgement Error:

| | |
|------------------------------------|-------------------------------------|
| Original File Submission File Name | SUBID_MYID_20170307000123.json.bz2 |
| Meta Feedback File Name | SUBID_MYID_20170307000123.ack.error |
| Acknowledgement of Data File | empty |

7.2.3. CSV Example for File Integrity Feedback

Metadata File Submission Integrity Success:

| | | |
|------------------------------------|---|----------------|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.meta.csv | |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.meta.integrity.csv | |
| Meta File | | Not applicable |

Metadata File Submission Integrity Error:

| | | |
|------------------------------------|---|--|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.meta.csv | |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.meta.integrity.csv | |
| Meta File | LINE 1 | 2.1.1, SUBID, MYID, 20170307, SUBID_MYID_20170307_OrderEvents_000123.meta.csv, 20170307T153552.000001089, FILE_INTEGRITY, 20170307T154152.000001089, Failure, Error, 1107, , , , , |

Data File Submission Integrity Success:

| | |
|------------------------------------|--|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.csv.bz2 |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.integrity.csv |

| | | |
|-----------|--------|---|
| Meta File | LINE 1 | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, 20170307T153552.000001089,FILE_INTEGRITY, 20170307T154152.000001089,Success,,,,,,,, |
|-----------|--------|---|

Data File Submission Integrity Error:

| | | |
|------------------------------------|--|---|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.csv.bz2 | |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.integrity.csv | |
| Meta File | LINE 1 | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, 20170307T153552.000001089,FILE_INTEGRITY, 20170307T154152.000001089,Failure,Error,1107,,,,, |

7.2.4. CSV Examples of File Acknowledgement

Metadata File Submission Acknowledgement:

| | | |
|------------------------------------|---|--|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.meta.csv | |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.meta.ack.csv | |
| Acknowledgement of Meta File | LINE 1 | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000123.meta.csv, 20170307T153552.000001089,FILE_ACKNOWLEDGEMENT, 20170307T154152.000001089,Success,,,,,,,, |

Data File Submission Acknowledgement:

| | | |
|------------------------------------|--|---|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.csv.bz2 | |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.ack.csv | |
| Acknowledgement of Meta File | LINE 1 | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, 20170307T153552.000001089,FILE_ACKNOWLEDGEMENT, 20170307T154152.000001089,Success,,,,,,,, |

7.3. File Integrity

During the File Integrity processing stage, file names are validated for uniqueness. Filename and Metadata file contents are validated to ensure they are readable, formatted as expected, and include valid information related to the Data file submission. Additionally, Metadata files are paired with Data files to ensure the included File Details represent the information contained in the associated Data file.

The following rules apply:

1. All files with a Success status generated during File Acknowledgement will enter the File Integrity processing stage.
2. File integrity feedback file will include the file extension `.integrity`.
3. Metadata and Data filenames which duplicate prior submissions accepted during File Integrity will reject.
4. Metadata files which are not readable, include invalid identifiers, or values that do not match the file name will reject.
5. Data files which include invalid values in the file name will reject.
6. The CAT Submitter ID of the metadata and data file must be equal to the Submitter ID of the submitter that sent the files (as determined from SFTP or CAT Reporter Portal username).
7. The CAT Reporter IMID within the filename must match the CAT Reporter IMID populated in the metadata file.
8. If the CAT Submitter is reporting on behalf of the CAT Reporter IMID, a Reporting Relationship must be effective.
9. If the CAT Submitter is designating a Third-party CAT Reporting Agent to be able to view and take action on reporting feedback, a Third Party Reporting Agent Relationship must be effective.
10. Metadata files that cannot be paired with a Data file will reject as Data files must be submitted prior to the Metadata file submission.
11. Data Files that do not pair with an associated metadata file within 30 minutes of the file submission (either because the metadata file was not uploaded or had a processing error) will result in a warning.
12. A Data file without an associated Metadata file within 2 hours of the data file submission will reject. The file must be resubmitted. The resubmitted filename may be the same.
13. Once a Data file and Metadata file are paired, validations of the Metadata Block will occur. If an error is found in the contents of the Metadata Block, the associated Data File will reject. In order to resubmit the Data file, a Metadata file for the Data file is also required.
14. Compressed Hash - computed SHA256 must equal metadata Compressed Hash.

7.3.1. JSON Examples for File Integrity Feedback

Metadata File Submission Integrity Success:

| | |
|------------------------------------|--|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.meta.json |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.meta.integrity.json |
| Meta File | Not applicable |

Metadata File Submission Integrity Error:

| | |
|------------------------------------|--|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.meta.json |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.meta.integrity.json |
| Meta File | <pre>{ "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.json", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_INTEGRITY", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Failure", "severity": "Error", "code": [1107] }</pre> |

Data File Submission Integrity Success:

| | |
|------------------------------------|--|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.json.bz2 |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.integrity.json |
| Meta File | <pre>{ "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_INTEGRITY", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success" }</pre> |

7.3.2. File Integrity Feedback Definition

Table 108: File Integrity Feedback

| Seq | Name | Data Type (Length) | Description |
|---|------------------------|-------------------------|---|
| 1 | feedbackVersion | Text (10) | The schema version of the feedback file. |
| 2 | submitter | Unsigned | The CAT Submitter ID from the file name. |
| 3 | reporter | CAT Reporter IMID | The CAT Reporter IMID from the file name. |
| 4 | fileGenerationDate | Date | The file generation date from the file name. |
| 5 | fileName | Alphanumeric (90) | File name as submitted for which feedback is being provided. |
| 6 | receiptTimestamp | Timestamp | Date and time the file was received. Timestamp will be in STRING format. |
| 7 | stage | Alphanumeric (20) | Set to 'FILE_INTEGRITY' |
| 8 | stageCompleteTimestamp | Timestamp | Date and time when the file completed the integrity stage. Timestamp will be in STRING format. |
| 9 | status | Alphanumeric (7) | Populated with 'Success' or 'Failure' as per the processing outcome. Set to 'Failure' when errors and/or warnings are identified. |
| 10 | severity | Alphanumeric (7) | Populated when the Status is 'Failure'. If status is 'Failure', severity will be set to 'Error' or 'Warning'. If one or more errors found, will be set to 'Error'. Otherwise will be set to 'Warning'. |
| 11 | code | Array | Error codes indicating reason for File Failure. Not applicable for Metadata block errors. |
| 12 | errorFileName | Alphanumeric (90) | Not applicable for the integrity stage. |
| 13 | errorCount | Unsigned | Not applicable for the integrity stage. |
| 14 | errorDetails | Multi-Dimensional Array | Only applicable for feedback file on a metadata file with multiple blocks. |
| Error Details – Metadata File Block Start | | | |
| For each Metadata Block for which there is an error, the following values will be included: | | | |
| 14.n.1 | blockFileName | Alphanumeric (90) | The <i>fileName</i> of the data file named within the metadata block which has an associated error. |
| 14.n.2 | code | Array | Error codes indicating reason for Failure of the metadata block. |
| Error Details – Metadata Block End | | | |
| 15 | doneForDay | Boolean | Not applicable for the integrity stage. |
| 16 | metaFileName | Alphanumeric (90) | Metadata file name that was paired with the Data file. Not populated when a meta and data files |

| Seq | Name | Data Type (Length) | Description |
|-----|------|--------------------|---|
| | | | were not able to be paired. Not populated for Metadata files for which feedback is being provided. |

7.4. Data Ingestion

During Data Ingestion, events within the Data file are validated. Validations to ensure correct syntax and semantics associated with record length, field length, data type, non-null and reference data checks are performed. Validations are initiated by the Action Type and event type of every record contained in the file. Ingestion feedback will be provided with reference to the file in which the data was transmitted.

During the ingestion phase, each record will be checked for proper formatting (JSON field names and values, CSV values in correct positions) and data contents.

The following rules apply:

1. File Ingestion feedback will be generated for every data file for which a Success status was generated during File Integrity. The feedback will consist of a metadata feedback file and an error feedback data file when errors are found.
2. Metadata File Ingestion feedback files will include the file extension `.ingestion`.
3. Ingestion feedback error data files will include the file extension `.ingestion.error`.
4. Data Files which are not readable and for which the record count does not match the record count provided in the meta will be rejected. Records within the file will not be processed. The file must be resubmitted. Meta feedback will be provided including the error code associated with the file error.
5. Any record within a Data File determined to be malformed or otherwise invalid will be rejected.
6. When a record is readable and can be parsed, Ingestion validations will occur for every field within the record.
7. One or more errors may be found within a record.
8. Records with associated errors found during Ingestion will result in a rejection. The record will not participate in Linkage Discovery.
9. Record rejections will be provided in feedback with the generation of a Meta feedback file and Error Data Feedback file that includes the error records.
10. Ingestion error feedback will provide up to eight (8) error codes. If there are more than 8 error codes, the eighth error code will inform the user that there are additional errors associated with the record that were not included in the feedback file.
11. When an error record that was originally submitted in CSV format is readable and parsable, the error feedback will be returned from the 3rd position.

12. When an error record that was originally submitted in CSV format is not readable, the original record submitted to CAT will be returned.
13. When an error is found for events originally submitted in JSON format, the original record submitted to CAT will be returned and will be formatted as a string using JSON rules.
14. Records that are not rejected during Ingestion will participate in Linkage Discovery.

7.4.1. Ingestion Feedback Definitions

Table 109: Ingestion Feedback Metadata File

| Seq | Name | Data Type (Length) | Description |
|---|------------------------|-------------------------|--|
| 1 | feedbackVersion | Text (10) | The schema version of the feedback file. |
| 2 | submitter | Unsigned | The CAT Submitter ID from the file name. |
| 3 | reporter | CAT Reporter IMID | The CAT Reporter IMID from the file name. |
| 4 | fileGenerationDate | Date | The file generation date from the file name. |
| 5 | fileName | Alphanumeric (90) | File name as submitted. |
| 6 | receiptTimestamp | Timestamp | Date and time the file was received. Timestamp will be in STRING format. |
| 7 | stage | Alphanumeric (20) | Set to 'INGESTION' |
| 8 | stageCompleteTimestamp | Timestamp | Date and time when the file completed the ingestion stage. Timestamp will be in STRING format. |
| 9 | status | Alphanumeric (7) | Populated with 'Success' or 'Failure' as per the processing outcome. Set to 'Failure' when data errors and/or warnings are identified. |
| 10 | severity | Alphanumeric (7) | Populated when the Status is 'Failure'. If status is 'Failure', severity will be set to 'Error'. |
| 11 | code | Unsigned | Error code indicating reason for File Failure. Populated when the Data File is rejected. |
| 12 | errorFileName | Alphanumeric (90) | File name associated with the feedback metadata file generated by CAT. Populated if errors were found associated with individual records contained in the Data file. |
| 13 | errorCount | Unsigned | Number of Error and Warning records in the file; If no errors found, will be set to 0. |
| 14 | errorDetails | Multi-Dimensional Array | Not applicable for the ingestion stage. |
| Error Details – Metadata Block Start | | | |
| For each Error Type <i>n</i> , the following values will be included: | | | |
| 14.n.1 | errorType | Alphanumeric (20) | Not applicable for the ingestion stage. |
| 14.n.2 | errorTypeCount | Unsigned | |

| Seq | Name | Data Type (Length) | Description |
|--|--------------|--------------------|--|
| Linkage Error Details – Metadata Block End | | | |
| 15 | doneForDay | Boolean | Not applicable for the ingestion stage. |
| 16 | metaFileName | Alphanumeric (90) | Metadata file name that was paired with the Data file. |

Table 110: Ingestion Feedback Error Data File

| Seq | Name | Data Type (Length) | Description |
|-----|-------------|--------------------|--|
| 1 | errorCode | Array | The CAT Error Codes associated with the <i>firmROEID</i> representing up to 8 error codes. If the record has more than 8 errors, 7 error codes will be presented. The 8 th error code will be set to “2999” which indicates the event has more than 8 errors. Refer to Appendix E for the definition of all Error Codes. |
| 2 | actionType | Alphanumeric (3) | Set to ‘RPR’ |
| 3 | errorROEID | Numeric (20) | Identifier for the record that has errors. Populated with a CAT assigned identifier |
| 4 | errorRecord | Unspecified | CSV Format: Original Record, containing all fields of the original record excluding <i>actionType</i> and <i>errorROEID</i> . JSON Format: Original Record, containing all fields of the original record. The original record will be escaped with JSON rules and returned as a string. Note: the length of the original record will be a max of 8190 characters. The errorRecord will be the original record that was submitted plus additional characters for JSON formats as specified. |

7.4.2. JSON Examples for Data Ingestion Feedback

Data File Submission Ingestion Success:

| | |
|------------------------------------|---|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.json.bz2 |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.ingestion.json |
| Meta File | { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "INGESTION", "stageCompleteTimestamp": "20170307T154152.000001089", |

| | |
|--|--|
| | <pre> "status": "Success", "errorCount": 0 "metaFileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.json" } </pre> |
|--|--|

Data File Submission Ingestion Error:

| | |
|------------------------------------|--|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.json.bz2 |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.ingestion.json |
| Meta File | <pre> { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "INGESTION", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Failure", "errorFileName": "SUBID_MYID_20170307_OrderEvents_000123 .ingestion.error.json.bz2", "errorCount": 2 "metaFileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.json" } </pre> |
| Error Data Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.ingestion.error.js on.bz2 |
| Data File | <pre> {"errorCode": [2001, 2002], "actionType": "RPR", "errorROEID": 123456, "errorRecord": "{ \"actionType\": \"NEW\", \"firmROEID\": \"20170901_ROE1234567\", \"type\": \"MEOJ\", \"orderKeyDate\": \"20170901T120102.123456\", \"eventTimestamp\": \"20170901T120102.123456\", \"manualFlag\": false, \"symbol\": \"XYZ\", \"orderID\": \"T12346\", \"priorOrderID\": \"T12345\", \"priorOrderKeyDate\": \"20170901T120102.000000\", \"initiator\": \"C\", \"quantity\": 1000, \"minQty\": 100, \"leavesQty\": 100}"} {"errorCode": [2003], "actionType": "RPR", "errorROEID": 144477, "errorRecord": "{ \"actionType\": \"NEW\", \"firmROEID\": \"20170901_ROE1230011\", \"type\": \"MEOJ\", \"orderKeyDate\": \"20170901T120162.123456\", \"eventTimestamp\": \"20170901T120162.123456\", \"manualFlag\": false, \"symbol\": \"XYZ\", \"orderID\": \"T12355\", \"priorOrderID\": \"T12344\", \"priorOrderKeyDate\": \"20170901T120092.000000\", \"initiator\": \"C\", \"quantity\": 1100, \"minQty\": 100, \"leavesQty\": 100}"} </pre> |

7.4.3. CSV Examples for File Ingestion Feedback

Data File Submission Ingestion Success:

| | | |
|------------------------------------|--|--|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.csv.bz2 | |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.ingestion.csv | |
| Meta File | LINE 1 | 2.1.1, SUBID, MYID, 20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, 20170307T153552.000001089, INGESTION, 20170307T154152.000001089, Success,,,,0,,, SUBID_MYID_20170307_OrderEvents_000123.meta.csv |

Data File Submission Ingestion Error:

| | | |
|------------------------------------|--|--|
| Original File Submission File Name | SUBID_MYID_20170307_OrderEvents_000123.csv.bz2 | |
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.ingestion.csv | |
| Meta File | LINE 1 | 2.1.1, SUBID, MYID, 20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, 20170307T153552.000001089, INGESTION, 20170307T154152.000001089, Failure,,,, SUBID_MYID_20170307_OrderEvents_000123.ingestion.error.csv.bz2,2,,, SUBID_MYID_20170307_OrderEvents_000123.meta.csv |
| Data Feedback File Name | SUBID_MYID_20170307_OrderEvents_000123.ingestion.error.csv | |
| Data File | LINE 1 | 2001 2002,RPR,123456,<error record> |
| | LINE 2 | 2003,RPR,123457,<error record> |

7.5. Linkage Discovery

During Linkage Discovery, events are compared with other events to perform duplicate checks, out of sequence checks and to perform linkages among events having the same Linkage Keys. The linkage types performed by CAT are defined in [Section 2.6](#).

Linkage Discovery processing will occur in the following order:

Table 111: Steps in Linkage Discovery

| Seq | Linkage Discovery Step | Feedback |
|-----|--|--|
| 1 | Full Duplicate Checks | When duplicates are found, one record is kept and all others are rejected |
| 2 | Order Key, Trade Key, Quote Key and Fulfillment Key Duplicate Checks | When an Event Key is duplicated, all events having the same key are rejected |
| 5 | Intrafirm Linkage and Out of Sequence | Events within a firm that do not match or are found to be out of sequence result in an unlinked event |
| | Interfirm Linkage | Events routed/received between firms that do not match result in an unlinked event, including Route Key duplicate checks |
| | Exchange Linkage | Events routed to an Exchange that do not match result in an unlinked event, including Route Key duplicate checks |
| | Trade Linkage | Trade events which name a TRF/ORF/ADF record that do not match result in an unlinked event |

The following rules apply:

1. Linkage Discovery processing will be performed for all events which pass Ingestion.
2. Linkage feedback files will include the file extension `.linkage`.
3. Linkage feedback error files will include the file extension `.linkage.error`.
4. The *CATReporterIMID* and all fields included on the original submission, except for the *firmROEID* participate in full duplicate checking.
5. When full duplicates are identified, one event will be kept and all other events which fully duplicate the record will be rejected.
6. When Event Key duplicates are identified, all events having the duplicated key will result in rejections for all records with the same key.
7. Events that passed Event Key duplicate validations participate in the process which generates linkages.
8. When Linkage Key duplicates are identified, all events having the duplicated Linkage Key will result in unlinked errors for all records with the same key.
9. When linkages are expected but do not occur, a linkage error will be generated reflecting an unlinked event.
10. In cases when linkage did not occur between venues, unlinked feedback will be generated for the CAT Reporter whose record did not link and the CAT Reporter that was named. Separate error codes will be assigned.
11. One or more linkage errors may be found within a record.
12. Named errors are considered repaired when the unlinked event is repaired.

- 13. Linkage feedback will be provided in the submission format of the unlinked event, including named unlinked errors.
- 14. Linkage Discovery Error Data Feedback files will be limited to an uncompressed file size of 1GB.
- 15. Multiple Unlinked Error Data Feedback files will be provided to ensure the file size maximum is not exceeded. The File Feedback number will be incremented to ensure the feedback file name is not duplicated.
- 16. When there are no Linkage Discovery Errors, an empty file will be returned with a .success extension.
- 17. Linkage Feedback Files are named by CAT. These feedback files represent Linkage Feedback across all submissions for the CATReporterIMID/Submitter combination. The Feedback is not associated with specific submission file(s). The file name includes the Processing Date for which the Unlinked Feedback represents.

7.5.1. Linkage Discovery Feedback Definitions

Linkage Discovery Errors include unlinked events reported by the CAT Reporter, and unlinked events on which the CAT Reporter was named. For named linkage errors, a subset of fields will be provided.

There are 5 types of Unlinked Data errors including:

| | |
|--|--|
| | |
| 1. Unlinked error reported by the CAT Reporter for all event types | Table 113: Linkage Error Reported by CAT Reporter |
| 2. Named on an Unlinked Industry Member Order Event | Table 114: Linkage Error – Named on Unlinked Industry Member Order Event |
| 3. Named on an Unlinked Industry Member Quote Event | Table 115: Linkage Error – Named on Unlinked Industry Member Quote Event |
| 4. Named on an Unlinked Exchange Event | Table 116: Linkage Error – Named on Unlinked Exchange Event |
| 5. Named on an Unlinked Trade Report | Table 117: Linkage Error – Named on Unlinked Trade Report |

7.5.1.1. Metadata Feedback File

A metadata feedback file is provided to deliver the status and outcome of validations and linkages that occurred during the Linkage Discovery processing stage. There is only one type of Metadata File, which will include the feedback meta information for all linkage errors, including unlinked events reported by the CAT Reporter and unlinked events on which the CAT Reporter was named.

Table 112: Linkage Discovery Feedback Metadata File Definition

| Seq | Name | Data Type (Length) | Description |
|---|------------------------|-------------------------|--|
| 1 | feedbackVersion | Text (10) | The schema version of the feedback file. |
| 2 | submitter | Unsigned | The Submitter ID associated with the original submission of the events. |
| 3 | reporter | CAT Reporter IMID | The CAT Reporter IMID associated with the events. |
| 4 | fileGenerationDate | Date | The CAT Processing Date on which the feedback file was generated. Since multiple file generation dates can participate in a single CAT Processing Date, the file generation date in the feedback file need not equal the file generation date in the actual submissions file. |
| 5 | fileName | Alphanumeric (90) | Not applicable for the linkage stage. |
| 6 | receiptTimestamp | Timestamp | Not applicable for the linkage stage. |
| 7 | stage | Alphanumeric (20) | Set to 'linkage' |
| 8 | stageCompleteTimestamp | Timestamp | Date and time when the file completed the linkage stage. Timestamp will be in STRING format. |
| 9 | status | Alphanumeric (7) | Populated with 'Success' or 'Failure' as per the processing outcome. |
| 10 | severity | Alphanumeric (7) | Not applicable for Linkage Discovery. |
| 11 | code | Unsigned | Not applicable for Linkage Discovery. |
| 12 | errorFileName | Alphanumeric (90) | File name associated with the feedback metadata file generated by CAT. |
| 13 | errorCount | Unsigned | Total number of Error and Warning records for the CAT Reporter IMID and CAT Submitter ID on the CAT Processing Date. |
| 14 | errorDetails | Multi-Dimensional Array | Linkage feedback information associated with each linkage type. The list will include all linkage types with the error record count associated with each linkage type. Refer to Linkage Error Details – Metadata Block for information that will be included. |
| Linkage Error Details – Metadata Block Start | | | |
| For each Linkage Type <i>n</i> , the following values will be included: | | | |
| 14.n.1 | linkageType | Alphanumeric (20) | The Linkage Type. Values include: <ul style="list-style-type: none"> • Intrafirm • Interfirm • Exchange • Trade |
| 14.n.2 | errorTypeCount | Unsigned | Number of Errors and Warnings for each linkage type. |
| Linkage Error Details – Metadata Block End | | | |

| Seq | Name | Data Type (Length) | Description |
|-----|--------------|--------------------|---|
| 15 | doneForDay | Boolean | Used to indicate the last metadata file for Ingestion feedback is delivered. <i>doneForDay=true</i> when the last file is delivered. |
| 16 | metaFileName | Alphanumeric (90) | Not applicable for Linkage Discovery. |

7.5.1.2. Linkage Error Reported by CAT Reporter

Table 113: Linkage Error Reported by CAT Reporter specifies the feedback format of unlinked errors reported by the CAT Reporter. All fields of the original event will be provided in the feedback.

Table 113: Linkage Error Reported by CAT Reporter

| Seq | Name | Data Type (Length) | Description |
|-----|-------------|--------------------|---|
| 1 | errorCode | Array | The CAT Error Codes associated with the <i>firmROEID</i> representing up to 2 error codes. Refer to Appendix E for the definition of all Error Codes. |
| 2 | actionType | Alphanumeric (3) | Set to 'RPR' |
| 3 | errorROEID | Numeric (20) | For unlinked events associated with the CAT Reporter, populated with a CAT assigned identifier. |
| 4 | errorRecord | Text (8190) | CSV Format: Original Record, containing all fields of the original record excluding <i>actionType</i> and <i>errorROEID</i> . JSON Format: Original Record, containing all fields of the original record. For unlinked events associated with the CAT Reporter, the original record will be populated with all fields of the original submission excluding <i>actionType</i> and <i>errorROEID</i> . Note: the length of the original record will be a max of 8190 characters and will be represented by the original record that was submitted. |

7.5.1.3. Named on Unlinked Industry Member Order Event

An unlinked Industry member order event occurs when any of the following linkages fail:

- Industry Member routes an order to another Industry Member or Exchange
- Industry Member receives an order from another Industry Member or Exchange

Table 114: Linkage Error – Named on Unlinked Industry Member Order Event

| Seq | Name | Data Type (Length) | Description |
|-----|----------------------|----------------------------------|--|
| 1 | errorCode | Array | The CAT Error Codes associated with the Named Error. One errorCode will be assigned. Refer to Appendix E. of the CAT Reporting Technical Specifications for Industry Members for the definition of Trade Linkage Named Error Codes. |
| 2 | errorType | Message Type | Named Error Type; Set equal to ERRIM |
| 3 | errorROEID | Numeric (20) | Not applicable for Named Errors. |
| 4 | firmROEID | Text(64) | firmROEID of the unlinked event as assigned by the CAT Reporter. |
| 5 | type | Message Type | Event Type of the unlinked event. |
| 6 | symbol | Symbol | Symbol when populated on the unlinked event. |
| 7 | optionID | Text(22) | OptionID when populated on the unlinked event. |
| 8 | eventTimestamp | Timestamp | Timestamp as populated on the unlinked event. |
| 9 | side | Choice | Side as populated on the unlinked event. |
| 10 | price | Price | Price as populated on the unlinked event. |
| 11 | quantity | Real Quantity | Quantity as populated on the unlinked event. |
| 12 | senderIMID | Industry Member ID / Exchange ID | senderIMID when populated on the unlinked event. |
| 13 | receiverIMID | Industry Member ID | receiverIMID when populated on the unlinked event. |
| 14 | destination | Industry Member ID / Exchange ID | destination when populated on the unlinked event. |
| 15 | routedOrderID | Text (64) | The routedOrderID as populated on the unlinked event. |
| 16 | reservedForFutureUse | | Field is Reserved for Future Use. |
| 17 | reservedForFutureUse | | Field is Reserved for Future Use. |

7.5.1.4. Named on Unlinked Industry Member Quote Event

An unlinked Industry member quote event occurs when any of the following linkages fail:

- Industry Member sends a quote to an Inter-dealer Quotation System
- Inter-dealer Quotation System receives a quote from an Industry Member

Table 115: Linkage Error – Named on Unlinked Industry Member Quote Event

| Seq | Name | Data Type (Length) | Description |
|-----|-----------|--------------------|---|
| 1 | errorCode | Array | The CAT Error Codes associated with the Named Error. One errorCode will be assigned. Refer to Appendix E. of the CAT Reporting Technical |

| Seq | Name | Data Type (Length) | Description |
|-----|----------------------|--------------------|--|
| | | | Specifications for Industry Members for the definition of all Error Codes. |
| 2 | errorType | Message Type | Named Error Type; Set equal to ERRQT |
| 3 | errorROEID | Numeric (20) | Not applicable for Named Errors. |
| 4 | firmROEID | Text(64) | firmROEID of the unlinked event as assigned by the CAT Reporter. |
| 5 | type | Message Type | Event Type of the unlinked event. |
| 6 | symbol | Symbol | Symbol when populated on the unlinked event. |
| 7 | eventTimestamp | Timestamp | Timestamp as populated on the unlinked event. |
| 8 | bidPrice | Price | bidPrice as populated on the unlinked event. |
| 9 | bidQty | Whole Quantity | bidQty as populated on the unlinked event. |
| 10 | askPrice | Price | askPrice as populated on the unlinked event. |
| 11 | askQty | Whole Quantity | askQty as populated on the unlinked event. |
| 12 | senderIMID | Industry Member ID | senderIMID as populated on the unlinked event. |
| 13 | receiverIMID | Industry Member ID | receiverIMID when populated on the unlinked event. |
| 14 | destination | Industry Member ID | <i>destination</i> when populated on the unlinked event. |
| 15 | routedQuoteID | Text (64) | <i>routedQuoteID</i> as populated on the unlinked event. |
| 16 | receivedQuoteID | Text (64) | <i>receivedQuoteID</i> as populated on the unlinked event. |
| 17 | reservedForFutureUse | | Field is Reserved for Future Use. |
| 18 | reservedForFutureUse | | Field is Reserved for Future Use. |

7.5.1.5. Named on Unlinked Exchange Event

An unlinked Exchange Event occurs when any of the following linkages fail:

- Exchange receives an order from an Industry Member
- Exchange routes an order to an Industry Member

Table 116: Linkage Error – Named on Unlinked Exchange Event

| Seq | Name | Data Type (Length) | Description |
|-----|------------|--------------------|---|
| 1 | errorCode | Array | The CAT Error Codes associated with the Named Error. One errorCode will be assigned. Refer to Appendix E. of the CAT Reporting Technical Specifications for Industry Members for the definition of Exchange Linkage Named Error Codes. |
| 2 | errorType | Message Type | Named Error Type; Set equal to ERREX |
| 3 | errorROEID | Numeric (20) | Not applicable for Named Errors. |
| 4 | recordID | Text(64) | Unique identifier of the unlinked exchange event as assigned by the Plan Participant |

| Seq | Name | Data Type (Length) | Description |
|-----|----------------------|--------------------|--|
| 5 | type | Message Type | Event Type of the unlinked event. |
| 6 | symbol | Symbol | Symbol when populated on the unlinked event. |
| 7 | optionID | Text(22) | OptionID when populated on the unlinked event. |
| 8 | eventTimestamp | Timestamp | Timestamp as populated on the unlinked event. |
| 9 | side | Choice | Side as populated on the unlinked event. |
| 10 | price | Price | Price as populated on the unlinked event. |
| 11 | quantity | Real Quantity | Quantity as populated on the unlinked event. |
| 12 | routingParty | Text(20) | RoutingParty as populated on the unlinked event. Populated to represent the identifier used to enter the order into the exchange. |
| 13 | exchange | Exchange ID | Plan Participant Exchange Identifier. |
| 14 | routedOrderID | Text (64) | The routedOrderID when populated on the unlinked event. Populated using identifier from Exchange Data that includes the Order Identifier for the respective exchange used as part of the linkage key. |
| 15 | session | Text (40) | Session as populated on the unlinked event. Populated using identifier from Exchange Data that includes the Session Identifier for the respective exchange used as part of the linkage key. |
| 16 | capacity | Choice | Capacity as populated on the unlinked event. |
| 17 | reservedForFutureUse | | Field is Reserved for Future Use. |
| 18 | reservedForFutureUse | | Field is Reserved for Future Use. |

7.5.1.6. Named on Unlinked Trade Report

An unlinked Trade Report occurs when the following linkage fails:

- Transaction reporting system receives a trade report from an Industry Member

Table 117: Linkage Error – Named on Unlinked Trade Report

| Seq | Name | Data Type (Length) | Description |
|-----|---------------|--------------------|--|
| 1 | errorCode | Array | The CAT Error Codes associated with the Named Error. One errorCode will be assigned. Refer to Appendix E. of the CAT Reporting Technical Specifications for Industry Members for the definition of all Error Codes. |
| 2 | errorType | Message Type | Named Error Type Set equal to ERTRF |
| 3 | errorROEID | Numeric (20) | Not applicable for Named Errors. |
| 4 | errorRecordID | Text(64) | Control Number of the unlinked Trade Report as |

| Seq | Name | Data Type (Length) | Description |
|-----|----------------------|--------------------|---|
| | | | assigned by the FINRA transaction reporting system. |
| 5 | symbol | Symbol | Symbol on the unlinked event. |
| 6 | eventTimestamp | Timestamp | Execution Timestamp as populated on the unlinked event. |
| 7 | quantity | Real Quantity | Execution Quantity on the unlinked event. |
| 8 | price | Price | Execution price on the unlinked event. |
| 9 | rptngExctgMPID | Text (5) | Reporting Side Executing MPID from the unlinked Trade Report. |
| 10 | rptngSideTradeID | Text (40) | Reporting Side Trade ID from the unlinked Trade Report. Populated with Compliance ID in ORF and ADF; Branch Sequence Number in FINRA/NQ TRF and FINRA/NYSE TRF |
| 11 | rptngCapacity | Text (1) | Reporting Side Executing Capacity Code from the unlinked Trade Report. |
| 12 | rptngSideCode | Text (1) | Reporting Side Code from the unlinked Trade Report. |
| 13 | rptngSideShortCode | Text (1) | Reporting Side Short Code from the unlinked Trade Report. |
| 14 | contraExctgMPID | Text (5) | Contra Side Executing MPID from the unlinked Trade Report. |
| 15 | contraSideTradeID | Text (40) | Contra Side Trade ID from the unlinked Trade Report. Populated with Compliance ID in ORF and ADF; Branch Sequence Number in FINRA/NQ TRF and FINRA/NYSE TRF |
| 16 | contraCapacity | Text (1) | Contra Side Executing Capacity Code from the unlinked Trade Report. |
| 17 | contraSideCode | Text (1) | Contra Side Code from the unlinked Trade Report. |
| 18 | marketCenterID | Text (2) | FINRA transaction reporting system identifier. |
| 19 | reservedForFutureUse | | Field is Reserved for Future Use. |
| 20 | reservedForFutureUse | | Field is Reserved for Future Use. |

7.5.2. JSON Examples for Linkage Discovery Feedback

Linkage Discovery Success:

| | |
|-------------------------|--|
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents.linkage_000001.success |
| Meta File | empty |

Linkage Discovery Errors:

| | |
|-------------------------------|--|
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents.linkage_000001.json |
| Meta File | <pre>{ "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "stage": "LINKAGE", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Failure", "errorFileName": "SUBID_MYID_20170307_OrderEvents .linkage.error_000001.json.bz2", "errorCount": 2 "linkages": [{ "linkageType": "Intrafirm", "errorTypeCount": 1 }, { "linkageType": "Interfirm", "errorTypeCount": 1 }, { "linkageType": "Exchange", "errorTypeCount": 0 }, { "linkageType": "Trade", "errorTypeCount": 0 }], "doneForDay": true }</pre> |
| Error Data Feedback File Name | SUBID_MYID_20170307_OrderEvents.linkage.error_000001.json.bz2 |
| Data File | 5004,RPR,123457,<error record as per Table 117: Linkage Error - Named on Unlinked Trade Report> |

7.5.3. CSV Examples for Linkage Discovery Feedback

Linkage Discovery Success:

| | | |
|-------------------------|--|-------|
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents.linkage_000001.success | |
| Meta File | | empty |

Linkage Discovery Error:

| | |
|-------------------------|--|
| Meta Feedback File Name | SUBID_MYID_20170307_OrderEvents.linkage_000001.csv |
|-------------------------|--|

| | | |
|-------------------------|--------|--|
| Meta File | LINE 1 | 2.1.1,SUBID,MYID,20170307,,,LINKAGE, 20170307T154152.000001089,Failure,,, SUBID_MYID_20170307_OrderEvents .linkage.error_000001.csv.bz2,2, Intrafirm@1 Interfirm@1 Exchange@0 Trade@0,true |
| Data Feedback File Name | | SUBID_MYID_20170307_OrderEvents.linkage.error_000001.csv.bz2 |
| Data File | LINE 1 | 3001 3002,RPR,123456,<errorRecord as per Table 113: Linkage Error Reported by CAT Reporter> |
| | LINE 2 | 5004,RPR,123457,<error record as per Table 117: Linkage Error - Named on Unlinked Trade Report> |

7.6. Corrections

Errors found during CAT processing and found by CAT Reporters subsequent to transmission must be repaired. The reporting of Error Corrections is facilitated in CAT through submissions via SFTP and the CAT Reporter Portal. Certain fields are defined within the Event definitions in [Section 3.5 Multi-Leg Option Orders and Paired Orders](#)

Paired Orders are defined for CAT reporting purposes as orders that contain both the buy and sell side that are routed to another Industry Member or exchange for crossing and/or price improvement. Orders routed or received as a pair must be reported to CAT, and all Order Route, Option Order Route, and Multi-Leg Order Route events routed in the pair must be identified using a *pairedOrderID*.

Paired Orders Do Not Include:

- Orders that are not treated as a paired order by the recipient such as “post and wait”
- Preferred or directed orders that do not contain both the buy side and the sell side

Multi-Leg orders must be reported using Multi-Leg Order events as defined in Section 5.2.

Equity Events, and [Section 5 Option Events](#), to facilitate the reporting of corrections including: *actionType*, *firmROEID*, *errorROEID*.

Corrections may be reported for any previously submitted event. A corrected record will replace the original record for all further processing when the corrected record is received prior to T+4. The following scenarios are supported:

- Repair of events for which a CAT Error was provided in feedback
- Correction of events initiated by firms for which there is no associated CAT error feedback
- Deletion of a single event to remove erroneous events which did or did not result in a CAT Error

- Deletion of a file, resulting in the deletion of all events and respective CAT Errors
- The reporting of corrections may occur on the same CAT Processing Date as the original submission

7.6.1. Repair CAT Errors

A repair is instructed when repairing events for which a CAT Error was provided in feedback. The following rules apply:

1. A Repair record must contain the *actionType* 'RPR'
2. Repair records must populate the *errorROEID* equal to the *errorROEID* value provided by CAT in the respective error feedback; otherwise the record will be rejected.
3. Repair records may be reported within data files, among other CAT action types.
4. A Repair record must be reported for CAT Errors generated as a result of a record that is not readable, or when the record has an error associated with the *eventTimestamp*, or *firmROEID*.
5. CAT errors for which a Repair record is processed will be considered repaired.
6. CAT errors for which a Repair record is processed after to T+3 8am will be considered as a late repair.
7. Repair records processed prior to T+4 8am will result in the elimination of the previously submitted record from further processing.
8. Repair records processed after T+4 8am will be appended to the audit trail.

7.6.1.1. JSON Repair Record Example

```
{
  "actionType": "RPR",
  "errorROEID": 12345678,
  "firmROEID": "20170801_firmROEO12345",
  "type": "MENO",
  "orderKeyDate": "20170801T143031.000000",
  "orderID": "O12345",
  "symbol": "XYZ",
  "eventTimestamp": "20170801T143031.123456",
  "manualFlag": false,
  "deptType": "O",
  "side": "B",
  "price": 10.01,
  "quantity": 500,
  "orderType": "LMT",
  "timeInForce": {"DAY":20170801},
  "tradingSession": "REG",
  "custDspIntrFlag": false,
  "firmDesignatedID": "PROP456",
  "accountHolderType": "O",
  "negotiatedTradeFlag": false
}
```

7.6.1.2. CSV Repair Record Example

```
LINE n RPR,12345678,20170801_firmROEO12345,MENO,,20170801T143031.000000,
O12345,XYZ,20170801T143031.123456,false,,,N,O,,Buy,10.01,500,,LMT,
DAY=20170801,REG,,false,PROP456,O,,,false,,,,,,,,,,,,,
```

7.6.2. Firm Initiated Corrections

A firm initiated correction is instructed for correcting events for which there is no associated CAT error feedback or the firm repairs an error without submitting an *errorROEID*. The following rules apply:

1. A firm initiated correction record must contain the *actionType* 'COR'.
2. Firm initiated correction records must assign the *firmROEID* equal to the *firmROEID* of the original submission, otherwise the record will be rejected.
3. Firm initiated corrections must be used for correcting events for which there is no associated CAT error.
4. Firm initiated corrections may be used to repair an event for which a CAT Error was provided in feedback.
5. Firm initiated corrections may be reported within data files, among other CAT event types.
6. Events for which a firm initiated correction is processed by 8 am on T+3 will be considered corrected.
7. Events for which a firm initiated correction is processed after to T+3 8am will be considered as a late correction.
8. Events for which a firm initiated correction is processed prior to T+4 8am will result in the elimination of the previously submitted record from further processing.
9. Events for which a firm initiated correction processed after T+4 8am will be appended to the audit trail.

7.6.2.1. JSON Firm Initiated Correction Example

```
{
  "actionType": "COR",
  "firmROEID": "20170801_firmROEO12345",
  "type": "MENO",
  "orderKeyDate": "20170801T143031.000000",
  "orderID": "O12345",
  "symbol": "XYZ",
  "eventTimestamp": "20170801T143031.123456",
  "manualFlag": false,
  "deptType": "O",
  "side": "B",
  "price": 10.01,
  "quantity": 500,
  "orderType": "LMT",
  "timeInForce": {"DAY":20170801},
  "tradingSession": "REG",
  "custDspIntrFlag": false,
```

```

"firmDesignatedID": "PROP456",
"accountHolderType": "O",
"negotiatedTradeFlag": false
}

```

7.6.2.2. CSV Repair Record Example

```

LINE n COR,,20170801_firmROEO12345,MENO,,20170801T143031.000000,O12345,
XYZ,20170801T143031.123456,false,,,N,O,,Buy,10.01,500,,LMT,
DAY=20170801,REG,,false,PROP456,O,,,false,,,,,,,,,,,,

```

7.6.3. Record Delete Instructions

Record deletions are used to support the removal of one or more erroneous events reported to CAT. The following rules apply:

1. A delete instruction must contain the *actionType* 'DEL'.
2. A delete instruction does not support the full restatement of the record that is being deleted.
3. Delete instructions associated with a CAT error may populate the *errorROEID* equal to the *errorROEID* value provided by CAT in the respective error feedback OR may populate the *firmROEID* equal to the *firmROEID* of the original submission.
4. A Delete instruction for an event for which a CAT error was not generated must populate the *firmROEID* equal to the *firmROEID* of the original submission.
5. Delete instructions may be reported within data files, among other CAT event types.
6. CAT errors for which a Delete instruction is processed will be considered deleted.
7. CAT errors for which a Delete instruction is processed after to T+3 8am will be considered as a late repair.
8. Delete instructions processed prior to T+4 8am will result in the elimination of the previously submitted record from further processing.
9. Delete instructions processed after T+4 8am will be appended to the audit trail.

Table 118: Delete Instruction Record Format

| Seq | Name | Data Type (Length) | Description | Include Key |
|-----|------------|--------------------|--|-------------|
| 1 | actionType | Choice | Set equal to 'DEL' | R |
| 2 | errorROEID | Numeric (20) | When deleting an event for which a CAT Error was provided, populate the <i>errorROEID</i> equal to the <i>errorROEID</i> value provided by CAT in the respective error feedback. | C |
| 3 | firmROEID | Text (64) | When deleting an event for which a CAT error was not generated must populate the <i>firmROEID</i> equal to the <i>firmROEID</i> of the | C |

| Seq | Name | Data Type (Length) | Description | Include Key |
|-----|------|--------------------|----------------------|-------------|
| | | | original submission. | |

7.6.3.1. JSON Record Delete Examples

Delete record for an event with an associated CAT Error:

```
{
  "actionType": "DEL",
  "errorROEID": 45678901
}
```

Delete record for an event without an associated CAT Error

```
{
  "actionType": "DEL",
  "firmROEID": "20190416_FirmROE123"
}
```

7.6.3.2. CSV Record Delete Example

Delete record for an event with an associated CAT Error:

```
LINE n DEL, 45678901,
```

Delete record for an event without an associated CAT Error:

```
LINE n DEL,,20190416_FirmROE123
```

7.6.4. File Deletion

File Deletion is used to support the deletion of all events within a single data file, including all respective CAT errors for those events. File Deletions are used for files with included Event data representing an Event Date that is prior to T+4 8am. Deletion of events for Event Dates after T+4 8am is possible using the Delete Record instructions described in 7.6.3.

The following rules apply:

1. Data files must be deleted individually by the original Submitter of the file. Blocks are not supported.
2. File Acknowledgement and File Integrity feedback will be generated for every file delete instruction submitted by the firm.

3. After the File Delete Instruction has been acknowledged, a *firmROEID* that was contained in the file being deleted can be reused in a new submission.
4. The file deletion process will not be supported after T+4 8am. All events contained in the original file for which the file delete instruction was received, must represent a CAT Trading Day that is prior to T+4 8am.
5. File deletions are not supported for events with an Action Type of COR, DEL or RPR. All events contained with the original file for which the file deletion instruction was received, must have an Action Type of NEW.
6. Records contained in the original file being deleted will be removed from further processing and related CAT Errors will be considered as deleted.
7. Delete file instructions are reported using a Metadata file with an associated empty file. The hash value represents the empty file.
8. Filenames must not be reused, even after a file is deleted.
9. Delete file instructions are reported by submitting a Metadata file named as: <file base name of original data file>.meta.DEL.<Format Extension> (refer to [Section 6.1.3](#)) and an associated empty data file named as: <file base name of original data file>.DEL.<Format Extension>.<Compression Extension> Refer to the following example:

Metadata filename: <CAT Submitter ID>_<CAT Reporter IMID>_<File Generation Date>_[<Group>_]<File Kind>_<File Number>.meta.DEL.<Format Extension>

```
{
  "type": "META",
  "fileGenerationDate": 20180130,
  "reporter": "MPID",
  "submitter": "ORGID",
  "fileVersion": "2.2.1",
  "files": [
    {
      "fileName": "SubmitterID_ReporterID_20190207_OrderEvents_000002.DEL.bz2"
    }
  ],
  "recordCount": "0",
  "compressedHash": "99A7712E2CC1CB3A5789B91E3C1D1E76D7F83D82C8D35FF1F56B156A49C228E2"
}
```

Empty Data File: <CAT Submitter ID>_<CAT Reporter IMID>_<File Generation Date>_[<Group>_]<File Kind>_<File Number>.DEL.<Format Extension>.<Compression Extension>

7.6.5. Same Day Corrections

When error feedback is received, the CAT Reporter can take immediate action which may result in the original submission and correction occurring during the same processing date. Additionally, there will be instances when a Submitter identifies a CAT submissions issue for which CAT error feedback is expected but has not yet been received. In such cases, it is also possible to submit a same day correction.

Although the CAT Processor design processes data submissions in processing stages, the data within each stage does not have a prescribed processing order. To support the processing of same day corrections for which error feedback has not been received, the following guidelines for usage of each correction mechanism are recommended:

1. File Deletion instructions may be reported any time subsequent to the delivery of File Integrity feedback of the associated file.
2. Record deletions may be instructed after receiving File Ingestion feedback for the file in which the record was submitted.
3. Firm initiated corrections may be reported after receiving File Ingestion feedback for the file in which the record was submitted.

8. Testing

CAT will provide an environment for testing that mirrors the current functionality of the CAT production environment, as well as functionality for the next release version of the CAT environment when available. The CAT testing environment will automatically determine which specification version Industry Members and CAT Reporting Agents are using for submissions. If error reporting formats change, Industry Members and CAT Reporting Agents will receive feedback in the current and new specification via sftp, as well as have access to current/new CAT Reporter portal URLs for specification changes that impact the CAT Reporter portal. Current/new connectivity changes will also be supported concurrently.

The testing environment performs lifecycle linkage, and Industry Members and CAT Reporting Agents are encouraged to coordinate testing with their counterparties so as to test lifecycle linkage with their counterparties. Without simultaneous contra-party reporting in the test environment, Industry Members and CAT Reporting Agents will not be able to test linkage with their counterparties.

Industry Members and CAT Reporting Agents must test their submissions using the testing environment before they begin submitting to the production environment.

The test environment is available 24 hours a day, 6 days a week. Refer to the CAT website for contact information and hours of operation for support.

Industry Members and CAT Reporting Agents connect to the test environment in the same manner they would connect to the production environment. However, for the connection to the test environment, one or more alternate IP addresses or URLs may be used.

Testing does not relieve an Industry Member of its responsibilities to submit production data to the CAT System.

9. Additional Information

9.1. Public Website

The CAT Public Website, www.catnmsplan.com, is available via the public internet, and is hosted outside the CAT secure network. The CAT Public Website provides information about CAT, including links to SEC Rule 613, Participant and Industry Member Technical Specifications, FAQs, training materials, and CAT Help Desk contact information.

Web announcements will be made available on the public website (www.catnmsplan.com). You can also subscribe to receive email notifications regarding changes to the website. These announcements are used to post information related to the operation of CAT.

Contact help@finracat.com for any questions and/or feedback regarding this document.

Appendices

Appendix A: Change Release Management Process

Following publication of version 1.0, changes to this Industry Member Technical Specification will be released as follows:

- All proposed amendments to the Technical Specifications will be made in accordance with the CAT NMS Plan, including being approved or deemed approved (as applicable) by the Consolidated Audit Trail, LLC Operating Committee.
- Prior to the go-live date for any system changes set forth in the Technical Specifications:
 - ◆ A new Technical Specifications will be posted to the CAT Public Website, www.catnmsplan.com.
 - ◆ A notice will be posted on the CAT NMS Plan Public website with a summary of changes, the go-live date for the changes and links to relevant information.
 - ◆ One or more email alerts will be sent to the email address(es) on file for the CAT Reporters with a summary of changes set forth in the revised Technical Specifications, the go-live date for the changes and links to relevant information.
 - ◆ Industry Members will be permitted to perform testing of the revised Technical Specifications in advance of the go-live date for the changes. Information on such testing will be set forth in the notices and alerts described above.
 - ◆ As the go-live date approaches, Industry Members will be able to conduct testing and will receive support from the Plan Processor to prepare for production reporting using the revised Technical Specifications format. The revised Technical Specifications will include a summary list of changes as well as a table listing the specific areas of the document where the changes have been made.

Appendix B: Clock Synchronization Requirement

In previous sections, details are described regarding Order Events and data elements. Timestamp, as one of the required data elements for each order event, must be correctly reported by Industry Members at predefined granularity. This section provides an overview of the corresponding clock synchronization requirements applicable to Industry Members.

In order to comply with applicable requirements of Clock Synchronization and correctly record the Timestamp fields for order events. Industry Members are required to synchronize Business Clocks at a minimum to within 50 milliseconds of the time maintained by the National Institute of Standards and Technology (NIST) and to maintain such synchronization. Business Clocks that are solely used for Manual CAT events or for the time of allocation on Allocation Reports must be synchronized at a minimum to within a one second tolerance.

The tolerance includes:

- The difference between the NIST standard and a time provider's clock;
- Transmission delay from the source; and
- The amount of drift in the Participant's clock.

To ensure the accuracy of timestamps for Reportable Events, Industry Members must document and maintain their synchronization procedures for Business Clocks. Industry Members must keep a log of the time when they synchronize their Business Clocks and the results of the synchronization process. This log must include notice of any time a Business Clock drifts more than the applicable tolerances specified above. Such log must include results for a period of time of not less than five years ending on the then current date, or for the entire period for which the Industry Member has been required to comply with this Rule if less than five years. Industry Members must also certify their compliance with these clock synchronization requirements and report violations according to requirements established by the Operating Committee.

Any time provider and technology may be used for clock synchronization as long as the Business Clocks are in compliance with the accuracy requirement.

If additional details are needed, refer to Participants' applicable rules.

Appendix C: Representative Order Linkages

The CAT NMS Plan requires that customer orders be linked to representative orders created in firm accounts for the purpose of facilitating the execution of a customer order. This Appendix outlines reporting requirements for creating linkages between customer and representative orders.

C.1 Representative Order Reporting Requirements

C.1.1 Representative Order Reporting

Representative orders must be reported to CAT and marked as a representative order using the *representativeInd* field on New Order events.

The table below describes the *representativeInd* field values:

Table 119: representativeInd Field Values

| Value | Definition | Explanation |
|-----------------|---|---|
| Equities Values | | |
| Y | Representative order, linkage required | This value must be used for representative orders where linkage is required as described below. |
| YS | Representative order, linkage required; details in supplement event | This value must be used if a firm provides aggregated order IDs on an order supplement event. |
| YP | Representative order, pricing guarantee, no linkage required | This value must be used when a firm receives a client order, guarantees an execution price (e.g., VWAP) and then originates proprietary orders in an effort to work the client order. Linkage may not be possible as the client order may not be filled from the proprietary orders if the guaranteed price is not achieved. |
| YE | Representative eligible - Order eligible for customer fills via an unlinked system (unlinked OMS-EMS or position fill workflow) | This value must be used to report proprietary orders that are originated as part of workflows where there is no systemic link between client orders and representative firm orders and which includes disparate OMS-EMS scenarios and position fill workflows. In such workflows, MENO events for any street side orders reported with a YE indicator are not required to be linked to a customer order, and the <i>aggregatedOrders</i> field must be blank. Firms should note that explicit linkage in workflows covered by YE may be required in future phases of CAT. |
| Options Values | | |
| O | Options combined order, linkage required | This value must be used for options combined orders where linkage is required. |

| Value | Definition | Explanation |
|---|--|--|
| OS | Options combined order, linkage required; details in a supplement event | This value must be used for options combined orders where a firm provides aggregated order IDs on an options order supplement event. |
| OML | Multi-Leg Option combined order, linkage required | This value must be used when multi-leg orders are combined into a single aggregated multi-leg order, or when a multi-leg order is received as single leg fix messages with instructions to treat as a multi-leg order. |
| OMS | Options combined order, linkage required; details in a supplement event | This value must be used for Multi-Leg options combined orders where a firm provides aggregated order IDs on a Multi-Leg Order Supplement event. |
| Common Values – Applicable to both equities and options | | |
| N | Not a representative order/options combined order, linkage is not applicable | The value of N must be provided on any order that a firm is able to explicitly determine is not a representative order or an options combined order. |

C.1.2 Representative Order Linkages

Linkage is required between the representative street side order and the order being represented for both executed and unexecuted orders. Executed orders must also have a link between the Order Fulfillment event for the customer/client order and the representative order from which the fill came.

The following fields are used in the linkage process:

At the Order Level

- *representativeInd* indicates if an order was originated to represent a customer/client order.
- *aggregatedOrders* specifies the original order IDs and quantities being consolidated in the representative order.

At the Order Fulfillment Level

- *orderID* contains the firm side order that was used to fill the customer order.
- *fulfillmentLinkType* indicates whether there is order level and trade level linkage, only trade level linkage (e.g., fill from the pre-existing customer order), or why the firm side details are not present.
- *FDID* contains the firm account that was used to fill the customer order (only applicable when a *fulfillmentLinkType* of YE is populated).
- Linkage on the Order Fulfillment is indicated by the *fulfillmentLinkType*.

The following table describes the *fulfillmentLinkType* field values:

Table 120: fulfillmentLinkType Field Values

| Value | Definition | Explanation |
|-----------------|---|--|
| Equities Values | | |
| Y | Representative order, linkage required | This value must be used for representative orders where linkage is required. If this value is used, the <i>orderID</i> field in the firm side details is required to be populated. |
| YS | Client order filled from multiple representative orders, linkage required; details provided in a supplement event | This value must be used when a client order is filled from multiple representative orders. If this value is used, <i>firmDetails</i> in the MEOF event must be blank, and the details of each representative order used to fill the client order must be provided in a MEOFS event. |
| YP | Fill from pre-existing Principal order, linkage required | This value must be used when a client order is filled from a proprietary order that was originated prior to receipt of the client order. For example, this value must be used when a client order is filled as a result of a Manning obligation and the proprietary order was not reported to CAT with the client order ID in the <i>aggregatedOrders</i> field. |
| YE | Representative eligible - Order eligible for customer fills via an unlinked system (unlinked OMS-EMS or position fill workflow) | <p>This value must be used to report proprietary orders that are originated as part of workflows where there is no systemic link between client orders and representative firm orders and which includes disparate OMS-EMS scenarios and position fill workflows.</p> <p>In such workflows, MEOF events for any client orders that are filled from a representative order reported with a YE indicator are required to contain the FDID of the firm account from which the order was filled. In addition, the <i>accountHolderType</i> must be populated with the type of firm account.</p> <p>Firms should note that explicit linkage in workflows covered by YE may be required in future phases of CAT.</p> |
| FOR | Fulfillment on an order routed to a foreign destination, no linkage required | This value must be used to report the fill of an order (customer or proprietary) that was routed to a foreign destination. When a value of FOR is populated, the <i>firmDetails</i> must be blank. |
| Options Values | | |
| O | Combined options order, linkage required | This value must be used for options combined orders where linkage is required. If this value is used, the <i>orderID</i> field in the <i>firmDetails</i> is required to be populated. |
| OML | Multi-Leg Option combined order, linkage required | This value must be used to report the fill of a Multi-Leg option order at the leg level when the <i>orderID</i> referenced in the <i>firmDetails</i> is a Multi-Leg New Order event. |

C.2 Representative Order Marking and Linkage Requirements

C.2.1 Single Order Scenarios

The table below details requirements for both linkage and marking of a Representative Order in Single Order scenarios. Refer to the Data Dictionary for relevant field values. Refer to the [CAT Industry Member Reporting Scenarios](#) document for further information on how the relevant field values must be populated for each scenario.

Table 121: Requirements for Both Linkage and Marking of a Representative Order in Single Order Scenarios

| Scenario Description | Is Linkage Required? | | Is Rep Order Marking Required? | |
|--|----------------------|------|--------------------------------|------|
| | MENO | MEOF | MENO | MEOF |
| Riskless Principal Scenarios | | | | |
| A. Single Prop Order, single fill | Yes | Yes | Yes | Yes |
| B. Single Prop Order, multiple fills, print for print | Yes | Yes | Yes | Yes |
| C. Single Prop Order, multiple fills, average price fill to customer | Yes | Yes | Yes | Yes |
| D. Multiple Prop Orders, multiple fills, print for print | Yes | Yes | Yes | Yes |
| E. Multiple Prop Orders, multiple fills, average price fill to customer | Yes | Yes | Yes | Yes |
| F. Fill of a customer order from a pre-existing principal order (Manning scenario) | No | Yes | No | Yes |
| Agency Scenarios - applies when a firm's order handling and/or reporting system does not allow for a route to be directly associated with the customer order or child order (with the same Order ID) and instead must generate/report a route from a separate order (with a different Order ID) created by the firm for the purpose of working the customer order. | | | | |
| G. Single Rep Order, single fill | Yes | Yes | Yes | Yes |
| H. Single Rep Order, multiple fills, print for print to customer account | Yes | Yes | Yes | Yes |
| I. Single Rep Order, multiple fills, single average price booking to customer account; no print for print details available to customer account | Yes | Yes | Yes | Yes |
| J. Multiple Rep Orders, multiple fills, print for print | Yes | Yes | Yes | Yes |
| K. Multiple Prop Orders, multiple fills, average price fill to customer | Yes | Yes | Yes | Yes |
| Other Single Order Scenarios | | | | |

| Scenario Description | Is Linkage Required? | | Is Rep Order Marking Required? | |
|--|----------------------|------|--------------------------------|------|
| | MENO | MEOF | MENO | MEOF |
| Q. Price Guarantee Scenarios (e.g., VWAP, Stop Stock) - either single or aggregated orders | No | Yes | Yes | Yes |
| R. Single customer order filled from multiple representative orders | Yes | Yes | Yes | Yes |

C.2.2 Net Trading Scenarios

The table below details requirements for both linkage and marking of a Representative Order in Net Trading scenarios. Refer to the Data Dictionary for relevant field values. Refer to the [CAT Industry Member Reporting Scenarios](#) document for further information on how the relevant field values must be populated for each scenario.

Table 122: Requirements for Both Linkage and Marking of a Representative Order in Net Trading Scenarios

| Scenario Description | Is Linkage Required? | | Is Rep Order Marking Required? | |
|---|----------------------|------|--------------------------------|------|
| | MENO | MEOT | MENO | MEOT |
| Principal Net Trading - assumed that all street side fills are guaranteed to go to the customer order | | | | |
| L. Single Prop Order, multiple fills, print for print | Yes | Yes | Yes | N/A |
| M. Single Prop Order, multiple fills, print for print | Yes | Yes | Yes | N/A |
| N. Single Prop Order, multiple fills, average price fill to customer | Yes | Yes | Yes | N/A |
| O. Multiple Prop Orders, multiple fills, print for print | Yes | Yes | Yes | N/A |
| P. Multiple Prop Orders, multiple fills, average price fill to customer | Yes | Yes | Yes | N/A |

C.2.3 Aggregated Order Scenarios

The table below details requirements for both linkage and marking of a Representative Order in Aggregated Order scenarios. Refer to the Data Dictionary for relevant field values. Refer to the [CAT Industry Member Reporting Scenarios](#) document for further information on how the relevant field values must be populated for each scenario.

Table 123: Requirements for Both Linkage and Marking of a Representative Order in Aggregated Order Scenarios

| Scenario Description | Is Linkage Required? | | Is Rep Order Marking Required? | |
|---|----------------------|------|--------------------------------|------|
| | MENO | MEOF | MENO | MEOF |
| A. Multiple customer orders, single aggregated order | Yes | Yes | Yes | Yes |
| B. Multiple customer orders, multiple aggregated orders | Yes | Yes | Yes | Yes |
| C. Multiple orders from one customer combined into one aggregated order in the customer's account | Yes | Yes | Yes | Yes |
| D. Multiple customer orders combined into a single aggregated order, Riskless Principal order created to represent the aggregated order | Yes | Yes | Yes | Yes |

C.2.4 Representative Eligible Scenarios

The table below details requirements for both linkage and marking of an order that is “Representative Eligible”. Refer to the Data Dictionary for relevant field values. Refer to the [CAT Industry Member Reporting Scenarios](#) document for further information on how the relevant field values must be populated for each scenario.

Table 124: Requirements for Both Linkage and Marking of a Representative Eligible Order

| Scenario Description | Is Linkage Required? | | Is Rep Order Marking Required? | |
|--|----------------------|------|--------------------------------|------|
| | MENO | MEOF | MENO | MEOF |
| A. There is no systemic link between customer orders and representative firm orders because of disparate OMS-EMS. | No* | No* | Yes | Yes |
| B. There is no systemic link between customer orders and representative firm orders because the customer orders were filled from an existing position. | No* | No* | Yes | Yes |

* Firms should note that explicit linkage may be required in future phases of CAT.

C.2.5 Options Scenarios

The table below details requirements for both linkage and marking of options combined orders. Refer to the Data Dictionary for relevant field values. Refer to the [CAT Industry Member Reporting Scenarios](#) document for further information on how the relevant field values must be populated for each scenario.

Table 125: Requirements for Both Linkage and Marking of Options Combined Orders

| Scenario Description | Is Linkage Required? | | Is Rep Order Marking Required? | |
|---|----------------------|------|--------------------------------|------|
| | MONO | MOOF | MONO | MOOF |
| A. Single combined order, multiple customer fills | Yes | Yes | Yes | Yes |

C.2.6 Multi-Leg Option Scenarios

The table below details requirements for both linkage and marking of multi-leg option orders. Fills of a Multi-Leg order occur at the leg level and must be reported to CAT as simple Order Fulfillment or Options Order Fulfillment events with a *fulfillmentLinkType* value of “OML” to indicate that the *orderID* referenced in the *firmDetails* is a Multi-Leg New Order event.

Refer to the Data Dictionary for relevant field values. Refer to the [CAT Industry Member Reporting Scenarios](#) document for further information on how the relevant field values must be populated for each scenario.

Table 126: Requirements for Both Linkage and Marking of Multi-Leg Option Orders

| Scenario Description | Is Linkage Required? | | Is Rep Order Marking Required? | |
|--|----------------------|-----------|--------------------------------|-----------|
| | MLNO | MEOF/MOOF | MLNO | MEOF/MOOF |
| A. Single combined order, multiple customer fills | Yes | Yes | Yes | Yes |
| B. Customer order received as FIX messages representing single legs with instructions to treat as a Multi-Leg order. | No | N/A | No | N/A |
| C. Multi-Leg order received manually and followed by FIX messages representing individual legs | No | N/A | No | N/A |

Appendix D: CAT Date Definitions and Reporting Guidelines

The following key date terms are used throughout the document for reporting instructions:

Table 127: Key Date Terms

| Term | Definition | Usage |
|----------------------|--|---|
| Event Timestamp | <p>The date and time the event occurred.</p> <p>If electronic, required to be reported at the most granular level an Industry Member's order handling or execution systems use to capture data for the reported event, with at least millisecond granularity.</p> <p>If manual, required to be reported in increments of at least one second. If the order is immediately systematized, required to be reported with at least millisecond granularity.</p> | <p><i>eventTimestamp</i> is a field defined on every CAT event.</p> <p>Used to assign the CAT Trading Day.</p> |
| Event Date | The date portion of the Event Timestamp. | <p>Part of all Route Linkage Keys and the TRF Linkage Key, used to link records within the Event Date.</p> <p>Required to be populated as the prefix of a <i>firmROEID</i> assignment.</p> |
| File Generation Date | The date the file was generated or reported. | Used to guarantee uniqueness for a file across dates. |
| CAT Trading Day | <p>Trading Day for Industry Members is defined as beginning immediately after 4:15:00PM and no fractions of a second Eastern Time on one trade date and ending at exactly 4:15:00PM and no fractions of a second Eastern Time on the next trading date.</p> <p>Weekends and holidays are not considered a Trading Day.</p> <p>Trading Days that close early end 15 minutes after the Market Close.</p> <p>For an event occurring on CAT Trading Day T, submissions are due to CAT by T+1 8:00 AM EST; Corrections are due by T+3 8:00 AM EST.</p> <p>Refer to Section 6.4 for more information. Examples demonstrating the calculation of CAT Trading Day, Reporting Due Date and Repair Due Date.</p> | <p>Used to calculate the submission due date, and corrections due date.</p> <p>Submission Due Date: CAT Trading Day + 1 8:00AM ET</p> <p>Correction Due Date: CAT Trading Day + 3 8:00AM ET</p> |
| Trade Date | <p>Trade Date for Industry Member is defined as beginning immediately after 23:59:59.999999 ET on Trade Date T - 1 and up to 23:59:59.999999 ET of the next Trade Date T.</p> <p>Weekends and holidays are not considered a Trade Date.</p> <p>An event occurring on a weekend or holiday</p> | <p>Used to calculate the due date of data delivered to Regulatory Users.</p> <p>Due Date for Data and Associated Lifecycle Assignment delivery to Regulatory Users: Trade Date + 5 8:00AM ET</p> <p>Used to calculate summaries and present feedback on the CAT Reporter Portal representing events for the same Trade</p> |

| Term | Definition | Usage |
|---------------------|---|--|
| | will be assigned to the next Trade Date. | Date, regardless of when the events were reported. |
| CAT Processing Date | Date representing the set of events reported for a CAT Trading Day. Events reported late to CAT will be assigned the CAT Processing Date reflective of when they were reported. For example, an event, that occurred at 2pm on T which is reported to CAT after T+1 8am and prior to T+2 8AM will be assigned CAT Processing Date of T+1. | Used to identify late submissions and late repairs. Used to calculate summaries and present feedback on the CAT Reporter Portal representing events reported on the CAT Processing Date, regardless of the Event Date. |
| Order Key Date | The date and time the OrderID was assigned. | <i>orderKeyDate</i> is a field defined on Order events, and other events which specify an Order Key. Used to support uniqueness of an Order Key. If time is not needed to guarantee a unique Order Key, the time portion may be populated with zeros. |
| Trade Key Date | The date and time the TradeID was assigned. | <i>tradeKeyDate</i> is a field defined on Trade events. Used to support uniqueness of a Trade Key. If time is not needed to guarantee a unique Trade Key, the time portion may be populated with zeros. |
| Quote Key Date | The date and time the QuoteID was assigned. | <i>quoteKeyDate</i> is a field defined on Quote events. Used to support uniqueness of a Quote Key. If time is not needed to guarantee a unique Quote Key, the time portion may be populated with zeros. |
| Fill Key Date | The date and time the FulfillmentID was assigned. | <i>fillKeyDate</i> is a field defined on Fulfillment events. Used to support uniqueness of a Fulfillment Key. If time is not needed to guarantee a unique fulfillment Key, the time portion may be populated with zeros. |
| Allocation Key Date | The date and time the AllocationID was assigned | <i>allocationKeyDate</i> is a field defined on Allocation events. Used to support uniqueness of an Allocation Key. If time is not needed to guarantee a unique Allocation Key, the time portion may be populated with zeros. |

The following table illustrates the assignment of the Event Date, CAT Trading Day and the associated deadlines for Submission and Correction.

Table 128: Deadlines for Submission and Correction

| # | Event Timestamp | Event Date | Holiday | CAT Trading Day | Submission Due | Corrections Due |
|----|------------------------------|------------|---------|-----------------|---------------------|--------------------|
| 1 | Wed, 9/12/18 16:13:00 ET | 9/12/18 | n/a | 9/12/18 | 9/13/18, 8:00 AM ET | 9/17/18 8:00 AM ET |
| 2 | Wed, 9/12/18 16:16:00 ET | 9/12/18 | n/a | 9/13/18 | 9/14/18, 8:00 AM ET | 9/18/18 8:00 AM ET |
| 3 | Fri, 9/14/18 16:01:00 ET | 9/14/18 | n/a | 9/14/18 | 9/17/18, 8:00 AM ET | 9/19/18 8:00 AM ET |
| 4 | Fri, 9/14/18 16:45:00 ET | 9/14/18 | n/a | 9/17/18 | 9/18/18, 8:00 AM ET | 9/20/18 8:00 AM ET |
| 5 | Sat, 9/15/18 12:30:01 ET | 9/15/18 | n/a | 9/17/18 | 9/18/18, 8:00 AM ET | 9/20/18 8:00 AM ET |
| 6 | Mon, 9/17/18 10:30:05 ET | 9/17/18 | n/a | 9/17/18 | 9/18/18, 8:00 AM ET | 9/20/18 8:00 AM ET |
| 7 | Wed, 1/16/19 11:00 AM ET | 1/16/19 | 1/21/19 | 1/16/19 | 1/17/19 8:00 AM ET | 1/22/19 8:00 AM ET |
| 8 | Thur, 1/17/19 16:22 PM ET | 1/17/19 | 1/21/19 | 1/18/19 | 1/22/19 8:00 AM ET | 1/24/19 8:00 AM ET |
| 9 | Sat, 1/19/19 11:15 AM ET | 1/19/19 | 1/21/19 | 1/22/19 | 1/23/19 8:00 AM ET | 1/25/19 8:00 AM ET |
| 10 | Mon, 1/21/19 10:00 AM ET | 1/21/19 | 1/21/19 | 1/22/19 | 1/23/19 8:00 AM ET | 1/25/19 8:00 AM ET |

Appendix E: Error Codes

This section defines the error and warning codes generated by CAT. Each code is defined to include the reason for the error or warning, including the associated fields. Warnings are not subject to further processing and firms are not required to take any action on them. Codes are assigned in ranges to represent similar types of errors within the same range, related by validation type and/or by linkage type. Codes are organized by the CAT Processing stages including:

- File Integrity
- Data Ingestion
- Linkage Discovery

E.1 File Integrity Errors

The table below contains error messages that are associated with file integrity. Errors are associated with files, filenames and metadata within Metadata files.

Table 129: File Integrity Errors

| Error Code | Error Code Description | Explanation | Error/Warning |
|------------|---|---|---------------|
| 1101 | Missing Metadata File | Timeout waiting for associated metadata file. Data files for which an associated Metadata file is not received within 30 minutes of the receipt of the data file. | Warning |
| 1103 | Duplicate File | A file with the same base name was previously accepted by CAT. | Error |
| 1104 | Missing or Invalid CAT Submitter ID | CAT Submitter ID is missing or invalid. | Error |
| 1105 | Missing or Invalid CAT Reporter IMID | CAT Reporter IMID is missing or is not a valid Market Participant for the Generation Date. | Error |
| 1106 | Missing or Invalid File Generation Date | File Generation Date is missing or is not a valid date. | Error |
| 1107 | Metadata File Not Readable | Metadata file format is not readable as it is not in a valid JSON format or contains an incorrect delimiter. | Error |
| 1108 | File exceeds the supported size limit | File size exceeds the maximum uncompressed size of 100 GB via SFTP and 1GB via the CAT Reporter Portal. | Error |
| 1109 | Unauthorized CAT Submitter ID | CAT Submitter ID has not been authorized to submit for the CAT Reporter IMID. Verify that the CAT Submitter ID and CAT Reporter IMID in the file name have a transmitting relationship. | Error |

| Error Code | Error Code Description | Explanation | Error/Warning |
|------------|---|--|---------------|
| 1110 | Missing File Information | File information is not found in the Metadata File submission. | Error |
| 1111 | Missing or Invalid record count | The record count in the metadata file is missing or is a negative number, or a non-zero number for DEL file. | Error |
| 1112 | Mismatched Metadata File Format | The associated Metadata file is not in the same format as the data file submitted to CAT. | Error |
| 1115 | Missing or Invalid Compressed Hash | Compressed Hash in meta file is missing or invalid (e.g., doesn't match the data file). | Error |
| 1116 | Missing or Invalid File Version | File Version in Metadata file is missing or invalid. | Error |
| 1120 | Invalid File in Delete Instruction | The delete instruction is on a file that does not exist in CAT, contains event dates more than four days prior to the current processing date, or contains <i>actionType</i> other than 'NEW'. | Error |
| 1121 | Missing Metadata File | Timeout waiting for associated metadata file. Data files for which an associated Metadata file is not received within 2 hours of the receipt of the data file. | Error |
| 1122 | Missing Data File | Metadata file includes one or more data files that were not received prior to the receipt of the metadata file. | Error |
| 1123 | Invalid thirdParty | Third Party is invalid. | Error |
| 1124 | Unauthorized thirdParty | Third Party Reporting Agent has not been authorized to view feedback and error data for data submitted on behalf of the CAT Reporter. Verify that the CAT Reporter IMID and the thirdParty provided in the meta data file have an active reporting relationship. | Error |
| 1126 | Missing or Invalid doneForDay | doneForDay is missing or with invalid value. | Error |
| 1127 | Missing or Invalid Type | Type in the Metadata file is missing or invalid. | Error |
| 1128 | File exceeds maximum records allowed for Web upload | A single data file uploaded via the Reporter Portal must not contain greater than 100,000 records. | Error |

E.2 Data Ingestion Errors

The table below contains error messages that are associated with Data Ingestion. Error codes are associated with specific fields within an event.

Table 130: CAT Event Ingestion Errors

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|---|--|---------------|
| 2001 | Missing or Invalid <i>accountHolderType</i> | <i>accountHolderType</i> must be populated with one of the allowable values. | Error |
| 2002 | Missing or Invalid <i>actionType</i> | <i>actionType</i> must be populated with one of the allowable values. | Error |
| 2003 | Missing or Invalid <i>affiliateFlag</i> | <i>affiliateFlag</i> must be populated with one of the allowable values. | Error |
| 2004 | Missing or Invalid <i>aggregatedOrders</i> | If populated, <i>aggregatedOrders</i> must be in the correct format. | Error |
| 2005 | Missing or Invalid <i>askPrice</i> | When required, <i>askPrice</i> must be in the correct format. Required when <i>askQty</i> is populated. | Error |
| 2006 | Missing or Invalid <i>askQty</i> | When required, <i>askQty</i> must be in the correct format. Required <i>askPrice</i> is populated. | Error |
| 2007 | Missing or Invalid <i>atsDisplayInd</i> | When required, <i>atsDisplayInd</i> must be one of the allowable values. | Error |
| 2008 | Missing or Invalid <i>atsOrderType</i> | When required, <i>atsOrderType</i> must be equal to a unique identifier representing the specific order type provided to CAT by the ATS. | Error |
| 2009 | Missing or Invalid <i>bidPrice</i> | When required, <i>bidPrice</i> must be in the correct format; must be populated if <i>bidQty</i> is populated. | Error |
| 2010 | Missing or Invalid <i>bidQty</i> | When required, <i>bidQty</i> must be in the correct format; must be populated if <i>bidPrice</i> is populated. | Error |
| 2011 | Invalid <i>CATReporterIMID</i> | If populated, <i>CATReporterIMID</i> must be valid for the Event Date and must equal the <i>CATReporterIMID</i> in the filename. | Error |
| 2012 | Missing or Invalid <i>cancelQty</i> | <i>cancelQty</i> must be populated in the correct format. | Error |
| 2013 | Missing or Invalid <i>cancelFlag</i> | <i>cancelFlag</i> must be populated in the correct format. | Error |
| 2014 | Missing or Invalid <i>cancelTimestamp</i> | When required, <i>cancelTimestamp</i> must be in the correct format; must be populated if <i>cancelFlag</i> is True. | Error |
| 2015 | Missing or Invalid <i>capacity</i> | <i>capacity</i> must be populated with one of the allowable values. | Error |
| 2017 | Missing or Invalid <i>custDspIntrFlag</i> | <i>custDspIntrFlag</i> must be populated with one of the allowable values. | Error |
| 2018 | Missing or Invalid <i>deptType</i> | <i>deptType</i> must be populated with one of the allowable values. | Error |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|--|--|---------------|
| 2019 | Combination of <i>destination</i> and <i>destinationType</i> is Invalid | For Route Events, the following <i>destinationType</i> and <i>destination</i> combinations are required: <ul style="list-style-type: none"> If <i>destinationType</i> is F, the <i>destination</i> must be the IMID of an Industry Member. Must be valid for the Event Date. If <i>destinationType</i> is E, the <i>destination</i> must be one of the allowable values. | Error |
| 2020 | Missing or Invalid <i>destinationType</i> | <i>destinationType</i> must be populated with one of the allowable values. | Error |
| 2021 | Missing or Invalid <i>displayPrice</i> | When required, <i>displayPrice</i> must be in the correct format. | Error |
| 2022 | Missing or Invalid <i>displayQty</i> | When required, <i>displayQty</i> must be in the correct format. | Error |
| 2023 | Missing or Invalid <i>dupROIDCond</i> | <i>dupROIDCond</i> must be populated with one of the allowable values. | Error |
| 2024 | Missing or Invalid <i>electronicDupFlag</i> | <i>electronicDupFlag</i> must be populated and is one of the allowable values. | Error |
| 2025 | Invalid <i>electronicTimestamp</i> | <i>electronicTimestamp</i> must be in the correct format. | Error |
| 2026 | Missing or Invalid <i>errorROEID</i> | <i>errorROEID</i> must be blank when the <i>actionType</i> is 'NEW'; must be populated when <i>actionType</i> is 'RPR'. | Error |
| 2027 | Missing or Invalid <i>eventTimestamp</i> | <i>eventTimestamp</i> must be in the correct format. If <i>manualFlag</i> is true, <i>eventTimestamp</i> must be reported in increments of at least one second. If <i>manualFlag</i> is false, <i>eventTimestamp</i> must be reported in increments of at least milliseconds. | Error |
| 2028 | Combination of <i>exchOriginCode</i> and <i>destinationType</i> is invalid | For Option Order Route events, the following <i>exchOriginCode</i> and <i>destinationType</i> combination are required: <ul style="list-style-type: none"> If <i>destinationType</i> is not E, <i>exchOriginCode</i> must be blank. If <i>destinationType</i> is E, <i>exchOriginCode</i> must be populated. | Error |
| 2030 | Missing or Invalid <i>fillKeyDate</i> | <i>fillKeyDate</i> must be populated in the correct format. | Error |
| 2031 | Missing or Invalid <i>firmDesignatedID</i> | When required, <i>firmDesignatedID</i> must be in the correct format and unique among all identifiers from any given Industry Member for each business date. | Error |
| 2032 | Missing or Invalid <i>firmROEID</i> | <i>firmROEID</i> must be populated and in the correct format. | Error |
| 2033 | Invalid Event Date in the <i>firmROEID</i> | The Event Date portion of the <i>firmROEID</i> must be in the correct format and must equal the date portion of <i>eventTimestamp</i> . | Error |
| 2034 | Missing or Invalid <i>fulfillmentID</i> | <i>fulfillmentID</i> must be populated in the correct format. | Error |
| 2035 | Missing or Invalid <i>fulfillmentLinkType</i> | <i>fulfillmentLinkType</i> must be populated with one of the allowable values. | Error |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|---|---|---------------|
| 2036 | Invalid <i>handlingInstructions</i> | <i>handlingInstructions</i> must be in the correct format and must include allowable values. Name and value must be provided when applicable. | Error |
| 2037 | Invalid <i>infoBarrierID</i> | <i>infoBarrierID</i> must be in the correct format. | Error |
| 2038 | Missing or Invalid <i>initiator</i> | <i>initiator</i> must be populated with one of the allowable values. | Error |
| 2039 | Missing or Invalid <i>isolnd</i> | When required, <i>isolnd</i> value must be one of the allowable values. | Error |
| 2040 | Missing or Invalid <i>leavesQty</i> | When required, <i>leavesQty</i> must be in the correct format, and must be less than or equal to quantity. | Error |
| 2041 | Missing or Invalid <i>manualFlag</i> | <i>manualFlag</i> must be one of the allowable values. | Error |
| 2042 | Missing or Invalid <i>manualOrderKeyDate</i> | <i>manualOrderKeyDate</i> must be in the correct format; required if <i>manualOrderID</i> is populated. | Error |
| 2043 | Missing or Invalid <i>manualOrderID</i> | <i>manualOrderID</i> must be in the correct format. | Error |
| 2044 | Missing or Invalid <i>marketCenterID</i> | When required, <i>marketCenterID</i> must be one of the allowable values. | Error |
| 2045 | Invalid <i>minQty</i> | <i>minQty</i> must be in the correct format, must be greater than zero. | Error |
| 2046 | Invalid <i>mpStatusCode</i> | <i>mpStatusCode</i> must be one of the allowable values. | Error |
| 2047 | Missing or Invalid <i>nbboSource</i> | When required, <i>nbboSource</i> must be one of the allowable values. | Error |
| 2048 | Missing or Invalid <i>nbboTimestamp</i> | When required, <i>nbboTimestamp</i> must be in the correct format. | Error |
| 2049 | Missing or Invalid <i>nbbPrice</i> | When required, <i>nbbPrice</i> must be in the correct format. | Error |
| 2050 | Missing or Invalid <i>nbbQty</i> | When required, <i>nbbQty</i> must be in the correct format. | Error |
| 2051 | Missing or Invalid <i>nboPrice</i> | When required, <i>nboPrice</i> must be in the correct format. | Error |
| 2052 | Missing or Invalid <i>nboQty</i> | When required, <i>nboQty</i> must be in the correct format. | Error |
| 2053 | Missing or Invalid <i>negotiatedTradeFlag</i> | <i>negotiatedTradeFlag</i> must be populated and one of the allowable values. | Error |
| 2054 | Missing or Invalid <i>sideDetailsInd</i> | <i>sideDetailsInd</i> must be populated with one of the allowable values. | Error |
| 2056 | Missing or Invalid <i>onlyOneQuoteFlag</i> | <i>onlyOneQuoteFlag</i> must be populated with one of the allowable values if required to populate. | Error |
| 2057 | Missing or Invalid <i>openCloseIndicator</i> | When required, <i>openCloseIndicator</i> must be one of the allowable values. | Error |
| 2058 | Missing or Invalid <i>optionID</i> | <i>optionID</i> must be populated in the correct format. | Error |
| 2060 | <i>optionID</i> not effective on Event Date | <i>optionID</i> is not effective on the event date. | Error |
| 2061 | Missing or Invalid <i>orderID</i> | <i>orderID</i> must be populated in the correct format. | Error |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|--|---|---------------|
| 2062 | Missing or Invalid <i>orderType</i> | <i>orderType</i> must be populated one of the allowable values. | Error |
| 2063 | Missing or Invalid <i>orderKeyDate</i> | <i>orderKeyDate</i> must be populated and in the correct format. | Error |
| 2064 | Missing or Invalid <i>originatingIMID</i> | If populated, <i>originatingIMID</i> must be in the correct format on all secondary events. Must be valid for the Event Date. | Error |
| 2065 | Missing or Invalid <i>parentOrderID</i> | <i>parentOrderID</i> must be populated in the correct format. | Error |
| 2066 | Missing or Invalid <i>parentOrderKeyDate</i> | <i>parentOrderKeyDate</i> must be populated in the correct format. | Error |
| 2067 | Missing or Invalid <i>price</i> | <i>price</i> must be in the correct format. | Error |
| 2068 | Missing or Invalid <i>priorFillKeyDate</i> | When required, <i>priorFillKeyDate</i> must be populated and in the correct format. | Error |
| 2070 | Missing or Invalid <i>priorFulfillmentID</i> | When required, <i>priorFulfillmentID</i> must be in the correct format. | Error |
| 2071 | Missing or Invalid <i>priorOrderID</i> | When required, <i>priorOrderID</i> must be populated in the correct format. | Error |
| 2072 | Missing or Invalid <i>priorOrderKeyDate</i> | When required, <i>priorOrderKeyDate</i> must be populated in the correct format. | Error |
| 2073 | Missing or Invalid <i>priorQuoteKeyDate</i> | When required, <i>priorQuoteKeyDate</i> must be populated in the correct format. | Error |
| 2074 | Missing or Invalid <i>priorQuoteID</i> | When required, <i>priorQuoteID</i> must be populated and must be in the correct format. | Error |
| 2076 | Missing or Invalid <i>quantity</i> | <i>quantity</i> must be in the correct format. | Error |
| 2077 | Missing or Invalid <i>quoteID</i> | <i>quoteID</i> must be populated in the correct format. | Error |
| 2078 | Missing or Invalid <i>quoteKeyDate</i> | <i>quoteKeyDate</i> must be populated and in the correct format. | Error |
| 2080 | Missing or Invalid <i>quoteRejectedFlag</i> | When required, <i>quoteRejectedFlag</i> must be populated in one of the allowable values. | Error |
| 2081 | Missing or Invalid <i>receivedQuoteID</i> | <i>receivedQuoteID</i> must be populated in the correct format. | Error |
| 2082 | Missing or Invalid <i>receiverIMID</i> | <i>receiverIMID</i> must be populated in the correct format. Must be valid for the Event Date. | Error |
| 2083 | Missing or Invalid <i>receivingDeskType</i> | <i>receivingDeskType</i> must be populated in one of the allowable values. | Error |
| 2084 | Invalid <i>reportingExceptionCode</i> | <i>reportingExceptionCode</i> must be one of the allowable values. | Error |
| 2085 | Missing or Invalid <i>representativeInd</i> | <i>representativeInd</i> must be populated in one of the allowable values. | Error |
| 2086 | Invalid <i>routedOrderID</i> | <i>routedOrderID</i> must be populated in the correct format. | Error |
| 2087 | Invalid <i>routedQuoteID</i> | When required, <i>routedQuoteID</i> must be populated in the correct format. | Error |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|---|--|---------------|
| 2088 | Invalid <i>routeRejectedFlag</i> | <i>routeRejectedFlag</i> must be one of the allowable values. | Error |
| 2089 | Combination of <i>senderType</i> and <i>senderIMID</i> is invalid | If <i>senderType</i> = F, <i>senderIMID</i> is the IMID of an Industry Member. If <i>senderType</i> = E, <i>senderIMID</i> must be one of the allowable values. | Error |
| 2090 | Missing or Invalid <i>senderType</i> | When required, <i>senderType</i> must be one of the allowable values. | Error |
| 2091 | Missing or Invalid <i>senderIMID</i> | When required, <i>senderIMID</i> must be populated in the correct format. Must be valid for the Event Date. | Error |
| 2092 | Missing or Invalid <i>seqNum</i> | When required, <i>seqNum</i> must be in the correct format. | Error |
| 2093 | Missing or Invalid <i>session</i> | When required, <i>session</i> must be populated. Required when <i>destinationType</i> is E. | Error |
| 2095 | Missing or Invalid <i>side</i> | <i>side</i> must be populated in one of the allowable values. | Error |
| 2096 | Missing or Invalid <i>symbol</i> | <i>symbol</i> must be populated in the correct format. | Error |
| 2098 | <i>symbol</i> not effective on Event Date | <i>symbol</i> is not effective on the event date. | Error |
| 2099 | <i>symbol</i> does not match listing market format | For exchange listed securities, the <i>symbol</i> format must match the format published by the primary listing market. | Error |
| 2100 | Invalid <i>tapeTradeID</i> | If populated, <i>tapeTradeID</i> must be in the correct format. | Error |
| 2101 | Missing or Invalid <i>timeInForce</i> | <i>timeInForce</i> value must be populated in the correct format. Name and value must be provided when applicable. | Error |
| 2102 | Missing or Invalid <i>tradeID</i> | <i>tradeID</i> must be populated in the correct format. | Error |
| 2103 | Missing or Invalid <i>tradeKeyDate</i> | <i>tradeKeyDate</i> must be populated in the correct format. | Error |
| 2104 | Missing or Invalid <i>tradingSession</i> | <i>tradingSession</i> must be populated in one of the allowable values. | Error |
| 2105 | Missing or Invalid <i>type</i> | For each event type, <i>type</i> must be populated and one of the allowable values. | Error |
| 2106 | Missing or Invalid <i>unsolicitedInd</i> | <i>unsolicitedInd</i> must be populated in one of the allowable values. | Error |
| 2107 | Invalid <i>workingPrice</i> | <i>workingPrice</i> must be blank if <i>atsDisplayInd</i> is blank. When required, <i>workingPrice</i> must be populated in the correct format if <i>atsDisplayInd</i> is populated. If no <i>workingPrice</i> is applicable, it must be 0. | Error |
| 2108 | Missing or Invalid <i>buyDetails</i> | If <i>sideDetailsInd</i> = BUY, <i>buyDetails</i> must be populated. If <i>sideDetailsInd</i> = SELL, <i>buyDetails</i> must not be populated. | Error |
| 2109 | Missing or Invalid <i>orderID</i> in <i>buyDetails</i> | When required, <i>orderID</i> must be populated in the correct format. | Error |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|--|---|---------------|
| 2110 | Missing or Invalid <i>orderKeyDate</i> in <i>buyDetails</i> | When required, <i>orderKeyDate</i> must be populated in the correct format. | Error |
| 2111 | Missing or Invalid <i>side</i> in <i>buyDetails</i> | <i>side</i> must be populated in the correct format. | Error |
| 2112 | Missing or Invalid <i>firmDesignatedID</i> in <i>buyDetails</i> | When required, <i>firmDesignatedID</i> must be populated in the correct format. | Error |
| 2113 | Missing or Invalid <i>accountHolderType</i> in <i>buyDetails</i> | When required, <i>accountHolderType</i> must be one of the allowable values. | Error |
| 2114 | Invalid combination of <i>firmDesignatedID</i> and <i>orderID</i> in <i>buyDetails</i> | When required, the combination of <i>firmDesignatedID</i> and <i>orderID</i> in <i>buyDetails</i> must be valid. See Table 38: Trade Side Details for more details. | Error |
| 2115 | Missing or Invalid <i>sellDetails</i> | If <i>sideDetailsInd</i> = SELL, <i>sellDetails</i> must be populated. If <i>sideDetailsInd</i> = BUY, <i>sellDetails</i> must not be populated. | Error |
| 2116 | Missing or Invalid <i>orderID</i> in <i>sellDetails</i> | When required, <i>orderID</i> must be populated in the correct format. | Error |
| 2117 | Missing or Invalid <i>orderKeyDate</i> in <i>sellDetails</i> | When required, <i>orderKeyDate</i> must be populated in the correct format. | Error |
| 2118 | Missing or Invalid <i>side</i> in <i>sellDetails</i> | <i>side</i> must be populated in the correct format. | Error |
| 2119 | Missing or Invalid <i>firmDesignatedID</i> in <i>sellDetails</i> | When required, <i>firmDesignatedID</i> must be populated in the correct format. | Error |
| 2120 | Missing or Invalid <i>accountHolderType</i> in <i>sellDetails</i> | When required, <i>accountHolderType</i> must be populated in the correct format. | Error |
| 2121 | Missing or Invalid <i>orderID</i> in <i>clientDetails</i> | <i>orderID</i> must be populated in the correct format. | Error |
| 2122 | Missing or Invalid <i>orderKeyDate</i> in <i>clientDetails</i> | <i>orderKeyDate</i> must be populated in the correct format. | Error |
| 2123 | Missing or Invalid <i>side</i> in <i>clientDetails</i> | <i>side</i> must be populated in the correct format. | Error |
| 2124 | Invalid <i>firmDesignatedID</i> in <i>clientDetails</i> | <i>firmDesignatedID</i> must be blank. | Error |
| 2125 | Invalid <i>accountHolderType</i> in <i>clientDetails</i> | <i>accountHolderType</i> must be blank. | Error |
| 2126 | Missing or Invalid <i>orderID</i> in <i>firmDetails</i> | When required, <i>orderID</i> must be populated and in the correct format. | Error |
| 2127 | Missing or Invalid <i>orderKeyDate</i> in | When required, <i>orderKeyDate</i> must be populated in the correct format. | Error |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|---|--|---------------|
| | <i>firmDetails</i> | | |
| 2128 | Missing or Invalid <i>side</i> in <i>firmDetails</i> | <i>side</i> must be populated and in the correct format. | Error |
| 2129 | Missing or Invalid <i>firmDesignatedID</i> in <i>firmDetails</i> | When required, <i>firmDesignatedID</i> must be in the correct format. | Error |
| 2130 | Missing or Invalid <i>accountHolderType</i> in <i>firmDetails</i> | When required, <i>accountHolderType</i> must be one of the allowable values. | Error |
| 2132 | Record exceeds maximum length | Record length must not exceed the maximum length for each record. | Error |
| 2133 | Additional fields are specified in the record but are not defined for this CAT event type | Refer to Sections 3.4 & 4.15 for permitted fields for each CAT event type. | Error |
| 2134 | Invalid JSON or CSV format | The record is not represented in a valid format as specified in Section 2.5 Data Types . | Error |
| 2136 | Invalid Alphanumeric Character | A field value in the record contains a delimiter or a non-allowable ASCII character | Error |
| 2137 | Invalid correction, deletion or a repair | <i>actionType</i> 'COR', 'RPR' or 'DEL' is received for a <i>firmROEID</i> or an <i>errorROEID</i> that does not exist in CAT. | Error |
| 2139 | <i>eventTimestamp</i> is greater than the current date and time | The <i>eventTimestamp</i> is greater than system date. | Error |
| 2142 | Invalid combination of <i>aggregatedOrders</i> and <i>representativeInd</i> | The combination of <i>aggregatedOrders</i> and <i>representativeInd</i> must be valid. See Appendix C for more details on reporting representative and combined orders. | Error |
| 2143 | Invalid combination of <i>electronicDupFlag</i> and <i>manualFlag</i> | The combination of <i>electronicDupFlag</i> and <i>manualFlag</i> must be valid. See Section 3.2.2 for more details. | Error |
| 2144 | Invalid combination of <i>electronicTimestamp</i> and <i>manualFlag</i> | The combination of <i>electronicTimestamp</i> and <i>manualFlag</i> must be valid. See Section 3.2.2 for more details. | Error |
| 2145 | Invalid combination of <i>fulfillmentLinkType</i> and <i>firmDetails</i> | The combination of <i>fulfillmentLinkType</i> and <i>firmDetails</i> must be valid. See Appendix C for more details on reporting representative and combined orders. | Error |
| 2146 | Missing or Invalid <i>clientDetails</i> | <i>clientDetails</i> must be populated in the correct format. | Error |
| 2148 | Invalid combination of <i>firmDesignatedID</i> and <i>orderID</i> in <i>sellDetails</i> | When required, the combination of <i>firmDesignatedID</i> and <i>orderID</i> in <i>sellDetails</i> must be valid. See Table 38: Trade Side Details for more details. | Error |
| 2149 | <i>CATReporterIMID</i> and <i>senderIMID</i> must be assigned to the same firm | <i>CATReporterIMID</i> and <i>senderIMID</i> must be assigned to the same firm. | Error |
| 2150 | <i>CATReporterIMID</i> and | <i>CATReporterIMID</i> and <i>receiverIMID</i> must be | Error |

| Error Code | Error Code Description | Explanation | Warning/ Error |
|------------|---|--|----------------|
| | <i>receiverIMID</i> must be assigned to the same firm | assigned to the same firm. | |
| 2151 | Firm provided record count in meta file does not equal row count in the data file | The record count in the data file as calculated by CAT does not match the record count provided in the metadata file. | Error |
| 2153 | Data File is not Readable | Data file format is not readable as it contains an invalid compression format. | Error |
| 2154 | Invalid <i>quoteWantedInd</i> | When required, <i>quoteWantedInd</i> must be populated in one of the allowable values. | Error |
| 2156 | Invalid <i>reservedForFutureUse</i> | <i>reservedForFutureUse</i> must not be populated. | Error |
| 2157 | Invalid <i>quantity</i> in <i>buyDetails</i> | If populated, <i>quantity</i> in <i>buyDetails</i> must be in the correct format. | Error |
| 2158 | Invalid <i>originatingIMID</i> in <i>buyDetails</i> | If populated, <i>originatingIMID</i> in <i>buyDetails</i> must be in the correct format. | Error |
| 2159 | Invalid <i>quantity</i> in <i>sellDetails</i> | If populated, <i>quantity</i> in <i>sellDetails</i> must be in the correct format. | Error |
| 2160 | Invalid <i>originatingIMID</i> in <i>sellDetails</i> | If populated, <i>originatingIMID</i> in <i>sellDetails</i> must be in the correct format. | Error |
| 2161 | Invalid <i>quantity</i> in <i>clientDetails</i> | If populated, <i>quantity</i> in <i>clientDetails</i> must be in the correct format. | Error |
| 2162 | Invalid <i>originatingIMID</i> in <i>clientDetails</i> | If populated, <i>originatingIMID</i> in <i>clientDetails</i> must be in the correct format. | Error |
| 2163 | Invalid <i>quantity</i> in <i>firmDetails</i> | If populated, <i>quantity</i> in <i>firmDetails</i> must be in the correct format. | Error |
| 2164 | Invalid <i>originatingIMID</i> in <i>firmDetails</i> | If populated, <i>originatingIMID</i> in <i>firmDetails</i> must be in the correct format. | Error |
| 2165 | Missing or Invalid <i>orderID</i> in <i>aggregatedOrders</i> | When required, <i>orderID</i> in <i>aggregatedOrders</i> must be populated in the correct format. | Error |
| 2166 | Missing or Invalid <i>orderKeyDate</i> in <i>aggregatedOrders</i> | When required, <i>orderKeyDate</i> in <i>aggregatedOrders</i> must be populated in the correct format. | Error |
| 2167 | Invalid <i>quantity</i> in <i>aggregatedOrders</i> | If populated, <i>quantity</i> in <i>aggregatedOrders</i> must be in the correct format. | Error |
| 2168 | Invalid <i>originatingIMID</i> in <i>aggregatedOrders</i> | If populated, <i>originatingIMID</i> in <i>aggregatedOrders</i> must be in correct format. | Error |
| 2169 | Invalid combination of <i>reportingExceptionCode</i> and <i>tapeTradeID</i> | The combination of <i>reportingExceptionCode</i> and <i>tapeTradeID</i> must be valid. Refer to Section 4.12 for more details. | Error |
| 2170 | Missing or Invalid <i>allocationKeyDate</i> | <i>allocationKeyDate</i> must be populated in the correct format. | Error |
| 2171 | Missing or Invalid <i>allocationID</i> | <i>allocationID</i> must be populated in the correct format. | Error |
| 2172 | Missing or Invalid <i>priorAllocationKeyDate</i> | When required, <i>priorAllocationKeyDate</i> must be populated in the correct format. | Error |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|--|--|---------------|
| 2173 | Missing or Invalid <i>priorAllocationID</i> | When required, <i>priorAllocationID</i> must be populated and must be in the correct format. | Error |
| 2174 | Missing or Invalid <i>custType</i> | When required, <i>custType</i> must be populated with an allowable value. | Error |
| 2175 | Missing or Invalid <i>institutionFlag</i> | <i>institutionFlag</i> must be populated with one of the allowable values | Error |
| 2176 | Missing or Invalid <i>tradeDate</i> | <i>tradeDate</i> must be populated in the correct format. | Error |
| 2177 | Missing or Invalid <i>settlementDate</i> | <i>settlementDate</i> must be populated in the correct format. | Error |
| 2178 | Missing or Invalid <i>allocationType</i> | <i>allocationType</i> must be populated with one of the allowable values | Error |
| 2179 | Missing or Invalid <i>DVPCustodianID</i> | When required, <i>DVPCustodianID</i> must be populated in the correct format. | Error |
| 2180 | Invalid <i>correspondentCRD</i> | If populated, <i>correspondentCRD</i> must be populated in the correct format. | Error |
| 2181 | Invalid <i>newOrderFDID</i> | If populated, <i>newOrderFDID</i> must be populated in the correct format. | Error |
| 2182 | Invalid <i>allocationInstructionTime</i> | If populated, <i>allocationInstructionTime</i> must be in the correct format. | Error |
| 2183 | Missing or Invalid <i>quotingIDQS</i> | When required, <i>quotingIDQS</i> must be populated in the correct format. | Error |
| 2184 | Invalid combination of <i>clearingFirm</i> and <i>reportingExceptionCode</i> | Combination of <i>clearingFirm</i> and <i>reportingExceptionCode</i> must be valid. | Error |
| 2185 | Invalid combination of counterparty and <i>reportingExceptionCode</i> | Combination of <i>counterparty</i> and <i>reportingExceptionCode</i> must be valid. | Error |
| 2186 | Missing or Invalid <i>solicitationFlag</i> | <i>solicitationFlag</i> must be populated with one of the allowable values | Error |
| 2187 | Invalid <i>RFQID</i> | If populated, <i>RFQID</i> must be in the correct format. | Error |
| 2188 | Missing or Invalid <i>unpricedInd</i> | <i>unpricedInd</i> must be populated with one of the allowable values | Error |
| 2189 | Invalid combination of <i>senderIMID</i> and <i>destination</i> or <i>receiverIMID</i> | On Order Route or New Quote events, <i>senderIMID</i> must not equal <i>destination</i> . On Order Accepted, Order Modified, and Quote Received events, <i>senderIMID</i> must not equal <i>receiverIMID</i> . | Error |
| 2190 | Invalid combination of <i>orderID</i> and <i>parentOrderID</i> or <i>priorOrderID</i> | When populated, the combination of <i>parentOrderID</i> and <i>parentOrderKeyDate</i> or <i>priorOrderID</i> and <i>priorOrderKeyDate</i> must not equal the combination of <i>orderID</i> and <i>orderKeyDate</i> . | Error |
| 2191 | Invalid combination of <i>orderID</i> and <i>orderID</i> in <i>aggregatedOrders</i> | When populated, the combination of <i>orderID</i> and <i>orderKeyDate</i> must not equal any combination of <i>orderID</i> and <i>orderKeyDate</i> within the <i>aggregatedOrders</i> field. | Error |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|-------------------------|---|---------------|
| 2801 | | <i>Reserved</i> | |
| 2802 | | <i>Reserved</i> | |
| 2803 | | <i>Reserved</i> | |
| 2999 | Exceeds Max Error Limit | The record contains more than 8 errors. | Error |

E.3 Linkage Discovery Errors

Linkage Discovery errors are generated by performing event comparisons that result in the identification of duplicates, out of sequence events and unlinked events. To identify duplicate Linkage Keys, the CAT Processor will ensure the *CAT Linkage Keys*, as defined in [Section 2.6.1](#), are not repeated.

Unlinked error codes are assigned based on a processing order when determining the reason for an unlinked event. The process begins with the check associated with the codes having the lowest sequence value. When the “Multiple Fields did not Match” reason is assigned, it is because a determination could not be made. In such cases, it is possible that the unlink reason is because the other party’s event was not reported or had a processing error which prevented the event from participating in Linkage Discovery.

In cases when linkage did not occur between venues, separate error codes will be assigned to the CAT Reporter whose record did not link and the CAT Reporter that was named. Error Code Descriptions that begin with “Named” indicate when the CAT Reporter was named in a record submitted by another CAT Reporter (Industry Member, Exchange or TRF/ADF/ORF) that is unlinked.

The below table contains error messages that are associated with Linkage Discovery Errors.

Table 131: Intra-Linkage Errors

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|--|---|---------------|
| 3002 | Duplicate <i>firmROEID</i> on same day | Duplicate <i>firmROEID</i> received by CAT; must be unique for the Event Date and CAT Reporter IMID. | Error |
| 3003 | Duplicate <i>firmROEID</i> on a prior processing day | One or more events were reported with the same <i>firmROEID</i> as an event reported on a previous day. All events received on the current CAT Processing Date associated with the duplicate <i>firmROEID</i> will be rejected. The events received on a previous day associated with the duplicate <i>firmROEID</i> will not be rejected. This is only applicable to events with an <i>actionType</i> of ‘NEW’. | Error |
| 3004 | Duplicate Order Key | More than one primary order event was reported with the same Order Key on the current CAT Processing | Error |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|---|---|---------------|
| | reported on same day | Date. All events associated with the duplicate Order Key will be rejected. | |
| 3007 | Duplicate Order Key reported on a prior processing day | One or more primary order events were reported that have the same Order Key as an order reported on a previous day. All events received on the current CAT Processing Date associated with the duplicate Order Key will be rejected. The events received on a previous day associated with the duplicate Order Key will not be rejected. | Error |
| 3010 | Duplicate Trade Key reported on same day | More than one Trade event was reported with the same Trade Key on the current CAT Processing Date. All events associated with the duplicate Trade Key will be rejected. | Error |
| 3011 | Duplicate Trade Key reported on prior processing day | One or more Trade events were reported with the same Trade Key as an event reported on a previous day. All events received on the current CAT Processing Date with a duplicate Trade Key will be rejected. The events received on a previous day associated with the duplicate Trade Key will not be rejected. | Error |
| 3012 | Duplicate Fulfillment Key reported on same day | More than one Fulfillment events were reported with the same Fulfillment Key on the current CAT Processing Date. All events with a duplicate Fulfillment Key will be rejected. | Error |
| 3015 | Duplicate Fulfillment Key reported on prior processing day | One or more Fulfillment events was reported with the same Fulfillment Key as an event reported on a previous day. All events received on the current CAT Processing Date associated with the duplicate Fulfillment Key will be rejected. The events received on a previous day with a duplicate Fulfillment Key will not be rejected. | Error |
| 3016 | Duplicate Quote Key reported on same day | More than one New Quote event were reported with the same Quote Key on the current CAT Processing Date. All events associated with the duplicate Quote Key will be rejected. | Error |
| 3017 | Duplicate Quote Key reported on prior processing day | One or more New Quote events were reported that have the same Quote Key as an event reported on a previous day. All events received on the current CAT Processing Date associated with the duplicate Quote Key will be rejected. The events received on a previous day associated with the duplicate Quote Key will not be rejected. | Error |
| 3018 | Duplicate Manual Order Key reported on same day | More than one primary order event was reported with the same Manual Order Key on the current CAT Processing Date. All events associated with the duplicate Manual Order Key will be rejected. | Error |
| 3019 | Duplicate Manual Order Key reported on prior processing day | One or more primary order events were reported that have the same Manual Order Key as an order reported on a previous day. All events received on the current CAT Processing Date associated with the duplicate Manual Order Key will be rejected. The events received on a previous day associated with the duplicate Manual Order Key will not be rejected. | Error |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|---|--|---------------|
| 3501 | Secondary Event – Order Key, Trade Key, Quote Key or Fulfillment Key not found | The Secondary Event (as defined in Appendix F) references an Order Key, Trade Key, Quote Key or Fulfillment Key that does not exist in CAT because it was not reported or was rejected. | Error |
| 3502 | Trade Event –Order not found | The Trade Event side details reference an Order Key that does not exist in CAT because it was not reported or was rejected. | Error |
| 3503 | Fulfillment Event –Order not found | The Fulfillment Event side details reference an Order Key that does not exist in CAT because it was not reported or was rejected. | Error |
| 3504 | Aggregated Order – Client order not found | Aggregated order references an Order Key that does not exist in CAT because it was not reported or was rejected. | Error |
| 3505 | Electronic Duplicate Order – Manual order not found | Electronic duplicate order references a Manual Order Key that does not exist in CAT because it was not reported or was rejected. | Error |
| 3601 | Intrafirm Out of Sequence Event | <i>eventTimestamp</i> of a Secondary Event (as defined in Appendix F) is prior to the <i>eventTimestamp</i> of the related Primary Event (as defined in Appendix F). When comparing <i>eventTimestamp</i> , the Clock Drift allowance as specified in Appendix B must be considered. | Error |
| 3602 | Mismatched <i>eventTimestamp</i> on the Order/Modification/Trade supplement event | <i>eventTimestamp</i> on the Order/Modification/Trade supplement event did not match the <i>eventTimestamp</i> on the corresponding Order/Modification/Trade event. Timestamp compared up to milliseconds. | Error |

Table 132: Trade Linkage Error Codes (Reported to CAT)

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|---|---|---------------|
| 4003 | Matching <i>tapeTradeID</i> cannot be found | The <i>tapeTradeID</i> reported on a Trade event did not match the unique identifier (e.g., Branch Sequence Number, Compliance ID) provided on the TRF/ADF/ORF Trade Report. | Error |
| 4005 | Event Date cannot be found | The Event Date portion of the <i>eventTimestamp</i> reported on the Trade event did not match the Event Date portion of the Execution Time on the TRF/ADF/ORF trade report. | Error |
| 4007 | <i>symbol</i> cannot be found | The <i>symbol</i> reported on the Trade event did not match the symbol on the TRF/ADF/ORF trade report. | Error |
| 4009 | Multiple fields did not match | A TRF/ADF/ORF Trade Report with a matching unique identifier (i.e. Branch Sequence Number) was found; however, the <i>symbol</i> , <i>CATReporterIMID</i> or a combination of fields reported on the Trade event did not match the corresponding symbol or reporting/contra firm on the TRF/ADF/ORF Trade Report. | Error |
| 4011 | Duplicate TRF Linkage | Unlinked due to duplicated TRF Linkage Key. | Error |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|------------------------|-------------|---------------|
| | Key | | |

Table 133: Trade Linkage Error Codes (Reported to TRF/ADF/ORF)

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|---|---|---------------|
| 5004 | Named - Matching <i>tapeTradeID</i> cannot be found | Named on a TRF/ADF/ORF Trade Report, but the <i>tapeTradeID</i> on the Trade event did not match the unique identifier (e.g., Branch Sequence Number, Compliance ID) on the corresponding TRF/ADF/ORF Trade Report. | Error |
| 5006 | Named - Event Date cannot be found | Named on a TRF/ADF/ORF Trade Report, but the Event Date portion of the <i>eventTimestamp</i> reported on the Trade event did not match the Event Date portion of the Execution Time on the corresponding Trade event. | Error |
| 5008 | Named - <i>symbol</i> cannot be found | Named on a TRF/ADF/ORF Trade Report, but the <i>symbol</i> reported on the Trade event did not match the symbol on the TRF/ADF/ORF Trade Report. | Error |
| 5010 | Named - Multiple fields did not match | Named on a TRF/ADF/ORF Trade Report and a matching <i>tapeTradeID</i> on the CAT Trade Event was found; however, the <i>symbol</i> , <i>CATReporterIMID</i> or a combination of fields reported on the Trade event did not match the corresponding symbol or reporting/contra firm on the TRF/ADF/ORF Trade Report. | Error |

Table 134: Exchange Linkage Error Codes (Reported to CAT)

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|---|--|---------------|
| 6003 | Matching <i>routedOrderID</i> cannot be found | The <i>routedOrderID</i> reported on the Order Route event does not match to a corresponding <i>routedOrderID</i> on the exchange order. | Error |
| 6005 | <i>senderIMID</i> did not match | A matching <i>routedOrderID</i> was identified on the exchange order; however, the <i>senderIMID</i> on the Order Route event did not match the corresponding <i>routingParty</i> on the exchange order. | Error |
| 6007 | <i>symbol</i> did not match | A matching <i>routedOrderID</i> was identified in the exchange order; however, the <i>symbol</i> on the Order Route event did not match the corresponding symbol on the exchange order. | Error |
| 6009 | <i>session</i> did not match | A matching <i>routedOrderID</i> was identified on the exchange order; however, the <i>session</i> on the Order Route event did not match the <i>session</i> on the exchange order. | Error |
| 6011 | Multiple fields did not | A matching <i>routedOrderID</i> was identified on the | Error |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|---|---|---------------|
| | match | exchange order; however, the <i>symbol</i> , <i>senderIMID</i> , or a combination of fields reported on the Order Route event did not match the corresponding <i>symbol</i> , <i>routingParty</i> or a combination of fields on the exchange order. | |
| 6013 | Duplicate Route Linkage Key on Route to Exchange | Unlinked due to duplicated Route Linkage Key on a Route to an Exchange. | Error |
| 6015 | Duplicate Route Linkage Key on Order Accepted or Modification from Exchange | Unlinked due to duplicated Route Linkage Key on an Order Accepted or Modification received from an Exchange. | Error |

Table 135: Exchange Linkage Error Codes (Reported by Exchange)

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|---|---|---------------|
| 7004 | Named - Matching <i>routedOrderID</i> cannot be found | Named on an exchange order, but the <i>routedOrderID</i> reported on the Order Route event does not match to a corresponding <i>routedOrderID</i> on the exchange order. | Error |
| 7006 | Named - <i>senderIMID</i> did not match | Named on an exchange order with a matching <i>routedOrderID</i> identified on the Order Route event; however, the <i>senderIMID</i> on the Order Route event did not match the <i>routingParty</i> reported on the corresponding exchange order. | Error |
| 7008 | Named - <i>symbol</i> did not match | Named on an exchange order with a matching <i>routedOrderID</i> identified on the Order Route event; however, the <i>symbol</i> on the Order Route event did not match the <i>symbol</i> on the corresponding exchange order. | Error |
| 7010 | Named - <i>session</i> did not match | Named on an exchange order with a matching <i>routedOrderID</i> identified on the Order Route event; however, the <i>session</i> on the Order Route event did not match the <i>session</i> on the corresponding exchange order. | Error |
| 7012 | Named - Multiple fields did not match | Named on an Order Route event with a matching <i>routedOrderID</i> identified in the Order Route event; however, the <i>symbol</i> , <i>senderIMID</i> or a combination of fields reported on the Order Route event did not match the <i>symbol</i> or <i>routingParty</i> on the corresponding exchange order. | Error |

Table 136: Inter-firm Linkage Error Codes (Sender Reported to CAT)

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|-------------------------------|--|---------------|
| 8003 | Matching <i>routedOrderID</i> | The <i>routedOrderID</i> reported on the Order Route event | Error |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|---|--|---------------|
| | cannot be found | does not match to a corresponding <i>routedOrderID</i> on the Order Accepted event. | |
| 8004 | Named - Matching <i>routedOrderID</i> cannot be found | Named on an Order Route event, but the <i>routedOrderID</i> reported on the Order Accepted event does not match to a corresponding <i>routedOrderID</i> on the Order Route event. | Error |
| 8005 | <i>senderIMID</i> did not match | A matching <i>routedOrderID</i> was identified in the Order Accepted event; however, the <i>senderIMID</i> on the Order Route event did not match the <i>senderIMID</i> on the Order Accepted event. | Error |
| 8006 | Named - <i>senderIMID</i> did not match | Named on an Order Route event, but the <i>senderIMID</i> on the Order Accepted event does not match the <i>senderIMID</i> reported on the corresponding Order Route event. | Error |
| 8007 | <i>destination</i> did not match | A matching <i>routedOrderID</i> was identified in the Order Accepted event; however, the <i>destination</i> on the Order Route event did not match the <i>receiverIMID</i> on the Order Accepted event. | Error |
| 8008 | Named – <i>destination</i> did not match | Named on an Order Route event, but the <i>receiverIMID</i> on the Order Accepted event does not match the <i>destination</i> reported on the corresponding Order Route event. | Error |
| 8009 | <i>symbol</i> did not match | A matching <i>routedOrderID</i> was identified in the Order Accepted event; however, the <i>symbol</i> on the Order Route event did not match the <i>symbol</i> on the Order Accepted event. | Error |
| 8010 | Named - <i>symbol</i> did not match | Named on an Order Route event with a matching <i>routedOrderID</i> identified in the Order Accepted Event; however, the <i>symbol</i> on the Order Accepted event did not match the <i>symbol</i> on the Order Route event. | Error |
| 8011 | Multiple fields did not match | A matching <i>routedOrderID</i> was identified in the Order Accepted event; however, the <i>symbol</i> , <i>senderIMID</i> , <i>destination</i> , or a combination of fields on the Order Route event did not match the <i>symbol</i> , <i>senderIMID</i> , or <i>receiverIMID</i> on the Order Accepted Event. | Error |
| 8012 | Named - Multiple fields did not match | Named on an Order Route event with a matching <i>routedOrderID</i> identified in the Order Accepted Event; however, the <i>symbol</i> , <i>senderIMID</i> , <i>receiverIMID</i> or a combination of fields on the Order Accepted event did not match the corresponding <i>symbol</i> , <i>senderIMID</i> , or <i>destination</i> on the Order Route event. | Error |
| 8013 | Duplicate Route Linkage Key on Route to Industry Member | Unlinked due to duplicated Route Linkage Key on a Route to another Industry Member. | Error |

Table 137: Interfirm Linkage Error Codes (Receiver Reported to CAT)

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|--|---|---------------|
| 9003 | Matching <i>routedOrderID</i> cannot be found | The <i>routedOrderID</i> reported on the Order Accepted event does not match to a corresponding <i>routedOrderID</i> on the Order Route event. | Error |
| 9004 | Named - Matching <i>routedOrderID</i> cannot be found | Named on an Order Accepted event, but the <i>routedOrderID</i> reported on the Order Route event does not match to a corresponding <i>routedOrderID</i> on the Order Accepted event. | Error |
| 9005 | <i>senderIMID</i> did not match | A matching <i>routedOrderID</i> was identified in the Order Route event; however, the <i>senderIMID</i> on the Order Accepted event did not match the <i>senderIMID</i> on the Order Route event. | Error |
| 9006 | Named - <i>senderIMID</i> did not match | Named on an Order Accepted event but the <i>senderIMID</i> reported on the Order Route does not match to a corresponding <i>senderIMID</i> on the Order Accepted event. | Error |
| 9007 | <i>receiverIMID</i> did not match | A matching <i>routedOrderID</i> was identified in the Order Route event; however, the <i>receiverIMID</i> on the Order Accepted event did not match the <i>destination</i> on the Order Route event. | Error |
| 9008 | Named - <i>receiverIMID</i> did not match | Named on an Order Accepted event but the <i>destination</i> reported on the Order Route does not match to a corresponding <i>receiverIMID</i> on the Order Accepted event. | Error |
| 9009 | <i>symbol</i> did not match | A matching <i>routedOrderID</i> was identified in the Order Route event; however, the <i>symbol</i> on the Order Accepted event did not match the <i>symbol</i> on the Order Route event. | Error |
| 9010 | Named - <i>symbol</i> did not match | Named on an Order Accepted event with a matching <i>routedOrderID</i> identified in the Order Route event; however, the <i>symbol</i> on the Order Route event did not match the <i>symbol</i> on the Order Accepted Event. | Error |
| 9011 | Multiple fields did not match | A matching <i>routedOrderID</i> was identified in the Order Route event; however, the <i>symbol</i> , <i>senderIMID</i> , <i>receiverIMID</i> , <i>receiverIMID</i> , or a combination of fields on the Order Accepted event did not match the corresponding <i>symbol</i> , <i>senderIMID</i> , or <i>destination</i> on the Order Route event. | Error |
| 9012 | Named - Multiple fields did not match | Named on an Order Accepted Event with a matching <i>routedOrderID</i> identified in the Order Route event; however, the <i>symbol</i> , <i>senderIMID</i> , <i>destination</i> or a combination of fields on the Order Route event did not match the corresponding <i>symbol</i> , <i>senderIMID</i> , <i>receiverIMID</i> or a combination of fields on an Order Accepted event. | Error |
| 9013 | Duplicate Route Linkage Key on Order Accepted or Modification received | Unlinked due to duplicated Route Linkage Key on an Order Accepted or Modification received from another Industry Member. | Error |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|------------------------|-------------|---------------|
| | from Industry Member | | |

E.4 Warning Error Codes

The tables below contain Warnings that will be included in the Error Feedback Files. Warnings are not required to be repaired. Codes are separated by Linkage type.

Table 138: Intra-Linkage Warnings

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|---|---|---------------|
| 399 | Duplicate Event | The event has already been received by CAT. The first instance of the event will be retained; all subsequent submissions will be rejected. This rejection is not repairable. | Warning |
| 398 | Order Key, Trade Key, Quote Key or Fulfillment Key prior to CAT go-live | The Secondary Event (as defined in Appendix F) references an Order Key, Trade Key, Quote Key or Fulfillment Key that does not exist in CAT because it references a date prior to CAT go-live; or The <i>aggregatedOrders</i> field references an Order Key that does not exist in CAT because it references a date prior to CAT go-live. | Warning |
| 397 | Late Reported event | Event is unmatched because it was reported to CAT beyond the processing window. This warning is not repairable. | Warning |

Table 139: Trade Linkage Warnings

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|------------------------------------|---|---------------|
| 499 | Late Reported Trade event | A Trade event unmatched as it was reported to CAT beyond the processing window. This warning is not repairable. | Warning |
| 498 | Named - Late Reported Trade Report | Named on a TRF/ADF/ORF Trade Report that was reported beyond the processing window. This warning is not repairable. | Warning |

Table 140: Exchange Linkage Warnings

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|------------------------|--|---------------|
| 799 | Late reported Order | An Order Route event unmatched as it was reported to CAT beyond the processing window. This warning is | Warning |

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|--------------------------------------|--|---------------|
| | Route event | not repairable. | |
| 798 | Named - Late reported exchange order | Named on an exchange order that was reported beyond the processing window. This warning is not repairable. | Warning |

Table 141: Inter-firm Linkage Warnings

| Error Code | Error Code Description | Explanation | Warning/Error |
|------------|------------------------|--|---------------|
| 897 | Early reported event | Event is unmatched because it was reported to CAT prior to the due date. This warning is not repairable. | Warning |

Appendix F: Glossary

| | |
|---------------------------------------|---|
| CAT Processing Date | Date representing the set of events reported for a <i>CAT Trading Day</i> . Events reported late to CAT will be assigned the CAT Processing Date reflective of when they were reported. For example, an event, that occurred at 2pm on T which is reported to CAT after T+1 8am and prior to T+2 8AM will be assigned CAT Processing Date of T+1. |
| CAT Reporter IMID | The CAT Reporter IMID is the SRO assigned identifier that an Industry Member uses to report CAT events. A CAT Reporter may use any SRO assigned identifier that is valid on the CAT Trading Day for which CAT events are submitted. |
| CAT Submitter ID | The CAT Submitter ID is the identifier of the CAT Reporting Agent, the entity authorized to submit the files to CAT on behalf of the Industry Member. CAT Reporters may authorize third-parties ("CAT Reporting Agents") to submit data to CAT on their behalf. Each CAT Reporting Agent and CAT Reporter will be assigned a unique CAT Submitter ID. If a CAT Reporter is performing its own submissions, these files will be submitted using its own CAT Submitter ID. If the Submitter is an Industry Member, the CAT Submitter's CRD number. If the Submitter is not an Industry Member and does not have a CRD number (i.e. Service Bureaus), the CAT Submitter ID is the Submitter's Organization ID. |
| CAT Trading Day | CAT Trading Day for Industry Members is defined as beginning immediately after 4:15:00PM and no fractions of a second Eastern Time on one trade date and ending at exactly 4:15:00PM and no fractions of a second Eastern Time on the next trading date. Weekends or any day that all equities or options national securities exchanges are closed are not considered a CAT Trading Day. Trading Days that close early end 15 minutes after the Market Close. |
| Client Order | For the purpose of this document, Client Order is defined as an order received from a CAT Reporter. |
| Customer Order | For the purpose of this document, Customer Order is defined as an order received from a non-CAT Reporter, including non-US broker-dealers. |
| Display ATS | An ATS that displays subscriber orders outside of the ATS. |
| Eligible Security | "Eligible Security" includes: (i) all NMS Securities, meaning "any security or class of securities for which transaction reports are collected, processed, and made available pursuant to an effective transaction reporting plan, or an effective national market system plan for reporting transaction in Listed Options"; and (ii) all OTC Equity Securities, meaning "any equity security, other than an NMS Security, subject to prompt last sale reporting rules of a registered national securities association and reported to one of such association's equity trade reporting facilities". |
| Electronic Capture Time | For manual orders, the timestamp or when the Manual CAT Event was captured electronically in the relevant order handling and execution system of the CAT Reporter. |
| Electronic Paired Option Order | Electronic option orders that contain both the buy and sell side that is routed to another Industry Member or exchange for crossing and/or price improvement as a single transaction on an exchange. |
| FDID | FDID is defined in Section 1.1 of the CAT NMS Plan as "a unique identifier for each trading account designated by Industry Members for purposes of providing data to the Central Repository." See CAT FAQ M2 for more information on the prohibition on use of actual account numbers. Refer to the CAT Industry Presentation on FDID for additional information. |

| | |
|-----------------------------------|--|
| IMID | An Industry Member Identifier, IMID, is any identifier assigned by an SRO to one of its members and is used as part of the Linkage Key in orders routed between Industry Members. Examples include FINRA MPIDs, Nasdaq MPIDs, NYSE Mnemonics, Cboe EFIDs, and CHX Acronyms. |
| Manual Event | A non-electronic communication of order/trade/quote/fulfillment-related information for which CAT Reporters must record and report to CAT. |
| Material Terms of an Order | Includes: the NMS Security or OTC Equity Security symbol; security type; price (if applicable); size (displayed and non-displayed); side (buy/sell); order type; if a sell order, whether the order is long, short, short exempt; open/close indicator (except on transactions in equities); time in force (if applicable); if the order is for a Listed Option, option type (put/call), option symbol or root symbol, underlying symbol, strike price, expiration date, and open/close (except on market maker quotations); and any special handling instructions. |
| Order | The term order shall include: (i) Any order received by a member of a national securities exchange or national securities association from any person; (ii) Any order originated by a member of a national securities exchange or national securities association; or (iii) Any bid or offer. |
| Primary Event | <p>An event that is received or originated by an Industry Member. Primary events include Orders, Trades, Quotes and Fulfillments each with a respective Event Key including: Order Key, Trade Key, Quote Key, Quote Route Key and Fulfillment Key.</p> <p>Primary events require the assignment of a unique Key which does not duplicate the Key for other Primary Events with the same Key type. For example, an Order Key will not be compared to a Trade Key for uniqueness. If an Event Key is duplicated, all events having the same Event Key will be rejected.</p> <p>Primary events include: MENO, MEOA, MENQ, MEQR, MEOT, MEOF, MONO, MOOA, MOOF, MEPA, MOPA, MLNO, MLOA, MLIR, MLCO, and MLOM.</p> |
| Reportable Event | Includes, but is not limited to, the original receipt or origination, modification, cancellation, routing, execution (in whole or in part) and allocation of an order, and receipt of a routed order |
| Representative Order | Refer to CAT FAQ F1 . |
| ROE | Reportable Order Event |
| Secondary Event | <p>Represents an event occurring subsequent to the origination of a Primary Event.</p> <p>Secondary events require the assignment of an Event Key which provides linkage to the related Primary event that assigned the Key or to another Secondary event that assigned a new Key.</p> <p>Secondary events with event definitions that do not allow for the reassignment of an Event Key must populate the Event Key equal to the related event from which the Secondary event originated. Secondary events that are not defined to assign a new Event Key include: MENOS, MEOR, MEMR, MECR, MEORS, MEIC, MEIMR, MEICR, MECOC, MEOMR, MEOMS, MEOC, MEOCR, MEQC, MEOTS, MEOFS, MEOE, MONOS, MOOR, MOMR, MOCR, MOORS, MOIC, MOIMR, MOICR, MOCOC, MOOMR, MOOMS, MOOCR, MOOC, MOOE, MLOR, MLOC, and MLOS.</p> <p>Secondary events with event definitions that allow for the reassignment of an Event Key (Order Key, Trade Key, Quote Key, Quote Route Key and Fulfillment Key) must assign an Event Key that is unique and does not duplicate the Event Key of any other Primary event or of any Secondary event which has assigned a new Event Key. When a new Event Key is assigned, the Prior Key representing the Event Key that is being replaced must be populated. Secondary events with event definitions that allow for the reassignment of an Event Key include: MEIR, MEIM, MECO, MECOM, MEOM, MEOJ, MEFA, MEAA, MOIR, MOIM, MOCO, MOCOM, MOOM, MOOJ, MOFA, and MOAA.</p> <p>Secondary events with event definitions that allow for the reassignment of an</p> |

| | |
|--|--|
| | Event Key are not required to assign a new Event Key. In such cases, when reported, the Event Key must be equal to the related event from which the Secondary event originated. |
| Simple Electronic Option Orders | <p>Orders to buy or sell a single option that are not related to or dependent on any other transaction for pricing or timing of execution that are either received or routed electronically by an Industry Member CAT Reporter.</p> <p>Electronic receipt of an order is defined as the initial receipt of an order by an Industry Member in electronic form in standard format directly into an order handling or execution system. Electronic routing of an order is the routing of an order via electronic medium in standard format from one Industry Member's order handling or execution system to an exchange or another Industry Member.</p> |
| Smart Order Router | For the purpose of CAT reporting, a Smart Order Router is defined as an automated system that solely routes orders to another market center based on pre-defined routing criteria. |
| Trading Algorithm | FINRA Rule 1220(b)(4)(a) defines Trading Algorithmic Strategy as "an automated system that generates or routes orders (or order-related messages) but shall not include an automated system that solely routes orders received in their entirety to a market center." |
| Trade Date | <p>Trade Date for Industry Member is defined as beginning immediately after 23:59:59.999999 ET on Trade Date T - 1 and up to 23:59:59.999999 ET of the next Trade Date T.</p> <p>Weekends and holidays are not considered a Trade Date.</p> <p>An event occurring on a weekend or holiday will be assigned to the next Trade Date.</p> |

Appendix G: Data Dictionary

| Field Name | Data Type | Description |
|-------------------|-------------------|---|
| accountHolderType | Choice | <p>Represents the type of beneficial owner of the account for which an order was received or originated.</p> <p>Allowed Values:</p> <p>A Institutional Customer – An institutional account as defined in FINRA Rule 4512(c)</p> <p>E Employee Account – An employee or associated person of an Industry Member</p> <p>F Foreign - A non-broker-dealer foreign affiliate or non-reporting foreign broker-dealer</p> <p>I Individual Customer – An account that does not meet the definition of FINRA Rule 4512(c) and is also not a proprietary account.</p> <p>O Market Making – See CAT FAQ C5</p> <p>V Firm agency average price account</p> <p>P Other Proprietary</p> <p>X Error Account – Error account of the firm</p> |
| actionType | Choice | <p>Indicates whether the event is a new event, a correction, a repair or a record level deletion.</p> <p>Allowed Values:</p> <p>NEW New Record</p> <p>COR Correction of events initiated by firms.</p> <p>RPR Repair of events for which a CAT error was provided in feedback</p> <p>DEL Record level delete instruction. When deleting a record, Industry Members must not restate the event that is being deleted. Refer to Section 7 for instructions on record level deletions.</p> |
| affiliateFlag | Boolean | <p>Indicates if the order is being routed to an affiliate or received from an affiliate of the Industry Member.</p> <p>For definition of affiliate, refer to CAT FAQ C4.</p> <p>Allowed Values:</p> <p>true order is routed to or received from an affiliate</p> <p>false order is routed to or received from a non-affiliate</p> |
| aggregatedOrders | Aggregated Orders | <p>When an Industry Member generates a New Order event to represent one or more customer orders, the <i>aggregatedOrders</i> field specifies the individual customer order(s) being represented.</p> <p>For each order being represented, the <i>orderID</i> and <i>orderKeyDate</i> must be provided. Quantity is required when a portion of the order's quantity is included in the aggregation.</p> <p>In instances when the <i>aggregatedOrders</i> field causes the event to exceed the maximum length (8190 bytes) allowed, one or more corresponding New Order Supplement events</p> |

| Field Name | Data Type | Description |
|---------------------------|----------------|---|
| | | must be reported to capture the additional orders in the <i>aggregatedOrders</i> field. Refer to Appendix C for additional information on representative and combined order linkage requirements. |
| allocationID | Text (64) | The internal allocation ID assigned to the allocation event by the Industry Member. The combination of <i>CATReporterIMID</i> , <i>allocationKeyDate</i> , <i>symbol</i> and <i>allocationID</i> must be unique. |
| allocationInstructionTime | Timestamp | The date/time the time the allocation instruction was received. |
| allocationKeyDate | Timestamp | The date and time the <i>allocationID</i> was assigned. |
| allocationType | Choice | Indicates the type of allocation being made. Allowed Values for activity that is required to be reported to CAT: CUS Allocation to a custody account DVP Allocation to a DVP account Allowed Values for activity that is being optionally reported to CAT: FLP Correspondent Flip FRM An allocation to a firm owned or controlled account STO Step out OTH Other non-reportable transactions (e.g. option exercises, conversions) |
| askPrice | Price | Price being asked in a quote. |
| askQty | Whole Quantity | Quantity being asked in a quote. |
| atsDisplayInd | Choice | ATS only field. Indicates if the order is displayed outside of the ATS to subscribers only, or via publicly disseminated quotation data. Allowed Values: S Order is displayed outside of the ATS to subscribers only A Order is displayed outside of the ATS to subscribers only, aggregated by price level on a timer basis Y Order is displayed outside of the ATS via public quotation N Order is not displayed outside of the ATS |
| atsOrderType | Array | ATS only field. Unique identifier representing the specific order type(s) offered by the ATS. ATSs will provide their order types and handling instructions to CAT by submitting data dictionaries. Multiple <i>atsOrderType</i> values may be populated. |
| bidPrice | Price | Price being bid in a quote. |
| bidQty | Whole Quantity | Quantity being bid in a quote. |
| buyDetails | Trade Side | Captures the Order Key and additional information for the |

| Field Name | Data Type | Description |
|------------------|--------------------|---|
| | Details | <p>Order associated with the buy side of a Trade Event.</p> <p>This field is in the format of Trade Side Details, a compound data type that consists of a list of fields (see Section 2.5 Data Types). The <i>buyDetails</i> field is only used in Trade events and Trade Supplement events to capture the buy side details of the trade. Refer to Section 4.12.1 for a list of fields.</p> <p>This field is applicable in Trade event if there is only one <i>orderID</i> associated with this side of the trade. If there is more than one <i>orderID</i>, the <i>buyDetails</i> must be populated in separate Trade Supplement events.</p> |
| cancelQty | Real Quantity | <p>The quantity being cancelled.</p> <p>Value > 0 must be provided; Quantity must represent the quantity being cancelled, even in cases of a full cancellation.</p> |
| cancelFlag | Boolean | <p>Represents instances when a trade was cancelled because the trade was rejected by the TRF/ADF/ORF, when a trade executed in a foreign market was cancelled, or when a customer fulfillment is cancelled. In such instances, set to <i>true</i>.</p> <p>Allowed Values:</p> <p>true trade event was cancelled upon rejection by the TRF/ADF/ORF; or fulfillment was cancelled.</p> <p>false trade event was not cancelled or cancellation was reported to the TRF/ADF/ORF; or fulfillment event was not cancelled.</p> |
| cancelTimestamp | Timestamp | <p>The time at which a trade or fulfillment was cancelled. Must be populated when <i>cancelFlag</i> is <i>true</i>.</p> |
| capacity | Choice | <p>Specifies the capacity in which the Industry Member acted.</p> <p>Allowed Values:</p> <p>A Agency</p> <p>P Principal</p> <p>R Riskless Principal</p> |
| CATReporterIMID | CAT Reporter IMID | <p>The SRO assigned identifier that an Industry Member uses to report to CAT.</p> |
| correspondentCRD | Unsigned | <p>The CRD number of the related Introducing Broker or Correspondent firm, if applicable.</p> |
| clearingFirm | Unsigned | <p>The clearing number of the Industry Member's clearing firm.</p> |
| clientDetails | Trade Side Details | <p>Specifies the Order Key and additional information for a Client Order for which a fulfillment event is associated.</p> <p>This field is in the format of Trade Side Details, a multi-dimensional array that consists of a list of fields (see Section 2.5 Data Types). The <i>clientDetails</i> field is only used in Equity and Option Order Fulfillment and Fulfillment Amendment Events to capture the customer or client side details of the Fulfillment. Refer to Section 4.13.1 for a list of fields.</p> |
| counterparty | Industry Member ID | <p>The counterparty to the trade.</p> |

| Field Name | Data Type | Description |
|-----------------|--------------------------------|--|
| custDsplntrFlag | Boolean | <p>Indicates if a customer has instructed that a limit order must not be displayed or that a block size order must be displayed.</p> <p>Allowed Values:</p> <p>true Customer has instructed that a limit order should not be displayed or that a block size order be displayed.</p> <p>false No instruction has been received from the customer that a limit order should not be displayed or that a block size order should be displayed.</p> |
| custType | Choice | <p>Customer Type. Indicates if the account holder is a natural person or legal entity.</p> <p>Allowed Values:</p> <p>NP account holder is a natural person (i.e. Tax ID is a Social Security Number)</p> <p>LE account holder is a legal entity (i.e. Tax ID is a TIN)</p> |
| deptType | Choice | <p>Represents the internal department, unit or desk originating or accepting the order.</p> <p>Allowed Values:</p> <p>A Agency - a desk or department where orders may be routed to other trading centers, either by a trading system or with the assistance of traders. This would include smart routers and algorithmic trading.</p> <p>ATS A trading system that meets the definition of "Alternative Trading System" under Regulation ATS.</p> <p>DMA Direct Market Access – For CAT reporting purposes, represents when an Industry Member permits a customer to use a market participant identifier assigned to the Industry Member to route orders directly to market centers.</p> <p>SA Sponsored Access - For CAT reporting purposes, represents when an Industry Member permits another broker-dealer to use a market participant identifier assigned to the Industry Member to route orders directly to market centers.</p> <p>T Trading - A desk or department where orders are executed. This may be interpreted as either a trading system or a desk or department where orders are executed with the assistance of traders.</p> <p>O Other – A department that does not execute orders or route orders to other trading centers. The value of 'O' must only be used on events that are followed by Internal Route Accepted events.</p> |
| destination | Industry Member ID/Exchange ID | <p>The SRO assigned identifier of the Industry Member or Exchange to which an order was routed.</p> <p>When <i>destinationType</i> is N, this field is not required to be populated.</p> <p>When <i>destinationType</i> is F, populate with the IMID of an</p> |

| Field Name | Data Type | Description |
|-----------------|----------------|---|
| | | <p>Industry Member.</p> <p>When <i>destinationType</i> is E, Allowed Values include:</p> <p>BOX BOX Options Exchange CBOE Cboe Exchange C2 Cboe C2 Options BYX Cboe BYX Exchange BZX Cboe BZX Equities BZXOP Cboe BZX Options EDGA Cboe EDGA Exchange EDGX Cboe EDGX Equities EDGXOP Cboe EDGX Options IEX Investor's Exchange LTSE Long Term Stock Exchange MEMX Members Exchange MIAMI Miami International Securities Exchange PEARL MIAX PEARL PEARLEQ MIAX PEARL Equities EMLD MIAX Emerald BX Nasdaq BX Equities NOBO Nasdaq BX Options PSX Nasdaq PHLX Equities PHLX Nasdaq PHLX Options NSDQ Nasdaq Stock NOM Nasdaq Options ISE Nasdaq ISE GEMX Nasdaq GEMX MRX Nasdaq MRX AMER NYSE American Equities AMEROP NYSE American Options ARCA NYSE ARCA Equities ARCAOP NYSE ARCA Options NYSE The New York Stock Exchange CHX NYSE CHX NSX NYSE National</p> |
| destinationType | Choice | <p>Indicates whether the destination of the route is an Industry Member, an exchange or a foreign broker-dealer.</p> <p>Allowed Values:</p> <p>F Industry Members E Exchange N Foreign – Not applicable to options events</p> |
| displayPrice | Price | <p>ATS only field. The current price displayed by the ATS. Required when the ATS displays the order outside of the ATS.</p> |
| displayQty | Whole Quantity | <p>ATS only field. The current quantity displayed by the ATS. Required when the ATS displays the order outside of the</p> |

| Field Name | Data Type | Description |
|---------------------|-----------|---|
| | | ATS. |
| dupROIDCond | Boolean | Indicates when a modification to an order previously routed to a national securities exchange requires the use of the original <i>routedOrderID</i> . Allowed Values: true Event contains a duplicated <i>routedOrderID</i> false Event does not contain a duplicated <i>routedOrderID</i> |
| DVPCustodianID | Text (40) | Applicable to DVP transactions. If the custodian is a US broker-dealer, this field must represent the clearing number of the custodian. If the custodian is a US bank and is not a registered broker-dealer, this field must represent the DTC number of the bank. If the custodian is a foreign entity, must be populated with a value of 'FOREIGN'. |
| electronicDupFlag | Boolean | Indicates whether the event is a duplicative electronic message of a manual event. Must be present if true. Allowed Values: true event is a duplicative electronic message false event is not a duplicative electronic message |
| electronicTimestamp | Timestamp | For manually executed events, the time at which the event was systematized. Must be reported at the most granular level an Industry Member's order handling or execution systems use to capture data for the reported event, with at least millisecond granularity. |
| errorROEID | Unsigned | The unique identifier assigned by CAT to an error record. Must be populated when the <i>actionType</i> is RPR. |
| eventTimestamp | Timestamp | The date and time the event occurred. If electronic, required to be reported at the most granular level an Industry Member's order handling or execution systems use to capture data for the reported event, with at least millisecond granularity. If manual, required to be reported in increments of at least one second. If the order is immediately systematized, required to be reported with at least millisecond granularity. |
| exchOriginCode | Text (4) | The code signifying the origin of the account exactly as sent to an Options exchange. Required for orders routed to an Options exchange. In instances where the market maker sends a market maker order through an options exchange protocol that does not require an exchange origin code, Industry Members must populate the <i>exchOriginCode</i> with MM. Refer to CAT FAQ E28 for additional information. |
| fillKeyDate | Timestamp | The date and time the <i>fulfillmentID</i> was assigned. Used to support uniqueness of a Fulfillment Key. If time is not needed to guarantee a unique Fulfillment Key, the time portion may be populated with zeros. |
| firmDesignatedID | Text (40) | See FDID guidance and FDID FAQs . |

| Field Name | Data Type | Description |
|----------------------|--------------------------|---|
| | | A value of 'PENDING' must be populated in instances when an Industry Member receives an order for a new account and the new account number, on which the FDID is based, is not yet available. Once the FDID becomes available, the Industry Member must report the actual FDID in the <i>firmDesignatedID</i> field in a New Order Supplement event. |
| firmDetails | Fulfillment Side Details | <p>Specifies the Order Key and additional information for a Firm Originated Order for which a fulfillment event is associated.</p> <p>Refer to Appendix C for representative order linkage requirements.</p> <p>It is in the format of Fulfillment Side Details, a compound data type that consists of a list of fields (see Section 2.5 Data Types). <i>firmDetails</i> is only used in Equity and Option Order Fulfillment, Order Fulfillment Supplement and Fulfillment Amendment Events to capture the firm side details of the Fulfillment. See Section 4.13.1 for list of fields.</p> <p>This field is applicable on an Order Fulfillment event if there is only one <i>orderID</i> associated with the firm side of the fulfillment. If there is more than one <i>orderID</i> associated with the firm side, the <i>firmDetails</i> must be populated in separate Order Fulfillment Supplement events.</p> |
| firmROEID | Text (64) | <p>An identifier of the record assigned by the CAT Reporter. The <i>firmROEID</i> is composed based on the following format: <eventDate>_<firm ROE Identifier></p> <p>The <i>firmROEID</i> must be unique for the Event Date and CAT Reporter IMID.</p> |
| fulfillmentID | Text (64) | The identifier for the order fulfillment. The combination of <i>CATReporterIMID</i> , <i>fillKeyDate</i> , <i>symbol</i> and <i>fulfillmentID</i> must be unique per Order Fulfillment event. |
| fulfillmentLinkType | Choice | <p>Specifies the type of the fulfillment. Refer to Appendix C for additional information on Representative Order linkage requirements.</p> <p>Allowed Values for Equity Events:</p> <p>Y Representative Order, linkage required</p> <p>YS Representative Order, linkage required, details provided in a supplement event</p> <p>YP Fill from pre-existing Principal order, linkage required</p> <p>YE Representative eligible - Order eligible for customer fills via an unlinked system (unlinked OMS-EMS or position fill)</p> <p>FOR Fulfillment on an order routed to a foreign destination, no linkage required</p> <p>Allowed Values for Option Events:</p> <p>O Options Order Fulfillment</p> <p>OML Multi-Leg Options Order Fulfillment</p> |
| handlingInstructions | Name/Value Pairs | Order handling instructions qualify the pricing, quantity, execution timing, or execution method of an order. All instructions that apply to the order must be included, excluding <i>handlingInstructions</i> on MEOR and MOOR |

| Field Name | Data Type | Description |
|------------------------------|------------------|---|
| | | <p>events.</p> <p>The <i>handlingInstructions</i> field may contain zero or more order handling instruction codes. There is no limit to the number of <i>handlingInstructions</i> that may be populated in a record.</p> <p>Codes which require a value will include that value immediately after the code Field Name and a single equal sign (ASCII decimal 61, hex 3D).</p> <p>Allowed Values include both choice fields and Name/Value Pairs. Name/Value Pairs must be accompanied by a Value. Values are case sensitive.</p> <p>Allowed Values:</p> <p>ADD Add on Order. The customer adds additional shares to the order after it was fully executed.</p> <p>ALG Order was received or originated with instructions to work using a trading algorithm as defined in FINRA Rule 1220(b)(4)(a) and shall not include Smart Order Routers.</p> <p>ALGMod Order originally received with instructions to work using a trading algorithm is later modified by the customer/client to use a different trading algorithm or change the settings of the trading algorithm</p> <p>ALO Add Liquidity Only</p> <p>AOB At or Between. Instructs the trader to execute at a trade price equal to the NBBO or between the NBBO and the midpoint.</p> |
| handlingInstructions (Cont.) | Name/Value Pairs | <p>AOK Auction or Kill</p> <p>AON All or None</p> <p>ATT Attributable</p> <p>BIN Buy-In – Refer to CAT FAQ B37</p> <p>CAC Customer Initiated Account Correction. ‘COR’ event was submitted to CAT as the result of a customer initiated account change prior to allocation. Not to be used if the ‘COR’ event was submitted to correct an error by the Industry Member.</p> <p>CMC Contingent on Market Conditions</p> <p>CMPX Complex option order that is tracked as a single leg option order with separate complex instructions</p> <p>CND Conditional Order. An order where the terms and conditions of the order are derived from a related transaction.</p> <p>CNH Cash Not Held. Instructs the Trader to buy or sell as much stock as possible, over the course of the trading day, for a specified amount.</p> <p>CPR Counterparty Restriction. Instructions that the order cannot be placed against certain counterparties.</p> <p>CSH Delivery Instruction: Cash trade settles on the same date</p> |

| Field Name | Data Type | Description |
|------------------------------|------------------|---|
| | | <p>d Discretionary Peg</p> <p>DAC Delta-Adjusted at Close. A DAC order is an options order that executes during the trading day and, for which, the execution price is adjusted based on a delta value applied to the change in the price of the underlying reference price from the time of order execution to the market close.</p> <p>DIR Directed Orders – Orders that meet the definition of “Directed Order” under Rule 600(b)(19) of Regulation NMS (formerly defined under SEC Rule 11Ac1–6). That definition specifies that the term directed order shall mean a customer order that the customer specifically instructed the broker or dealer to route to a particular venue for execution.</p> <p>DIV Dividend Reinvestment Order. Order is part of a dividend reinvestment program.</p> <p>DNI Do Not Increase</p> <p>DNR Do Not Reduce</p> <p>DNRT Do Not Route</p> <p>EW Exchange for Physical Transaction – Equity trade component of an “exchange for physical” transaction. An exchange for physical transaction involves two parties simultaneously executing a futures contract and an equity transaction (for the securities covered by the futures contract), typically involving baskets that replicate common indices.</p> |
| handlingInstructions (Cont.) | Name/Value Pairs | <p>FB Cboe Floor Broker. Indicates that the order is directed to a Cboe floor broker</p> <p>FBA NYSE Floor Broker Algorithm indicates that the order is routed to the Exchange via a NYSE Floor Broker Algorithm</p> <p>FOK Fill or Kill - Indicates the order is intended for immediate execution in its entirety, and if not executed in its entirety, the order is cancelled</p> <p>FS Suspend</p> <p>FUT Futures Related Trade. Price or size of a cash order is contingent upon a related futures trade.</p> <p>G G Order – An order for an account covered by Exchange Act §11(a) that relies on §11(a)(1)(G) as an exemption to §11(a)(1)</p> <p>GVWAP Guaranteed VWAP. Order was received or originated with instructions to execute at a guaranteed volume-weighted average price.</p> <p>IDX Intra-Day Cross</p> <p>IO Imbalance Only</p> <p>LOC Limit on Close - Instructs the trader to execute the order at the closing price provided that the closing price is at or within the limit specified</p> <p>LOO Limit on Open - Instructs trader to execute the order at the opening price provided that the opening price is at or within the limit specified.</p> |

| Field Name | Data Type | Description |
|------------------------------|------------------|--|
| | | <p>M Midpoint Peg</p> <p>MAC Market at Close. Instructs the trader to execute the order at the closing inside quote price of regular market hours.</p> |
| handlingInstructions (Cont.) | Name/Value Pairs | <p>MAO Market at Open. Instructs the trader to execute the order at the opening inside quote price of regular market hours.</p> <p>MOB Midpoint or Better. Instructs the trader to execute at a trade price equal to the midpoint or better.</p> <p>MOC Market on Close. Instructs the trader to execute the order at the closing last sale price of regular market hours.</p> <p>MOO Market on Open. Instructs the trader to execute the order at the opening print price of regular market hours.</p> <p>MRP Merger Related Transfer Position</p> <p>MTL Market to Limit. An order that is sent in as a market order to execute at the current best price. If the entire order does not immediately execute at the market price, the remainder of the order is resubmitted as a limit order with the limit price set to the price at which the original order executed.</p> <p>NAV Net Asset Value. Order was received or originated with instructions to execute at a Net Asset Value.</p> <p>ND Delivery Instructions: Next Day - trade settles on next trade date</p> <p>NH Not Held</p> <p>OPO Opt Out of Locked Market</p> <p>OPT Options Related Trade. Price or size of a cash order is contingent upon a related option trade Refer to CAT FAQ K5 for additional information.</p> <p>OVD Over the Day. Requires that a trader break up an order into several partial executions. The customer may specify the number of executions.</p> <p>P Market Peg</p> <p>PEG Indicates that the limit price is to be determined by a specific market price and/or volume factor or that the limit price should be determined pursuant to a specific formula</p> <p>P Market Peg</p> <p>QCC Qualified Contingent Cross</p> <p>R Primary Peg</p> <p>RAR Routed as Received. For orders routed without any changes to the handling instructions, reporters may use this code to indicate that the handling instructions are equal to the received order.</p> <p>RLO Retail Liquidity Order (On Exchange)</p> <p>RSV Reserve Size Order. Required for an order for which a customer has authorized the public display of part of the full size of the order with the remainder held in reserve on an undisplayed basis</p> |

| Field Name | Data Type | Description |
|------------------------------|------------------|--|
| | | <p>to be displayed in whole or in part as the displayed part is executed.</p> <p>SCL Scale. Requires partial executions that are not more than a specified price increment apart.</p> <p>SLD Slide —Instruction to adjust limit price to prevent locked or crossed market</p> <p>SLQ Stop Limit on Quote. An order that is triggered by a quotation at which point the stopped order becomes a limit order.</p> <p>SLR Delivery Instructions: Seller's Option - trade settles on the date determined by a seller.</p> <p>SMT Smart Router. Indicates that the order is routed out via a Smart Router.</p> <p>SOQ Stop on Quote. An order that is triggered by a quotation at which point the stopped order becomes a market order.</p> <p>STP Self Trade Prevention</p> <p>TS Trailing Stop</p> <p>UNP Unpriced Quote on an Order Driven Market – Applicable to orders received by Global OTC.</p> <p>UNS Unsolicited Quote on an Order Driven Market – Applicable to orders received by Global OTC.</p> |
| handlingInstructions (Cont.) | Name/Value Pairs | <p>WDP With Discretion Price</p> <p>WRK Work. Leaves the time of execution to the trader's discretion; either full execution or partial executions are accepted.</p> <p>Allowed Values (Name/Value Pairs):</p> <p>AucResp Auction Response. Requires the Auction ID value for option orders originated in response to an exchange auction. If there is no Auction ID, must be populated with a value of 'NOAUCID' Data Type: Alphanumeric (40)</p> <p>DISP Display Price. The display price at the time the order is receive or originated. Requires a numeric value representing the display price (e.g., DISP=10.00) Data Type: Price.</p> <p>DISQ Display Quantity. The display quantity at the time the order is received or originated. Requires a numeric value representing the display quantity (e.g., DISQ=1000) Data Type: Real Quantity</p> <p>STOP Stop Price - requires a Numeric value representing the stop price (e.g., STOP=17.95) Data Type: Price</p> <p>SW Stop Stock Transaction – Any transaction resulting from an order for which a member and another party agree that the order will be executed at a Stop Stock Price or better. Requires a numeric value representing the agreed stop price. Data Type: Price</p> <p>SWQ Stop Stock Quantity - requires a Numeric value representing the quantity of shares of a stop stock</p> |

| Field Name | Data Type | Description |
|------------------|---------------|---|
| | | <p>order being stopped if the entire shares quantity of the order is not being stopped (e.g., SWQ=500). When SWQ is populated, SW must also be populated.</p> <p>TMO The trigger time of the Time Managed Order (e.g. the specific date and time that an order becomes a market or limit price order) - requires a Timestamp value. Data Type: Timestamp</p> |
| infoBarrierID | Text (20) | The identifier of the information barrier in place for a trading unit that will meet the criteria of the “no-knowledge” exception in FINRA Rule 5320.02. |
| initiator | Choice | <p>Indicates who initiated a cancel or modification request.</p> <p>Allowed Values:</p> <p>C Initiated by the Customer F Initiated by the firm</p> |
| institutionFlag | Boolean | <p>Indicates if the account meets the definition of institution under FINRA Rule 4512(c)</p> <p>Allowed Values:</p> <p>true account meets the definition of institution under FINRA Rule 4512(c) false account does not meet the definition of institution under FINRA Rule 4512(c)</p> |
| isoInd | Choice | <p>Indicates the order was an Intermarket Sweep Order</p> <p>Allowed Values:</p> <p>ISOD Intermarket Sweep Order - Day ISOI Intermarket Sweep Order - IOC NA Not applicable</p> |
| leavesQty | Real Quantity | The quantity remaining unfilled after the event. The meaning of this field is dependent on the event in which it's used. Refer to each individual event definition for more detail. |
| legDetails | Leg Details | <p>Captures the leg level details for each leg associated with a Multi-Leg order event.</p> <p>This field is in the format of Leg Details, a compound data type that consists of a list of fields (see Section 2.5 Data Types). The <i>legDetails</i> field is used in all Multi-Leg order events to capture the leg level details of each event. Refer to Section 5.2 for a the <i>legDetails</i> required in each Multi-Leg order event.</p> <p>If there are more <i>legDetails</i> than can be represented in one event, any additional <i>legDetails</i> must be populated in separate Multi-Leg Order Supplement events.</p> |
| legRatioQuantity | Real Quantity | The ratio of quantity for this individual leg relative to the entire multi-leg security. May be represented as the entire quantity for the leg, or as the lowest common factor. |
| legRefID | Text (64) | Unique identifier of the leg, optionally populated in the <i>legDetails</i> . |

| Field Name | Data Type | Description |
|--------------------|----------------|---|
| manualFlag | Boolean | Indicates whether an order was received or handled manually. Allowed Values: true event was received/handled manually false event was not received/handled manually |
| manualOrderID | Text (64) | In cases when a duplicative electronic message is reported, the <i>manualOrderID</i> is the <i>orderID</i> of the related manual order. |
| manualOrderKeyDate | Timestamp | In cases when a duplicative electronic message is reported, the <i>manualOrderKeyDate</i> is the <i>orderKeyDate</i> of the related manual order. |
| marketCenterID | Choice | The national securities exchange or transaction reporting system operated by a registered securities association where the trade was reported. Allowed Values: <i>FINRA transaction reporting systems:</i> DN FINRA/NYSE Trade Reporting Facility D ADF L FINRA/Nasdaq Trade Reporting Facility DC FINRA/Nasdaq Chicago Trade Reporting Facility O OTC Reporting Facility <i>National Securities Exchanges:</i> A NYSE MKT B Nasdaq BX C NYSE National F Non-US Exchange H MIAX PEARL Equities I International Securities Exchange J Cboe EDGA Exchange K Cboe EDGX Exchange LT Long Term Stock Exchange M NYSE Chicago Stock Exchange N New York Stock Exchange P NYSE Arca Q The Nasdaq Stock Market U Members Exchange V Investors Exchange W Cboe Stock Exchange X Nasdaq PSX Y Cboe BYX Exchange Z Cboe BZX Exchange |
| minQty | Whole Quantity | Indicates the minimum quantity allowed to be executed in a single transaction. Must be > 0. |

| Field Name | Data Type | Description |
|---------------------|----------------|---|
| mpStatusCode | Choice | <p>Market Participant Status Code- indicates if the market maker's quote was open or closed. Only applicable for quotes sent to an IDQS.</p> <p>Allowed Values:</p> <p>O Open</p> <p>C Close</p> |
| multiLegInd | Boolean | Indicates when the immediately preceding event in the order life cycle is a Multi-Leg order event. Refer to Section 5.2.2 for additional guidance. |
| nbboSource | Choice | <p>ATS only field. Source of the NBBO data used.</p> <p>Allowed Values:</p> <p>D Direct</p> <p>S SIP</p> <p>H Hybrid - NBBO Source of Hybrid is used in instances where the firm uses a combination of Direct and SIP feeds as its NBBO Source.</p> <p>NA Not Applicable</p> <p>NBBO Source of 'NA' is used when the NBBO Engine Look up Date and Time is not applicable for the ATS Order Type or the ATS cancelled the order without referencing the NBBO. If this value is used, the related NBBO price and quantity fields must be populated with a value of '0' and the <i>nbboTimestamp</i> must be blank.</p> |
| nbboTimestamp | Timestamp | ATS only field. The date and time at which the NBBO was referenced. |
| nbbPrice | Price | <p>ATS only field. The national best bid price in effect at the event timestamp.</p> <p>If the event changed the NBBO, populate with the national best bid price before the change effected by the event.</p> |
| nbbQty | Whole Quantity | <p>ATS only field. The national best bid quantity in effect at the event timestamp.</p> <p>If the event changed the NBBO, populate with national best bid quantity before the change effected by the event.</p> |
| nboPrice | Price | <p>ATS only field. The national best offer price in effect at the event timestamp.</p> <p>If the event changed the NBBO, populate with the national best offer price before the change effected by the event.</p> |
| nboQty | Whole Quantity | <p>ATS only field. The national best offer quantity in effect at the event timestamp.</p> <p>If the event changed the NBBO, populate with the national best offer quantity before the change effected by the event.</p> |
| negotiatedTradeFlag | Boolean | <p>Identifies if an order is the result of a negotiated trade between two parties.</p> <p>Allowed Values:</p> <p>true indicates the trade is a result of a negotiation</p> |

| Field Name | Data Type | Description |
|--------------------|-------------------|---|
| | | false indicates the trade is not the result of a negotiation |
| newOrderFDID | Text (40) | The FDID of the related New Order event, if available in the booking system. Requirements for populating this field may be expanded in future phases of CAT. |
| numberOfLegs | Whole Quantity | Indicates the number of legs in the multi-leg order. |
| onlyOneQuoteFlag | Boolean | Identifies instances when the quoting system allows only one quote to be active at a time for the particular market maker. Allowed Values: true system allows only one quote false system allows multiple quotes |
| openCloseIndicator | Choice | Indicates when exchange rules require an order to be marked as open or close upon entry into the exchange. Must be reported as a point-in-time value on each event (therefore, this may differ between New Option Order and Option Order Route for the same <i>orderID</i>). Allowed Values: Open Close |
| optionID | Text (22) | The 21-character OSI Symbol of the option. For FLEX Percent options, a percentage symbol (%) is prepended to the OSI symbol elements. |
| orderID | Text (64) | The internal order ID assigned to the order by the Industry Member. The combination of <i>CATReporterIMID</i> , <i>orderKeyDate</i> , <i>symbol</i> and <i>orderID</i> must be unique. |
| orderKeyDate | Timestamp | For Primary Events and Secondary Events that assign the Order Key, the date and time the <i>orderID</i> was assigned. For Secondary events that did not assign a new Order Key, the <i>orderKeyDate</i> of the related event from which the Secondary event originated. Used to support uniqueness of an Order Key. If time is not needed to guarantee a unique Order Key, the time portion may be populated with zeros. |
| orderType | Choice | The type of order being submitted. Allowed Values: CAB Cabinet LMT Limit MKT Market |
| originatingIMID | CAT Reporter IMID | An identifier used in instances of a merger or acquisition where the originating firm had open limit orders on its books that will be executed or otherwise resolved under the surviving firm. Must be provided to support linkage to an event that was reported with a different <i>CATReporterIMID</i> . |
| parentOrderID | Text (64) | The <i>orderID</i> of the event from which the Child Order Event or Order Internal Route Accepted event originated. |

| Field Name | Data Type | Description |
|------------------------|---------------|---|
| parentOrderKeyDate | Timestamp | The <i>parentOrderKeyDate</i> is the <i>orderKeyDate</i> of the event from which the Child Order or Order Internal Route Accepted event originated. |
| price | Price | For Equity and Simple Option Order events, the limit price of the order. For Trade events, the price of the trade. For Order Fulfillment events, the price of the fulfillment. For Post-Trade Allocation events, the price of the allocated shares. For Multi-Leg Order events, the net price of the order inclusive of ratio and side represented as a debit/credit. |
| priorAllocationID | Text (64) | If a new allocation ID is assigned, this is the <i>allocationID</i> of the event being modified. |
| priorAllocationKeyDate | Timestamp | In cases when a new <i>allocationID</i> is assigned, the <i>priorAllocationKeyDate</i> is the <i>allocationKeyDate</i> of the allocation event that is being modified. |
| priorFulfillmentID | Text (64) | In cases when a new <i>fulfillmentID</i> is assigned, the <i>priorFulfillmentID</i> is the <i>fulfillmentID</i> that is being amended. |
| priorFillKeyDate | Timestamp | In cases when a new <i>fulfillmentID</i> is assigned, the <i>priorFillKeyDate</i> is the <i>fillKeyDate</i> of the fulfillment that is being amended. |
| priorOrderID | Text (64) | In cases when an event assigns a new <i>orderID</i> , the <i>priorOrderID</i> is the <i>orderID</i> that is being replaced. |
| priorOrderKeyDate | Timestamp | In cases when an event assigns a new <i>orderID</i> , the <i>priorOrderKeyDate</i> is the <i>orderKeyDate</i> of the order whose <i>orderID</i> is being replaced. |
| priorRoutedOrderID | Text (64) | In cases where a Route Modified event assigns a new <i>routedOrderID</i> , the <i>priorRoutedOrderID</i> is the <i>routedOrderID</i> of the Order Route event being modified. |
| priorQuoteID | Text (64) | In cases when a new <i>quoteID</i> is assigned, the <i>priorQuoteID</i> is the <i>quoteID</i> that is being replaced. |
| priorQuoteKeyDate | Timestamp | In cases when an event assigns a new <i>quoteID</i> , the <i>priorQuoteKeyDate</i> is the <i>quoteKeyDate</i> of the order whose <i>quoteID</i> is being replaced. |
| quantity | Real Quantity | The quantity of the order. |
| quoteID | Text (64) | The internal quote ID assigned to the quote by the reporter. Required to report at the start of the lifecycle if initiated by a quote. |
| quoteKeyDate | Timestamp | The date and time the <i>quoteID</i> was assigned. Used to support uniqueness of a Quote Key. If time is not needed to guarantee a unique Quote Key, the time portion may be populated with zeros. |
| quoteRejectedFlag | Boolean | Indicates if the quote was not accepted by the destination. Allowed Values: true false |
| quoteWantedInd | Choice | Indicates if the quote message received by an IDQS is a request for a bid or an ask. |

| Field Name | Data Type | Description |
|------------------------|--------------------|---|
| | | <p>Allowed Values:</p> <p>A Ask Wanted</p> <p>B Bid Wanted</p> |
| quotingIDQS | Industry Member ID | If a trade was the result of a quote that was sent to an IDQS, this is the IMID of the IDQS that submitted the related Quote Received event. |
| receivedQuoteID | Text (64) | Identifies the quote ID as received by the ATS or broker-dealer, It must match the <i>routedQuoteID</i> in the New Quote event reported by the issuer of the quote. |
| receiverIMID | Industry Member ID | The IMID of the Industry Member receiving the order or quote. <i>receiverIMID</i> must match the <i>destination</i> field on the Order Route event reported by the routing Industry Member. If receiving from an exchange as the routing broker, then this must match the <i>routingParty</i> on the Order Route event reported by the exchange. |
| receivingDeskType | Choice | <p>Indicates the type of desk or department within the firm that received the order. More granular than the field <i>deptType</i>. Only required when the destination of an internal route is a desk.</p> <p>Allowed Values:</p> <p>A Agency</p> <p>AR Arbitrage</p> <p>B Block Trading</p> <p>C Convertible Desk</p> <p>CR Central Risk Books</p> <p>D Derivatives</p> <p>EC Equity Capital Markets</p> <p>FB Floor Broker</p> <p>IN International</p> <p>IS Institutional</p> <p>O Other</p> <p>PF Preferred Trading</p> <p>PR Proprietary</p> <p>PT Program Trading</p> <p>S Sales</p> <p>SW Swaps</p> <p>T Trading Desk</p> <p>TR Treasury</p> |
| reportingExceptionCode | Choice | <p>Indicates the reason that a unique identifier (e.g., Branch Sequence Number, Compliance ID) was not supplied to a transaction reporting system.</p> <p>Allowed Values:</p> <p>C Industry Member was the contra side of the trade report for a negotiatedTrade which was reported to a</p> |

| Field Name | Data Type | Description |
|----------------------|-----------|---|
| | | <p>TRF via a QSR or AGU.</p> <p>F Reported on Form T pursuant to FINRA Trade Reporting Rules.</p> <p>N Trade was executed by a non-FINRA member and reported to the TRF by the FINRA member counterparty.</p> <p>P Intra-firm order where there is no change in beneficial ownership.</p> |
| representativeInd | Choice | <p>Indicates the type of representative order being reported and whether linkage is required. Refer to Appendix C for additional information on Representative Order linkage requirements.</p> <p>Allowed Values for Equities:</p> <p>Y Representative order, linkage required</p> <p>YS Representative order, linkage required; details in supplement event</p> <p>YP Representative order, pricing guarantee, no linkage required</p> <p>YE Representative eligible - Order eligible for customer fills via an unlinked system (unlinked OMS-EMS or position fill workflow)</p> <p>N Not a representative order, linkage is not applicable</p> <p>Allowed Values for Options:</p> <p>O Options Combined Order</p> <p>OS Options Combined Order; details in supplement event</p> <p>OML Multi-Leg Options Combined Order</p> <p>OMS Multi-Leg Options Combined Order; details in supplement event</p> <p>N Not a combined order, linkage is not applicable</p> |
| reservedForFutureUse | Text (0) | Field is Reserved for Future Use and must remain blank. Future enhancements to Message Types with positions that are Reserved for Future Use will occupy the available position before adding a new position. |
| RFQID | Text (64) | For New Order events representing a response to an RFQ or solicitation, the ID assigned to the related RFQ or solicitation being responded to. |
| routedOrderID | Text (64) | <p>For orders routed, the ID assigned to the order by the routing firm when routing the order.</p> <p>For orders received, the ID assigned to the order by the routing firm.</p> <p>Must be unique per combination of Event Date, symbol (or optionID), <i>destination/receiverIMID</i>, <i>senderIMID</i>, and <i>session</i> (applicable only on routes to exchanges).</p> |
| routedQuoteID | Text (64) | <p>For quotes sent, the <i>quoteID</i> as sent to the recipient of the quote.</p> <p>For quotes received, the <i>quoteID</i> as received from the routing firm.</p> |
| routeRejectedFlag | Boolean | Indicates the routed order was not accepted by the |

| Field Name | Data Type | Description |
|-------------|---------------------------------|---|
| | | <p>destination (i.e. rejected, no response).</p> <p>Allowed Values: true rejected or no response false not rejected</p> |
| sellDetails | Trade Side Details | <p>Captures the Order Key and additional information for the Order associated with the sell side of a Trade Event.</p> <p>This field is in the format of Trade Side Details, a compound data type that consists of a list of fields (see Section 2.5 Data Types). The <i>sellDetails</i> field is only used in Trade events and Trade Supplement events to capture the sell side details of the trade. Refer to Section 4.12.1 for a list of fields.</p> <p>This field is applicable on a Trade event if there is only one <i>orderID</i> associated with this side of the trade. If there is more than one <i>orderID</i>, the <i>sellDetails</i> must be populated in separate Trade Supplement events.</p> |
| senderIMID | Industry Member ID/ Exchange ID | <p>Provides the identity of the party routing the order or quote, known also by the destination. The <i>senderIMID</i> reported by the routing entity must match the <i>senderIMID</i> reported by the receiving party.</p> <p>When receiving an order, the <i>senderIMID</i> is the IMID from which the order was received. When receiving orders from an exchange, the <i>senderIMID</i> must be equal to the Exchange ID and must match the <i>exchange</i> field in the Route event reported by the exchange.</p> <p>When routing an order, the <i>senderIMID</i> is the IMID being used by the Industry Member to route the order, as known by the destination. The <i>senderIMID</i> is either the IMID of the Industry Member, corresponding to <i>senderType</i> F, or the Exchange ID of the exchange, corresponding to <i>senderType</i> E.</p> <p>Allowed Values for Exchange ID (When <i>senderType</i> = E)</p> <p>BOX BOX Options Exchange CBOE Cboe Exchange C2 Cboe C2 Options BYX Cboe BYX Exchange BZX Cboe BZX Equities BZXOP Cboe BZX Options EDGA Cboe EDGA Exchange EDGX Cboe EDGX Equities EDGXOP Cboe EDGX Options IEX Investor's Exchange LTSE Long Term Stock Exchange MEMX Members Exchange MIAMI Miami International Securities Exchange PEARL MIAX PEARL PEARLEQ MIAX PEARL Equities EMLD MIAX Emerald BX Nasdaq BX Equities</p> |

| Field Name | Data Type | Description |
|----------------|-------------------|---|
| | | NOBO Nasdaq BX Options PSX Nasdaq PHLX Equities PHLX Nasdaq PHLX Options NSDQ Nasdaq Stock NOM Nasdaq Options ISE Nasdaq ISE GEMX Nasdaq GEMX MRX Nasdaq MRX AMER NYSE American Equities AMEROP NYSE American Options ARCA NYSE ARCA Equities ARCAOP NYSE ARCA Options NYSE The New York Stock Exchange CHX NYSE CHX NSX NYSE National |
| senderType | Choice | Identifies from where a routed order originated. Allowed Values: F Industry Member E Exchange |
| seqNum | Alphanumeric (40) | ATS only field. The sequence number of the event, used to sequence events when multiple events have the same timestamp. The sequence number is required to be an increasing value for a CAT Reporter, Event Date, and symbol, such that it can be used to sequence events having the same event timestamp in chronological order. Refer to Section 2.3.1 Timestamps and Section 3.1.3 Sequence Number . |
| session | Text (40) | The identifier representing the name or identifier of the session used when routing to an exchange. <i>Session</i> may be blank or populated with any string value that is shared between sender and receiver. Used to ensure a unique Route Linkage Key. Refer to the Order Routing Field Mapping document published on the IM Technical Specifications page of the CAT Public Website. |
| settlementDate | Date | The settlement date of the securities being allocated |
| side | Choice | Side of the event. Allowed Values for Equities Events: B Buy SL Sell Long SS Short Sale SX Short Sale Exempt Allowed Values for Options Events: |

| Field Name | Data Type | Description |
|------------------|-----------------|--|
| | | <p>B Buy</p> <p>S Sell</p> |
| sideDetailsInd | Choice | <p>Identifies if a Trade event is one sided, and which side of the trade the Industry Member is populating in the Trade Side Details.</p> <p>Allowed Values:</p> <p>BUY The Trade event is one sided, and the reporter is on the Buy side of the trade. Only the <i>buyDetails</i> are populated.</p> <p>SELL The Trade event is one sided, and the reporter is on the Sell side of the trade. Only the <i>sellDetails</i> are populated.</p> <p>NA Not Applicable – the Trade event is not one sided.</p> |
| solicitationFlag | Boolean | <p>Indicates if the order was originated in response to an RFQ or other solicitation process.</p> <p>This field is not used to indicate if a registered representative of the firm solicited a client order.</p> <p>Allowed Values:</p> <p>true Event was received or originated as the result of a response to an RFQ or other solicitation process.</p> <p>false Event was not received or originated as the result of a response to an RFQ or other solicitation process.</p> |
| symbol | Symbol | The symbol of the stock in the symbology of the primary listing exchange or FINRA OTC symbology for OTC Equity Securities. |
| tapeTradeID | Text (40) | <p>The unique identifier reported by the Industry Member to the TRF/ADF/ORF based on the reporting specifications of the specific facility. Required when the <i>tapeTradeID</i> was supplied to a transaction reporting system:</p> <ul style="list-style-type: none"> • Compliance ID in ORF and ADF • Branch Sequence Number in FINRA/NQ TRF • FINRA Control Number in FINRA/NYSE TRF <p>Must be unique per combination of Event Date, <i>CATReporterIMID</i>, <i>marketCenterID</i> and <i>symbol</i>.</p> <p>The <i>tapeTradeID</i> may link to either the reporting side or the contra-side of the tape report.</p> |
| timeInForce | Name/Value Pair | <p>Specifies the Time-In-Force for an order.</p> <p>Allowed Values:</p> <p>DAY A day order. Requires the expiration date which must be equal to Event Date or Event Date plus one Trading Day. Data Type: Date</p> <p>IOC Immediate or Cancel</p> <p>IOR Immediate or Return. Only applicable to options floor brokers.</p> <p>GTC Good till Cancelled</p> |

| Field Name | Data Type | Description |
|----------------|--------------|--|
| | | <p>GTT Good till Time. Requires the expiration timestamp. Data Type: Timestamp</p> <p>GTD Good till Date Requires the expiration date. Data Type: Date</p> <p>GTM Good this Month (valid until last business day of the month in which the order originated)</p> <p>GTX Good till Crossing</p> |
| tradeDate | Date | The trade date of the securities being allocated |
| tradeID | Text (64) | The internal trade ID assigned to the trade event by the Industry Member. The combination of <i>tradeKeyDate</i> , <i>CATReporterIMID</i> , <i>symbol</i> , and <i>tradeID</i> must be unique. |
| tradeKeyDate | Timestamp | The date and time the <i>tradeID</i> was assigned. Used to support uniqueness of a Trade Key. If time is not needed to guarantee a unique Trade Key, the time portion may be populated with zeros. |
| tradingSession | Choice | <p>The trading session(s) during which an order is eligible to trade.</p> <p>Allowed Values:</p> <p>FOR To be executed only on a Foreign Market</p> <p>PRE Pre-Market Only</p> <p>PREREG Pre-Market and Regular</p> <p>REG Regular Only</p> <p>REGPOST Regular and Post-Market</p> <p>POST Post-Market Only</p> <p>PREPOST Pre-Market and Post-Market</p> <p>ALL All Sessions - order can trade in any available session at the venue where it is sent. Refer to FAQ D32 for additional information.</p> |
| type | Message Type | <p>Specifies the event type.</p> <p>Equity Events:</p> <p>MENO New Order</p> <p>MENOS New Order Supplement</p> <p>MEOR Order Route Event</p> <p>MEMR Route Modified Event</p> <p>MECR Route Cancelled Event</p> <p>MEORS Order Route Supplement Event</p> <p>MEOA Order Accepted</p> <p>MEIR Order Internal Route Accepted</p> <p>MEIM Order Internal Route Modified</p> <p>MEIC Order Internal Route Cancelled</p> <p>MEIMR Order Internal Route Modification Request</p> <p>MEICR Order Internal Route Cancel Request</p> <p>MECO Child Order</p> <p>MECOM Child Order Modified</p> <p>MECOC Child Order Cancelled</p> |

| Field Name | Data Type | Description |
|------------|-----------|---|
| | | MEOM Order Modified |
| | | MEOMR Order Modification Request |
| | | MEOMS Order Modified Supplement |
| | | MEOJ Order Adjusted |
| | | MEOC Order Cancelled |
| | | MEOCR Order Cancel Request |
| | | MENQ New Quote |
| | | MEQR Quote Received |
| | | MEQC Quote Cancelled |
| | | MEOT Trade |
| | | MEOTS Trade Supplement |
| | | MEOF Order Fulfillment |
| | | MEOFS Order Fulfillment Supplement |
| | | MEFA Order Fulfillment Amendment |
| | | MEPA Post Trade Allocation |
| | | MEAA Amended Allocation |
| | | MEOE Order Effective |
| | | Simple Option Events: |
| | | MONO New Option Order |
| | | MONOS Option Order Supplement |
| | | MONP Paired Option Order |
| | | MOOR Option Order Route |
| | | MOMR Option Route Modified |
| | | MOCR Option Route Cancelled |
| | | MOORS Option Order Route Supplement |
| | | MOOA Option Order Accepted |
| | | MOIR Option Order Internal Route Accepted |
| | | MOIM Option Order Internal Route Modified |
| | | MOIC Option Order Internal Route Cancelled |
| | | MOIMR Option Order Internal Route Modification Request |
| | | MOICR Option Order Internal Route Cancel Request |
| | | MOCO Child Option Order |
| | | MOCOM Child Option Order Modified |
| | | MOCOC Child Option Order Cancelled |
| | | MOOM Option Order Modified |
| | | MOOMR Option Order Modification Request |
| | | MOOMS Option Order Modified Supplement |
| | | MOOJ Option Order Adjusted |
| | | MOOC Option Order Cancelled |
| | | MOOCR Option Order Cancel Request |
| | | MOOF Option Order Fulfillment |
| | | MOFA Option Order Fulfillment Amendment |
| | | MOPA Option Post Trade Allocation |
| | | MOAA Option Amended Allocation |
| | | MOOE Option Order Effective |

| Field Name | Data Type | Description |
|----------------|-----------|--|
| | | <p>Multi-Leg Option Events:</p> <p>MLNO Multi-Leg New Order</p> <p>MLOR Multi-Leg Order Route</p> <p>MLOA Multi-Leg Order Accepted</p> <p>MLIR Multi-Leg Order Internal Route Accepted</p> <p>MLCO Multi-Leg Child Order</p> <p>MLOM Multi-Leg Order Modified</p> <p>MLOC Multi-Leg Order Cancelled</p> <p>MLOS Multi-Leg Order Supplement</p> |
| underlying | Symbol | The symbol of the underlying stock in the symbology of the primary listing exchange or FINRA for OTC Equity Securities. |
| unsolicitedInd | Choice | <p>Indicates when the quote is unsolicited.</p> <p>Allowed Values:</p> <p>U Unsolicited Bid and Ask</p> <p>A Unsolicited Ask</p> <p>B Unsolicited Bid</p> <p>N Not Unsolicited</p> |
| unpricedInd | Boolean | <p>Indicates when a quote is unpriced.</p> <p>Allowed Values:</p> <p>true quote is unpriced</p> <p>false quote is not unpriced</p> |
| workingPrice | Price | <p>ATS only field. The working price of the order. If the price at which an order is currently priced on the matching engine is different than the stated limit price, the current price at which the order is priced on the matching engine should be populated.</p> <p>For example, in a PEG order, the adjusted price due to NBBO movement if the ATS repriced the order must be captured in <i>workingPrice</i>.</p> <p>If an ATS does not maintain a separate working price within its matching engine, this field would not be applicable.</p> |

Appendix H: Processing Stages Feedback and Examples

This section describes the types of validations, feedback files and associated error files that are generated by CAT during each processing stage. Related examples are included representing the Meta Feedback and Data Feedback.

H.1: Processing Stages Feedback

The table below contains types of validations generated by CAT at different stages of processing for both the Data File and the Metadata File

Table 142: Processing Stages Types of Validation and Associated Feedback

| Processing Stage | Validations | Meta File Validation | Data File Validation | Record Validation | Error Feedback |
|----------------------|--|----------------------|----------------------|-------------------|---|
| File Acknowledgement | Validate file name construct | ✓ | ✓ | | Meta File and Data File with error are rejected |
| File Integrity | Duplicate file name | ✓ | ✓ | | Feedback Meta is returned indicating the <u>file</u> for which the filename is duplicated is rejected |
| | Filename elements validations including submitter relationship | ✓ | | | Feedback Meta is returned indicating the <u>Meta File</u> is rejected |
| | Unreadable Meta file | ✓ | | | |
| | Meta File without a Data file | ✓ | | | |
| | Data File without a Meta file | | | ✓ | Feedback Meta is returned indicating the <u>Data File</u> is rejected |
| | Data file and Meta file paired but Hash not matching; file format not matching | ✓ | ✓ | | |
| Data Ingestion | Unreadable data file | | ✓ | | Feedback Meta is returned indicating the <u>Data File</u> is rejected |
| | Record count mismatch | | ✓ | | |

| Processing Stage | Validations | Meta File Validation | Data File Validation | Record Validation | Error Feedback |
|-------------------|---|----------------------|----------------------|-------------------|--|
| | Validate Events correct syntax and semantics associated with record length, field length, data type, non-null and reference data checks | | | ✓ | Feedback Meta is returned indicating the Data File has Errors; Feedback Error Data file is returned with errors |
| Linkage Discovery | Validate Events, Event Keys and Linkage Keys are not duplicated | | | ✓ | Feedback Meta is returned indicating Linkage Discovery Errors have been detected; Feedback Error Data file is returned with errors |
| | Perform Linkage and Out of Sequence checks | | | ✓ | |

H.2: File Feedback (JSON)

The tables below illustrate examples of file feedback associated with all stages of processing when an Industry Member submits a data and meta file in JSON format.

Table 143: Successful Meta/Data Pair – No Errors

| Successful Meta/Data Pair – No Errors | | | |
|---------------------------------------|--------------------|---|---|
| Submission Files | | Submission FileName | |
| Meta | | SUBID_MYID_20170307_OrderEvents_000123.meta.json | |
| Data | | SUBID_MYID_20170307_OrderEvents_000123.json.bz2 | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement of Meta File | Meta | SUBID_MYID_20170307_OrderEvents_000123.meta.ac.k.json | { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID MYID 20170307 OrderEvents 000123.meta.json", |

| Successful Meta/Data Pair – No Errors | | | |
|---------------------------------------|------|---|--|
| | | | <pre>"receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_ACKNOWLEDGEMENT", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success" }</pre> |
| Acknowledgement of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.ack.json | <pre>{ "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_ACKNOWLEDGEMENT", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success" }</pre> |
| Integrity of Meta File | n/a | None | None |
| Integrity of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.integrity.json | <pre>{ "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_INTEGRITY", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success", "metaFileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.json" }</pre> |
| Ingestion | Meta | SUBID_MYID_20170307_OrderEvents_000123.ingestion.json | <pre>{ "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "receiptTimestamp": "20170307T153552.000001089",</pre> |

| Successful Meta/Data Pair – No Errors | | | |
|---------------------------------------|------|---|--|
| | | | <pre> "stage": "INGESTION", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success", "errorCount": 0, "metaFileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.json" } </pre> |
| | Data | None | None |
| Linkage Discovery | Meta | SUBID_MYID_20170307_OrderEvents.linkage_000001.json | <pre> { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "stage": "LINKAGE", "stageCompleteTimestamp": "20170308T104152.000001089", "status": "Success", "errorCount": 0, "errorDetails": [{ "linkageType": "Intrafirm", "errorTypeCount": 0 }, { "linkageType": "Interfirm", "errorTypeCount": 0 }, { "linkageType": "Exchange", "errorTypeCount": 0 }, { "linkageType": "Trade", "errorTypeCount": 0 }], "doneForDay": true } </pre> |
| | Data | None | None |

Table 144: Acknowledgement Error for Data or Meta File

| Acknowledgement Error for Data or Meta File | | | |
|---|--------------------|----------------------------------|------------------|
| Submission Files | | Submission FileName | |
| Data File | | SUBID_MYID_201703.bz2 | |
| Meta File | | SUBID_MYID_201703.meta | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement of Data File | n/a | SUBID_MYID_201703.ack.error | Empty |
| Acknowledgement of Meta File | n/a | SUBID_MYID_201703.meta.ack.error | Empty |
| Integrity | Meta | None | None |
| Ingestion | Meta | None | None |
| | Data | None | None |
| Linkage Discovery | Meta | None | None |
| | Data | None | None |

Table 145: File Integrity Error of Meta or Data File

| File Integrity Error of Meta or Data File | |
|---|--|
| Submission Files | Submission FileName |
| Meta | SUBID_MYID_20170307_OrderEvents_000123.meta.json |
| Data | SUBID_MYID_20170307_OrderEvents_000123.json.bz2 |

| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
|------------------------------|--------------------|--|--|
| Acknowledgement of Meta File | Meta | SUBID_MYID_20170307_OrderEvents_000123.meta.ack.json | { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.json", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_ACKNOWLEDGEMENT", "stageCompleteTimestamp": "20170307T153652.000001089", "status": "Success" } |
| Acknowledgement of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.ack.json | { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_ACKNOWLEDGEMENT", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success" } |
| Integrity of Meta File | Meta | SUBID_MYID_20170307_OrderEvents_000123.meta.integrity.json | { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.json", "receiptTimestamp": "20170307T153553.000001089", "stage": "FILE_INTEGRITY", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Failure", "severity": "Error", "code": [1107] } |
| Integrity of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.integrity | { "feedbackVersion": "2.2.1", "submitter": "SUBID", |

| | | | |
|-------------------|------|---------|---|
| | | ty.json | <pre> "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_INTEGRITY", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Failure", "severity": "Error", "code": [1121] } </pre> |
| Ingestion | Meta | None | None |
| | Data | None | None |
| Linkage Discovery | Meta | None | None |
| | Data | None | None |

Table 146: File Integrity Error of Meta File with Multiple Blocks

| File Integrity Error of Meta File with Multiple Blocks | | | |
|--|--------------------|--|---|
| Submission Files | | Submission FileName | |
| Meta | | SUBID_MYID_20170307_OrderEvents_000124.meta.json | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement of Meta File | Meta | SUBID_MYID_20170307_OrderEvents_000124.meta.ack.json | <pre> { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000124.meta.json", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_ACKNOWLEDGEMENT", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success" } </pre> |

| File Integrity Error of Meta File with Multiple Blocks | | | |
|--|------|--|--|
| Integrity of Meta File | Meta | SUBID_MYID_20170307_OrderEvents_000124.meta.integrity.json | <pre> } { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000124.meta.json", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_INTEGRITY", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Failure", "severity": "Error", "errorDetails": [{ "blockFileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "code": [1121]}, {"blockFileName": "SUBID_MYID_20170307_OrderEvents_000122.json.bz2", "code": [1121]}] } </pre> |
| Ingestion | n/a | None | None |
| Linkage Discovery | n/a | None | None |

Table 147: File Ingestion Error – Data File is not Readable

| File Ingestion Error - Data File is not Readable | |
|--|--|
| Submission File Type | Submission FileName |
| Meta File | SUBID_MYID_20170307_OrderEvents_000123.meta.json |
| Data File | SUBID_MYID_20170307_OrderEvents_000123.json.bz2 |

| File Ingestion Error - Data File is not Readable | | | |
|--|--------------------|---|--|
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement | Meta | SUBID_MYID_20170307_OrderEvents_000123.ack.json | { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_ACKNOWLEDGEMENT", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success" } |
| Integrity | Meta | SUBID_MYID_20170307_OrderEvents_000123.integrity.json | { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_INTEGRITY", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success", "metaFileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.json" } |
| Ingestion | Meta | SUBID_MYID_20170307_OrderEvents_000123.ingestion.json | { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "INGESTION", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Failure", "severity": "Error", "code": 2153, } |

| File Ingestion Error - Data File is not Readable | | | |
|--|------|------|--|
| | | | "metaFileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.json" } |
| | Data | None | None |
| Linkage Discovery | Meta | None | None |
| | Data | None | None |

Table 148: Data File having Ingestion and Linkage Errors

| Data File having Ingestion and Linkage Errors | | | |
|---|--------------------|---|--|
| Submission Files | | Submission FileName | |
| Meta | | SUBID_MYID_20170307_OrderEvents_000123.meta.json | |
| Data | | SUBID_MYID_20170307_OrderEvents_000123.json.bz2 | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.ack.json | { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_ACKNOWLEDGEMENT", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success" } |
| Integrity of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.integrity.json | { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, } |

| Data File having Ingestion and Linkage Errors | | | |
|---|-------|---|--|
| | | | <pre>"fileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_INTEGRITY", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success", "metaFileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.json" }</pre> |
| Ingestion | Meta | SUBID_MYID_20170307_OrderEvents_000123.ingestion.json | <pre>{ "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "INGESTION", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Failure", "errorFileName": "SUBID_MYID_20170307_OrderEvents_000123.ingestion.error.json.bz2", "errorCount": 2, "metaFileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.json" }</pre> |
| | Error | SUBID_MYID_20170307_OrderEvents_000123.ingestion.error.json.bz2 | <pre>{ "errorCode": [2001,2002] "actionType": "RPR" "errorROEID": 123456 "errorRecord": {<error record>} } { "errorCode": [2003] "actionType": "RPR" "errorROEID": 123457 "errorRecord": {<error record>} }</pre> |
| Linkage Discovery | Meta | SUBID_MYID_20170307_OrderEvents_000001.linkage.json | <pre>{ "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID",</pre> |

Data File having Ingestion and Linkage Errors

| | | | |
|--|-------|---|---|
| | | | <pre> "fileGenerationDate": 20170307, "stage": "LINKAGE", "stageCompleteTimestamp": "20170308T114152.000001089", "status": "Failure", "errorFileName": "SUBID_MYID_20170307_OrderEvents.linkage.error_000001.json.bz2", "errorCount": 2 "errorDetails": [{ "linkageType": "Intrafirm", "errorTypeCount": 1 }, { "linkageType": "Interfirm", "errorTypeCount": 1 }, { "linkageType": "Exchange", "errorTypeCount": 0 }, { "linkageType": "Trade", "errorTypeCount": 0 }], "doneForDay": true, "metaFileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.json" } </pre> |
| | Error | SUBID_MYID_20170307_OrderEvents.linkage.error_000001.json.bz2 | <pre> { "errorCode": [3002,3003] "actionType": "RPR" "errorROEID": 123456 "errorRecord": {<errorRecord>} } { "errorCode": [8010] "actionType": "RPR" "errorROEID": 123457 "errorRecord": {<linkage key information>} } </pre> |

Table 149: Successful Meta/Data Pair Deletion Instruction

| Successful Meta/Data Pair File Delete Instruction – No Errors | | | |
|---|--------------------|--|---|
| Submission Files | | Submission FileName | |
| Meta | | SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.json | |
| Data - Empty File | | SUBID_MYID_20170307_OrderEvents_000123.DEL.json.bz2 | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement of Meta File | Meta | SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.ack.json | { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.json", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_ACKNOWLEDGEMENT", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success" } |
| Acknowledgement of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.DEL.ack.json | { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.DEL.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_ACKNOWLEDGEMENT", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success" } |
| Integrity of Meta File | n/a | None | None |

| Successful Meta/Data Pair File Delete Instruction – No Errors | | | |
|---|------|---|--|
| Integrity of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.DEL.integrity.json | { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.DEL.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_INTEGRITY", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success", "metaFileName": "SUBID MYID 20170307 OrderEvents 000123.meta.DEL.json"} |
| Ingestion | Meta | None | None |
| | Data | None | None |
| Linkage Discovery | Meta | None | None |
| | Data | None | None |

Table 150: File Integrity Error - Invalid File Deletion Instruction

| File Ingestion Error – Invalid File Delete Instruction | | | |
|--|--------------------|--|---|
| Submission Files | | Submission FileName | |
| Meta | | SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.json | |
| Data | | SUBID_MYID_20170307_OrderEvents_000123.DEL.json.bz2 | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement of Meta File | Meta | SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.ack.json | { "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, |

| File Ingestion Error – Invalid File Delete Instruction | | | |
|--|--------------------|---|--|
| Submission Files | | Submission FileName | |
| Meta | | SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.json | |
| Data | | SUBID_MYID_20170307_OrderEvents_000123.DEL.json.bz2 | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| | | | <pre>"fileName": "SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.json", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_ACKNOWLEDGEMENT", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success" }</pre> |
| Acknowledgement of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.DEL.ack.json | <pre>{ "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.DEL.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_ACKNOWLEDGEMENT", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Success" }</pre> |
| Integrity of Meta File | n/a | None | None |
| Integrity of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.DEL.integrity.json | <pre>{ "feedbackVersion": "2.2.1", "submitter": "SUBID", "reporter": "MYID", "fileGenerationDate": 20170307, "fileName": "SUBID_MYID_20170307_OrderEvents_000123.DEL.json.bz2", "receiptTimestamp": "20170307T153552.000001089", "stage": "FILE_INTEGRITY", "stageCompleteTimestamp": "20170307T154152.000001089", "status": "Failure", "severity": "Error", }</pre> |

| File Ingestion Error – Invalid File Delete Instruction | | | |
|--|--------------------|--|---|
| Submission Files | | Submission FileName | |
| Meta | | SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.json | |
| Data | | SUBID_MYID_20170307_OrderEvents_000123.DEL.json.bz2 | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| | | | "code": 1120, "metaFileName": "SUBID_MYID 20170307_OrderEvents_000123.meta.DEL.json"} |
| Ingestion | Meta | None | None |
| | Data | None | None |
| Linkage Discovery | Meta | None | None |
| | Data | None | None |

H.3: File Feedback (CSV)

The tables below illustrate examples of file feedback associated with all stages of processing when an Industry Member submits a data and meta file in CSV format.

Table 151: Successful Meta/Data Pair

| Successful Meta/Data Pair – No Errors | | | |
|---------------------------------------|--------------------|--|--|
| Submission Files | | Submission FileName | |
| Meta | | SUBID_MYID_20170307_OrderEvents_000123.meta.csv | |
| Data | | SUBID_MYID_20170307_OrderEvents_000123.csv.bz2 | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement of Meta File | Meta | SUBID_MYID_20170307_OrderEvents_000123.meta.ack.csv | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000123.meta.csv, 20170307T153552.000001089,FILE_ACKNOWLEDGEMENT, 20170307T154152.000001089,Success,,,,,,,, |
| Acknowledgement of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.ack.csv | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, 20170307T153552.000001089,FILE_ACKNOWLEDGEMENT, 20170307T154152.000001089,Success,,,,,,,, |
| Integrity of Meta File | n/a | None | None |
| Integrity of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.integrity.csv | 2.1.1,SUBID,MYID,20170307,SUBID_MYID_20170307_OrderEvents_000123.csv.bz2,20170307T153552.000001089,FILE_INTEGRITY,20170307T154152.000001089,Success,,,,,,,, SUBID_MYID_20170307_OrderEvents_000123.meta.csv |
| Ingestion | Meta | SUBID_MYID_20170307_OrderEvents_000123.ingestion.csv | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, 20170307T153552.000001089,INGESTION, 20170307T154152.000001089,Success,,,,,0,,, SUBID_MYID_20170307_OrderEvents_000123.meta.csv |
| | Data | None | None |
| Linkage Discovery | Meta | SUBID_MYID_20170307_OrderEvents.linkage_000001.csv | 2.1.1,SUBID,MYID,20170307,,,LINKAGE, 20170308T104152.000001089,Success,,,,,0, Intrafirm@0 Interfirm@0 Exchange@0 Trade@0,true, |

| Successful Meta/Data Pair – No Errors | | | |
|---------------------------------------|--------------------|---|------------------|
| Submission Files | | Submission FileName | |
| Meta | | SUBID_MYID_20170307_OrderEvents_000123.meta.csv | |
| Data | | SUBID_MYID_20170307_OrderEvents_000123.csv.bz2 | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| | Data | None | None |

Table 152: Acknowledgement Error for Data or Meta File

| Acknowledgement Error for Data or Meta File | | | |
|---|--------------------|----------------------------------|------------------|
| Submission Files | | Submission FileName | |
| Data File | | SUBID_MYID_201703.bz2 | |
| Meta File | | SUBID_MYID_201703.meta | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement of Data File | n/a | SUBID_MYID_201703.ack.error | Empty |
| Acknowledgement of Meta File | n/a | SUBID_MYID_201703.meta.ack.error | Empty |
| Integrity | Meta | None | None |
| Ingestion | Meta | None | None |
| | Data | None | None |
| Linkage Discovery | Meta | None | None |
| | Data | None | None |

Table 153: File Integrity Error of Meta or Data File

| File Integrity Error of Meta or Data File | | | |
|---|--------------------|---|--|
| Submission Files | | Submission FileName | |
| Meta | | SUBID_MYID_20170307_OrderEvents_000123.meta.csv | |
| Data | | SUBID_MYID_20170307_OrderEvents_000123.csv.bz2 | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement of Meta File | Meta | SUBID_MYID_20170307_OrderEvents_000123.meta.ack.csv | 2.1.1, SUBID, MYID, 20170307, SUBID_MYID_20170307_OrderEvents_000123.meta.csv, 20170307T153552.000001089, FILE_ACKNOWLEDGEMENT, 20170307T154152.000001089, Success, , , , , , , |
| Acknowledgement of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.ack.csv | 2.1.1, SUBID, MYID, 20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, 20170307T153552.000001089, FILE_ACKNOWLEDGEMENT, 20170307T154152.000001089, Success, , , , , , , |
| Integrity of Meta File | Meta | SUBID_MYID_20170307_OrderEvents_000123.meta.integrity.csv | 2.1.1, SUBID, MYID, 20170307, SUBID_MYID_20170307_OrderEvents_000123.meta.csv, 20170307T153552.000001089, FILE_INTEGRITY, 20170307T154152.000001089, Failure, Error, 1107, , , , , , |
| Integrity of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.integrity.csv | 2.1.1, SUBID, MYID, 20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, 20170307T153552.000001089, FILE_INTEGRITY, 20170307T154152.000001089, Failure, Error, 1107, , , , , , |
| Ingestion | Meta | None | None |
| | Data | None | None |
| Linkage Discovery | Meta | None | None |

| File Integrity Error of Meta or Data File | | | |
|---|------|------|------|
| | Data | None | None |

Table 154: File Integrity Error of Meta File with Multiple Blocks

| File Integrity Error of Meta File with Multiple Blocks | | | |
|--|--------------------|---|---|
| Submission Files | | Submission FileName | |
| Meta | | SUBID_MYID_20170307_OrderEvents_000124.meta.csv | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement of Meta File | Meta | SUBID_MYID_20170307_OrderEvents_000124.meta.csv | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000124.meta.csv, 20170307T153552.000001089,FILE_ACKNOWLEDGEMENT, 20170307T154152.000001089,Success,,,,,,,, |
| Integrity of Meta File | Meta | SUBID_MYID_20170307_OrderEvents_000124.meta.integrity.csv | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000124.csv.bz2, 20170307T153552.000001089,FILE_INTEGRITY, 20170307T154152.000001089,Failure,Error,,,,, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2@1121 SUBID_MYID_20170307_OrderEvents_000122.csv.bz2@1121,, |
| Ingestion | Meta | None | None |
| | Data | None | None |
| Linkage Discovery | Meta | None | None |
| | Data | None | None |

Table 155: File Ingestion Error – Data File is not Readable

| File Ingestion Error - Data File is not readable | | | |
|--|--------------------|--|--|
| Submission File Type | | Submission FileName | |
| Meta File | | SUBID_MYID_20170307_OrderEvents_000123.meta.csv | |
| Data File | | SUBID_MYID_20170307_OrderEvents_000123.csv.bz2 | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement | Meta | SUBID_MYID_20170307_OrderEvents_000123.ack.csv | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, 20170307T153552.000001089,FILE_ACKNOWLEDGEMENT, 20170307T154152.000001089,Success,,,,,,,, |
| Integrity | Meta | SUBID_MYID_20170307_OrderEvents_000123.integrity.csv | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, 20170307T153552.000001089,FILE_INTEGRITY, 20170307T154152.000001089,Success,,,,,,,, SUBID_MYID_20170307_OrderEvents_000123.meta.csv |
| Ingestion | Meta | SUBID_MYID_20170307_OrderEvents_000123.ingestion.csv | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, ,INGESTION,20170307T154152.000001089,Failure,Error,2153,,,,, SUBID_MYID_20170307_OrderEvents_000123.meta.csv |
| | Data | None | None |
| Linkage Discovery | Meta | None | None |
| | Data | None | None |

Table 156: Data File having Ingestion and Linkage Errors

| Data File having Ingestion and Linkage Errors | |
|---|---------------------|
| Submission Files | Submission FileName |
| | |

| Data File having Ingestion and Linkage Errors | | | |
|---|--------------------|--|--|
| Meta | | SUBID_MYID_20170307_OrderEvents_000123.meta.csv | |
| Data | | SUBID_MYID_20170307_OrderEvents_000123.csv.bz2 | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.ack.csv | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, 20170307T153552.000001089,FILE_ACKNOWLEDGEMENT, 20170307T154152.000001089,Success,,,,,,,, |
| Integrity of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.integrity.csv | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, 20170307T153552.000001089,FILE_INTEGRITY, 20170307T154152.000001089,Success,,,,,,,, SUBID_MYID_20170307_OrderEvents_000123.meta.csv |
| Ingestion | Meta | SUBID_MYID_20170307_OrderEvents_000123.ingestion.csv | 2.1.1,SUBID,MYID,20170307, SUBID_MYID_20170307_OrderEvents_000123.csv.bz2, ,INGESTION,20170307T154152.000001089,Failure,,, SUBID_MYID_20170307_OrderEvents_000123 .ingestion.error.csv.bz2,2,,, SUBID_MYID_20170307_OrderEvents_000123.meta.csv |
| | Error | SUBID_MYID_20170307_OrderEvents_000123.ingestion.error.csv.bz2 | 2001 2002,RPR,123456,<error record> 2003,RPR,123457,<error record> |
| Linkage Discovery | Meta | SUBID_MYID_20170307_OrderEvents.linkage_000001.csv | 2.1.1,SUBID,MYID,20170307,,,LINKAGE, 20170308T104152.000001089,Failure,,, SUBID_MYID_20170307_linkage_OrderEvents .linkage.error_000001.csv.bz2,2, Intrafirm@1 Interfirm@1 Exchange@0 Trade@0,true, |
| | Error | SUBID_MYID_20170307_OrderEvents.linkage.error_000001.csv.bz2 | 3002 3003,RPR,123456,<errorRecord> 8010,RPR,123457,<linkage key information> |

Table 157: Successful Meta/Data Pair File Delete Instruction

| Successful Meta/Data Pair File Delete Instruction – No Errors | | | |
|---|--------------------|--|--|
| Submission Files | | Submission FileName | |
| Meta | | SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.csv | |
| Data | | SUBID_MYID_20170307_OrderEvents_000123.DEL.csv.bz2 | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement of Meta File | Meta | SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.ack.csv | 2.1.1, SUBID, MYID, 20170307, SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.csv, 20170307T153552.000001089, FILE_ACKNOWLEDGEMENT, 20170307T154152.000001089, Success, , , , , , , |
| Acknowledgement of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.DEL.ack.csv | 2.1.1, SUBID, MYID, 20170307, SUBID_MYID_20170307_OrderEvents_000123.DEL.csv.bz2, 20170307T153552.000001089, FILE_ACKNOWLEDGEMENT, 20170307T154152.000001089, Success, , , , , , , |
| Integrity of Meta File | n/a | None | None |
| Integrity of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.DEL.integrity.csv | 2.1.1, SUBID, MYID, 20170307, SUBID_MYID_20170307_OrderEvents_000123.DEL.csv.bz2, 20170307T153552.000001089, FILE_INTEGRITY, 20170307T154152.000001089, Success, , , , , , , SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.csv |
| Ingestion | Meta | None | None |
| | Data | None | None |
| Linkage Discovery | Meta | None | None |
| | Data | None | None |

Table 158: File Ingestion Error - Invalid File Deletion Instruction

| File Ingestion Error – Invalid File Delete Instruction | | | |
|--|--------------------|--|---|
| Submission Files | | Submission FileName | |
| Meta | | SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.csv | |
| Data | | SUBID_MYID_20170307_OrderEvents_000123.DEL.csv.bz2 | |
| Feedback Type | Feedback File Type | Feedback FileName | Feedback Content |
| Acknowledgement of Meta File | Meta | SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.ack.csv | 2.1.1, SUBID, MYID, 20170307, SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.csv, 20170307T153552.000001089, FILE_ACKNOWLEDGEMENT, 20170307T154152.000001089, Success, , , , , , , |
| Acknowledgement of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.DEL.ack.csv | 2.1.1, SUBID, MYID, 20170307, SUBID_MYID_20170307_OrderEvents_000123.DEL.csv.bz2, 20170307T153552.000001089, FILE_ACKNOWLEDGEMENT, 20170307T154152.000001089, Success, , , , , , , |
| Integrity of Meta File | n/a | None | None |
| Integrity of Data File | Meta | SUBID_MYID_20170307_OrderEvents_000123.DEL.integrity.csv | 2.1.1, SUBID, MYID, 20170307, SUBID_MYID_20170307_OrderEvents_000123.DEL.csv.bz2, 20170307T153552.000001089, FILE_INTEGRITY, 20170307T154152.000001089, Failure, Error, 1120, , , , , , SUBID_MYID_20170307_OrderEvents_000123.meta.DEL.csv |
| Ingestion | Meta | None | None |
| | Data | None | None |
| Linkage Discovery | Meta | None | None |
| | Data | None | None |